

BLACKFRIAR PAINTS LTD

TECHNICAL DATA SHEET

Revision
date:
08/01/07

BF645 Anti Slip Deck Coating

<u>Product Information</u>	<u>Technical Spec</u>	<u>Drying Time</u>
<p><u>Description</u></p> <p>A single pack clear coating to provide an anti slip finish for decking</p>	<p><u>Composition</u></p> <p>A urethane alkyd based resin thinned with white spirit. Contains aluminium oxide aggregate.</p>	<p>Touch dry 2 – 4 hours. Overcoatable after 8 hours. Drying times are based on a substrate temperature of 20°C. Lower temperatures will prolong drying and overcoating times.</p>
<p><u>Usage/purpose</u></p> <p>For use over previously stained timber decking to provide an anti slip finish. Can also be used on other timber substrates subject to light to medium pedestrian traffic.</p>	<p><u>Properties</u></p> <p>VOC Content: 378 g/litre.</p>	<p><u>Cleaning</u></p> <p>Clean application equipment or spills with white spirit.</p>
<p><u>Characteristics</u></p> <p>A clear textured liquid coating containing micro aggregates.</p>	<p><u>Performance</u></p> <p>For use on exterior timber decking.</p>	<p><u>Limitations</u></p> <p>The Anti Slip finish is difficult to clean.</p> <p>Not suitable for heavy duty use or steel wheeled vehicles.</p> <p>Clear products do not give UV resistance to timber. A decking stain should be used prior to application of this product.</p> <p>Situations can arise where the decking may be slippery, such as a build up of moss/ mould, accumulation of wet leaves, during a heavy downpour and spillages of any liquids. Caution should be exercised when walking on any decking in these situations.</p>
<p><u>Finish</u></p> <p>Glossy / gritty</p>	<p><u>Surface Preparation</u></p> <p>Ensure the substrate to be painted is clean, dry and free from mould or any other surface contaminant likely to give adhesion problems (e.g. wax, grease, oil etc).</p>	
<p><u>Colour(s)</u></p> <p>Clear</p>	<p><u>Application Method</u></p> <p>A short pile roller is preferable. A brush may be used for small areas. Ensure product is thoroughly stirred with a broad stirrer. Apply two full coats.</p>	
<p><u>Packaging</u></p> <p>2.5litre.</p>	<p><u>Recommended Spreading Rate</u></p> <p>9 m²/ltr</p>	
<p><u>Disclaimer:</u> The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. It is our recommendation that a trial area is first coated to ensure the product is satisfactory to individual requirements</p>	<p><u>Environmental Info.</u></p> <p>Dangerous for the environment.</p>	
	<p><u>Thinning</u></p> <p>Up to 10% with white spirit.</p>	
	<p>For Technical Enquiries, Material Safety Data sheets Telephone 0191 4106611</p>	<p>Paint Product UN No. 1263.</p>
		<p>Tor Coatings Ltd. Portobello Industrial Est, Birtley Chester-le Street County Durham DH3 2RE</p>