

CENTRECOAT

Light Reflective Paint

Description: Centrecoat Light Reflective Paint is a specially formulated transparent water based Acrylic resin based paint coating, combining graded levels of reflective beads to reflect a high degree of light back towards the light source. It will also provide a tough, durable, exterior or interior finish suitable for use on a wide range of substrates.

Preparation: The substrate must be sound, dry and free from oil and grease. Cleaning should be carried out with liquid detergent solution, rinsed with clean water and allowed to dry. Surfaces which are contaminated with lichen or moss should be brushed clean, treated with Anti-Fungal Wash and allowed to dry. Any structural repairs should be carried out before application of **Centrecoat Light Reflective Paint**. Plastic, metal and timber surfaces should be rubbed down with abrasive paper. Ferrous metals should be primed with an appropriate anti corrosive primer.

Application:

Apply by Brush or Roller. No primer or undercoat is necessary unless used on ferrous metal or where staining could occur. For porous substrates thin the first coat with 30% water. Do not apply at temperatures below 8°C.

Coverage: Approximately 8-12 sq. metres/litre, depending on texture and porosity of substrate.

Drying: Normally recoatable after 4 hours. Optimum hardness is reached after 2 weeks. Ensure good ventilation during application and drying.

Flash Point: Not applicable.

Clean up: Warm soapy water.

Pack sizes: 2.5litres 5litres 20litres

Storage: Protect from frost. Keep out of reach of children.

Colour Range: Tranparent.

All materials and specifications are provided in accordance with the terms and conditions of Promain UK Limited. Refer to [Health and Safety Data Sheet](#) prior to using this product.