



## SAFETY DATA SHEET DAMPSHIELD - BASE

### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NO. 103/Q124/DAMP - BASE  
APPLICATION BASE FOR TWO COMPONENT DAMP-PROOF MEMBRANE  
SUPPLIER COO-VAR  
Lockwood Street  
Hull  
HU2 0HN  
+44 (0) 1482 328053(T)  
+44 (0) 1482 219266(F)  
info@coo-var.co.uk  
CONTACT PERSON Technical Department - 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri as above

### 2 HAZARDS IDENTIFICATION

Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION (1999/45) Xi;R36/38. R43. N;R51/53.

#### PHYSICAL AND CHEMICAL HAZARDS

When handled correctly, undamaged units represent no danger.

#### HUMAN HEALTH

The product contains a small amount of sensitising substance which may provoke an allergic reaction among sensitive individuals in contact with skin.

### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content %	Classification (67/548/EEC)
EPOXY RESIN (Number average MW <= 700 )	500-033-5	25068-38-6	60-100%	R43 Xi;R36/38 N;R51/53
Phenol Formaldehyde Polymer Glycidyl Ether		28064-14-4	10-30%	Xi;R36/38. N;R51/53. R43.

The Full Text for all R-Phrases is Displayed in Section 16

### 4 FIRST-AID MEASURES

#### GENERAL INFORMATION

General first aid, rest, warmth and fresh air. Do not give victim anything to drink if they are unconscious.

#### INHALATION

Remove victim immediately from source of exposure. Provide rest, warmth and fresh air. Get medical attention if any discomfort continues. Place unconscious person on the side in the recovery position and ensure breathing can take place.

#### INGESTION

Immediately give a couple of glasses of water or milk, provided the victim is fully conscious. Do not induce vomiting. Get medical attention if any discomfort continues.

#### SKIN CONTACT

Remove affected person from source of contamination. Wash off promptly and flush contaminated skin with water. Promptly remove clothing if soaked through and flush skin with water. Get medical attention if irritation persists after washing.

#### EYE CONTACT

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Get medical attention immediately. Continue to rinse.

## DAMPSHIELD - BASE

### 5 FIRE-FIGHTING MEASURES

#### EXTINGUISHING MEDIA

Non flammable at room temperature, but will burn. Use fire-extinguishing media appropriate for surrounding materials. Fire can be extinguished using: Water spray, fog or mist. Foam, carbon dioxide or dry powder.

#### SPECIAL FIRE FIGHTING PROCEDURES

Avoid breathing fire vapours. Containers close to fire should be removed or cooled with water.

#### SPECIFIC HAZARDS

When heated and in case of fire, harmful vapours/gases may be formed.

#### PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

### 6 ACCIDENTAL RELEASE MEASURES

#### PERSONAL PRECAUTIONS

Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. Wear protective clothing as described in Section 8 of this safety data sheet.

#### ENVIRONMENTAL PRECAUTIONS

Avoid discharge into drains, water courses or onto the ground. Contain spillages with sand, earth or any suitable adsorbent material. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

#### SPILL CLEAN UP METHODS

Should be prevented from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

### 7 HANDLING AND STORAGE

#### USAGE PRECAUTIONS

Avoid inhalation of vapours. Avoid spilling, skin and eye contact. Do not eat, drink or smoke when using the product. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. The Manual Handling Operations Regulations may apply to the handling of containers of this product. For products sold by weight refer to the guide net weight indicated on the container. Allowance will have to be made for the immediate packaging to give an approximate gross weight.

#### USAGE DESCRIPTION

Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled container.

#### STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Store in closed original container at temperatures between 5°C and 25°C. Protect from freezing and direct sunlight. Keep upright.

### 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

#### INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

#### PROTECTIVE EQUIPMENT



#### PROCESS CONDITIONS

Use engineering controls to reduce air contamination to permissible exposure level.

#### ENGINEERING MEASURES

Provide adequate ventilation. Observe Occupational Exposure Limits and minimise the risk of inhalation of vapours.

#### RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.

## DAMPSHIELD - BASE

### HAND PROTECTION

Use suitable protective gloves if risk of skin contact. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Barrier cream applied before work may make it easier to clean the skin after exposure, but does not prevent absorption through the skin.

### EYE PROTECTION

Wear approved chemical safety goggles where eye exposure is reasonably probable.

### OTHER PROTECTION

Wear appropriate clothing to prevent reasonably probable skin contact.

### HYGIENE MEASURES

No specific hygiene procedures noted, but good personal hygiene practices are always advisable, especially when working with chemicals.

### PERSONAL PROTECTION

Unprotected persons should be kept away from treated areas.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Clear liquid.
COLOUR	Light (or pale). Yellow.
ODOUR	Slight odour.
SOLUBILITY	Immiscible with water
BOILING POINT (°C)	>150 760 mm Hg
RELATIVE DENSITY	1.15 approx. @ 20C
VAPOUR PRESSURE	<0.01 kPa @ 20C
VISCOSITY	<1 Pas @ 25C
FLASH POINT (°C)	>100 CC (Closed cup).

## 10 STABILITY AND REACTIVITY

### STABILITY

Stable under normal temperature conditions and recommended use.

### CONDITIONS TO AVOID

Not known.

### HAZARDOUS POLYMERISATION

Will not occur

### MATERIALS TO AVOID

Strong acids. Bases, alkalis (inorganic). Amines. Mercaptans (thiols).

### HAZARDOUS DECOMPOSITION PRODUCTS

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

## 11 TOXICOLOGICAL INFORMATION

### TOXICOLOGICAL INFORMATION

No data recorded.

### GENERAL INFORMATION

No specific health warnings noted.

### INHALATION

May cause irritation to the respiratory system.

### INGESTION

Harmful if swallowed. Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract.

### SKIN CONTACT

Irritating to skin. May cause sensitisation by skin contact.

### EYE CONTACT

Irritating to eyes.

### HEALTH WARNINGS

May cause sensitisation by skin contact. Delayed appearance of the complaints and development of hypersensitivity (difficulty breathing, coughing, asthma) are possible.

## DAMPSHIELD - BASE

### ROUTE OF ENTRY

Inhalation. Skin absorption. Ingestion. Skin and/or eye contact.

### MEDICAL CONSIDERATIONS

Skin disorders and allergies.

## 12 ECOLOGICAL INFORMATION

### ECOTOXICITY

There are no data on the ecotoxicity of this product.

### MOBILITY

The product is non-volatile.

### BIOACCUMULATION

No data available on bioaccumulation.

### DEGRADABILITY

No data available.

### ACUTE FISH TOXICITY

Toxicity to bacteria, algae and higher marine organisms not tested. COD: Not determined

## 13 DISPOSAL CONSIDERATIONS

### GENERAL INFORMATION

Do not allow to enter drains, sewers or watercourses. Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority. When handling waste, consideration should be made to the safety precautions applying to handling of the product. DO NOT reuse containers containing residual product without commercial cleaning


### WASTE CLASS

When this material, in its liquid state, as supplied, becomes a waste, it is categorised as a hazardous waste, with code 08 01 11\* (EPOXY BASED LIQUID WASTE). Part-used containers, not drained and/or rigorously scraped out and containing residues of the supplied material, are categorised as hazardous waste, with code 08 01 11\* (EPOXY BASED LIQUID WASTE). Ideally this component should be mixed with the appropriate hardener and allowed to react fully to produce a solid waste. Neutralised empty packages, are categorised as non-hazardous waste, with code 15 01 02(plastic packaging) or 15 01 04 (metal packaging)

## 14 TRANSPORT INFORMATION

### GENERAL

This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG.



### PROPER SHIPPING NAME

Paint

### PROPER SHIPPING NAME

Contains Biphenol A Epox Resin, Class 9, PG III, MARINE POLLUTANT

### UN NO. ROAD

3082

### ADR CLASS NO.

9

### ADR CLASS

Class 9: Environmentally hazardous substance, liquid, N.O.S. contains: epoxy constituents

### ADR PACK GROUP

III

### TUNNEL RESTRICTION CODE

(E)

### UN NO. SEA

3082

### IMDG CLASS

9

### IMDG PACK GR.

III

## 15 REGULATORY INFORMATION

### DAMPSHIELD - BASE

#### LABELLING



Irritant



Dangerous for the environment

#### CONTAINS

EPOXY RESIN (Number average MW <= 700 )  
Phenol Formaldehyde Polymer Glycidyl Ether

#### RISK PHRASES

R36/38	Irritating to eyes and skin.
R43	May cause sensitisation by skin contact.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### SAFETY PHRASES

S24/25	Avoid contact with skin and eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S37	Wear suitable gloves.
S57	Use appropriate containment to avoid environmental contamination.
S61	Avoid release to the environment. Refer to special instructions/safety data sheets.
P5	Contains epoxy constituents. See information supplied by the manufacturer.
S28	After contact with skin, wash immediately with plenty of water.

#### UK REGULATORY REFERENCES

Chemicals (Hazard Information & Packaging) Regulations. The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments. Health and Safety at Work Act 1974.

#### ENVIRONMENTAL LISTING

Control of Pollution Act 1974. Rivers (Prevention of Pollution) Act 1961.

#### EU DIRECTIVES

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC.

#### STATUTORY INSTRUMENTS

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716). Control of Substances Hazardous to Health.

#### APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

#### GUIDANCE NOTES

Workplace Exposure Limits EH40. CHIP for everyone HSG(108).

#### NATIONAL REGULATIONS

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689. Workplace Exposure Limits 2005 (EH40) Health and Safety at Work Act (As Amended) 1974 Control of Substances Hazardous to Health Regulations 2002 (as amended) The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2007 (CDG 2007) The Manual Handling Operations Regulations 1992 [SI 1992:2793]

### 16 OTHER INFORMATION

#### REVISION COMMENTS

Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in compliance with 30th & 31st ATP to Council Directive 67/548, as detailed in Commission Directive 2004/73/EC (1st ATP of EC Regulation 1272/2008)

#### ISSUED BY

Technical Dept. (P.E.)

REVISION DATE 29/11/2010

REV. NO./REPL. SDS GENERATED 1

SDS NO. 11108

#### SAFETY DATA SHEET STATUS

Approved.

DATE Date printed \_\_\_\_\_

SIGNATURE Initials \_\_\_\_\_

## DAMPSHIELD - BASE

### RISK PHRASES IN FULL

R36/38	Irritating to eyes and skin.
R43	May cause sensitisation by skin contact.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.