

TECHNICAL HEALTH AND DATA SHEET

PRODUCT:-	LINE MARKING PAINT
REFERENCE:-	W/463/1
COLOUR:-	WHITE, YELLOW, RED, BLUE, GREEN, OTHERS ON REQUEST.
FINISH:-	SEMI-MATT
TYPE:-	ACRYLIC COPOLYMER, WATER THINNABLE
TYPICAL SG:-	1.35 AT 20°C
TYPICAL VISCOSITY:-	3.0 POISE AT 25°C
TYPICAL TOTAL SOLIDS:-	52.6% BY WEIGHT
FLASH POINT:-	NON-FLAMMABLE
RECOMMENDED THINNERS:-	WATER
APPLICATION:-	BRUSH, ROLLER OR SPRAY DO NOT APPLY WHEN THE TEMPERATURE IS BELOW 5°C
*COVERAGE GUIDE:-	10 SQ. METRES/LITRE
*DRYING TIME:-	SURFACE DRY - 1 HOUR THROUGH DRY - 4 HOURS (COLD DAMP CONDITIONS WILL PROLONG THESE TIMES)
USES:-	AS A WATER BASED LINE MARKING PAINT
STORAGE:-	PROTECT FROM FROST AND ABNORMAL HEAT
HEALTH & SAFETY:-	SEE SHEET HSD 'B'

*BY BRUSH TO A DRIED FILM THICKNESS OF 25 MICRONS AT 20°C.