

Key Points

Water Based Low odour Non Flammable

Description: A specially formulated water based coating, combining high build modified Acrylic resins to provide a tough, durable, exterior or interior finish suitable for use on a wide range of substrates.

Uses: Ideal as a decorative, protective coating for most building surfaces such as concrete, brickwork, rendering, asbestos, asphalt, bitumen, iron, steel, aluminium, lead, zinc, copper, timber, slate, Galvanising without the need for etch primer and most plastics and rubberised surfaces after suitable preparation.

Preparation: The substrate must be sound, dry and free from oil and grease. Cleaning should be carried out with liquid detergent solution, rinsed with clean water and allowed to dry. Surfaces which are contaminated with lichen or moss should be brushed clean, treated with Anti-Fungal Wash and allowed to dry. Any structural repairs should be carried out before application of MSP. Plastic, metal and timber surfaces should be rubbed down with abrasive paper. Ferrous metals should be primed with an appropriate anti corrosive primer.

Application: Apply by Brush or Roller. No primer or undercoat is necessary unless used on ferrous metal or where staining could occur. For porous substrates thin the first coat with 30% water. Do not apply at temperatures below 8°C.

Coverage: **Approximately 12-14 sq. metres/litre**, depending on texture and porosity of substrate.

Drying: Normally recoatable after 4 hours. Optimum hardness is reached after 2 weeks. Ensure good ventilation during application and drying.

Flash Point: Not applicable.

Clean up: Warm soapy water.

Pack sizes: 250ml 750ml 2.5litres 5litres 20litres

Storage: Protect from frost. Keep out of reach of children.

Colour Range: See colour card