



SAFETY DATA SHEET

Dac-Hydro-Alu

1. Identification of the substance/preparation and of the company/undertaking

Product name and/or code : Dac-Hydro-Alu
Manufacturer : Rust-Oleum Netherlands BV, PO. Box 138, NL-4700 AC Roosendaal, The Netherlands
 NV Martin Mathys, Kolenberg 23, B-3545 Zelem, Belgium
Emergency telephone number : Rust-Oleum: (+31)165-593636; Fax (+31)165-593600
 Martin Mathys: (+32)13-460200; Fax (+32)13-460201
Product use : Paint.

2. Composition/information on ingredients

Substance/preparation : Preparation

Chemical name*	CAS No.	%	EC number	Classification
Europe Naphtha (petroleum), hydrotreated heavy	64742-48-9	1 - 2.5	265-150-3	R10 Xn; R65 R66
See section 16 for the full text of the R Phrases declared above				

* Occupational Exposure Limit(s), if available, are listed in section 8

3. Hazards identification

The preparation is not classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : This product is not classified according to the EU regulations.

4. First aid measures

First-Aid measures

General : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

Inhalation : Remove to fresh air. Keep person warm and at rest. Get medical attention if irritation develops.

Skin Contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

Eye Contact : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open.

Ingestion : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting.

See section 11 for more detailed information on health effects and symptoms.

5. Fire-fighting measures

Extinguishing Media : Recommended: alcohol resistant foam, CO₂, powders, water spray.
 Not to be used : waterjet.

Recommendations : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not release runoff from fire to sewers or waterways.

Special fire-fighting procedures : Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

6. Accidental release measures

- Personal precautions** : Avoid breathing vapors of this product. Refer to protective measures listed in sections 7 and 8.
- Spill** : Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth, and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses. Clean preferably with a detergent; avoid use of solvents. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

Note: see section 8 for personal protective equipment and section 13 for waste disposal.

7. Handling and storage

- Handling** : Keep container tightly closed.
- Avoid contact with skin and eyes. Avoid breathing vapors of this product.
- Eating, drinking and smoking should be prohibited in area where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.
- Put on appropriate personal protective equipment (see Section 8).
- Never use pressure to empty: container is not a pressure vessel. Always keep in containers made from the same material as the original one.
- Comply with the health and safety at work laws.
- Storage** : Store in accordance with local regulations. Do not store below 0°C (32°F). Must be stored in a dry location. Keep container in a well-ventilated place. Keep away from: oxidizing agents, strong alkalis, strong acids.
- No smoking. Prevent unauthorized access. Containers that are opened must be carefully resealed and kept upright to prevent leakage.
- Do not empty into drains..

8. Exposure controls/personal protection

- Engineering measures** : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction.
- Hygiene measures** : Keep away from food, drink and animal feeding stuffs. It is generally recognized that contact lenses should not be worn when working with chemicals because contact lenses may contribute to the severity of an eye injury. Apply water proof skin cream before beginning work. Separate contaminated work clothes from street clothes. Launder before reuse. Remove material from shoes and clean personal protective equipment. After handling, always wash hands thoroughly with soap and water.

<u>Ingredient name</u>	<u>Occupational exposure limits</u>
Europe Naphtha (petroleum), hydrotreated heavy	CEFIC-HSPA (Europe, 2000). Notes: Recommended by manufacturer (200 ppm) TWA: 1200 mg/m ³ 8 hour(s).

Recommended monitoring procedures : No special measures are required. General ventilation is typically sufficient. Provide eye wash and quick drench shower close to work station. Air monitoring can be used to determine ventilation requirements and compliance with applicable employee exposure limits.

Occupational exposure controls : Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits.

Personal protective equipment

Respiratory system : In case of insufficient ventilation, wear suitable respiratory equipment.

Hands : For prolonged or repeated handling, use gloves: nitrile.

Barrier creams may help to protect the exposed areas of the skin, but should not be applied once exposure has occurred.

Skin and body : Wear overalls or long sleeved shirt.

Eyes : Use safety eyewear designed to protect against splash of liquids.

9. Physical and chemical properties

Physical state	: Liquid.
Color	: Silvery.
Odor	: Faint Odor
Specific gravity	: 1.3 kgs/l
pH	: 8 to 9 [Basic.]
Melting point	: 0°C (32°F)
Boiling point	: > 100 °C Nonflammable, but will burn on prolonged exposure to flame or high temperature. No unusual hazard if involved in a fire.
Vapor pressure	: 2.3 kPa (17.3 mmHg)(at 20°C)(water)
Vapor density	: >1 (Air = 1)
Evaporation rate	: <1 compared to Butyl acetate.
Solubility	: Soluble in cold water, hot water.
Viscosity	: Dynamic: 5000 to 6000 cP
Volatility (%)	: 51 to 53% (v/v). 48 to 50% (w/w).
VOC (W/W):	: <65 (g/l).

10. Stability and reactivity

Stable under recommended storage and handling conditions (see section 7).

Hazardous decomposition products: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

11. Toxicological information

There is no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is classified for eco-toxicological properties accordingly. See Sections 2 and 15 for details. See Chapters 2 and 15 for details.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage.

Potential acute health effects

Ingestion	: No known acute effects of this product resulting from ingestion. However, in light of good industrial hygiene, exposure to any chemical should be kept to a minimum.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known acute effects of this product resulting from skin contact. Not considered a skin irritant or skin corrosive.
Eye contact	: Slightly hazardous in case of eye contact.
Other toxic effects on humans	: Alcohol consumption before or after exposure may increase adverse effects.

Acute Data (LD₅₀, LC₅₀) - Toxicity to Test Animals

<u>Ingredient name</u>	<u>Test</u>	<u>Result</u>	<u>Route</u>	<u>Species</u>
Naphtha (petroleum), hydrotreated heavy	LD50	>5000 mg/kg	Oral	Rat
	LD50	>3000 mg/kg	Dermal	Rabbit
	LC50	>5.5 mg/l (4 hour(s))	Inhalation	Rat

Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

12. Ecological information

There is no data available on the preparation itself.
Do not allow to enter drains or watercourses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment.

Ecotoxicity data

<u>Ingredient name</u>	<u>Result</u>	<u>Period</u>	<u>Species</u>
Naphtha (petroleum), hydrotreated heavy	Fish (LC50)	4 hour(s)	>1000 mg/l
	Daphnia (EC50)	4 hour(s)	>1000 mg/l
	Algae (IC50)	4 hour(s)	>1000 mg/l

Dac-Hydro-Alu

Ingredient name	Persistence/degradability						Bioaccumulative potential		
	BOD ₅	COD	ThOD	Aquatic half-life	Photolysis	Biodegradability	LogP _{ow}	BCF	Potential
Naphtha (petroleum), hydrotreated heavy				< 28 day(s)	>50%; < 28 day(s).	Readily			

Mobility : Non-volatile.

13. Disposal considerations

Do not allow to enter drains or watercourses.
Dispose of according to all federal, state and local applicable regulations.

Methods of disposal ; : Type: Hazardous chemical waste.
Waste of residues ; : Location: European Union
Contaminated packaging : Classification: - (Not classified.)
Disposal.: via incineration
Storage: * (No specific storage is required. Use shelves or cabinets sturdy enough to bear the weight of the chemicals. Be sure that it is not necessary to strain to reach materials, and that shelves are not overloaded.)
Recycling: * (Not applicable.)

European waste catalogue (EWC) : 080115

14. Transport information

International transport regulations

Regulatory Information	UN number	Proper shipping name	Class	Packing group	Label	Additional information
ADR/RID Class	--	-	-	-		Not controlled under ADR (Europe).
IMDG Class	--	-	-	-		Not controlled under IMDG.
IATA-DGR Class	--	-	-	-		Not controlled under IATA.

This preparation is not classified as dangerous according to international transport regulations, (ADR/RID, IMDG, ICAO/IATA).

15. Regulatory information

EU Regulations : This preparation is not classified as dangerous according to the EC Directive 88/379/EEC.
Risk Phrases : This product is not classified according to the EU regulations.
Safety Phrases : S56- Dispose of this material and its container at hazardous or special waste collection point.
Product use : Classification and labeling have been performed according to EU directives 67/548/EEC, 1999/45/EC including amendments and the intended use.
- Industrial applications.
Additional warning phrases : Contains epoxy constituents. See information supplied by the manufacturer. This information is provided by the current Safety Data Sheet. Contains (Bisphenol-A-epoxy resin avg.mol.wght. <700). May produce an allergic reaction. Safety Data Sheet available for professional user on request.
EC Statistical classification (Tariff Code) : 3209 10 00

16. Other information

Full text of R-phrases appearing in section 2: : R10- Flammable.
R65- Harmful: may cause lung damage if swallowed.
R66- Repeated exposure may cause skin dryness or cracking.

Designation of symbols in Section 2 : Xn - Harmful

HISTORY

Date of printing : 16-11-2004. **Date of issue** : 9-6-2004.

Dac-Hydro-Alu

Version : 1.04

Prepared by : RPM Europe - Department Environment, Health and Safety

Notice to Reader

This is an internet download copy, for information purposes only. The information in this sheet is believed to be in compliance with EU regulations, but neither Rust-Oleum nor any of its subsidiaries can guarantee it's full correctness. Any data contained herein may possibly not be up-to-date and specific national regulations apply in addition to the EU regulations. Up-to-date information and specific national editions are available upon request from our H&S dept. at fax nr. +31 165 593 600 or email address RPMEUROHAS@RO-M.COM. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards may be described herein, we cannot guarantee that these are the only hazards that exist.

©Copyright by Rust-Oleum Netherlands B.V. / Martin Mathys B.V.

An  Company

Page: 5/5