



SAFETY DATA SHEET

9200 WB Rust-O-Thane®

1. Identification of the substance/preparation and of the company/undertaking

- Product name and/or code** : 9200 WB Rust-O-Thane®
- Manufacturer** : Rust-Oleum Netherlands BV, PO. Box 138, NL-4700 AC Roosendaal, The Netherlands
NV Martin Mathys, Kolenberg 23, B-3545 Zelem, Belgium
- Emergency telephone number** : Rust-Oleum: (+31)165-593636; Fax (+31)165-593600
Martin Mathys: (+32)13-460200; Fax (+32)13-460201
- Product use** : Base for 2-component paint.

2. Composition/information on ingredients

Substance/preparation : Preparation

To present knowledge of the supplier, this product does not contain any hazardous ingredients in accordance to EU regulations or National regulations.

* Occupational Exposure Limit(s), if available, are listed in section 8

3. Hazards identification

The preparation is not classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : This product is not classified according to the EU regulations.

4. First aid measures

First-Aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if irregular breathing, or respiratory arrest occurs provide artificial respiration or oxygen by trained personnel. Give nothing by mouth. If unconscious, place in recovery position and seek medical advice.
- Skin Contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
- Eye Contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open.
- Ingestion** : If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do not induce vomiting.

See section 11 for more detailed information on health effects and symptoms.

5. Fire-fighting measures

- Extinguishing Media** : Recommended: alcohol resistant foam, CO₂, powders, water spray.
Not to be used : waterjet.
- Recommendations** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not release runoff from fire to sewers or waterways.
- Special fire-fighting procedures** : Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

6. Accidental release measures

- Personal precautions** : Due to the organic solvents content of the preparation:
Exclude sources of ignition and ventilate the area. Avoid breathing vapor or mist. Refer to protective measures listed in sections 7 and 8.
- Spill** : Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth, and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses. Clean preferably with a detergent; avoid use of solvents. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

Note: see section 8 for personal protective equipment and section 13 for waste disposal.

7. Handling and storage

- Handling** : Keep container tightly closed. Keep away from heat, sparks and flame.
- Avoid contact with skin and eyes. Use only in well-ventilated areas. Avoid the inhalation of dust, particulates and spray mist arising from the application of this preparation. Avoid inhalation of dust from sanding.
- Eating, drinking and smoking should be prohibited in area where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.
- Put on appropriate personal protective equipment (see Section 8).
- Comply with the health and safety at work laws.
- Storage** : Store in accordance with local regulations. Observe label precautions. Store in a cool, well-ventilated area away from incompatible materials and ignition sources. Keep away from heat and direct sunlight.
- Due to the organic solvents content of the preparation:
 Keep away from: oxidizing agents, strong alkalis, strong acids.
 No smoking. Prevent unauthorized access. Containers that are opened must be carefully resealed and kept upright to prevent leakage.
 Do not empty into drains..

8. Exposure controls/personal protection

- Engineering measures** : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn.
- Hygiene measures** : Keep away from food, drink and animal feeding stuffs. Never eat, drink or smoke in work areas. Practice good personal hygiene when using this material, especially before eating, drinking, smoking, using the toilet, or applying cosmetics. It is generally recognized that contact lenses should not be worn when working with chemicals because contact lenses may contribute to the severity of an eye injury.
- Occupational exposure limits** : Not available.
- Recommended monitoring procedures** : Air monitoring should be used to determine ventilation requirements and compliance with applicable employee exposure limits. Frequency of monitoring and levels at which suspension and re-exposure to product may take should be at the discretion of an occupational physician.
- Occupational exposure controls** : Good general ventilation should be sufficient to control airborne levels. Wear appropriate respirator when ventilation is inadequate.
- Personal protective equipment**
- Respiratory system** : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.
- Hands** : For prolonged or repeated handling, use gloves: nitrile, neoprene, latex rubber.
- Barrier creams may help to protect the exposed areas of the skin, but should not be applied once exposure has occurred.
- Skin and body** : Personnel should wear protective clothing.
- Eyes** : Use safety eyewear designed to protect against splash of liquids.

9. Physical and chemical properties

- Physical state** : Liquid.
- Color** : Depending on product number
- Specific gravity** : 1 to 1.2 (Water = 1)
- pH** : 9 [Basic.]
- Melting point** : 0°C (32°F)
- Boiling point** : 100°C (212°F)
- Vapor pressure** : The highest known value is 2.3 kPa (17.3 mm Hg) (at 20°C) (Water).
- Solubility** : Partially soluble in cold water, hot water.
- Viscosity** : Dynamic: 950 cP
- Volatility (%)** : 50 to 56% (v/v). 54 to 58% (w/w).
- VOC (W/W):** : <20 (g/l).

10. Stability and reactivity

Stable under recommended storage and handling conditions (see section 7).

Hazardous decomposition products: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

11. Toxicological information

There is no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is classified for eco-toxicological properties accordingly. See Sections 2 and 15 for details.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage.

Potential acute health effects

Ingestion	: Slightly hazardous in case of ingestion.
Inhalation	: Slightly hazardous in case of inhalation.
Skin contact	: Slightly hazardous in case of skin contact (irritant, sensitizer). Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering.
Eye contact	: Slightly hazardous in case of eye contact (irritant).
Other toxic effects on humans	: May cause sensitization by skin contact. Repeated exposure may cause allergic skin rash, itching, swelling. The onset of symptoms may be delayed. Persons with a history of skin sensitization problems should not be employed in any process in which this preparation is used.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

12. Ecological information

There is no data available on the preparation itself.
Do not allow to enter drains or watercourses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment.

Mobility : Non-volatile.

13. Disposal considerations

Do not allow to enter drains or watercourses.
Dispose of according to all federal, state and local applicable regulations.

Methods of disposal ;	: Type: Hazardous chemical waste.
Waste of residues ;	Location: European Union
Contaminated packaging	Classification: - (Not classified.) Disposal.: via incineration Storage: * (No specific storage is required. Use shelves or cabinets sturdy enough to bear the weight of the chemicals. Be sure that it is not necessary to strain to reach materials, and that shelves are not overloaded. Storage of controlled substances must comply with applicable regulatory security requirements.) Recycling: * (Not applicable.)

European waste catalogue (EWC) : 080115

14. Transport information

International transport regulations

Regulatory Information	UN number	Proper shipping name	Class	Packing group	Label	Additional information
ADR/RID Class	Not regulated.	-	-			-
IMDG Class	Not regulated.	-	-			-

9200 WB Rust-O-Thane®

IATA-DGR Class	Not regulated.	-	-			-
----------------	----------------	---	---	--	--	---

This preparation is not classified as dangerous according to international transport regulations, (ADR/RID, IMDG, ICAO/IATA).

15. Regulatory information

EU Regulations

: The product is labelled as follows, in accordance with local regulations:

Risk Phrases

: This product is not classified according to the EU regulations.

Safety Phrases

: S23- Do not breathe vapor or spray.
S51- Use only in well-ventilated areas.

Product use

: Classification and labeling have been performed according to EU directives 67/548/EEC, 1999/45/EC including amendments and the intended use.
- Industrial applications, Used by Spraying.

EC Statistical

: 3209 90 00

classification (Tariff Code)

16. Other information

Full text of R-phrases appearing in section 2: : Not applicable.

Designation of symbols in Section 2 : Not applicable.

HISTORY

Date of printing : 16-11-2004. **Date of issue** : 30-6-2004.

Version : 1.02

Prepared by : RPM Europe - Department Environment, Health and Safety

Notice to Reader

This is an internet download copy, for information purposes only. The information in this sheet is believed to be in compliance with EU regulations, but neither Rust-Oleum nor any of its subsidiaries can guarantee it's full correctness. Any data contained herein may possibly not be up-to-date and specific national regulations apply in addition to the EU regulations. Up-to-date information and specific national editions are available upon request from our H&S dept. at fax nr. +31 165 593 600 or email address RPMEUROHAS@RO-M.COM. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards may be described herein, we cannot guarantee that these are the only hazards that exist.

©Copyright by Rust-Oleum Netherlands B.V. / Martin Mathys B.V.