

PRODUCT DATA

FK 111 FUNGICIDAL CLEANING SOLUTION

DESCRIPTION

RUST-OLEUM® FK 111 Fungicidal Cleaning Solution is an easy-to-use, non-flammable and virtually odour-free cleaning solution.

RECOMMENDED USES

RUST-OLEUM FK 111 Fungicidal Cleaning Solution should be used to kill mould, mildew and bacteria; it removes oil, grease, protein's and many other surface contaminations; it neutralizes acids and acidic salts. FK 111 Fungicidal Cleaning Solution should be applied with a stiff nylon brush or broom.

TECHNICAL DATA

Colour: bluish liquid

VOC-content: 0 g/l

Coverage

Theoretical: 6 - 8 m²/l

Practical: Practical usage depends on many factors such as type and amount of contaminants, shape of the substrate and material losses during application.

DIRECTION FOR USE

To ensure homogeneity shake well before use.

Scrape or sweep away grease, oil, dirt, mould and all other surface contaminations as much as possible.

Scrub FK 111 Fungicidal Cleaning Solution into the surface using a stiff (nylon) bristle brush. Allow to stand for 5 to 10 minutes and clean thoroughly by flushing with plenty of fresh water. FK 111 Fungicidal Cleaning Solution should normally be applied as delivered. However, it can be diluted with fresh water up to 1 : 2 parts, when applied on surfaces which are slightly contaminated.

FK 111 Fungicidal Cleaning Solution can also be used as an additive for (high-pressure) steam cleaning, in concentrations from 5% up to 25% for severely contaminated surfaces, followed by (steam) cleaning or rinsing with fresh water.

After cleaning, remove any remaining water and allow to dry completely, as moisture left on the surface or entrapped into pores may cause failure of the coating system.

Do not allow the FK111 Fungicidal Cleaning Solution to dry before rinsing!

Large surface areas or poor drying conditions may require longer drying times before a coating system can be applied.

APPLICATION CONDITIONS

Temperature of air, substrate and material between 5 and 35°C.

SAFETY

Consult Safety Data Sheet and Safety Information printed on the can.

SHELLIFE / STORAGE CONDITIONS

5 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Rust-Oleum Netherlands B.V.

Braak 1, 4704 RJ
P.O. Box 138, 4700 AC
Roosendaal, The Netherlands
T +31 (0)165 593 636
F +31 (0)165 593 600
info.nl@ro-m.com
www.ro-m.com

N.V. Martin Mathys S.A

Kolenbergstraat 23
B - 3545 Zelem
Halen, Belgium
T +32 (0)13 460 200
F +32 (0)13 460 201
info.be@ro-m.com
www.ro-m.com

Rust-Oleum France S.A

11, Rue Jules Verne, B.P. 39
95322 St-Leu-la-Forêt Cedex
France
T +33 (0)130 400 044
F +33 (0)130 409 980
info.fr@ro-m.com
www.ro-m.com

Rust-Oleum UK Ltd.

Unit 5D, Alexandra Way
Ashchurch B. Centre,
Tewkesbury, Gloucestershire
GL20 8NB, United Kingdom
T +44 (0)1684 273 333
F +44 (0)1684 273 331
info.uk@ro-m.com
www.ro-m.com

Rust-Oleum Mathys Italia s.r.l.

Via Mazzetta 36, 13856
Vigliano Biellese BI, Italia
T +39 015 8122 160
F +39 015 8122 161
info.it@ro-m.com
www.ro-m.com