

PREPDECK Technical Data Sheet

Description

Prepdeck Stripper/Cleaner is a professional, high grade product specially designed for the removing of old solid and semi transparent stains, grade stamps, mill glaze and other surface contaminants from wood

Where to use Prepdeck Stripper/Cleaner

Prepdeck Stripper/Cleaner may be used on soft or hardwoods and thermo (burnt) wood. It is ideal for garden decks, fences, cladding, log homes and garden furniture

TECHNICAL DATA

Composition: 12.5% Sodium Hydroxide

Shelf Life: 2 years minimum

VOC: N/A

Flash Point: N/A

Temperature Application: 0°C – 40°C

Coverage: Undiluted one 1 litre of Prepdeck Stripper/Cleaner will strip up to 4m²

Application Method

Soft brush or broom, Stiff bristle/nylon brush or broom, Garden sprayer, Power washer or hose. If cleaning vertical surfaces, work from bottom to top to avoid streaking. Do not apply on a hot surface; product will dry to quickly.

Prepdeck Stripper/Cleaner is very slippery. Take special care when walking on it

Limitations

- For exterior use only
- Avoid contact with aluminium and tin metals

Sizes: 2.5ltr

Clean Up

- Clean all tools and equipment with water
- Store and maintain equipment as directed by manufacturer
- Store any leftover Prepdeck Stripper/Cleaner in a tightly sealed, glass or plastic container

Dilutions: SOFTWOOD i.e. Pine, Douglas Fir

HARDWOOD

New:

- Removing Finishes & Grade Stamps – Use Prepdeck Undiluted
- Removing Mill Glaze – Use Prepdeck diluted 1:5 with water

Weathered:

- Removing Finishes – Use Prepdeck Undiluted
- Cleaning – Use Prepdeck diluted 1:20 with water
- SOFTWOODS with high Tanin/Extractive content i.e. Cedar, Redwood

THERMO (BURNT) WOOD

New:

- Removing Finishes & Grade Stamps – Use Prepdeck Undiluted
- Removing Mill Glaze – Contact Igoe International Ltd for Specific Advice

Weathered:

- Removing Finishes – Use Prepdeck Undiluted
- Cleaning – Contact Igoe International Ltd for specific advice

Note: Prepdeck will not remove epoxy or urethane coatings. For advice on removing these types of coatings please contact our technical department on the number below.

DIRECTION FOR USE

Removing Finishes and Grade Stamps

1. Remove all surface debris
2. Shake container well before use
3. Use full-strength
4. Apply Prepdeck Stripper/Cleaner in sections you can complete within 20-30 minutes
5. Keep the surface wet with Prepdeck Stripper/Cleaner while it is working. Do not allow it to dry
6. When the finish begins to lift, scrub as needed with a stiff bristle brush. Do not use a wire brush
7. Rinse with large amounts of fresh water, using the highest pressure from the water source available, or use a pressure washer at 500 - 1000 psi (35 - 70 bars)
8. Allow the wood to dry thoroughly (minimum of 2 - 3 warm, dry days) before refinishing
9. To remove grade stamps, use full strength and scrub until the stamp is gone, then rinse thoroughly

Removing Mill Glaze and Cleaning

1. Remove all surface debris
2. Shake container well before use
3. Dilute according to directions above
4. Apply Prepdeck Stripper/Cleaner dilution in sections you can complete within 15 minutes
5. Keep surface wet with Prepdeck while it is working. Do not allow it to dry
6. Scrub surface with a stiff bristle/nylon brush Do not use a wire brush
7. Rinse with large amounts of fresh water, using the highest pressure from the water source available, or use a pressure washer at 500 - 1000 psi (35 - 70 bars)
8. Allow the wood to dry thoroughly (minimum of 2 - 3 warm, dry days) before refinishing

Note: Prepdeck Stripper/Cleaner may darken some woods such as Cedar, Redwood and Hardwoods. To brighten wood after using Prepdeck Stripper/Cleaner, dilute Net-trol Wood Cleaner & Colour Restorer 1:4 with water for solvent based finishes i.e. Textrol or use Bleach diluted 1:3 with water for acrylic finishes i.e. Tropitech (Spa-n-Deck) and apply to the surface. Wait 15 minutes or until timber has changed colour i.e. lightened, change of colour should be clearly noticeable with the naked eye. Then rinse off.

Do not allow the surface to dry prior to using the Net-trol or Bleach solution. Do not mix Bleach and Net-trol together

Good Application Practice

Cover everything you do not wish to treat including plants and shrubs

Wear skin and eye protection

Health and Safety

Material Safety Data Sheets for this and all other Owatrol products are freely available from the place of purchase or the address below. Store in secure dry conditions inaccessible to children and animals. Containers should be kept closed during storage. Do not empty into drains, watercourses or access routes to septic tanks.