



SAFETY DATA SHEET

ROADLINE PAINT

Page 1

Issued: 19/01/2004

Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: ROADLINE PAINT
Company name: FLAG Paints Ltd
8 Springfield Road
Springfield Industrial Estate
Burnham on Crouch
Essex
CM0 8UA
United Kingdom
Tel: +44 (0) 1621 785 173
Fax: +44 (0) 1621 785 393
Emergency tel: +44 (0) 1621 785 173

2. HAZARDS IDENTIFICATION

Main hazards: Harmful by inhalation and in contact with skin. Irritating to skin.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: XYLENE 30-50%
EINECS: 215-535-7 CAS: 1330-20-7
[-] R10; [Xn] R20/21; [Xi] R38
• ETHYLBENZENE 1-10%
EINECS: 202-849-4 CAS: 100-41-4
[F] R11; [Xn] R20

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be mild irritation at the site of contact.
Eye contact: There may be irritation and redness.
Ingestion: There may be soreness and redness of the mouth and throat.
Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4. FIRST AID MEASURES (ACTION)

Skin contact: Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin.
Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.
Ingestion: Do not induce vomiting. Wash out mouth with water. Consult a doctor.
Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Alcohol or polymer foam. Dry chemical powder. Carbon dioxide.
Exposure hazards: Highly flammable.

[cont...]

SAFETY DATA SHEET

ROADLINE PAINT

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Contain spillage with sand or earth, sweep up and dispose of in accordance with a recognised method of waste disposal.

7. HANDLING AND STORAGE

Handling requirements: Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Smoking is forbidden.

Storage conditions: Store in cool, well ventilated area. Keep away from sources of ignition.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**Workplace exposure limits**

WEL (8 hr TWA): 100-150ppm

Hazardous ingredients: XYLENE

WEL (8 hr TWA): 220 mg/m³ WEL (15 min STEL): 441 mg/m³

- ETHYLBENZENE

WEL (8 hr TWA): 441 mg/m³ WEL (15 min STEL): 552 mg/m³

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Gas/vapour filter, type A: organic vapours (EN141).

Hand protection: Viton gloves. Nitrile gloves.

Eye protection: Safety goggles.

Skin protection: Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Odour: Characteristic odour

Oxidising: Non-oxidising (by EC criteria)

Viscosity: Viscous

Viscosity value: 4-6poise

Boiling point/range°C: 137-143

Flash point°C: 25

Autoflammability°C: <500

Vapour pressure: 6.72nmgh

Relative density: 1.1-1.3

SAFETY DATA SHEET

ROADLINE PAINT

10. STABILITY AND REACTIVITY**Stability:** Stable under normal conditions.**Conditions to avoid:** Sources of ignition.**Materials to avoid:** Oxidising agents.**Haz. decomp. products:** In combustion emits toxic fumes of carbon dioxide.**11. TOXICOLOGICAL INFORMATION****Hazardous ingredients:** XYLENE
ORL MUS LD50 2119 mg/kg
ORL RAT LD50 4300 mg/kg
SCU RAT LD50 1700 mg/kg

- ETHYLBENZENE
IPR MUS LD50 2624 µl/kg
ORL RAT LD50 3500 mg/kg

Chronic toxicity: Danger of cumulative effects through inhalation.**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.**12. ECOLOGICAL INFORMATION****Mobility:** Highly volatile.**Persistence and degradability:** Not biodegradable.**Bioaccumulative potential:** No bioaccumulation potential.**Other adverse effects:** Toxic to aquatic organisms.**13. DISPOSAL CONSIDERATIONS****Disposal operations:** The relevant EC directives and local, regional and national regulations must be complied with.**Disposal of packaging:** Dispose of as normal industrial waste.**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.**14. TRANSPORT INFORMATION****ADR / RID**

UN no: 1263	ADR Class: 3
Packing group: III	Classification code: F1
Shipping name: PAINT	
Labelling: 3	Hazard ID no: 30



SAFETY DATA SHEET

ROADLINE PAINT

IMDG / IMO

UN no: 1263 **Class:** 3
Packing group: III **EmS:** F-E,S-E
Marine pollutant: .
Labelling: 3

IATA / ICAO

UN no: 1263 **Class:** 3
Packing group: III
Packing instructions: 309(P&CA); 310(CAO)
Labelling: 3

15. REGULATORY INFORMATION

Hazard symbols: Harmful.



Risk phrases: R20/21: Harmful by inhalation and in contact with skin.
R38: Irritating to skin.

Safety phrases: S36/37: Wear suitable protective clothing and gloves.

Haz. ingredients (label): XYLENE

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.3: R10: Flammable.
R20/21: Harmful by inhalation and in contact with skin.
R38: Irritating to skin.
R11: Highly flammable.
R20: Harmful by inhalation.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.