



*J. McRatcliffe*



Ardenbrite™

classidur®

SOLIGNUM®

SAFETY DATA SHEET  
ARCHITECTURAL WB JACOBAN

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME ARCHITECTURAL WB JACOBAN  
PRODUCT NO. PS5400010  
APPLICATION Intended for use as a water-borne, decorative, coating for timber.  
SUPPLIER Blackfriar Paints Ltd  
Portobello Industrial Estate  
Birtley  
County Durham  
DH3 2RE  
+44(0)191 4106611  
+44(0)191 4113147  
blackfriar@tor-coatings.com  
CONTACT PERSON ian.mccormack@tor-coatings.com

2 HAZARDS IDENTIFICATION

May cause sensitisation by skin contact.

CLASSIFICATION R43.

ENVIRONMENT

The product is not expected to be hazardous to the environment.

HUMAN HEALTH

In high concentrations, vapours and spray mists are narcotic and may cause headache, fatigue, dizziness and nausea. Vapours/aerosol spray may irritate the respiratory system. Risk of sensitisation or allergic reactions among sensitive individuals.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
ETHANEDIOL	203-473-3	107-21-1	1-5%	Xn;R22
FORMALDEHYDE ...%	200-001-8	50-00-0	< 1%	Carc3;R40 T;R23/24/25 C;R34 R43
2-(2-BUTOXYETHOXY)ETHANOL	203-961-6	112-34-5	< 1%	Xi;R36
2-OCTYL-2H-ISOTHIAZOL-3-ONE	247-761-7	26530-20-1	< 1%	T;R23/24 C;R34 Xn;R22 R43 N;R50/53
METHYL-2H or METHYL-4 (3:1) Mixture of EC NO 220-239-6		55965-84-9	< 1%	T;R23/24/25 C;R34 R43 N;R50/53
AMMONIA ...%	215-647-6	1336-21-6	< 1%	C;R34 N;R50
ETHANOL	200-578-6	64-17-5	< 1%	F;R11

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

GENERAL INFORMATION

General first aid, rest, warmth and fresh air. Do not give victim anything to drink if they are unconscious. Get medical attention if any discomfort continues.

INHALATION

Place unconscious person on the side in the recovery position and ensure breathing. If respiratory problems, artificial respiration/oxygen. Get medical attention if any discomfort continues.

INGESTION

Immediately rinse mouth and drink plenty of water or milk. Keep person under observation. Do not induce vomiting. If vomiting occurs, keep head low. Transport immediately to hospital and take these instructions.

SKIN CONTACT

Use appropriate hand lotion to prevent defatting and cracking of skin. Immediately remove contaminated clothing. Wash off promptly and flush contaminated skin with water. Promptly remove clothing if soaked through and flush skin with water.

## ARCHITECTURAL WB JACOBAN

### EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Get medical attention promptly if symptoms occur after washing.

## 5 FIRE-FIGHTING MEASURES

### EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

### SPECIAL FIRE FIGHTING PROCEDURES

Use pressurised air mask if product is involved in a fire. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

### UNUSUAL FIRE & EXPLOSION HAZARDS

Fire causes formation of toxic gases.

### PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

## 6 ACCIDENTAL RELEASE MEASURES

### PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

### ENVIRONMENTAL PRECAUTIONS

Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

### SPILL CLEAN UP METHODS

Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.

## 7 HANDLING AND STORAGE

### USAGE PRECAUTIONS

Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

### STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container. Avoid contact with oxidising agents.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
2-(2-BUTOXYETHOXY)ETHANOL		10 ppm	67.5 mg/m <sup>3</sup>	15 ppm	101.2 mg/m <sup>3</sup>	
AMMONIA ...%	WEL	25 ppm	18 mg/m <sup>3</sup>	35 ppm	25 mg/m <sup>3</sup>	
ETHANEDIOL	WEL		52 mg/m <sup>3</sup> (Sk)		104 mg/m <sup>3</sup> (Sk)	
ETHANOL	WEL	1000 ppm	1920 mg/m <sup>3</sup>			
FORMALDEHYDE ...%	WEL	2 ppm	2,5 mg/m <sup>3</sup>	2 ppm	2,5 mg/m <sup>3</sup>	

WEL = Workplace Exposure Limit.

### INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

### PROTECTIVE EQUIPMENT



### PROCESS CONDITIONS

Provide eyewash station.

## ARCHITECTURAL WB JACOBAN

### ENGINEERING MEASURES

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined workplace exposure limit is not exceeded. All handling to take place in well-ventilated area.

### RESPIRATORY EQUIPMENT

Provide adequate ventilation. Observe Workplace Exposure Limits and minimise the risk of inhalation of vapours.

### HAND PROTECTION

Protective gloves should be used if there is a risk of direct contact or splash.

### EYE PROTECTION

Wear splash-proof eye goggles to prevent any possibility of eye contact.

### OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

### HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid		
COLOUR	Dark Brown		
ODOUR	Mild		
SOLUBILITY	Miscible with water.		
RELATIVE DENSITY	1.18 approx 20	VAPOUR DENSITY (air=1)	Heavier than air
pH-VALUE, CONC. SOLUTION	7 - 8	FLASH POINT (°C)	>65

## 10 STABILITY AND REACTIVITY

### STABILITY

No particular stability concerns.

### HAZARDOUS DECOMPOSITION PRODUCTS

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

## 11 TOXICOLOGICAL INFORMATION

### INHALATION

In high concentrations, vapours may irritate throat and respiratory system and cause coughing. In high concentrations, vapours are narcotic and may cause headache, fatigue, dizziness and nausea.

### INGESTION

Gastrointestinal symptoms, including upset stomach.

### SKIN CONTACT

May cause sensitisation by skin contact.

### EYE CONTACT

Irritating and may cause redness and pain.

Name	2,2,4-Trimethyl-1,3-Pentanediol-Monoisobutyrate
Toxic Dose 1 - LD 50	6517 mg/kg (oral rat)
Toxic Dose 2 - LD 50	1600 - 3200 mg/kg (oral-mouse)
Name	MonoPropylene Glycol
Toxic Dose 1 - LD 50	>2000 mg/kg (oral rat)

## 12 ECOLOGICAL INFORMATION

### ECOTOXICITY

The product is not expected to be hazardous to the environment.

### ARCHITECTURAL WB JACOBAN

Name	2,2,4-Trimethyl-1,3-Pentanediol-Monoisobutyrate
Partition coefficient	P: 2951; Log P: 3.47
LC 50, 96 Hrs, FISH mg/l	19 - Oncorhynchus mykiss
EC 50, 48 Hrs, DAPHNIA, mg/l	19
IC 50, 72 Hrs, ALGAE, mg/l	15
Mobility	
Mobile.	
Degradability	
The product is biodegradable.	
Name	MonoPropylene Glycol
Partition coefficient	0.92 (water/Octanol)
LC 50, 96 Hrs, FISH mg/l	>100
EC 50, 48 Hrs, DAPHNIA, mg/l	>100

### 13 DISPOSAL CONSIDERATIONS

#### GENERAL INFORMATION

Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority.

#### DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements. Absorb in vermiculite or dry sand, dispose in licensed hazardous waste.

### 14 TRANSPORT INFORMATION

GENERAL The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

No transport warning sign required.

MARINE POLLUTANT No.

### 15 REGULATORY INFORMATION

#### LABELLING



Irritant

CONTAINS 2-OCTYL-2H-ISOTHIAZOL-3-ONE  
METHYL-2H or METHYL-4 (3:1) Mixture of EC NO 220-239-6

#### RISK PHRASES

R43 May cause sensitisation by skin contact.

#### SAFETY PHRASES

S24 Avoid contact with skin.  
S37 Wear suitable gloves.  
S46 If swallowed, seek medical advice immediately and show this container or label.  
S56 Dispose of this material and its container to hazardous or special waste collection point.

#### EU DIRECTIVES

System of specific information relating to Dangerous Preparations. 2001/58/EC. Dangerous Preparations Directive 1999/45/EC.

#### APPROVED CODE OF PRACTICE

Safety Data Sheets for Substances and Preparations. Classification and Labelling of Substances and Preparations Dangerous for Supply.

#### NATIONAL REGULATIONS

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689. Workplace Exposure Limits 2005 (EH40)

### 16 OTHER INFORMATION

#### INFORMATION SOURCES

Croner's Emergency Spillage Guide Croner's Emergency First Aid Guide Croner's Substances Hazardous to Health

## ARCHITECTURAL WB JACOBAN

### REVISION COMMENTS

Modified formulation. Format of Material Safety Data Sheet altered in accordance with the requirements of REACH Regulations

### ISSUED BY

T Smith

REVISION DATE 12/05/2009

REV. NO./REPL. SDS GENERATED 2

SDS NO. 15386

### SAFETY DATA SHEET STATUS

Approved.

### RISK PHRASES IN FULL

R11	Highly flammable.
R22	Harmful if swallowed.
R23/24	Toxic by inhalation and in contact with skin.
R23/24/25	Toxic by inhalation, in contact with skin and if swallowed.
R34	Causes burns.
R36	Irritating to eyes.
R37	Irritating to respiratory system.
R40	Limited evidence of a carcinogenic effect.
R43	May cause sensitisation by skin contact.
R50	Very toxic to aquatic organisms.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.