

DESCRIPTION

Johnstone's Anti Graffiti Coatings have been formulated to provide a permanent water based, easily cleaned Anti Graffiti finish for all types of internal and external surfaces including brick, masonry, natural stonework and previously painted surfaces. On application it provides a seamless tile-like surface enabling easy removal of graffiti, grease and other contaminants.

RECOMMENDED USES



Areas prone to graffiti

SPECIAL PROPERTIES

Class 0 fire rated
Polyurethane
Extremely durable

COLOUR RANGE

White, over 30 pastel shades

FINISH

Satin

VOLUME SOLID

36%

COVERAGE



Johnstone's Anti-Graffiti Coatings will cover approximately 10-12 square metres per litre depending on the nature and porosity of the surface.

DRYING TIME



Touch dry in 2 hours. Recoatable after 8 hours (minimum) and 72 hours (maximum).

TRANSPORTATION & STORAGE

To avoid the risk of spillage always store and transport in a secure upright position. **STORE AWAY FROM HEAT AND FLAME.**

THINNER

Do not thin.

VOC CONTENT

LOW VOC CONTENT 0.30-7.99%

VOC'S (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/I): 140g/l (2007) / 140g/l (2010).

This product contains max 80g/l VOC.

FILM THICKNESS

Wet: 88µm, dry: 30µm

SIZE

4.3L base, 700ml activator

PREPARATION

All surfaces to be coated should be clean, dry and free from loose and friable material. When applying directly over brick or stonework, use a wire brush to remove all loose material. Prime bare surfaces as appropriate. Treat mould or fungal growth with fungicidal wash as directed. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead.

APPLICATION



The base and activator should be mixed together. Do not mix part units. Ensure that the components are completely mixed together before application. Apply 2 coats by brush or roller. The mixture must be used within 4 hours of mixing. Do not apply in temperatures below 10°C.

CLEANING



Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Mixed, part used containers must not be resealed after use, due to pressure build up. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Ensure good ventilation during application and drying.
- Avoid contact with eyes and skin.
- Wear suitable protective clothing and gloves.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- Keep out of the reach of children.

PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.

