



Technical Data Sheet

Blackfriar Professional Line-Marking Paint

A quick drying and durable paint which provides clear, long-lasting markings on concrete, tarmac and painted surfaces. Ideal for indoor and outdoor use on kerbs, factory floors, car parks, schools and public areas.

Performance characteristics –

- 30 minute drying time.
- Solvent-based with excellent resistance to abrasion and cleaning products.
- Ideal for domestic, commercial and industrial traffic areas.
- Indoor and outdoor use.
- Brush or roller application.

Preparation

First ensure the surface to be painted is clean, thoroughly dry, and free from powdery deposits. If you are marking new concrete, make sure its has had at least 6 months to dry out before coating.

Application

Before use, stir the paint well with a broad stirrer. Apply by brush, roller or line marking machine. If applying by brush, apply a generous, even coat with the minimum of brushing. For best results, apply 2 coats. Do not apply this paint in damp, wet, or excessively hot conditions. If necessary, this paint may be thinned with up to 10% Blackfriar Professional Degreaser / Cleaner – it must not be thinned with white spirit. Please note that Blackfriar Professional Line Marking Paint is not suitable for use as a floor paint, only for marking lines.

Drying Time

30 minutes in good conditions.

Covering Capacity

Approximately 6m²/litre per coat depending on the porosity of the surface.

Clean Up

Remove as much product from application equipment as possible before washing with Blackfriar Professional Degreaser / Cleaner. Do not empty into drains or watercourses. Some local authorities have special facilities for the disposal of waste coatings.

Warning

Contains: Xylene

Flammable liquid and vapour.

Harmful in contact with skin. Causes skin irritation.

Harmful if inhaled.

Keep out of reach of children.

Keep away from heat/sparks/open flame/hot surfaces. - No smoking.

Use only outdoors or in a well ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

IF ON SKIN: Gently wash with plenty of soap and water.

Dispose of contents/container in recognised waste collection point.

VOC - EU limit value for this product (cat A/j): 500 g/l.

This product contains max 500 g/l VOC.

Whilst every effort is made to ensure the accuracy of colour, due to limitations of the print process, colour / finish shown is for guidance only.