



TECHNICAL DATASHEET

6-810

WATERBORNE DEGREASER

PRODUCT DESCRIPTION

Selemix Aqua 6-810 is a very low VOC waterborne degreasing agent, specifically designed to remove grease and oils from the surface of substrates prior to painting. Both solvent borne and waterborne products can be used over substrates cleaned with 6-810 waterborne degreaser.

APPLICATION GUIDE



This degreaser is supplied ready for use.



Apply using a clean, lint free cloth.



Note:

Application by either spray or brush is recommended over blasted surfaces. Rubber or PVC gloves, and eye protection should be worn during application.



Remove grease and residual degreaser with another clean, lint free cloth. Ensure that ALL liquid degreaser is wiped off.



When degreased area is dry, Selemix Aqua and Selemix System primers can be applied.

TECHNICAL DATA

Storage:

STORE FREE FROM FROST ABOVE 4°C. Prolonged exposure to high temperatures or direct sources of heat should be avoided.

HEALTH AND SAFETY

These products are for professional painting only, and are not to be used for purposes other than those specified. The information on this TDS is based on present scientific and technical knowledge, and it is the responsibility of the user to take all necessary steps in order to ensure the suitability of the product for the intended purpose.

For Health and Safety information please refer to the material Safety Data Sheet, also available at: http://www.selemix.com/selemix_MSDS

For further information please contact:

Customer Service Sales Group
PPG Industries (UK) Ltd
Needham Road
Stowmarket
Suffolk IP14 2AD

Tel: 01449 771771

Fax: 01449 773472

