

**Section 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Product name:** RAPID FLOOR PAINT

**Product code:** PW74

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of substance / mixture:** PC9a: Coatings and paints, thinners, paint removers. For professional use only.

**1.3. Details of the supplier of the safety data sheet**

**Company name:** Bradite Paints  
Ogwen Valley Works  
Bethesda  
Gwynedd  
LL57 4YP  
United Kingdom

**Tel:** +44 (0)1248 600315

**Fax:** +44 (0)1248 602782

**Email:** [sales@bradite.com](mailto:sales@bradite.com)

**1.4. Emergency telephone number**

**Emergency tel:** +44 (0)1248 600315  
(office hours only)

**Section 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification under CLP:** Aquatic Chronic 3: H412; Carc. 2: H351; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Resp. Sens. 1: H334; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT RE 2: H373; STOT SE 3: H335; -: EUH208

**Most important adverse effects:** Contains 4-isocyanatosulphonyltoluene, diphenylmethane-2,2'-di-isocyanate. May produce an allergic reaction. Flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.

**2.2. Label elements**

**Label elements:**

**Hazard statements:** EUH208: Contains 4-isocyanatosulphonyltoluene, diphenylmethane-2,2'-di-isocyanate.

# SAFETY DATA SHEET

## RAPID FLOOR PAINT

Page: 2

May produce an allergic reaction.  
H226: Flammable liquid and vapour.  
H315: Causes skin irritation.  
H317: May cause an allergic skin reaction.  
H319: Causes serious eye irritation.  
H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H335: May cause respiratory irritation.  
H351: Suspected of causing cancer.  
H373: May cause damage to organs through prolonged or repeated exposure.  
H412: Harmful to aquatic life with long lasting effects.

**Signal words:** Danger

**Hazard pictograms:** GHS02: Flame

GHS07: Exclamation mark

GHS08: Health hazard



**Precautionary statements:** P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P241: Use explosion-proof electrical/ventilating/lighting/.. equipment.  
P260: Do not breathe dust/fumes/gas/mist/vapours/spray.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P302+352: IF ON SKIN: Wash with plenty of water/soap and water.  
P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

### 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

PREPOLYMER BASED ON AROMATIC ISOCYANATE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
-	67815-87-6	-	Skin Sens. 1: H317; Aquatic Chronic 3: H412; Resp. Sens. 1: H334	30-50%

[cont...]

## SAFETY DATA SHEET

### RAPID FLOOR PAINT

Page: 3

#### DIPHENYLMETHANE-4,4'-DI-ISOCYANATE

202-966-0	101-68-8	-	Carc. 2: H351; Acute Tox. 4: H332; STOT RE 2: H373; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Resp. Sens. 1: H334; Skin Sens. 1: H317	10-30%
-----------	----------	---	---	--------

#### OLIGOMERIC MDI

-	32055-14-4	-	Carc. 2: H351; Acute Tox. 4: H332; Skin Sens. 1: H317; STOT RE 2: H373; Skin Irrit. 2: H315; Resp. Sens. 1: H334; Eye Irrit. 2: H319; STOT SE 3: H335	1-10%
---	------------	---	---	-------

#### 2-METHOXY-1-METHYLETHYL ACETATE - REACH registered number(s): 01-2119475791-29

203-603-9	108-65-6	Substance with a Community workplace exposure limit.	Flam. Liq. 3: H226	1-10%
-----------	----------	---	--------------------	-------

#### LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.

265-199-0	64742-95-6	-	Carc. 1B: H350; Muta. 1B: H340; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; Aquatic Chronic 2: H411	1-10%
-----------	------------	---	--	-------

#### 1,2,4-TRIMETHYLBENZENE

202-436-9	95-63-6	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Aquatic Chronic 2: H411	1-10%
-----------	---------	---	--	-------

#### POLYPROPYLENE GLYCOL

500-039-8	25322-69-4	-	Acute Tox. 4: H302	1-10%
-----------	------------	---	--------------------	-------

#### DIPHENYLMETHANE-2,4'-DI-ISOCYANATE

227-534-9	5873-54-1	-	Carc. 2: H351; Acute Tox. 4: H332; STOT RE 2: H373; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Resp. Sens. 1: H334; Skin Sens. 1: H317	1-10%
-----------	-----------	---	---	-------

#### TRIETHYL ORTHOFORMATE

204-550-4	122-51-0	-	Flam. Liq. 3: H226	1-10%
-----------	----------	---	--------------------	-------

#### 4-ISOCYANATOSULPHONYLTOLUENE - REACH registered number(s): 01-2119980050-47

223-810-8	4083-64-1	-	Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Resp. Sens. 1: H334; -: EUH014	<1%
-----------	-----------	---	--	-----

[cont...]

# SAFETY DATA SHEET

## RAPID FLOOR PAINT

Page: 4

DIPHENYLMETHANE-2,2'-DI-ISOCYANATE

219-799-4	2536-05-2	-	Carc. 2: H351; Acute Tox. 4: H332; STOT RE 2: H373; Eye Irrit. 2: H319; STOT SE 3: H335; Skin Irrit. 2: H315; Resp. Sens. 1: H334; Skin Sens. 1: H317	<1%
-----------	-----------	---	---	-----

### Section 4: First aid measures

#### 4.1. Description of first aid measures

**Skin contact:** Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin. Consult a doctor.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and pain.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Show this safety data sheet to the doctor in attendance.

### Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

**Extinguishing media:** Carbon dioxide. Alcohol or polymer foam. Dry chemical powder. Do not use water.

#### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

#### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus.

### Section 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details.

#### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

[cont...]

# SAFETY DATA SHEET

## RAPID FLOOR PAINT

Page: 5

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Refer to section 13 of SDS for suitable method of disposal.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 13 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Ensure there is sufficient ventilation of the area. Smoking is forbidden.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep away from sources of ignition.

**Suitable packaging:** Must only be kept in original packaging.

**Storage quantity limits:** 250 L

### 7.3. Specific end use(s)

**Specific end use(s):** PC9a: Coatings and paints, thinners, paint removers.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Hazardous ingredients:**

#### DIPHENYLMETHANE-4,4'-DI-ISOCYANATE

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	0.02 mg/m <sup>3</sup>	0.07 mg/m <sup>3</sup>	-	-

#### 2-METHOXY-1-METHYLETHYL ACETATE

UK	274 mg/m <sup>3</sup>	548 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

#### 1,2,4-TRIMETHYLBENZENE

UK	125 mg/m <sup>3</sup>	-	-	-
----	-----------------------	---	---	---

#### DIPHENYLMETHANE-2,4'-DI-ISOCYANATE

UK	0.02 mg/m <sup>3</sup>	0.07 mg/m <sup>3</sup>	-	-
----	------------------------	------------------------	---	---

#### 4-ISOCYANATOSULPHONYLTOLUENE

UK	0.02 mg/m <sup>3</sup>	0.07 mg/m <sup>3</sup>	-	-
----	------------------------	------------------------	---	---

[cont...]

# SAFETY DATA SHEET

## RAPID FLOOR PAINT

Page: 6

### DIPHENYLMETHANE-2,2'-DI-ISOCYANATE

UK	0.02 mg/m3	0.07 mg/m3	-	-
----	------------	------------	---	---

#### DNEL/PNEC Values

DNEL / PNEC No data available.

#### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Gas/vapour filter, type A: organic vapours (EN141).

**Hand protection:** Gloves (solvent-resistant).

**Eye protection:** Tightly fitting safety goggles.

**Skin protection:** Protective clothing with elasticated cuffs and closed neck.

**Environmental:** Prevent from entering in public sewers or the immediate environment.

#### Section 9: Physical and chemical properties

##### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** Various

**Odour:** Characteristic odour

**Evaporation rate:** Slow

**Oxidising:** Non-oxidising (by EC criteria)

**Solubility in water:** Not miscible

**Also soluble in:** Most organic solvents.

**Viscosity:** Non-viscous

**Boiling point/range°C:** 150 - 181

**Melting point/range°C:** No data available.

**Flammability limits %: lower:** 0.8

**upper:** 7.5

**Flash point°C:** 23 - 55

**Part.coeff. n-octanol/water:** No data available.

**Autoflammability°C:** 300

**Vapour pressure:** No data available.

**Relative density:** 1.07

**pH:** Not applicable.

**VOC g/l:** 263

##### 9.2. Other information

**Other information:** Not applicable.

#### Section 10: Stability and reactivity

##### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

##### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

[cont...]

# SAFETY DATA SHEET

## RAPID FLOOR PAINT

Page: 7

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.

### 10.4. Conditions to avoid

**Conditions to avoid:** Direct sunlight. Sources of ignition.

### 10.5. Incompatible materials

**Materials to avoid:** Strong acids. Strong bases. Strong oxidising agents.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

**Hazardous ingredients:**

#### DIPHENYLMETHANE-4,4'-DI-ISOCYANATE

ORL	MUS	LD50	2200	mg/kg
ORL	RAT	LD50	9200	mg/kg

#### 2-METHOXY-1-METHYLETHYL ACETATE

IPR	MUS	LD50	750	mg/kg
ORL	RAT	LD50	8532	mg/kg

#### LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.

ORL	RAT	LD50	8400	mg/kg
-----	-----	------	------	-------

#### 1,2,4-TRIMETHYLBENZENE

IPR	RAT	LDLO	1752	mg/kg
ORL	RAT	LD50	5	gm/kg

#### POLYPROPYLENE GLYCOL

DERMAL	RAT	LD50	>3000	mg/kg
ORAL	RAT	LD50	>500 - <2000	mg/kg

#### 4-ISOCYANATOSULPHONYLTOLUENE

IPR	RAT	LD50	775	mg/kg
ORL	RAT	LD50	2234	mg/kg

[cont...]

# SAFETY DATA SHEET

## RAPID FLOOR PAINT

Page: 8

### Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	INH DRM	Hazardous: calculated
Carcinogenicity	--	Hazardous: calculated
STOT-single exposure	INH	Hazardous: calculated
STOT-repeated exposure	-	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and pain.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

**Other information:** Not applicable.

### Section 12: Ecological information

#### 12.1. Toxicity

##### Hazardous ingredients:

##### POLYPROPYLENE GLYCOL

ALGAE	72H ErC50	>= 100	mg/l
Daphnia magna	48H EC50	>100	mg/l
FISH	96H LC50	>100	mg/l

#### 12.2. Persistence and degradability

**Persistence and degradability:** No data available.

#### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No data available.

#### 12.4. Mobility in soil

**Mobility:** No data available.

#### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

#### 12.6. Other adverse effects

**Other adverse effects:** No data available.

[cont...]



# SAFETY DATA SHEET

RAPID FLOOR PAINT

Page: 9

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Recovery operations:** Solvent reclamation/regeneration.

**Waste code number:** 08 01 11

**Disposal of packaging:** Retain for recovery.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN1263

### 14.2. UN proper shipping name

**Shipping name:** PAINT

### 14.3. Transport hazard class(es)

**Transport class:** 3

### 14.4. Packing group

**Packing group:** III

### 14.5. Environmental hazards

**Environmentally hazardous:** No

**Marine pollutant:** No

### 14.6. Special precautions for user

**Special precautions:** No special precautions.

**Tunnel code:** D/E

**Transport category:** 3

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Specific regulations:** Not applicable.

### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No

[cont...]

# SAFETY DATA SHEET

## RAPID FLOOR PAINT

Page: 10

453/2010.

\* indicates text in the SDS which has changed since the last revision.

- Phrases used in s.2 and s.3:** EUH014: Reacts violently with water.  
EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.  
H226: Flammable liquid and vapour.  
H302: Harmful if swallowed.  
H304: May be fatal if swallowed and enters airways.  
H315: Causes skin irritation.  
H317: May cause an allergic skin reaction.  
H319: Causes serious eye irritation.  
H332: Harmful if inhaled.  
H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H335: May cause respiratory irritation.  
H340: May cause genetic defects <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.  
H350: May cause cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.  
H351: Suspected of causing cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.  
H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.  
H411: Toxic to aquatic life with long lasting effects.  
H412: Harmful to aquatic life with long lasting effects.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.