

COO-VAR[®]

PAINTS, PRIMERS AND SPECIALISED COATINGS

SAFETY DATA SHEET

301/V606 - POLYURETHANE VARNISH - EGGSHELL, MATT & EXTRA PALE FLAT (2010 compliant)

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name 301/V606 - POLYURETHANE VARNISH - EGGSHELL, MATT & EXTRA PALE FLAT (2010 compliant)

Product number 301/V606/13, 14 & 15

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses CLEAR VARNISH

1.3. Details of the supplier of the safety data sheet

Supplier COO-VAR
Lockwood Street
Hull
HU2 0HN
+44 (0) 1482 328053(T)
+44 (0) 1482 219266(F)
info@coo-var.co.uk

Contact person Technical Department -, 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri, as above

1.4. Emergency telephone number

Emergency telephone +44 (0) 1482 328053 Coo-Var (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)

SDS No. 10655

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226

Health hazards STOT SE 3 - H336

Environmental hazards Not Classified

Classification (67/548/EEC or 1999/45/EC) R43. R10,R52/53,R66,R67.

2.2. Label elements

Pictogram



301/V606 - POLYURETHANE VARNISH - EGGSHELL, MATT & EXTRA PALE FLAT (2010 compliant)

| | |
|---|--|
| Signal word | Warning |
| Hazard statements | H226 Flammable liquid and vapour. H336 May cause drowsiness or dizziness. EUH208 Contains 2-BUTANONE OXIME. May produce an allergic reaction. |
| Precautionary statements | P102 Keep out of reach of children. P101 If medical advice is needed, have product container or label at hand. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing vapour/ spray. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P501 Dispose of contents/ container in accordance with national regulations. |
| Supplemental label information | EUH066 Repeated exposure may cause skin dryness or cracking. |
| Contains | HYDROCARBONS, C9-C11, <2% AROMATICS |
| Supplementary precautionary statements | P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical equipment. P242 Use non-sparking tools. P243 Take action to prevent static discharges. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTRE/doctor if you feel unwell. P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P403+P235 Store in a well-ventilated place. Keep cool. P405 Store locked up. |

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

| | |
|---|--|
| HYDROCARBONS, C9-C11, <2% AROMATICS | 30-60% |
| CAS number: — | EC number: 919-857-5 |
| | REACH registration number: 01-2119463258-33-XXXX |
| Classification | Classification (67/548/EEC or 1999/45/EC) |
| Flam. Liq. 3 - H226 | Xn;R65. R10,R66,R67. |
| STOT SE 3 - H336 | |
| Asp. Tox. 1 - H304 | |
| Silica (amorphous) | 5-10% |
| CAS number: 112926-00-8 | EC number: 231-545-4 |
| | REACH registration number: 01-2119379499-16-0000 |
| Classification | Classification (67/548/EEC or 1999/45/EC) |
| Not Classified | - |

301/V606 - POLYURETHANE VARNISH - EGGSHELL, MATT & EXTRA PALE FLAT (2010 compliant)

| | | | |
|---|----------------------|--|---------------|
| Hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics | | | 1-5% |
| CAS number: 64742-48-9 | EC number: 918-481-9 | REACH registration number: 01-2119457273-39-0000 | |
| Classification | | | |
| Flam. Liq. 3 - H226 STOT SE 3 - H336 Asp. Tox. 1 - H304 | | | |
| ZIRCONIUM SALT, 2-ETHYLHEXANOIC ACID | | | <1% |
| CAS number: 22464-99-9 | EC number: 245-018-1 | REACH registration number: 01-2119979088-21-0002 | |
| Classification | | Classification (67/548/EEC or 1999/45/EC) | |
| Repr. 2 - H361d | | Repr. Cat. 3;R63. | |
| 2-BUTANONE OXIME | | | <1% |
| CAS number: 96-29-7 | EC number: 202-496-6 | REACH registration number: 01-2119539477-28 | |
| Classification | | Classification (67/548/EEC or 1999/45/EC) | |
| Acute Tox. 4 - H312 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Carc. 2 - H351 | | Carc. Cat. 3;R40 Xn;R21 R43 Xi;R41 | |
| 2,6-Di-tert-butyl-p-cresol | | | <1% |
| CAS number: 128-37-0 | EC number: 204-881-4 | REACH registration number: 01-2119565113-46-xxxx | |
| M factor (Acute) = 1 | | | |
| Classification | | Classification (67/548/EEC or 1999/45/EC) | |
| Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410 | | N;R50/53. | |

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person.

Inhalation

Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues. Place unconscious person on their side in the recovery position and ensure breathing can take place.

Ingestion

DO NOT induce vomiting. Get medical attention immediately. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.

301/V606 - POLYURETHANE VARNISH - EGGSHELL, MATT & EXTRA PALE FLAT (2010 compliant)

Skin contact Remove affected person from source of contamination. Remove contaminated clothing immediately and wash skin with soap and water.

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General information Get medical attention promptly if symptoms occur after washing.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog. Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Toxic gases or vapours. FLAMMABLE. Solvent vapours may form explosive mixtures with air.

5.3. Advice for firefighters

Protective actions during firefighting Risk of re-ignition after fire has been extinguished. Cool containers exposed to flames with water until well after the fire is out. Avoid the spillage or runoff entering drains, sewers or watercourses.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid inhalation of vapours and contact with skin and eyes. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Ensure suitable respiratory protection is worn during removal of spillages in confined areas.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground. Contain spillage with sand, earth or other suitable non-combustible material. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Avoid the spillage or runoff entering drains, sewers or watercourses. Absorb in vermiculite, dry sand or earth and place into containers. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

301/V606 - POLYURETHANE VARNISH - EGGSHELL, MATT & EXTRA PALE FLAT (2010 compliant)

Usage precautions Observe any occupational exposure limits for the product or ingredients. Avoid inhalation of vapours and spray/mists. Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Do not eat, drink or smoke when using the product. The Manual Handling Operations Regulations may apply to the handling of containers of this product. To assist employers, the following method of calculating the weight for any pack size is given. Take the pack size volume in litres and multiply this figure by the specific gravity value given in section 9. This will give the net weight of the coating in kilograms. Allowance will then have to be made for the immediate packaging to give an approximate gross weight.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in closed original container at temperatures between 5°C and 25°C. Keep away from heat, sparks and open flame. Keep container tightly closed. Keep containers upright. Store away from the following materials: Oxidising materials. Alkalis. Acids.

Storage class Flammable liquid storage. The storage and use of this product is subject to the Dangerous Substances and Explosive Atmospheres Regulations (DSEAR). The requirements are given in the HSE Approved Code of Practice and Guidance, Storage of Dangerous Substances: DSEAR. Up to 250 litres of liquids with a flashpoint above 32C but below 55C may be kept in a workroom provided they are kept in closed containers in a marked, fire-resisting cupboard or bin. Larger quantities must be kept in a separate, marked storeroom conforming to the structural requirements contained in the HSE guidance note Storage of Flammable Liquids in Containers.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

Usage description Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Silica (amorphous)

Long-term exposure limit (8-hour TWA): WEL 2.4 mg/m³ resp.dust

Long-term exposure limit (8-hour TWA): WEL 6 mg/m³ inhalable dust

ZIRCONIUM SALT, 2-ETHYLHEXANOIC ACID

Long-term exposure limit (8-hour TWA): WEL 5 mg/m³

Short-term exposure limit (15-minute): WEL 10 mg/m³

2,6-Di-tert-butyl-p-cresol

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³

WEL = Workplace Exposure Limit

HYDROCARBONS, C9-C11, <2% AROMATICS

DNEL

Consumer - Oral; Long term systemic effects: 300 mg/kg/day
 Industry - Inhalation; Long term systemic effects: 1500 mg/m³
 Industry - Dermal; Long term systemic effects: 300 mg/kg/day
 Consumer - Dermal; Long term systemic effects: 300 mg/kg/day
 Consumer - Inhalation; Long term systemic effects: 900 mg/m³

301/V606 - POLYURETHANE VARNISH - EGGSHELL, MATT & EXTRA PALE FLAT (2010 compliant)

PNEC No PNEC available. Substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for the risk assessment of this complex substance.

Hydrocarbons, C10-13, n-alkanes, isoalkanes, cyclics, <2% aromatics (CAS: 64742-48-9)

DNEL Workers - Inhalation; Long term systemic effects: 1500 mg/m³
 Workers - Dermal; Long term systemic effects: 300 mg/kg/day
 General population - Inhalation; Long term systemic effects: 900 mg/m³
 General population - Dermal; Long term systemic effects: 300 mg/kg/day
 General population - Oral; Long term systemic effects: 300 mg/kg/day

2,6-Di-tert-butyl-p-cresol (CAS: 128-37-0)

DNEL Industry - Dermal; : 0.5 mg/kg/day
 Industry - Inhalation; : 3.5 mg/kg/day

PNEC - Fresh water; 0.000199 mg/l
 - Sediment; 0.0996 mg/l
 - Soil; 0.04769 mg/l
 - Marine water; 0.0000199 mg/l

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Wear chemical splash goggles.

Hand protection

To protect hands from chemicals, gloves should comply with European Standards EN388 and 374. As a general principle, exposure should be managed by means other than the provision of protective gloves. Manufacturer's performance data suggest that the optimum glove for use should be: Wear protective gloves made of the following material: Nitrile rubber. Thickness: ≥ 0.31 mm Permeation breakthrough time according to EN374 - class: (1-6) e.g. minimum 480 mins. Caution: The performance of gloves under actual working conditions can be significantly affected by many factors and the information provided according to EN374 may not accord with what is achieved in practice. We recommend that expert professional advice is sought that takes into account of the work processes and working environment applicable for each task where gloves are to be worn.

Other skin and body protection

Wear appropriate clothing to prevent reasonably probable skin contact.

Hygiene measures

No specific hygiene procedures recommended but good personal hygiene practices should always be observed when working with chemical products.

Respiratory protection

Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. In case of inadequate ventilation use suitable respirator. It is recommended to use respiratory equipment with combination filter, type A2/P2.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

301/V606 - POLYURETHANE VARNISH - EGGSHELL, MATT & EXTRA PALE FLAT (2010 compliant)

| | |
|---|---------------------------------|
| Appearance | Viscous, cloudy liquid. |
| Colour | Colourless. |
| Odour | Organic solvents. |
| Odour threshold | Not determined. |
| pH | Technically not feasible. |
| Melting point | Not determined. |
| Initial boiling point and range | Not determined. |
| Flash point | 39 approx. °C Closed cup. |
| Evaporation rate | Not determined. |
| Evaporation factor | Not determined. |
| Upper/lower flammability or explosive limits | : 0.8 |
| Other flammability | Not determined. |
| Vapour pressure | Not determined. |
| Vapour density | heavier than air |
| Relative density | 0.92 - 0.98 @ @ 20 C°C |
| Solubility(ies) | Insoluble in water |
| Partition coefficient | Not determined. |
| Auto-ignition temperature | Not determined. |
| Decomposition Temperature | Not determined. |
| Viscosity | 2.0 (Rotothinner) P @ 25 C°C |
| Explosive properties | Not determined. |
| Explosive under the influence of a flame | Not considered to be explosive. |
| Oxidising properties | Not determined. |

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not determined.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Acids. Oxidising agents.

301/V606 - POLYURETHANE VARNISH - EGGSHELL, MATT & EXTRA PALE FLAT (2010 compliant)

10.5. Incompatible materials

Materials to avoid Strong alkalis. Strong acids. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

| | |
|---|--|
| Inhalation | Vapour from this product may be hazardous by inhalation. Vapour may irritate respiratory system/lungs. |
| Ingestion | Liquid irritates mucous membranes and may cause abdominal pain if swallowed. |
| Skin contact | Product has a defatting effect on skin. Repeated exposure may cause skin dryness or cracking. May cause allergic contact eczema. Prolonged or repeated exposure may cause severe irritation. |
| Eye contact | May cause temporary eye irritation. |
| Acute and chronic health hazards | This product has low toxicity. Only large quantities are likely to have adverse effects on human health. |
| Route of exposure | Inhalation Skin absorption. Ingestion. Skin and/or eye contact. |
| Medical considerations | Skin disorders and allergies. Avoid vomiting and stomach flushing because of the risk of aspiration. |

Toxicological information on ingredients.

HYDROCARBONS, C9-C11, <2% AROMATICS

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,100.0

Species Rat

ATE oral (mg/kg) 5,100.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 5,100.0

Species Rabbit

ATE dermal (mg/kg) 5,100.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 5,100.0

Species Rat

ATE inhalation (vapours mg/l) 5,100.0

Skin corrosion/irritation

301/V606 - POLYURETHANE VARNISH - EGGSHELL, MATT & EXTRA PALE FLAT (2010 compliant)

| | |
|--|---|
| Skin corrosion/irritation | Not irritating. |
| <u>Serious eye damage/irritation</u> | |
| Serious eye damage/irritation | Not irritating. |
| <u>Respiratory sensitisation</u> | |
| Respiratory sensitisation | Not sensitising. |
| <u>Skin sensitisation</u> | |
| Skin sensitisation | Not sensitising. |
| <u>Germ cell mutagenicity</u> | |
| Genotoxicity - in vitro | Chromosome aberration: Negative. This substance has no evidence of mutagenic properties. |
| <u>Carcinogenicity</u> | |
| Carcinogenicity | Based on available data the classification criteria are not met. |
| <u>Reproductive toxicity</u> | |
| Reproductive toxicity - fertility | Fertility: - , Inhalation, Rat This substance has no evidence of toxicity to reproduction. |
| Reproductive toxicity - development | Developmental toxicity: - : , Inhalation, Rat This substance has no evidence of toxicity to reproduction. |
| <u>Specific target organ toxicity - repeated exposure</u> | |
| STOT - repeated exposure | Not available. |
| <u>Aspiration hazard</u> | |
| Aspiration hazard | Kinematic viscosity <= 20.5 mm ² /s. |
| . | |
| Inhalation | Vapours may cause drowsiness and dizziness. Central nervous system depression. |
| Ingestion | Harmful: danger of serious damage to health by prolonged exposure if swallowed. |
| Skin contact | Product has a defatting effect on skin. May cause allergic contact eczema. |
| Eye contact | No specific health hazards known. |
| Route of exposure | Inhalation Dermal |

SECTION 12: Ecological Information

Ecotoxicity The product contains substances which are toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

12.1. Toxicity

Ecological information on ingredients.

HYDROCARBONS, C9-C11, <2% AROMATICS

Acute aquatic toxicity

Acute toxicity - fish LC50, > 96 hours: 1000 mg/l, Oncorhynchus mykiss (Rainbow trout)
Substance did not cause acute toxicity to fish

301/V606 - POLYURETHANE VARNISH - EGGSHELL, MATT & EXTRA PALE FLAT (2010 compliant)

| | |
|---|--|
| Acute toxicity - aquatic invertebrates | Substance did not cause acute toxicity to the freshwater invertebrates EC ₅₀ , 48 hours: >1000 mg/l, Daphnia magna |
| Acute toxicity - aquatic plants | EC ₅₀ , > 72 hours: 1000 mg/l, Freshwater algae Substance did not cause acute toxicity to the freshwater green algae |
| Acute toxicity - microorganisms | EC ₅₀ , >: 100 mg/l, Activated sludge |
| <u>Chronic aquatic toxicity</u> | |
| Chronic toxicity - fish early life stage | NOEC, 28 days: 0.131 mg/l, Oncorhynchus mykiss (Rainbow trout) |
| Chronic toxicity - aquatic invertebrates | NOEC, 28 days: 0.23 mg/l, Daphnia magna |

12.2. Persistence and degradability

Persistence and degradability The product is not expected to be biodegradable.

Ecological information on ingredients.

HYDROCARBONS, C9-C11, <2% AROMATICS

| | |
|--------------------------------------|---|
| Persistence and degradability | The product is readily biodegradable. |
| Phototransformation | Oxidises rapidly by photo-chemical reactions in air |
| Biodegradation | - 80 Degradation (%): 28 days Test - 301F Ready Biodegradability - Manometric Respiratory Test |

12.3. Bioaccumulative potential

Bioaccumulative potential The product contains potentially bioaccumulating substances.

Partition coefficient Not determined.

Ecological information on ingredients.

HYDROCARBONS, C9-C11, <2% AROMATICS

| | |
|----------------------------------|--|
| Bioaccumulative potential | The product contains potentially bioaccumulating substances. |
| Partition coefficient | log Pow: 5 - 6.7 |

12.4. Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

Ecological information on ingredients.

HYDROCARBONS, C9-C11, <2% AROMATICS

| | |
|--|---|
| Mobility | The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces. Readily absorbed into soil. |
| Adsorption/desorption coefficient | Not available. |
| Surface tension | 24.5 mN/m @ 20°C |

301/V606 - POLYURETHANE VARNISH - EGGSHELL, MATT & EXTRA PALE FLAT (2010 compliant)

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.

HYDROCARBONS, C9-C11, <2% AROMATICS

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects The product contains volatile organic compounds (VOCs) which have a photochemical ozone creation potential.

Ecological information on ingredients.

HYDROCARBONS, C9-C11, <2% AROMATICS

Other adverse effects Not known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Avoid the spillage or runoff entering drains, sewers or watercourses.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Waste class When this coating, in its liquid state, as supplied, becomes a waste, it is categorised as hazardous waste, with code 08 01 11* (SOLVENT BASED LIQUID WASTE). Part-used containers, not drained and/or rigorously scraped out and containing dried residues of the supplied coating, are categorised as hazardous waste, with code 08 01 11* (SOLVENT BASED LIQUID WASTE). If mixed with other wastes, the above waste code may not be applicable. Used containers, drained and/or rigorously scraped out and containing dry residues of the supplied coating, are categorised as non-hazardous waste, with code 15 01 02 (plastic packaging) or 15 01 04 (metal packaging).

SECTION 14: Transport information

General This product is packed in accordance with the Limited Quantity Provisions of CDGCPL2, ADR and IMDG.

14.1. UN number

UN No. (ADR/RID) 1263

UN No. (IMDG) 1263

UN No. (ICAO) 1263

14.2. UN proper shipping name

Proper shipping name (ADR/RID) PAINT

Proper shipping name (IMDG) PAINT

Proper shipping name (ICAO) PAINT

Proper shipping name (ADN) PAINT

301/V606 - POLYURETHANE VARNISH - EGGSHELL, MATT & EXTRA PALE FLAT (2010 compliant)

14.3. Transport hazard class(es)

| | |
|---------------------|------|
| ADR/RID class | 1263 |
| IMDG class | 3 |
| ICAO class/division | 3 |

Transport labels



14.4. Packing group

| | |
|-----------------------|-----|
| ADR/RID packing group | III |
| IMDG packing group | III |
| ICAO packing group | III |

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

| | |
|-------------------------|----------|
| EmS | F-E, S-E |
| Tunnel restriction code | (D/E) |

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

| | |
|-----------------------------|--|
| National regulations | The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716). |
| EU legislation | Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). |
| Guidance | Workplace Exposure Limits EH40. CHIP for everyone HSG228. Safety Data Sheets for Substances and Preparations. Approved Classification and Labelling Guide (Sixth edition) L131. Dangerous Substances and Explosive Atmospheres Regulations 2002 [L138] |

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

301/V606 - POLYURETHANE VARNISH - EGGSHELL, MATT & EXTRA PALE FLAT (2010 compliant)

SECTION 16: Other information

| | |
|----------------------------------|--|
| Revision comments | Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 2015/830 Revision to sections 2, 8, 11 & 12 for reclassification of solvents. |
| Issued by | Technical Dept. (P.E.) |
| Revision date | 29/05/2018 |
| Revision | 9.0 |
| Supersedes date | 23/01/2015 |
| SDS number | 10655 |
| SDS status | Approved. |
| Risk phrases in full | Not classified. R10 Flammable. R20/21 Harmful by inhalation and in contact with skin. R21 Harmful in contact with skin. R36/37/38 Irritating to eyes, respiratory system and skin. R36/38 Irritating to eyes and skin. R40 Limited evidence of a carcinogenic effect. R41 Risk of serious damage to eyes. R43 May cause sensitisation by skin contact. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R63 Possible risk of harm to the unborn child. R65 Harmful: may cause lung damage if swallowed. R66 Repeated exposure may cause skin dryness or cracking. R67 Vapours may cause drowsiness and dizziness. |
| Hazard statements in full | H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer. H361d Suspected of damaging the unborn child. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. EUH208 Contains 2-BUTANONE OXIME. May produce an allergic reaction. |
| Signature | Initials _____ |

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.