



### THINNERS 15

#### DESCRIPTION:

Thinners 15 is a C8 - C10 Aromatic hydrocarbon solvent mixture.

#### RECOMMENDED USE:

As a slow evaporating thinner / brushwash. Can be used in Chlorvar, Hammercote, Floorcote. See specified thinners for paint being used.

#### AVAILABILITY:

0.25 litre, 0.5 litre, 1 litre, 2.5 litre, 25 litre

#### FINISH:

N/A

#### COLOUR:

Clear thin liquid.

#### TYPICAL S.G. (SPECIFIC GRAVITY):

0.86 @ 20 °C

#### VOLUME SOLIDS:

N/A

#### WET FILM THICKNESS W.F.T

N/A

#### DRY FILM THICKNESS D.F.T

N/A

#### EXPECTED SPREADING RATE:

N/A

The practical spreading rate may be lower as this depends on factors such as the porosity and roughness of the surface to be painted and material losses during application.

#### TYPICAL VISCOSITY

N/A

#### FLASH POINT:

41 °C (closed cup)

#### DRYING TIME: @ RECOMMENDED D.F.T

Touch dry: N/A

Hard dry: N/A

Full hardness: N/A

Low temperature and high humidity will adversely affect application, drying and performance of any coating.

#### MINIMUM OVERCOATING TIME:

N/A

#### APPLICATION SPECIAL CONDITIONS:

N/A

#### VOC CONTENT:

N/A

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution

#### APPLICATION DETAILS:

Application N/A  
restrictions

Method N/A

Thinner N/A  
(Max vol):

Nozzle size: N/A

Nozzle N/A  
pressure:

Cleaning N/A  
solvent:

Recoat N/A  
interval:

#### SURFACE PREPARATION:

N/A

#### MIXING INSTRUCTIONS:

N/A

**For further advice contact Teamac Technical Services on +44(0)1482 320194**

**The physical constants are subject to normal manufacturing tolerances.**

**"COVERING OUR CUSTOMERS' NEEDS SINCE 1908"**

**TEAMAC**

Lockwood Street, Hull HU2 0HN

Tel.: +44(0)1482 320194. Fax: +44(0)1482 219266

Email: [info@teamac.co.uk](mailto:info@teamac.co.uk)

[www.teamac.co.uk](http://www.teamac.co.uk)

**THINNERS 15****600/V607/15**

---

**APPLICATION CONDITIONS:**

N/A

**PRECEDING COAT:**

N/A

**SUBSEQUENT COAT:**

N/A

**REMARKS:**

Flamability limits in air:- Lower - 0.6% by volume  
Upper - 7% by volume

Vapour pressure:- 2.9mm HG @ 20°C

**HEALTH AND SAFETY:**

See safety data sheet - SDS 10699

**ISSUED:**

17 September 2009

**REVISION:**

0

The information given in this data sheet is based on experience and is accurate to the best of our knowledge. No guarantee should be implied, however, since the conditions of use are beyond our control. This data sheet does not constitute a specification. In case of doubt as to the suitability of the product please contact our Technical Service Department on 01482 320194.

**For further advice contact Teamac Technical Services on +44(0)1482 320194**

**The physical constants are subject to normal manufacturing tolerances.**

**"COVERING OUR CUSTOMERS' NEEDS SINCE 1908"**

---

**TEAMAC**

Lockwood Street, Hull HU2 0HN

Tel.: +44(0)1482 320194. Fax: +44(0)1482 219266

Email: [info@teamac.co.uk](mailto:info@teamac.co.uk)[www.teamac.co.uk](http://www.teamac.co.uk)