



SAFETY DATA SHEET

600/V607 - CHLORINATED RUBBER THINNERS

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name 600/V607 - CHLORINATED RUBBER THINNERS

Product number 600/V607/15/CR

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses As a paint thinner/cleaner

1.3. Details of the supplier of the safety data sheet

Supplier TEAL & MACKRILL LIMITED
LOCKWOOD STREET
HULL
HU2 0HN

+44(0)1482 320194(T)

+44(0)1482 219266(F)

info@teamac.co.uk

Contact person Technical Department -, 08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri, as above

1.4. Emergency telephone number

Emergency telephone +44 (0) 1482 320194 Teamac (08.30 - 16.30 hrs Mon - Thurs, 08.30 - 15.00 hrs Fri)

SDS No. 10704

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226

Health hazards STOT SE 3 - H335, H336 Asp. Tox. 1 - H304

Environmental hazards Aquatic Chronic 2 - H411

Classification (67/548/EEC or 1999/45/EC) Xn;R65. Xi;R37. N;R51/53. R10,R66,R67.

2.2. Label elements

Pictogram



Signal word

Danger

600/V607 - CHLORINATED RUBBER THINNERS

| | |
|---|--|
| Hazard statements | H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. |
| Precautionary statements | P102 Keep out of reach of children. P101 If medical advice is needed, have product container or label at hand. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing vapour/ spray. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P331 Do NOT induce vomiting. P501 Dispose of contents/ container in accordance with national regulations. |
| Supplemental label information | EUH066 Repeated exposure may cause skin dryness or cracking. |
| Contains | Hydrocarbons, C9, aromatics |
| Supplementary precautionary statements | P403+P233 Store in a well-ventilated place. Keep container tightly closed. |

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

| | |
|------------------------------------|--|
| Hydrocarbons, C9, aromatics | 60-100% |
| CAS number: — | EC number: 918-668-5 |
| | REACH registration number: 01-2119455851-35-xxxx |
| Classification | Classification (67/548/EEC or 1999/45/EC) |
| Flam. Liq. 3 - H226 | Xn;R65. Xi;R37. N;R51/53. R10,R66,R67. |
| STOT SE 3 - H335, H336 | |
| Asp. Tox. 1 - H304 | |
| Aquatic Chronic 2 - H411 | |

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|----------------------------|---|
| General information | Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel. |
| Inhalation | Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. |
| Ingestion | Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. |

600/V607 - CHLORINATED RUBBER THINNERS

| | |
|-----------------------------------|---|
| Skin contact | Remove affected person from source of contamination. Rinse immediately with plenty of water. |
| Eye contact | Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes. |
| Protection of first aiders | First aid personnel should wear appropriate protective equipment during any rescue. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|----------------------------|---|
| General information | See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure. |
| Inhalation | Prolonged inhalation of high concentrations may damage respiratory system. During application and drying, solvent vapours will be emitted. Vapours in high concentrations are narcotic. |
| Ingestion | Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation. |
| Skin contact | Prolonged contact may cause dryness of the skin. Discoloration of the skin. |
| Eye contact | May cause temporary eye irritation. |

4.3. Indication of any immediate medical attention and special treatment needed

| | |
|-----------------------------|--------------------------------|
| Notes for the doctor | Treat symptomatically. |
| Specific treatments | No special treatment required. |

SECTION 5: Firefighting measures

5.1. Extinguishing media

| | |
|---------------------------------------|--|
| Suitable extinguishing media | The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire. |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |

5.2. Special hazards arising from the substance or mixture

| | |
|--------------------------------------|---|
| Specific hazards | Containers can burst violently or explode when heated, due to excessive pressure build-up. Flammable liquid and vapour. Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive mixtures with air. Fire-water run-off in sewers may create fire or explosion hazard. |
| Hazardous combustion products | Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours. |

5.3. Advice for firefighters

| | |
|--|---|
| Protective actions during firefighting | Avoid breathing fire gases or vapours. Evacuate area. Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities. |
| Special protective equipment for firefighters | Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents. |

600/V607 - CHLORINATED RUBBER THINNERS

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Provide adequate ventilation.

6.2. Environmental precautions

Environmental precautions Avoid discharge to the aquatic environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Reuse or recycle products wherever possible. Absorb spillage to prevent material damage. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dispose of contents/container in accordance with national regulations.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimise spills. Keep container tightly sealed when not in use. Avoid the formation of mists.

Advice on general occupational hygiene Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store away from incompatible materials (see Section 10). No specific recommendations.

Storage class Unspecified storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

Usage description Take precautionary measures against static discharges.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Hydrocarbons, C9, aromatics

Long-term exposure limit (8-hour TWA): WEL 19 ppm 100 mg/m³ vapour

WEL = Workplace Exposure Limit

Hydrocarbons, C9, aromatics

600/V607 - CHLORINATED RUBBER THINNERS

| | |
|-------------|--|
| DNEL | Consumer - Oral; Long term systemic effects: 11 mg/kg/day Consumer - Dermal; Long term systemic effects: 11 mg/kg/day Consumer - Inhalation; Long term systemic effects: 32 mg/m ³ Industry - Dermal; Long term systemic effects: 25 mg/kg/day Industry - Inhalation; Long term systemic effects: 150 mg/m ³ |
| PNEC | No PNEC available. Substance is a hydrocarbon UVCB. Standard tests for this endpoint are intended for single substances and are not appropriate for the risk assessment of this complex substance. |

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Good general ventilation should be adequate to control worker exposure to airborne contaminants.

Eye/face protection

Chemical splash goggles.

Hand protection

To protect hands from chemicals, gloves should comply with European Standards EN388 and 374. As a general principle, exposure should be managed by means other than the provision of protective gloves. It is recommended that gloves are made of the following material: Polyvinyl alcohol (PVA). Thickness: 0.2 - 0.3 mm or Polyethylene. Thickness: > 0.062 mm Permeation breakthrough time according to EN374 - class: (1-6) e.g. minimum 480 mins. Caution: The performance of gloves under actual working conditions can be significantly affected by many factors and the information provided according to EN374 may not accord with what is achieved in practice. We recommend that expert professional advice is sought that takes into account of the work processes and working environment applicable for each task where gloves are to be worn.

Other skin and body protection

Wear suitable protective clothing as protection against splashing or contamination.

Hygiene measures

Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Do not smoke in work area.

Respiratory protection

In case of inadequate ventilation or risk of inhalation of vapours, use suitable respiratory equipment with combination filter (type A2/P3).

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

| | |
|--|--------------------------|
| Appearance | Clear liquid. |
| Colour | Colourless. |
| Odour | Organic solvents. |
| Odour threshold | Not available. |
| pH | Not applicable. |
| Melting point | Not applicable. |
| Initial boiling point and range | 140 - 200°C @ 760 mm Hg |
| Flash point | 43°C Closed cup. |
| Evaporation rate | 0.16 (butyl acetate = 1) |

600/V607 - CHLORINATED RUBBER THINNERS

| | |
|---|---|
| Upper/lower flammability or explosive limits | Lower flammable/explosive limit: 0.7 g/100 g Upper flammable/explosive limit: 7.0 g/100 g |
| Vapour pressure | 0.29 kPa @ °C |
| Vapour density | ~ 4.2 |
| Relative density | 0.882 @ 15°C |
| Bulk density | 882 kg/m ³ |
| Solubility(ies) | Immiscible with water Miscible with the following materials: Organic solvents. |
| Auto-ignition temperature | 450°C |
| Viscosity | <30 seconds 3mm ISO cup s @ 25°C |

9.2. Other information

| | |
|----------------------------------|---|
| Molecular weight | 122 |
| Volatility | 100 Scientifically unjustified. |
| Volatile organic compound | This product contains a maximum VOC content of 880 g/litre. |

SECTION 10: Stability and reactivity

10.1. Reactivity

| | |
|-------------------|--|
| Reactivity | See the other subsections of this section for further details. |
|-------------------|--|

10.2. Chemical stability

| | |
|------------------|---|
| Stability | Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions. |
|------------------|---|

10.3. Possibility of hazardous reactions

| | |
|---|---|
| Possibility of hazardous reactions | No potentially hazardous reactions known. |
|---|---|

10.4. Conditions to avoid

| | |
|----------------------------|--|
| Conditions to avoid | Avoid heat. Containers can burst violently or explode when heated, due to excessive pressure build-up. |
|----------------------------|--|

10.5. Incompatible materials

| | |
|---------------------------|--|
| Materials to avoid | No specific material or group of materials is likely to react with the product to produce a hazardous situation. |
|---------------------------|--|

10.6. Hazardous decomposition products

| | |
|---|--|
| Hazardous decomposition products | Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours. |
|---|--|

SECTION 11: Toxicological information

11.1. Information on toxicological effects

| | |
|------------------------------|--|
| Toxicological effects | Not regarded as a health hazard under current legislation. |
|------------------------------|--|

Acute toxicity - oral

| | |
|-------------------------------------|--|
| Notes (oral LD₅₀) | Based on available data the classification criteria are not met. |
|-------------------------------------|--|

Acute toxicity - dermal

| | |
|---------------------------------------|--|
| Notes (dermal LD₅₀) | Based on available data the classification criteria are not met. |
|---------------------------------------|--|

600/V607 - CHLORINATED RUBBER THINNERS

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Animal data Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity

None of the ingredients are listed or exempt.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity - development

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure STOT SE 3 - H335, H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Target organs Respiratory system, lungs Central nervous system

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Asp. Tox. 1 - H304 May be fatal if swallowed and enters airways. Pneumonia may be the result if vomited material containing solvents reaches the lungs.

General information

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation

A single exposure may cause the following adverse effects: Irritation of nose, throat and airway. Difficulty in breathing. Coughing. Vapours may cause headache, fatigue, dizziness and nausea. Central nervous system depression. During application and drying, solvent vapours will be emitted. Vapours in high concentrations are narcotic.

Ingestion

Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation. Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.

Skin contact

Prolonged contact may cause dryness of the skin. Discoloration of the skin.

Eye contact

May cause temporary eye irritation.

Route of exposure

Ingestion Inhalation Skin and/or eye contact

600/V607 - CHLORINATED RUBBER THINNERS

Target organs Central nervous system Respiratory system, lungs

Toxicological information

Toxicological information on ingredients.

Hydrocarbons, C9, aromatics

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 3,492.0

Species Rat

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

ATE oral (mg/kg) 3,492.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 3,160.0

Species Rabbit

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

ATE dermal (mg/kg) 3,160.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 6,193.0

Species Rat

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

ATE inhalation (vapours mg/l) 6,193.0

Skin corrosion/irritation

Animal data Repeated exposure may cause skin dryness or cracking.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity None of the ingredients are listed or exempt.

Reproductive toxicity

600/V607 - CHLORINATED RUBBER THINNERS

| | |
|--|---|
| Reproductive toxicity - fertility | Based on available data the classification criteria are not met. |
| Reproductive toxicity - development | Based on available data the classification criteria are not met. |
| <u>Specific target organ toxicity - single exposure</u> | |
| STOT - single exposure | STOT SE 3 - H335, H336 May cause respiratory irritation. May cause drowsiness or dizziness. |
| Target organs | Respiratory system, lungs Central nervous system |
| <u>Specific target organ toxicity - repeated exposure</u> | |
| STOT - repeated exposure | Not classified as a specific target organ toxicant after repeated exposure. |
| <u>Aspiration hazard</u> | |
| Aspiration hazard | Asp. Tox. 1 - H304 May be fatal if swallowed and enters airways. Pneumonia may be the result if vomited material containing solvents reaches the lungs. |
| <u>General information</u> | |
| General information | The severity of the symptoms described will vary dependent on the concentration and the length of exposure. |
| Inhalation | A single exposure may cause the following adverse effects: Irritation of nose, throat and airway. Difficulty in breathing. Coughing. Vapours may cause headache, fatigue, dizziness and nausea. Central nervous system depression. During application and drying, solvent vapours will be emitted. Vapours in high concentrations are narcotic. |
| Ingestion | Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation. Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis. |
| Skin contact | Repeated exposure may cause skin dryness or cracking. Discoloration of the skin. |
| Eye contact | May cause temporary eye irritation. |
| Route of exposure | Ingestion Inhalation Skin and/or eye contact |
| Target organs | Central nervous system Respiratory system, lungs |

SECTION 12: Ecological Information

Ecotoxicity Dangerous for the environment: May cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

Toxicity Based on available data the classification criteria are not met.

Ecological information on ingredients.

Hydrocarbons, C9, aromatics

Toxicity Aquatic Chronic 2 - H411 Toxic to aquatic life with long lasting effects.

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 9.2 mg/l, Oncorhynchus mykiss (Rainbow trout)

600/V607 - CHLORINATED RUBBER THINNERS

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 3.2 mg/l, Daphnia magna

Acute toxicity - microorganisms EC₅₀, 48 hours: 2.9 mg/l,

12.2. Persistence and degradability

Persistence and degradability The degradability of the product is not known.

Ecological information on ingredients.

Hydrocarbons, C9, aromatics

Persistence and degradability The degradability of the product is not known.

Biodegradation - 78%: 28 days

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Ecological information on ingredients.

Hydrocarbons, C9, aromatics

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not available.

12.4. Mobility in soil

Mobility No data available.

Ecological information on ingredients.

Hydrocarbons, C9, aromatics

Mobility No data available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

Ecological information on ingredients.

Hydrocarbons, C9, aromatics

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects None known.

Ecological information on ingredients.

Hydrocarbons, C9, aromatics

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

600/V607 - CHLORINATED RUBBER THINNERS

| | |
|----------------------------|--|
| General information | The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. |
| Disposal methods | Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste packaging should be collected for reuse or recycling. Incineration or landfill should only be considered when recycling is not feasible. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of the local water authority. |
| Waste class | When this coating, in its liquid state, as supplied, becomes a waste, it is categorised as hazardous waste, with code 08 01 11* (SOLVENT BASED LIQUID WASTE). Part-used containers, not drained and/or rigorously scraped out and containing dried residues of the supplied coating, are categorised as hazardous waste, with code 08 01 11* (SOLVENT BASED LIQUID WASTE). Used containers, drained and/or rigorously scraped out and containing dry residues of the supplied coating, are categorised as non-hazardous waste, with code 15 01 02 (plastic packaging) or 15 01 04 (metal packaging). |

SECTION 14: Transport information

General For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section.

14.1. UN number

| | |
|------------------|------|
| UN No. (ADR/RID) | 1263 |
| UN No. (IMDG) | 1263 |
| UN No. (ICAO) | 1263 |

14.2. UN proper shipping name

| | |
|--------------------------------|-------|
| Proper shipping name (ADR/RID) | PAINT |
| Proper shipping name (IMDG) | PAINT |
| Proper shipping name (ICAO) | PAINT |
| Proper shipping name (ADN) | PAINT |

14.3. Transport hazard class(es)

| | |
|---------------------|------|
| ADR/RID class | 1263 |
| IMDG class | 3 |
| ICAO class/division | 3 |

Transport labels



14.4. Packing group

| | |
|-----------------------|-----|
| ADR/RID packing group | III |
| IMDG packing group | III |
| ICAO packing group | III |

600/V607 - CHLORINATED RUBBER THINNERS

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

EmS F-E, S-E

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

| | |
|-----------------------|--|
| EU legislation | Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Commission Regulation (EU) No 2015/830 of 28 May 2015. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). |
| Guidance | Workplace Exposure Limits EH40. |

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

| | |
|---|---|
| Abbreviations and acronyms used in the safety data sheet | ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways. RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail. IATA: International Air Transport Association. ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air. IMDG: International Maritime Dangerous Goods. CAS: Chemical Abstracts Service. ATE: Acute Toxicity Estimate. LC ₅₀ : Lethal Concentration to 50 % of a test population. LD ₅₀ : Lethal Dose to 50% of a test population (Median Lethal Dose). EC ₅₀ : 50% of maximal Effective Concentration. PBT: Persistent, Bioaccumulative and Toxic substance. vPvB: Very Persistent and Very Bioaccumulative. |
|---|---|

600/V607 - CHLORINATED RUBBER THINNERS

| | |
|--|---|
| Classification abbreviations and acronyms | Acute Tox. = Acute toxicity Aquatic Acute = Hazardous to the aquatic environment (acute) Aquatic Chronic = Hazardous to the aquatic environment (chronic) Asp. Tox. = Aspiration hazard Eye Dam. = Serious eye damage Flam. Liq. = Flammable liquid STOT SE = Specific target organ toxicity-single exposure |
| Training advice | Read and follow manufacturer's recommendations. Only trained personnel should use this material. |
| Revision comments | Issued in new format for Reach compliance in accordance with EC 1272/2008 Issued in accordance with Annex II to REACH, as amended by Commission Regulation (EU) No. 2015/830 Revision to sections 2, 8, 11 & 12 for reclassification of solvents. |
| Issued by | Technical Dept. (P.E.) |
| Revision date | 26/02/2018 |
| Revision | 6.0 |
| Supersedes date | 15/04/2016 |
| SDS number | 10704 |
| SDS status | Approved. |
| Risk phrases in full | R10 Flammable. R37 Irritating to respiratory system. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 Harmful: may cause lung damage if swallowed. R66 Repeated exposure may cause skin dryness or cracking. R67 Vapours may cause drowsiness and dizziness. |
| Hazard statements in full | H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H411 Toxic to aquatic life with long lasting effects. |
| Signature | Initials |

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.