

TECHNICAL DATA SHEET PROFLOOR PLUS ANTI-SLIP AGGREGATE COMPONENT

TDS: CVM1123
136/M112/3

DESCRIPTION:

Profloor Anti-Slip Aggregate Component ground mineral powder of specific particle size (0.54 – 0.71mm)

RECOMMENDED USE:

Profloor Plus Anti-Slip Aggregate Component to be used to create anti-slip element to Profloor Plus finish.

AVAILABILITY:

440g

FINISH:

N/A

COLOUR:

Yellow

TYPICAL S.G. (SPECIFIC GRAVITY):

2.85 @ 20 °C

VOLUME SOLIDS:

N/A

WET FILM THICKNESS W.F.T

N/A

DRY FILM THICKNESS D.F.T

N/A

EXPECTED SPREADING RATE:

20 sq.m / can

To be scattered evenly.

The practical spreading rate may be lower as this depends on factors such as the porosity and roughness of the surface to be painted and material losses during application.

TYPICAL VISCOSITY:

N/A

FLASH POINT:

Non-flammable

DRYING TIME: @ RECOMMENDED D.F.T

Touch dry: N/A

Hard dry: N/A

Full hardness: N/A

Low temperature and high humidity will adversely affect application, drying and performance of any coating.

MINIMUM OVERCOATING TIME:

N/A

APPLICATION SPECIAL CONDITIONS:

N/A

VOC CONTENT:

N/A

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution

APPLICATION DETAILS:

Application N/A
restrictions

Method: Scattering

Thinner N/A
(Max vol):

Nozzle size: N/A

Nozzle N/A
pressure:

Cleaning N/A
solvent:

Recoat N/A
interval:

SURFACE PREPARATION:

N/A

For further advice contact Coo-Var Technical Services on +44(0)1482 328053

The physical constants are subject to normal manufacturing tolerances.

"COVERING OUR CUSTOMERS' NEEDS SINCE 1908"

MIXING INSTRUCTIONS:

N/A

APPLICATION CONDITIONS:

The product should be evenly scattered over the first coat of Coo-Var Profloor Plus Floor Paint whilst the coat is still tacky. The second coat of Profloor Plus, when applied over the top of the cured first coat will seal the anti-slip aggregate in place.

PRECEDING COAT:

Coo-Var Profloor Plus Floor Paint

SUBSEQUENT COAT:

Coo-Var Profloor Plus Floor Paint

REMARKS:**HEALTH AND SAFETY:**

See safety data sheet - SDS 11140

ISSUED:

18 April 2013

REVISION:

0

The information given in this data sheet is based on experience and is accurate to the best of our knowledge. No guarantee should be implied, however, as the conditions of use are beyond our control. This data sheet does not constitute a specification. In case of doubt as to the suitability of the product please contact our Technical Service Department on 01482 328053.

For further advice contact Coo-Var Technical Services on +44(0)1482 328053

The physical constants are subject to normal manufacturing tolerances.

"COVERING OUR CUSTOMERS' NEEDS SINCE 1908"

Ellenshaw Works

Lockwood Street, Hull HU2 0HN

Tel.: +44(0)1482 328053. Fax: +44(0)1482 219266

COO-VAR

Email: info@coo-var.co.ukwww.coo-var.co.uk