

SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830 - United Kingdom (UK)

Centrecoat MMA - Base Component

Compilation date: 29/10/2019 Revision date: 29/10/2019 Revision No: 1 Page: 1/8

SECTION 1: Identification of the substance/mixture and of the company/undertaking		
1.1. Product identifier		
Product name	Centrecoat MMA - Base	
1.2. Relevant identified uses of t	he substance or mixture and uses advised against	
Product Use	[SU3] Industrial uses: Uses of substances as such or in preparations at industrial sites; [PC9a] Coatings and paints, thinners, paint removers; [PROC10] Roller application or brushing;	
1.3. Details of the supplier of the safety data sheet		
Company	Promain UK Limited	
Address	Promain House	
	C1 Pierson Court	
	Knowl Piece, Hitchin	
	Hertfordshire	
	SG4 0TY	
Web	www.promain.co.uk	
Telephone	01462 421333	
Fax	-	
Email	info@promain.co.uk	
1.4. Emergency telephone number		
Emergency telephone number	01462 421333	
	8.30am - 5.30pm Mon - Thurs. 8.30am - 4.30pm Fri	
SECTION 2: Hazards identif	ication	

2.1. Classification of the substance or mixture

2.1.2. Classification - EC	Flam. Liq. 2: H225; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT SE 3: H335;
1272/2008	

2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
	Skin Irrit. 2: H315 - Causes skin irritation.
	Skin Sens. 1: H317 - May cause an allergic skin reaction.
	STOT SE 3: H335 - May cause respiratory irritation.
Precautionary Statement: Prevention	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Revision Revision date 2019-10-29

2.2. Label elements

P233 - Keep container tightly closed.

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting// equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 - Wash thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statement: Response

P302+P352 - IF ON SKIN: Wash with plenty of water/.

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 - Call a POISON CENTER/doctor/ /if you feel unwell.

P321 - Specific treatment (see on this label).

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P370+P378 - In case of fire: Use to extinguish.

Precautionary Statement: Storage

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

Precautionary Statement:

Disposal

P501 - Dispose of contents/container to

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Methyl methacrylate	607-035-00-6	80-62-6	201-297-1	01-2119452498-28		Flam. Liq. 2: H225; STOT SE 3: H335; Skin Irrit. 2: H315; Skin Sens. 1: H317;
2-Ethylhexyl acrylate	607-107-00-7	103-11-7	203-080-7	01-2119453158-37		STOT SE 3: H335; Skin Irrit. 2: H315; Skin Sens. 1: H317;
N,N-Dimethyl-p-toluidine	612-056-00-9	99-97-8	202-805-4			Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT RE 2: H373; Aquatic Chronic 3: H412;

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.	
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Remove contact	
	lenses, if present and easy to do. Continue rinsing.	
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing.	
Ingestion	DO NOT INDUCE VOMITING. Drink 1 to 2 glasses of water.	

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.		
Eye contact	Irritating to eyes.		
Skin contact	Irritating to skin.		
Ingestion	Ingestion may cause nausea and vomiting.		

4.3. Indication of any immediate medical attention and special treatment needed

Revision 1
Revision date 2019-10-29

4.3. Indication of any immediat	
Inhalation	Seek medical attention.
Eye contact	Seek medical attention if irritation or symptoms persist.
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	Seek medical attention.
SECTION 5: Firefighting me	easures
5.1. Extinguishing media	
	Carbon oxides. Dry chemical. Foam. Do NOT use water jet.
5.2. Special hazards arising fro	m the substance or mixture
	Highly flammable. Burning produces irritating, toxic and obnoxious fumes. Vapour may travel considerable distance to source of ignition and flash back.
5.3. Advice for firefighters	
	Self-contained breathing apparatus. Wear protective clothing.
SECTION 6: Accidental rele	ease measures
6.1. Personal precautions, prot	ective equipment and emergency procedures
	Ensure adequate ventilation of the working area. Wear suitable protective equipment. Eliminate a sources of ignition. Evacuate personnel to a safe area. Wear suitable respiratory equipment wher necessary.
6.2. Environmental precautions	
	Do not allow product to enter drains. Prevent further spillage if safe.
6.3. Methods and material for o	containment and cleaning up
	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water. Use explosion proof equipment.
6.4. Reference to other section	s
	See section 8 for further information. See section 13 for further information.
SECTION 7: Handling and	storage
7.1. Precautions for safe handl	ing
	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking. Vapours are heavier than air.
7.2. Conditions for safe storage	e, including any incompatibilities
	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers. Store in original container.
7.3. Specific end use(s)	
	See section 1.2 for further information.
SECTION 8: Exposure conf	trols/personal protection
8.1. Control parameters	

Revision Revision date 2019-10-29

8.1.1. Exposure Limit Values

Methyl methacrylate WEL 8-hr limit ppm: 50 WEL 8-hr limit mg/m3: 208 WEL 15 min limit ppm: 100 WEL 15 min limit mg/m3: 416 WEL 8-hr limit mg/m3 total WEL 15 min limit mg/m3 total inhalable dust: inhalable dust: WEL 8-hr limit mg/m3 total WEL 15 min limit mg/m3 total respirable dust: respirable dust:

8.2. Exposure controls



8.2.1. Appropriate engineering

controls 8.2.2. Individual protection

measures

Eye / face protection

Skin protection -Handprotection

Skin protection - Other

Respiratory protection

Ensure adequate ventilation of the working area.

Wear chemical protective clothing.

Approved safety goggles.

Chemical resistant gloves (PVC). Butyl rubber gloves.

Wear suitable protective clothing

Wear suitable respiratory equipment when necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance | Liquid

Colour Various

Odour Strong/Characteristic

Odour threshold No data available

> pН No data available

Melting point No data available

Freezing Point | 48 °C

Initial boiling point 100 °C

10 °C Flash point

Evaporation rate No data available Flammability (solid, gas) No data available

Upper Explosive Limit 12.5 %

Lower Explosive Limit | 2.1 %

Vapour pressure No data available

Relative density > 1 (H2O = 1 @ 20 °C)

Fat Solubility

Vapour density

No data available

No data available

Partition coefficient

No data available

430 °C Autoignition temperature

Viscosity

470 mPas (Cone & Plate)

Explosive properties No data available Oxidising properties

No data available

Solubility

Slightly soluble in water

9.2. Other information

Revision 1
Revision date 2019-10-29

		Revision date 2019-10-29
9.2. Other information		
Conductivity	No data available	
•	No data available	
Gas group	No data available	
Benzene Content	0 %	
Lead content	0 %	
VOC (Volatile organic compounds)	0 g/l	
SECTION 10: Stability and re	eactivity	
10.1. Reactivity		
	See section 10.2 for further information.	
10.2. Chemical stability		
	Stable under normal conditions.	
10.3. Possibility of hazardous re	actions	
	Oxidising agents.	
10.4. Conditions to avoid		
	Heat, sparks and open flames.	
10.5. Incompatible materials		
	Alkalis. Oxidising agents. Peroxides. Reducing agents. Su	ılphur oxides.
10.6. Hazardous decomposition	products	
	Will not decompose if stored and used as recommended.	
SECTION 11: Toxicological	nformation	
11.1. Information on toxicologica	ıl effects	
Acute toxicity	Oral Rat LD50 = >5,000mg/kg (Methyl Methacrylate).	
Skin corrosion/irritation	Irritating to skin.	
Serious eye damage/irritation	Irritating to eyes.	
Respiratory or skin sensitisation	May cause sensitisation by skin contact.	
Germ cell mutagenicity	No mutagenic effects reported.	
Carcinogenicity	No carcinogenic effects reported.	
Reproductive toxicity	No observed effect level. No teratogenic effects reported.	
Aspiration hazard	No Significant Hazard.	
11.1.4. Toxicological Information		
2-Ethylhexyl acrylate	Oral Rat LD50: 4,435mg/kg	Dermal Rabbit LD50: >5,000mg/kg
Methyl methacrylate	Dermal Rat LD50: >5,000mg/kg	Oral Rat LD50: >2,000mg/kg
	Dermal Rabbit LD50: >5,000mg/kg	Inhalation Rat LC50/4 h: 29.8mg/kg
SECTION 12: Ecological info	rmation	
12.1. Toxicity		
Methyl methacrylate	Daphnia EC50/48h: 69.0000 mg/l	Fish LC50/96h: 79.0000 mg/l
40.0 Develotors and describe		
12.2. Persistence and degradab	ılıty	

Readily biodegradable. OECD 301C, 14D.

12.3. Bioaccumulative potential

Revision 1
Revision date 2019-10-29

12.3. Bioaccumulative potential	
	No observed effect level.
Partition coefficient	
	Resbuild MMA Flexgrip - Base No data available
	3-1
12.4. Mobility in soil	
	Slightly soluble in water.
12.5. Results of PBT and vPvB a	assessment
	PBT no. vPvB no.
12.6. Other adverse effects	
	No data is available on this product.
SECTION 13: Disposal consi	iderations
General information	
	08 01 11* waste paint and varnish containing organic solvents or other dangerous substances.
Disposal methods	
	The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. Waste packaging should be recycled if possible. Incineration should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned. Empty containers or liners may still contain residue. Avoid dispersal of spilt material and runoff and contact sith soil, waterways, drains and sewers.
Disposal of packaging	
	Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.
SECTION 14: Transport info	rmation
Hazard pictograms	
14.1. UN number	
	UN1866
14.2. UN proper shipping name	
	RESIN SOLUTION ((Methyl Methacrylate))
14.3. Transport hazard class(es)	
ADR/RID	3
Subsidiary risk	 -
IMDG	3
Subsidiary risk	
IATA	3
Subsidiary risk	j -

Revision 1
Revision date 2019-10-29

	Revision date 2019-10-28
14.4. Packing group	
Packing group	II
14.5. Environmental hazards	
Environmental hazards	No
Marine pollutant	No
14.6. Special precautions for us	ser
	Not applicable.
14.7. Transport in bulk according	ng to Annex II of MARPOL 73/78 and the IBC Code
	Not applicable.
ADR/RID	
Hazard ID	33
Tunnel Category	(D/E)
IMDG	
EmS Code	F-E S-E
IATA	
Packing Instruction (Cargo)	364
Maximum quantity	60 L
Packing Instruction (Passenger)	353
Maximum quantity	5 L
Further information	
	The product is not classified as dangerous for carriage.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

15.2. Chemical safety assessment

This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Other information

Revision

This document differs from the previous version in the following areas:.

4 - Eye contact.

Text of Hazard Statements in Section 3

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

STOT SE 3: H335 - May cause respiratory irritation.

Revision 1 Revision date 2019-10-29

Other information				
	Acute Tox. 3: H301 - Toxic if swallowed. Acute Tox. 3: H311 - Toxic in contact with skin.			
	Acute Tox. 3: H331 - Toxic if inhaled.			
	STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure .			
	Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.			
Maximum content of VOC	0 g/l.			
Further information				
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in			
	combination with any other materials or in any other process.			