

SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830 - United Kingdom (UK)

Centrecoat MMA Damp Primer Base

Page 1/8

Revision 1

Revision date 2019-10-29

SECTION 1: Identification of	the substance/mixture and of the company/undertaking
.1. Product identifier	
Product name	Centrecoat MMA Damp Primer - Base
.2. Relevant identified uses of t	he substance or mixture and uses advised against
Product Use	[SU3] Industrial uses: Uses of substances as such or in preparations at industrial sites; [PC9a] Coatings and paints, thinners, paint removers; [PROC10] Roller application or brushing;
1.3. Details of the supplier of the	e safety data sheet
Company	Promain UK Limited
Address	C1 Pierson Court
	Knowl Piece, Hitchin
	Hertfordshire
	SG4 0TY
Web	www.promain.co.uk
Telephone	01462 421333
Fax	-
Email	info@promain.co.uk
I.4. Emergency telephone numb) Der
Emergency telephone number	01462 421333
	8.30am - 5.30pm Mon - Thurs. 8.30am - 4.30pm Fri
SECTION 2: Hazards identifi	ication
2.1. Classification of the substar	nce or mixture
2.1.2. Classification - EC 1272/2008	Flam. Liq. 2: H225; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT SE 3: H335;
2.2. Label elements	
Hazard pictograms	
Signal Word	Danger
Hazard Statement	Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
	Skin Irrit. 2: H315 - Causes skin irritation.
	Skin Sens. 1: H317 - May cause an allergic skin reaction.
Precautionary Statement:	STOT SE 3: H335 - May cause respiratory irritation. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
Prevention	1 210 Reep away non near, not surfaces, sparks, open names and other ignition sources. No

Revision 1 Revision date 2019-10-29

2.2. Label elements				
	P233 - Keep container tightly closed.			
	P240 - Ground/bond container and receiving equipment.			
	P241 - Use explosion-proof electrical/ventilating/lighting// equipment.			
	P242 - Use only non-sparking tools.			
	P243 - Take precautionary measures against static discharge.			
	P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.			
	P264 - Wash thoroughly after handling.			
	P271 - Use only outdoors or in a well-ventilated area.			
	P272 - Contaminated work clothing should not be allowed out of the workplace.			
	P280 - Wear protective gloves/protective clothing/eye protection/face protection.			
Precautionary Statement:	P302+P352 - IF ON SKIN: Wash with plenty of water/ .			
Response	P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse			
	skin with water/shower.			
	P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.			
	P312 - Call a POISON CENTER/doctor/ /if you feel unwell.			
	P321 - Specific treatment (see on this label).			
	P332+P313 - If skin irritation occurs: Get medical advice/attention.			
	P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.			
	P370+P378 - In case of fire: Use to extinguish.			
Precautionary Statement:	P403+P233 - Store in a well-ventilated place. Keep container tightly closed.			
Storage	P403+P235 - Store in a well-ventilated place. Keep cool.			
	P405 - Store locked up.			
Precautionary Statement:	P501 - Dispose of contents/container to			
Disposal				

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Methyl methacrylate	607-035-00-6	80-62-6	201-297-1	01-2119452498-28		Flam. Liq. 2: H225; STOT SE
						3: H335; Skin Irrit. 2: H315; Skin Sens. 1: H317;
Benzyl Methacrylate		2495-37-6	219-674-4			Skin Irrit. 2: H315; Skin Sens.
						1: H317; Eye Irrit. 2: H319;
N,N-Dimethyl-p-toluidine	612-056-00-9	99-97-8	202-805-4			STOT SE 3: H335; Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3:
						H301; STOT RE 2: H373; Aquatic Chronic 3: H412;
N,N-bis-(2-hydroxypropyl) -p-toluidine		38668-48-3	254-075-1	01-2119980937-17		Acute Tox. 2: H300; Eye Irrit. 2: H319; Aquatic Chronic 3: H412;

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.	
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Remove con lenses, if present and easy to do. Continue rinsing.	
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing.	
Ingestion	DO NOT INDUCE VOMITING. Drink 1 to 2 glasses of water.	
4.2. Most important symptoms	and effects, both acute and delayed	
Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.	
Eye contact	Irritating to eyes.	
Skin contact	Irritating to skin.	

4.2. Most important symptoms and effects, both acute and delayed	
Ingestion Ingestion may cause nausea and vomiting.	
4.3. Indication of any immediate medical attention and special treatment needed	
Inhalation Seek medical attention.	
Eye contact Seek medical attention if irritation or symptoms persist.	
Skin contact Seek medical attention if irritation or symptoms persist.	
Ingestion Seek medical attention.	
SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Carbon oxides. Dry chemical. Foam. Do NOT use water jet.	
5.2. Special hazards arising from the substance or mixture	
Highly flammable. Burning produces irritating, toxic and obnoxious fumes. V considerable distance to source of ignition and flash back.	/apour may travel
5.3. Advice for firefighters	
Self-contained breathing apparatus. Wear protective clothing.	
SECTION 6: Accidental release measures	
6.1. Personal precautions, protective equipment and emergency procedures	
Ensure adequate ventilation of the working area. Wear suitable protective e sources of ignition. Evacuate personnel to a safe area. Wear suitable respir necessary.	
6.2. Environmental precautions	
Do not allow product to enter drains. Prevent further spillage if safe.	
6.3. Methods and material for containment and cleaning up	
Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labell disposal. Clean spillage area thoroughly with plenty of water. Use explosion	
6.4. Reference to other sections	
See section 8 for further information.	
See section 13 for further information.	
SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Avoid contact with eyes and skin. Ensure adequate ventilation of the workin proof equipment. Keep away from sources of ignition - No smoking. Vapour	-
7.2. Conditions for safe storage, including any incompatibilities	
Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Sto containers. Store in original container.	re in correctly labelled
7.3. Specific end use(s)	
See section 1.2 for further information.	
SECTION 8: Exposure controls/personal protection	
8.1. Control parameters	
· · · · · · · · · · · · · · · · · · ·	
8.1.1. Exposure Limit Values	

8.1.1. Exposure Limit Values

8.1.1. Exposure Limit Values		
Methyl methacrylate	WEL 8-hr limit ppm: 50	WEL 8-hr limit mg/m3: 208
	WEL 15 min limit ppm: 100	WEL 15 min limit mg/m3: 416
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:

8.2. Exposure controls

|--|--|--|--|

Ensure adequate ventilation of the working area.
Wear chemical protective clothing.
Approved safety goggles.
Chemical resistant gloves (PVC). Butyl rubber gloves.
Wear suitable protective clothing.
Wear suitable respiratory equipment when necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Colourless
Odour	Strong/Characteristic
Odour threshold	No data available
рН	No data available
Melting point	No data available
Freezing Point	-48 °C
Initial boiling point	> 100 °C
Flash point	10 °C
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Upper Explosive Limit	12.5 %
Lower Explosive Limit	2.1 %
Vapour pressure	No data available
Vapour density	> 1 g/cm ³
Relative density	No data available
Fat Solubility	No data available
Partition coefficient	No data available
Autoignition temperature	430 °C
Viscosity	200 mPas (Cone & Plate)
Explosive properties	No data available
Oxidising properties	No data available
Solubility	Slightly soluble in water

9.2. Other information

9.2. Other information			
Conductivity	No data available		
Surface tension	No data available		
Gas group	No data available		
Benzene Content	0 %		
Lead content	0 %		
VOC (Volatile organic	g/l		
compounds)			
SECTION 10: Stability and r	eactivity		
10.1. Reactivity			
	See section 10.2 for further information.		
10.2. Chemical stability			
	Stable under normal conditions.		
10.3. Possibility of hazardous re	actions		
	Oxidising agents.		
10.4. Conditions to avoid			
	Heat, sparks and open flames.		
10.5. Incompatible materials			
	Alkalis. Oxidising agents. Peroxides. Reducing agents. Sul	phur oxides.	
10.6. Hazardous decomposition	products		
	Will not decompose if stored and used as recommended.		
SECTION 11: Toxicological	nformation		
11.1. Information on toxicologica	al effects		
Acute toxicity	Oral Rat LD50 = >5,000mg/kg (Methyl Methacrylate).		
Skin corrosion/irritation	Irritating to skin.		
Serious eye damage/irritation	Irritating to eyes.		
Respiratory or skin sensitisation	May cause sensitisation by skin contact.		
Germ cell mutagenicity	No mutagenic effects reported.		
Carcinogenicity	No carcinogenic effects reported.		
Reproductive toxicity	No observed effect level. No teratogenic effects reported.		
Aspiration hazard	No Significant Hazard.		
11.1.4. Toxicological Information	1		
Methyl methacrylate	Dermal Rat LD50: >5,000mg/kg	Oral Rat LD50: >2,000mg/kg	
	Dermal Rabbit LD50: >5,000mg/kg	Inhalation Rat LC50/4 h: 29.8mg/kg	
N,N-bis-(2-hydroxypropyl) -p-toluidine	Oral Rat LD50: 172mg/kg		
SECTION 12: Ecological info	prmation		
12.1. Toxicity			
Methyl methacrylate	Daphnia EC50/48h: 69.0000 mg/l	Fish LC50/96h: 79.0000 mg/l	
12.2. Persistence and degradab	ility		
	Readily biodegradable. OECD 301C, 14D.		
12.3. Bioaccumulative potential	· ·		

12.3. Bioaccumulative potential	
	No observed effect level.
Partition coefficient	
	Centrecoat MMA Damp Primer - No data available
	Base
12.4. Mobility in soil	
	Slightly soluble in water.
12.5. Results of PBT and vPvB a	assessment
	PBT no. vPvB no.
12.6. Other adverse effects	
	No data is available on this product.
SECTION 13: Disposal cons	iderations
General information	
	08 01 11* waste paint and varnish containing organic solvents or other dangerous substances.
Disposal methods	
Disposal of packaging	The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. Waste packaging should be recycled if possible. Incineration should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned. Empty containers or liners may still contain residue. Avoid dispersal of spilt material and runoff and contact sith soil, waterways, drains and sewers.
	Desiduas and emotive containers should be taken over of as beyondous wests according to lead
	Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.
SECTION 14: Transport info	rmation
Hazard pictograms	
14.1. UN number	
	UN1866
14.2. UN proper shipping name	
	RESIN SOLUTION ((Methyl Methacrylate))
14.3. Transport hazard class(es)	
ADR/RID	3
Subsidiary risk	-
IMDG	3
Subsidiary risk	-

-3

ΙΑΤΑ

14.3. Transport hazard class(es)	
Subsidiary risk	-
14.4. Packing group	
Packing group	Ш
14.5. Environmental hazards	
Environmental hazards	No
Marine pollutant	No
14.6. Special precautions for use	er
	Not applicable.
14.7. Transport in bulk according	g to Annex II of MARPOL 73/78 and the IBC Code
	Not applicable.
ADR/RID	
Hazard ID	33
Tunnel Category	(D/E)
IMDG	
EmS Code	F-E S-E
ΙΑΤΑ	
Packing Instruction (Cargo)	364
Maximum quantity	60 L
Packing Instruction (Passenger)	353
Maximum quantity	5 L
Further information	
	The product is not classified as dangerous for carriage.
SECTION 15: Regulatory inf	ormation
15.1. Safety, health and environ	mental regulations/legislation specific for the substance or mixture
	COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.
	REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.
15.2. Chemical safety assessme	ent
	This product contains substances for which Chemical Safety Assessments are still required.
SECTION 16: Other information	tion
Other information	
Revision	This document differs from the previous version in the following areas:.

4 - Eye contact.

Print date 2019-10-29

 Revision
 1

 Revision date
 2019-10-29

Other information	
Text of Hazard Statements in Section 3	 Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. STOT SE 3: H335 - May cause respiratory irritation. Eye Irrit. 2: H319 - Causes serious eye irritation. Acute Tox. 3: H301 - Toxic if swallowed. Acute Tox. 3: H311 - Toxic in contact with skin. Acute Tox. 3: H331 - Toxic if inhaled. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure . Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Maximum content of VOC	Acute Tox. 2: H300 - Fatal if swallowed. 0 g/l.
Further information	
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.