

## Centrecoat MMA Steel Primer Adhesion Promotor

Page 1/8

Revision 1

Revision date 2019-10-29

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name** Centrecoat MMA Steel Primer - Adhesion Promotor

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Product Use** [SU3] Industrial uses: Uses of substances as such or in preparations at industrial sites; [SU19] Building and construction work;  
-----  
[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [SU19] Building and construction work;

#### 1.3. Details of the supplier of the safety data sheet

**Company** Promain UK Limited  
**Address** C1 Pierson Court  
Knowl Piece, Hitchin  
Hertfordshire  
SG4 0TY  
**Web** www.promain.co.uk  
**Telephone** 01462 421333  
**Fax** -  
**Email** info@promain.co.uk

#### 1.4. Emergency telephone number

**Emergency telephone number** 01462 421333  
8.30am - 5.30pm Mon - Thurs. 8.30 - 4.30pm Fri

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

**2.1.2. Classification - EC 1272/2008** Flam. Liq. 2: H225; Skin Corr. 1B: H314; Skin Sens. 1: H317; STOT SE 3: H335;

#### 2.2. Label elements

**Hazard pictograms**



**Signal Word**

Danger

**Hazard Statement**

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.  
Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.  
Skin Sens. 1: H317 - May cause an allergic skin reaction.

# Centrecoat MMA Steel Primer - Adhesion Promotor

Revision 1

Revision date 2019-10-29

## 2.2. Label elements

<b>Precautionary Statement: Prevention</b>	<p>STOT SE 3: H335 - May cause respiratory irritation.</p> <p>P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P233 - Keep container tightly closed.</p> <p>P240 - Ground/bond container and receiving equipment.</p> <p>P241 - Use explosion-proof electrical/ventilating/lighting// equipment.</p> <p>P242 - Use only non-sparking tools.</p> <p>P243 - Take precautionary measures against static discharge.</p> <p>P260 - Do not breathe dust/fume/gas/mist/vapours/spray.</p> <p>P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.</p> <p>P264 - Wash thoroughly after handling.</p> <p>P271 - Use only outdoors or in a well-ventilated area.</p> <p>P272 - Contaminated work clothing should not be allowed out of the workplace.</p> <p>P280 - Wear protective gloves/protective clothing/eye protection/face protection.</p>
<b>Precautionary Statement: Response</b>	<p>P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting.</p> <p>P302+P352 - IF ON SKIN: Wash with plenty of water/ .</p> <p>P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.</p> <p>P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P310 -Immediately call a POISON CENTER/doctor/ .</p> <p>P312 - Call a POISON CENTER/doctor/ /if you feel unwell.</p> <p>P321 - Specific treatment (see on this label).</p> <p>P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.</p> <p>P363 - Wash contaminated clothing before reuse.</p> <p>P370+P378 - In case of fire: Use to extinguish.</p>
<b>Precautionary Statement: Storage</b>	<p>P403+P233 - Store in a well-ventilated place. Keep container tightly closed.</p> <p>P403+P235 - Store in a well-ventilated place. Keep cool.</p> <p>P405 - Store locked up.</p>
<b>Precautionary Statement: Disposal</b>	<p>P501 - Dispose of contents/container to</p>

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
methacryloyloxyethyl phosphate		52628-03-2	258-053-2			Skin Corr. 1B: H314; Eye Dam. 1: H318;
Methyl methacrylate	607-035-00-6	80-62-6	201-297-1	01-2119452498-28		Flam. Liq. 2: H225; STOT SE 3: H335; Skin Irrit. 2: H315; Skin Sens. 1: H317;
2-Methylpropenoic acid (Methacrylic acid)	607-088-00-5	79-41-4	201-204-4	01-2119463884-26		Acute Tox. 4: H312; Acute Tox. 4: H302; Skin Corr. 1A: H314;

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>Inhalation</b>	Move the exposed person to fresh air.
<b>Eye contact</b>	Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing.
<b>Skin contact</b>	Wash off immediately with plenty of soap and water. Remove contaminated clothing.
<b>Ingestion</b>	DO NOT INDUCE VOMITING. Drink 1 to 2 glasses of water.

### 4.2. Most important symptoms and effects, both acute and delayed

# Centrecoat MMA Steel Primer - Adhesion Promotor

Revision 1

Revision date 2019-10-29

## 4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.
Eye contact	Causes serious eye damage.
Skin contact	Causes severe burns.
Ingestion	Ingestion may cause nausea and vomiting.

## 4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	Seek medical attention.
Eye contact	Seek medical attention.
Skin contact	Seek medical attention.
Ingestion	Seek medical attention.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

	Carbon oxides. Dry chemical. Foam. Do NOT use water jet.
--	--

### 5.2. Special hazards arising from the substance or mixture

	Highly flammable. Burning produces irritating, toxic and obnoxious fumes. Vapour may travel considerable distance to source of ignition and flash back.
--	---

### 5.3. Advice for firefighters

	Self-contained breathing apparatus. Wear protective clothing.
--	---

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area. Wear suitable protective equipment. Eliminate all sources of ignition. Evacuate personnel to a safe area. Wear suitable respiratory equipment when necessary.
--	--

### 6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

### 6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water. Use explosion proof equipment.
--	--

### 6.4. Reference to other sections

	See section 8 for further information. See section 13 for further information.
--	---

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking. Vapours are heavier than air. Wash hands after handling the product.
--	---

### 7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers. Store in original container.
--	---

### 7.3. Specific end use(s)

	See section 1.2 for further information.
--	--

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

# Centrecoat MMA Steel Primer - Adhesion Promotor

Revision 1

Revision date 2019-10-29

## 8.1.1. Exposure Limit Values

2-Methylpropenoic acid (Methacrylic acid)	WEL 8-hr limit ppm: 20	WEL 8-hr limit mg/m3: 72
	WEL 15 min limit ppm: 40	WEL 15 min limit mg/m3: 143
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:
Methyl methacrylate	WEL 8-hr limit ppm: 50	WEL 8-hr limit mg/m3: 208
	WEL 15 min limit ppm: 100	WEL 15 min limit mg/m3: 416
	WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
	WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:

## 8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC). Butyl rubber gloves.
Skin protection - Other	Wear suitable protective clothing.
Respiratory protection	Wear suitable respiratory equipment when necessary.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Yellow/Brown
Odour	Characteristic
Vapour pressure	0.0004 Pa
Vapour density	No data available
Relative density	No data available
Fat Solubility	No data available
Partition coefficient	No data available
Autoignition temperature	430 °C
Viscosity	45 mPas (Cone & Plate)
Explosive properties	No data available
Oxidising properties	No data available
Odour threshold	No data available
pH	Not applicable.
Melting point	< 0 °C
Freezing Point	No data available
Initial boiling point	100 °C
Flash point	10 °C
Evaporation rate	No data available
Flammability (solid, gas)	No data available
Solubility	Not applicable.

### 9.2. Other information

# Centrecoat MMA Steel Primer - Adhesion Promotor

Revision 1

Revision date 2019-10-29

## 9.2. Other information

Conductivity	No data available
Surface tension	No data available
Gas group	No data available
Benzene Content	0 %
Lead content	0 %
VOC (Volatile organic compounds)	0 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

See section 10.2 for further information.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Oxidising agents.

### 10.4. Conditions to avoid

Heat, sparks and open flames.

### 10.5. Incompatible materials

Alkalis. Oxidising agents. Peroxides. Reducing agents. Sulphur oxides.

### 10.6. Hazardous decomposition products

Will not decompose if stored and used as recommended.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity	Oral Rat LD50 = >5,000mg/kg (Methyl Methacrylate).	
Skin corrosion/irritation	Causes severe burns.	
Serious eye damage/irritation	Causes serious eye damage.	
Respiratory or skin sensitisation	May cause sensitisation by skin contact.	
Germ cell mutagenicity	No mutagenic effects reported.	
Carcinogenicity	No carcinogenic effects reported.	
Reproductive toxicity	No observed effect level. No teratogenic effects reported.	
Aspiration hazard	No Significant Hazard.	

#### 11.1.4. Toxicological Information

methacryloyloxyethyl phosphate	Oral Rat LD50: >2000mg/kg	
Methyl methacrylate	Dermal Rat LD50: >5,000mg/kg	Oral Rat LD50: >2,000mg/kg
	Dermal Rabbit LD50: >5,000mg/kg	Inhalation Rat LC50/4 h: 29.8mg/kg

## SECTION 12: Ecological information

### 12.1. Toxicity

Methyl methacrylate	Daphnia EC50/48h: 69.0000 mg/l	Fish LC50/96h: 79.0000 mg/l
---------------------	--------------------------------	-----------------------------

### 12.2. Persistence and degradability

Readily biodegradable. OECD 301C, 14D.

### 12.3. Bioaccumulative potential

# Centrecoat MMA Steel Primer - Adhesion Promotor

Revision 1

Revision date 2019-10-29

## 12.3. Bioaccumulative potential

No observed effect level.

## Partition coefficient

Centrecoat MMA Steel Primer No data available  
Adhesion Promotor

## 12.4. Mobility in soil

Slightly soluble in water.

## 12.5. Results of PBT and vPvB assessment

PBT no. vPvB no.

## 12.6. Other adverse effects

No data is available on this product.

## SECTION 13: Disposal considerations

### General information

08 01 11\* waste paint and varnish containing organic solvents or other dangerous substances.

### Disposal methods

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. Waste packaging should be recycled if possible. Incineration should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned. Empty containers or liners may still contain residue. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

### Disposal of packaging

Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

## SECTION 14: Transport information

### Hazard pictograms



### 14.1. UN number

UN2924

### 14.2. UN proper shipping name

FLAMMABLE LIQUID, CORROSIVE, N.O.S. (contains methyl methacrylate &amp; methacryloyloxyethyl phosphate)

### 14.3. Transport hazard class(es)

ADR/RID	3
Subsidiary risk	8
IMDG	3
Subsidiary risk	8
IATA	3

Print date 2019-10-29

# Centrecoat MMA Steel Primer - Adhesion Promotor

Revision 1

Revision date 2019-10-29

<b>14.3. Transport hazard class(es)</b>	
Subsidiary risk	8
<b>14.4. Packing group</b>	
Packing group	II
<b>14.5. Environmental hazards</b>	
Environmental hazards	No
Marine pollutant	No
<b>14.6. Special precautions for user</b>	
	Not applicable.
<b>14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b>	
	Not applicable.
<b>ADR/RID</b>	
Hazard ID	338
Tunnel Category	(D/E)
<b>IMDG</b>	
EmS Code	F-E S-C
<b>IATA</b>	
Packing Instruction (Cargo)	363
Maximum quantity	5 L
Packing Instruction (Passenger)	352
Maximum quantity	1 L
<b>Further information</b>	
	The product is not classified as dangerous for carriage.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

### 15.2. Chemical safety assessment

This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

### Other information

Revision	This document differs from the previous version in the following areas: 4 - Eye contact.
----------	---

# Centrecoat MMA Steel Primer - Adhesion Promotor

Revision 1

Revision date 2019-10-29

## Other information

<b>Text of Hazard Statements in Section 3</b>	Skin Corr. 1B: H314 - Causes severe skin burns and eye damage. Eye Dam. 1: H318 - Causes serious eye damage. Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. STOT SE 3: H335 - May cause respiratory irritation. Acute Tox. 4: H302 - Harmful if swallowed. Acute Tox. 4: H312 - Harmful in contact with skin. Skin Corr. 1A: H314 - Causes severe skin burns and eye damage.
<b>Maximum content of VOC</b>	0 g/l.

## Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--