

## SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830 - United Kingdom (UK)

# Centrecoat MMA Colour Coat Base

**Page** 1/8

Revision 1
Revision date 2019-10-29

SECTION 1: Identification of the substance/mixture and	of the company/undertaking
--	----------------------------

#### 1.1. Product identifier

Product name	Centrecoat MMA Colour Coat - Base		
1.2. Relevant identified uses of the substance or mixture and uses advised against			
Product Use	[SU3] Industrial uses: Uses of substances as such or in preparations at industrial sites; [PC9a]		

Coatings and paints, thinners, paint removers; [PROC10] Roller application or brushing;

### 1.3. Details of the supplier of the safety data sheet

Company	Promain UK Limited
Address C1 Pierson Co	
	Knowl Piece, Hitchin
	Hertfordshire

SG4 0TY

Web www.promain.co.uk
Telephone 01462 421333

Fax .

Email info@promain.co.uk

### 1.4. Emergency telephone number

Emergency telephone 01462 421333

8.30am - 5.30pm Mon - Thurs. 8.30am - 4.30pm Fri

### SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

2.1.2. Classification - EC	Flam. Liq. 2: H225; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT SE 3: H335;
1272/2008	

### 2.2. Label elements

### Hazard pictograms



### Signal Word

Hazard Statement Flar

Danger

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

STOT SE 3: H335 - May cause respiratory irritation.

Precautionary Statement:

Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Revision Revision date 2019-10-29

2.2. Label elements	Revision date 2019-10-2
	P233 - Keep container tightly closed. P240 - Ground/bond container and receiving equipment. P241 - Use explosion-proof electrical/ventilating/lighting// equipment. P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement: Response	P302+P352 - IF ON SKIN: Wash with plenty of water/. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312 - Call a POISON CENTER/doctor/ /if you feel unwell. P321 - Specific treatment (see on this label). P332+P313 - If skin irritation occurs: Get medical advice/attention. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P370+P378 - In case of fire: Use to extinguish.
Precautionary Statement: Storage	P403+P233 - Store in a well-ventilated place. Keep container tightly closed. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to

### SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

### EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Methyl methacrylate	607-035-00-6	80-62-6	201-297-1	01-2119452498-28		Flam. Liq. 2: H225; STOT SE 3: H335; Skin Irrit. 2: H315; Skin Sens. 1: H317;
2-Ethylhexyl acrylate	607-107-00-7	103-11-7	203-080-7	01-2119453158-37		STOT SE 3: H335; Skin Irrit. 2: H315; Skin Sens. 1: H317;
N,N-bis-(2-hydroxypropyl) -p-toluidine		38668-48-3	254-075-1	01-2119980937-17		Acute Tox. 2: H300; Eye Irrit. 2: H319; Aquatic Chronic 3: H412;

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

2 occinpatori or mot alla moat			
Inhalation	Move the exposed person to fresh air.		
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing.		
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing.		
Ingestion	DO NOT INDUCE VOMITING. Drink 1 to 2 glasses of water.		
4.2. Most important symptoms a	and effects, both acute and delayed		
Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.		
Eve contact	Irritating to eyes		

Eye contact	Irritating to eyes.
Skin contact	Irritating to skin.
Ingestion	Ingestion may cause nausea and vomiting.

### 4.3. Indication of any immediate medical attention and special treatment needed

Inhalation Seek medical attention.

Revision 1
Revision date 2019-10-29

		Revision date 2019-10-		
4.3. Indication of any immed	liate medical attention and special treatment nee	ded		
Eye contact	Seek medical attention if irritation or sympt			
Skin contact	Seek medical attention if irritation or symptoms persist.			
Ingestion	Seek medical attention.			
SECTION 5: Firefighting	measures			
5.1. Extinguishing media				
	Carbon oxides. Dry chemical. Foam. Do N	OT use water jet.		
5.2. Special hazards arising	from the substance or mixture			
	Highly flammable. Burning produces irritati considerable distance to source of ignition	ng, toxic and obnoxious fumes. Vapour may travel and flash back.		
5.3. Advice for firefighters				
	Self-contained breathing apparatus. Wear	protective clothing.		
SECTION 6: Accidental I	release measures			
6.1. Personal precautions, p	protective equipment and emergency procedures			
	Ensure adequate ventilation of the working	area. Wear suitable protective equipment. Eliminate all a safe area. Wear suitable respiratory equipment when		
6.2. Environmental precaution	ons			
	Do not allow product to enter drains. Preve	ent further spillage if safe.		
6.3. Methods and material fo	or containment and cleaning up			
	Absorb with inert, absorbent material. Swe	ep up. Transfer to suitable, labelled containers for		
		disposal. Clean spillage area thoroughly with plenty of water. Use explosion proof equipment.		
6.4. Reference to other sect	ions			
	See section 8 for further information.			
	See section 13 for further information.			
SECTION 7: Handling ar	nd storage			
7.1. Precautions for safe ha	ndling			
		adequate ventilation of the working area. Use explosion of ignition - No smoking. Vapours are heavier than air.		
7.2. Conditions for safe stor	age, including any incompatibilities			
	Keep in a cool, dry, well ventilated area. Keep containers. Store in original container.	eep containers tightly closed. Store in correctly labelled		
7.3. Specific end use(s)				
	See section 1.2 for further information.			
SECTION 8: Exposure c	ontrols/personal protection			
8.1. Control parameters	ona dio, percenar protection			
8.1.1. Exposure Limit Value	s			
Methyl methacrylate	WEL 8-hr limit ppm: 50	WEL 8-hr limit mg/m3: 208		
	WEL 15 min limit ppm: 100	WEL 15 min limit mg/m3: 416		
	WEL 8-hr limit mg/m3 total  - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:		
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -		
	respirable dust:	respirable dust:		

Revision Revision date 2019-10-29

### 8.2. Exposure controls





Ensure adequate ventilation of the working area.



8.2.1. Appropriate engineering

controls

Wear chemical protective clothing.

8.2.2. Individual protection

measures Eye / face protection

Skin protection -

Approved safety goggles.

Handprotection

Chemical resistant gloves (PVC). Butyl rubber gloves.

Skin protection - Other Respiratory protection

Wear suitable protective clothing.

Wear suitable respiratory equipment when necessary.

### SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Liquid Appearance

> Colour Translucent

Odour Strong/Characteristic

Odour threshold No data available

> рΗ No data available

Melting point | Not applicable.

Freezing Point -48 °C

100 °C Initial boiling point

> Flash point 10 °C

Evaporation rate Not applicable.

Flammability (solid, gas) No data available

Upper Explosive Limit | 12.5 %

Lower Explosive Limit 2.1 %

> Vapour pressure No data available

Vapour density No data available

Relative density 0.979 (H2O = 1 @ 20 °C)

**Fat Solubility** No data available

Partition coefficient No data available

Autoignition temperature 430 °C

> Viscosity 200 mPas (Cone & Plate)

No data available **Explosive properties** 

Oxidising properties No data available

Solubility Slightly soluble in water

### 9.2. Other information

Conductivity No data available

Surface tension No data available

No data available Gas group

Benzene Content 0 %

Lead content

VOC (Volatile organic 0 g/l

compounds)

0 %

### SECTION 10: Stability and reactivity

### 10.1. Reactivity

Revision 1
Revision date 2019-10-29

		Revision date 2019-10-2	
10.1. Reactivity			
	See section 10.2 for further information.		
10.2. Chemical stability			
·	Stable under normal conditions.		
10.3. Possibility of hazardous re	1		
10.0. I Ossibility of Hazardous re			
40.4.0 199 4 11	Oxidising agents.		
10.4. Conditions to avoid	T		
	Heat, sparks and open flames.		
10.5. Incompatible materials			
	Alkalis. Oxidising agents. Peroxides. Reducing agent	s. Sulphur oxides.	
10.6. Hazardous decomposition	products		
	Will not decompose if stored and used as recommen	ded.	
SECTION 11: Toxicological	information		
11.1. Information on toxicologica	al effects		
Acute toxicity	Oral Rat LD50 = >5,000mg/kg (Methyl Methacrylate)		
Skin corrosion/irritation	Irritating to skin.		
Serious eye damage/irritation	Irritating to eyes.		
Respiratory or skin sensitisation	May cause sensitisation by skin contact.		
Germ cell mutagenicity	No mutagenic effects reported.		
Carcinogenicity	No carcinogenic effects reported.		
Reproductive toxicity	No observed effect level. No teratogenic effects repo	rted.	
Aspiration hazard	No Significant Hazard.		
11.1.4. Toxicological Information	1		
2-Ethylhexyl acrylate	Oral Rat LD50: 4,435mg/kg	Dermal Rabbit LD50: >5,000mg/kg	
Methyl methacrylate	Dermal Rat LD50: >5,000mg/kg	Oral Rat LD50: >2,000mg/kg	
	Dermal Rabbit LD50: >5,000mg/kg	Inhalation Rat LC50/4 h: 29.8mg/kg	
N,N-bis-(2-hydroxypropyl) -p-toluidine	Oral Rat LD50: 172mg/kg		
SECTION 12: Ecological info	ormation		
12.1. Toxicity			
Methyl methacrylate	<b>Daphnia EC50/48h:</b> 69.0000 mg/l	Fish LC50/96h: 79.0000 mg/l	
12.2. Persistence and degradab	ility		
	Readily biodegradable. OECD 301C, 14D.		
12.3. Bioaccumulative potential	Treadily bloadgradable. CEOD 6016, 11B.		
·			
	No observed effect level.		
Partition coefficient			
	Centrecoat MMA Colour Coat - Base - No info		
12.4. Mobility in soil			
7. MODING III 3011	Slightly soluble in water.		
12.5. Results of PBT and vPvB			

Revision

Revision date 2019-10-29 12.5. Results of PBT and vPvB assessment PBT no. vPvB no. 12.6. Other adverse effects No data is available on this product. **SECTION 13: Disposal considerations** General information 08 01 11\* waste paint and varnish containing organic solvents or other dangerous substances. Disposal methods The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. Waste packaging should be recycled if possible. Incineration should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned. Empty containers or liners may still contain residue. Avoid dispersal of spilt material and runoff and contact sith soil, waterways, drains and sewers. Disposal of packaging Residues and empty containers should be taken care of as hazardous waste according to local and national provisions SECTION 14: Transport information Hazard pictograms 14.1. UN number UN1866 14.2. UN proper shipping name RESIN SOLUTION ((Methyl Methacrylate)) 14.3. Transport hazard class(es) ADR/RID 3 Subsidiary risk **IMDG** 3 Subsidiary risk 3 **IATA** Subsidiary risk 14.4. Packing group Ш Packing group 14.5. Environmental hazards **Environmental hazards** No Marine pollutant No 14.6. Special precautions for user Not applicable.

Revision 1
Revision date 2019-10-29

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code		
	Not applicable.	
ADR/RID		
Hazard ID	33	
Tunnel Category	(D/E)	
IMDG		
EmS Code	F-E S-E	
IATA		
Packing Instruction (Cargo)	364	
Maximum quantity	60 L	
Packing Instruction (Passenger)	353	
Maximum quantity	5 L	
Further information		
	The product is not classified as dangerous for carriage.	

### **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

### 15.2. Chemical safety assessment

This product contains substances for which Chemical Safety Assessments are still required.

### **SECTION 16: Other information**

O4L	inform	-4!
CITHER	Intorm	ation

Revision	This document differs from the previous version in the following areas:.
	4 - Eye contact.
Text of Hazard Statements in	Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
Section 3	Skin Irrit. 2: H315 - Causes skin irritation.
	Skin Sens. 1: H317 - May cause an allergic skin reaction.
	STOT SE 3: H335 - May cause respiratory irritation.
	Acute Tox. 2: H300 - Fatal if swallowed.
	Eye Irrit. 2: H319 - Causes serious eye irritation.
	Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Maximum content of VOC	0 g/l.

### **Further information**

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in

Revision

1 Revision date 2019-10-29

**Further information** combination with any other materials or in any other process.