

SAFFTY DATA SHFFT

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830 - United Kingdom (UK)

Centrecoat MMA Multi-Use Primer Base

Coatings and paints, thinners, paint removers; [PROC10] Roller application or brushing;

Revision 1

Revision date 2019-10-29

SECTION 1: Identification of the substance/mixture and c	of the company/undertaking
--	----------------------------

1.1. Product identifier

Product name	Centrecoat MMA Multi-Use Primer - Base		
1.2. Relevant identified uses of the substance or mixture and uses advised against			
Product Use [SU3] Industrial uses: Uses of substances as such or in preparations at industrial sites; [PC			

1.3. Details of the supplier of the safety data sheet

Company	Promain UK Limited	
Address	C1 Pierson Court	
	Knowl Piece, Hitchin	

Hertfordshire SG4 0TY

Web www.promain.co.uk
Telephone 01462 421333

Fax |

Email info@promain.co.uk

1.4. Emergency telephone number

Emergency telephone number 01462 421333

8.30am - 5.30pm Mon - Thurs. 8.30am - 4.30pm Fri

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC	Flam. Liq. 2: H225; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT SE 3: H335;
1272/2008	

2.2. Label elements

Hazard pictograms



Signal Word

Hazard Statement

Danger

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

STOT SE 3: H335 - May cause respiratory irritation.

Precautionary Statement:

Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Revision 1
Revision date 2019-10-29

2.2. Label elements

Z.Z. Label elements	
	P233 - Keep container tightly closed.
	P240 - Ground/bond container and receiving equipment.
	P241 - Use explosion-proof electrical/ventilating/lighting// equipment.
	P242 - Use only non-sparking tools.
	P243 - Take precautionary measures against static discharge.
	P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
	P264 - Wash thoroughly after handling.
	P271 - Use only outdoors or in a well-ventilated area.
	P272 - Contaminated work clothing should not be allowed out of the workplace.
	P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement:	P302+P352 - IF ON SKIN: Wash with plenty of water/ .
Response	P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse
•	skin with water/shower.
	P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	P312 - Call a POISON CENTER/doctor/ /if you feel unwell.
	P321 - Specific treatment (see on this label).
	P332+P313 - If skin irritation occurs: Get medical advice/attention.
	P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
	P370+P378 - In case of fire: Use to extinguish.
Precautionary Statement:	P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
Storage	P403+P235 - Store in a well-ventilated place. Keep cool.
•	P405 - Store locked up.
Precautionary Statement:	P501 - Dispose of contents/container to

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Disposal

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Methyl methacrylate	607-035-00-6	80-62-6	201-297-1	01-2119452498-28		Flam. Liq. 2: H225; STOT SE 3: H335; Skin Irrit. 2: H315;
N,N-bis-(2-hydroxypropyl) -p-toluidine		38668-48-3	254-075-1	01-2119980937-17		Skin Sens. 1: H317; Acute Tox. 2: H300; Eye Irrit. 2: H319; Aquatic Chronic 3:
N,N-Dimethyl-p-toluidine	612-056-00-9	99-97-8	202-805-4			H412; Acute Tox. 3: H331; Acute
						Tox. 3: H311; Acute Tox. 3: H301; STOT RE 2: H373; Aquatic Chronic 3: H412;

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.	
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Remove contact	
	lenses, if present and easy to do. Continue rinsing.	
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing.	
Ingestion	DO NOT INDUCE VOMITING. Drink 1 to 2 glasses of water.	

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.	
Eye contact	Irritating to eyes.	
Skin contact	Irritating to skin.	
Ingestion	Ingestion may cause nausea and vomiting.	

4.3. Indication of any immediate medical attention and special treatment needed

Revision 1 Revision date 2019-10-29

4.2 Indication of any im	Revision date 2019-10-		
	mediate medical attention and special treatment needed		
Inhalation	Seek medical attention. Seek medical attention if irritation or symptoms persist.		
Eye contact Skin contact	Seek medical attention if irritation or symptoms persist. Seek medical attention if irritation or symptoms persist.		
Ingestion	Seek medical attention.		
SECTION 5: Firefight	ting measures		
5.1. Extinguishing media	a		
	Carbon oxides. Dry chemical. Foam. Do NOT use water jet.		
5.2. Special hazards ari	sing from the substance or mixture		
	Highly flammable. Burning produces irritating, toxic and obnoxious fumes. Vapour may travel considerable distance to source of ignition and flash back.		
5.3. Advice for firefighte	rs		
	Self-contained breathing apparatus. Wear protective clothing.		
SECTION 6: Acciden	tal release measures		
6.1. Personal precaution	ns, protective equipment and emergency procedures		
	Ensure adequate ventilation of the working area. Wear suitable protective equipment. Eliminate al sources of ignition. Evacuate personnel to a safe area. Wear suitable respiratory equipment when necessary.		
6.2. Environmental prec	autions		
	Do not allow product to enter drains. Prevent further spillage if safe.		
6.3. Methods and mater	ial for containment and cleaning up		
	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water. Use explosion proof equipment.		
6.4. Reference to other	sections		
	See section 8 for further information. See section 13 for further information.		
SECTION 7: Handlin	g and storage		
7.1. Precautions for safe	e handling		
	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking. Vapours are heavier than air.		
7.2. Conditions for safe	storage, including any incompatibilities		
	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers. Store in original container.		
7.3. Specific end use(s)			
	See section 1.2 for further information.		
SECTION 8: Exposur	re controls/personal protection		
8.1. Control parameters			
8.1.1. Exposure Limit Va	alues		

Revision 1
Revision date 2019-10-29

8.1.1. Exposure Limit Values

Methyl methacrylate

WEL 8-hr limit ppm: 50

WEL 15 min limit ppm: 100

WEL 15 min limit mg/m3: 416

WEL 8-hr limit mg/m3 total
inhalable dust:

WEL 8-hr limit mg/m3 total
well 15 min limit mg/m3 total
inhalable dust:

WEL 8-hr limit mg/m3 total
respirable dust:

respirable dust:

8.2. Exposure controls



8.2.1. Appropriate engineering controls

8.2.2. Individual protection

measures

Eye / face protection

Skin protection - Handprotection

Skin protection - Other

Respiratory protection

Ensure adequate ventilation of the working area.

Wear chemical protective clothing.

Approved safety goggles.

Chemical resistant gloves (PVC). Butyl rubber gloves.

Wear suitable protective clothing.

Wear suitable respiratory equipment when necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Liquid

Colour Colourless

Odour Strong/Characteristic

Odour threshold No data available

pH No data available

Melting point No data available

Freezing Point -48 °C

Initial boiling point > 100 °C

Flash point 10 °C

Evaporation rate No data available

Flammability (solid, gas) No data available

Upper Explosive Limit 12.5 %

Lower Explosive Limit 2.1 %

Vapour pressure No data available

Vapour density > 1 g/cm³

Relative density No data available Fat Solubility No data available

Partition coefficient No data available

Autoignition temperature 430 °C

Viscosity 200 mPas (Cone & Plate)

Explosive properties No data available

Oxidising properties No data available

Solubility | Slightly soluble in water

9.2. Other information

Revision 1
Revision date 2019-10-29

9.2. Other information Conductivity No data available Surface tension No data available Gas group No data available Benzene Content 0 % 0 % Lead content VOC (Volatile organic 0 g/l compounds) SECTION 10: Stability and reactivity 10.1. Reactivity See section 10.2 for further information. 10.2. Chemical stability Stable under normal conditions. 10.3. Possibility of hazardous reactions Oxidising agents. 10.4. Conditions to avoid Heat, sparks and open flames. 10.5. Incompatible materials Alkalis. Oxidising agents. Peroxides. Reducing agents. Sulphur oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

10.6. Hazardous decomposition products

Acute toxicity	Oral Rat LD50 = >5,000mg/kg (Methyl Methacrylate).
Skin corrosion/irritation	Irritating to skin.
Serious eye damage/irritation	Irritating to eyes.
Respiratory or skin sensitisation	May cause sensitisation by skin contact.
Germ cell mutagenicity	No mutagenic effects reported.
Carcinogenicity	No carcinogenic effects reported.
Reproductive toxicity	No observed effect level. No teratogenic effects reported.
Aspiration hazard	No Significant Hazard.

Will not decompose if stored and used as recommended.

11.1.4. Toxicological Information

Methyl methacrylate	Dermal Rat LD50: >5,000mg/kg	Oral Rat LD50: >2,000mg/kg
	Dermal Rabbit LD50: >5,000mg/kg	Inhalation Rat LC50/4 h: 29.8mg/kg
N,N-bis-(2-hydroxypropyl) -p-toluidine	Oral Rat LD50: 172mg/kg	

SECTION 12: Ecological information

12.1. Toxicity

Methyl methacrylate	Daphnia EC50/48h: 69.0000 mg/l	Fish LC50/96h: 79.0000 mg/l		
12.2. Persistence and degradability				
Readily biodegradable. OECD 301C, 14D.				
12.3. Bioaccumulative potential				

Revision 1
Revision date 2019-10-29

40.0 Plan	Revision date 2019-10-
12.3. Bioaccumulative potential	
	No observed effect level.
Partition coefficient	1.0 0000.100 0.1001.
	Centrecoat MMA Multi-Use Primer - Base No data available
12.4. Mobility in soil	
	Slightly soluble in water.
12.5. Results of PBT and v	/PvB assessment
	PBT no. vPvB no.
12.6. Other adverse effects	S
	No data is available on this product.
SECTION 13: Disposal	considerations
General information	
	08 01 11* waste paint and varnish containing organic solvents or other dangerous substances.
Disposal methods	•
Disposal of packaging SECTION 14: Transpor Hazard pictograms	The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. Waste packaging should be recycled if possible. Incineration should only be considered when recycling is not feasible. This material and its container must be dispose of in a safe way. Care should be taken when handling emptied containers that have not been cleaned. Empty containers or liners may still contain residue. Avoid dispersal of spilt material and runoff and contact sith soil, waterways, drains and sewers. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.
14.1. UN number	·
	UN1866
14.2. UN proper shipping r	name
	RESIN SOLUTION ((Methyl Methacrylate))
14.3. Transport hazard cla	ss(es)
ADR/RID	3
Subsidiary risk	-
IMDG	3
Subsidiary risk	
IATA	3

Revision 1
Revision date 2019-10-29

14.3. Transport hazard class(es	
Subsidiary risk	-
14.4. Packing group	
Packing group	П
14.5. Environmental hazards	
Environmental hazards	No
Marine pollutant	No
14.6. Special precautions for us	er
	Not applicable.
14.7. Transport in bulk according	g to Annex II of MARPOL 73/78 and the IBC Code
	Not applicable.
ADR/RID	
Hazard ID	33
Tunnel Category	(D/E)
IMDG	
EmS Code	F-E S-E
IATA	
Packing Instruction (Cargo)	364
Maximum quantity	60 L
Packing Instruction (Passenger)	353
Maximum quantity	5 L
Further information	
	The product is not classified as dangerous for carriage.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

15.2. Chemical safety assessment

This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Other information

RevisionThis document differs from the previous version in the following areas:.

4 - Eye contact.

Revision 1
Revision date 2019-10-29

Other information		
Text of Hazard Statements in Section 3	Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. STOT SE 3: H335 - May cause respiratory irritation. Acute Tox. 2: H300 - Fatal if swallowed. Eye Irrit. 2: H319 - Causes serious eye irritation. Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects. Acute Tox. 3: H301 - Toxic if swallowed. Acute Tox. 3: H311 - Toxic in contact with skin. Acute Tox. 3: H331 - Toxic if inhaled. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.	
Maximum content of VOC	0 g/l.	
Further information		
	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.	