

## Centrecoat Epoxy Paste Adhesive - Curing Agent

Page 1/8

Revision

0

Revision date 2019-10-02

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name** Centrecoat Epoxy Paste Adhesive - Curing Agent

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Product Use** [SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen); [PC9a] Coatings and paints, thinners, paint removers; [PROC10] Roller application or brushing; [ERC2] Formulation of preparations;

#### 1.3. Details of the supplier of the safety data sheet

**Company** Promain UK Limited  
**Address** Promain House  
 C1 Pierson Court  
 Knowl Piece, Hitchin  
 Hertfordshire  
 SG4 0TY  
**Web** www.promain.co.uk  
**Telephone** 01462 421333  
**Fax** -  
**Email** info@promain.co.uk

#### 1.4. Emergency telephone number

**Emergency telephone number** 01462 421333  
 8.30am - 5.30pm Mon - Thurs. 8.30am - 4.30pm Fri

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

**2.1.2. Classification - EC 1272/2008** Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1: H317; Acute Tox. 4: H332; Aquatic Chronic 3: H412;

#### 2.2. Label elements

**Hazard pictograms**



**Signal Word**

Danger

**Hazard Statement**

Acute Tox. 4: H302 - Harmful if swallowed.  
 Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.  
 Skin Sens. 1: H317 - May cause an allergic skin reaction.  
 Acute Tox. 4: H332 - Harmful if inhaled.  
 Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

# Centrecoat Epoxy Paste Adhesive - Curing Agent

Revision 0

Revision date 2019-10-02

## 2.2. Label elements

<b>Precautionary Statement: Prevention</b>	<p>P260 - Do not breathe dust/fume/gas/mist/vapours/spray.  P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.  P264 - Wash thoroughly after handling.  P270 - Do not eat, drink or smoke when using this product.  P271 - Use only outdoors or in a well-ventilated area.  P272 - Contaminated work clothing should not be allowed out of the workplace.  P273 - Avoid release to the environment.  P280 - Wear protective gloves/protective clothing/eye protection/face protection.</p>
<b>Precautionary Statement: Response</b>	<p>P301+P312 - IF SWALLOWED: Call a POISON CENTER/doctor/ /if you feel unwell.  P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting.  P302+P352 - IF ON SKIN: Wash with plenty of water/ .  P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  P310 -Immediately call a POISON CENTER/doctor/ .  P312 - Call a POISON CENTER/doctor/ /if you feel unwell.  P321 - Specific treatment (see on this label).  P330 - Rinse mouth.  P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  P363 - Wash contaminated clothing before reuse.</p>
<b>Precautionary Statement: Storage</b>	P405 - Store locked up.
<b>Precautionary Statement: Disposal</b>	P501 - Dispose of contents/container to

## 2.3. Other hazards

<b>Other hazards</b>	No data is available on this product.
----------------------	---------------------------------------

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Benzyl alcohol	603-057-00-5	100-51-6	202-859-9	01-2119492630-38	30 - 40%	Acute Tox. 4: H332; Acute Tox. 4: H302;
m-xylylenediamine		1477-55-0	216-032-5	01-2119480150-50	10 - 20%	Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1: H317; Acute Tox. 4: H332; Aquatic Chronic 3: H412;
3-Aminomethyl-3,5,5-trimethylcyclohexylamine	612-067-00-9	2855-13-2	220-666-8	01-2119514687-32	10 - 20%	Acute Tox. 4: H312; Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1: H317; Aquatic Chronic 3: H412;
Salicylic Acid		69-72-7	200-712-3	01-2119486984-17	1 - 10%	Acute Tox. 4: H302; Eye Dam. 1: H318;
4,4'-Isopropylidenediphol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with m-phenylenebis(methylamine)		113930-69-1			1 - 10%	Acute Tox. 4: H302; Skin Sens. 1: H317; Aquatic Chronic 2: H411;

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>Inhalation</b>	Move the exposed person to fresh air.
<b>Eye contact</b>	Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing.

Print date 2019-10-02

# Centrecoat Epoxy Paste Adhesive - Curing Agent

Revision 0

Revision date 2019-10-02

## 4.1. Description of first aid measures

Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing.
Ingestion	Move the exposed person to fresh air. Drink 1 to 2 glasses of water. DO NOT INDUCE VOMITING.

## 4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.
Eye contact	Risk of serious damage to eyes.
Skin contact	May cause irritation to skin.
Ingestion	HARMFUL IF SWALLOWED. Causes burns.

## 4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	If you feel unwell, seek medical advice (show the label where possible).
Eye contact	Seek medical attention.
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	Seek urgent medical attention.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

	Use extinguishing media appropriate to the surrounding fire conditions. Carbon oxides. Dry chemical. Foam. Do NOT use water jet.
--	--

### 5.2. Special hazards arising from the substance or mixture

	Burning produces irritating, toxic and obnoxious fumes.
--	---

### 5.3. Advice for firefighters

	Wear self contained breathing apparatus and protective clothing.
--	--

### Further information

	Dispose of as special waste in compliance with official regulations.
--	--

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

	Ensure adequate ventilation of the working area. Avoid contact with skin and eyes.
--	--

### 6.2. Environmental precautions

	Do not allow product to enter drains. Prevent further spillage if safe.
--	---

### 6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.
--	---

### 6.4. Reference to other sections

	See section 8 for further information. See section 13 for further information.
--	---

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

	Ensure adequate ventilation of the working area. Avoid contact with eyes and skin. Adopt best Manual Handling considerations when handling, carrying and dispensing.
--	--

### 7.2. Conditions for safe storage, including any incompatibilities

	Keep containers tightly closed. Keep in a cool, dry, well ventilated area. Store in correctly labelled containers.
--	--

### 7.3. Specific end use(s)

	See section 1.2. Relevant identified uses of the substance or mixture and uses advised against for further information.
--	---

# Centrecoat Epoxy Paste Adhesive - Curing Agent

Revision 0

Revision date 2019-10-02

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

This product does not contain any relevant quantities of materials with critical values that have to be monitored in the workplace.  
WEL-8hr Limit - 90mg/m<sup>3</sup>, (Benzyl Alcohol).

### 8.2. Exposure controls



#### 8.2.1. Appropriate engineering controls

Ensure adequate ventilation of the working area.

#### 8.2.2. Individual protection measures

Wear protective clothing.

#### Eye / face protection

Approved safety goggles.

#### Skin protection - Handprotection

Wear suitable gloves.

#### Skin protection - Other

Wear suitable protective clothing.

#### Respiratory protection

Wear suitable respiratory equipment when necessary.

#### Occupational exposure controls

Keep away from food, drink and animal feedingstuffs.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Liquid
<b>Colour</b>	Light yellow
<b>Odour</b>	Characteristic
<b>pH</b>	No data available
<b>Melting point</b>	No data available
<b>Freezing Point</b>	No data available
<b>Initial boiling point</b>	> 200 °C
<b>Flash point</b>	100 °C
<b>Evaporation rate</b>	No data available
<b>Flammability (solid, gas)</b>	No data available
<b>Vapour pressure</b>	10 Pa
<b>Vapour density</b>	No data available
<b>Relative density</b>	1.06 (H <sub>2</sub> O = 1 @ 20 °C)
<b>Fat Solubility</b>	No data available
<b>Partition coefficient</b>	No data available
<b>Autoignition temperature</b>	380 °C
<b>Viscosity</b>	200 mPas (Cone & Plate)
<b>Explosive properties</b>	No data available
<b>Oxidising properties</b>	No data available
<b>Solubility</b>	Insoluble in water

### 9.2. Other information

# Centrecoat Epoxy Paste Adhesive - Curing Agent

Revision 0

Revision date 2019-10-02

## 9.2. Other information

Conductivity	No data available
Surface tension	No data available
Gas group	No data available
Benzene Content	0 %
Lead content	0 %
VOC (Volatile organic compounds)	0 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Stable under normal conditions.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Reacts with. Acids. Alkalis. Oxidising agents.

### 10.4. Conditions to avoid

No data is available on this product.

### 10.5. Incompatible materials

Strong oxidising agents.

### 10.6. Hazardous decomposition products

No data is available on this product.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Skin corrosion/irritation	May cause severe irritation to skin, eyes and mucous membranes.
Serious eye damage/irritation	Risk of serious damage to eyes. Strong caustic effect.
Respiratory or skin sensitisation	May cause sensitisation by skin contact.
Germ cell mutagenicity	No mutagenic effects reported.
Reproductive toxicity	No observed effect level. No teratogenic effects reported.

#### 11.1.4. Toxicological Information

3-Aminomethyl-3,5,5-trimethylcy clohexylamine	Dermal Rat LD50: >2000mg/kg	Oral Rat LD50: 1030mg/kg
	Dermal Rabbit LD50: 1840mg/kg	
Benzyl alcohol	Oral Rat LD50: 1230mg/kg	Dermal Rabbit LD50: 2000mg/kg

#### 11.1.13. Other information

Swallowing will lead to a strong caustic effect on mouth and throat and danger of perforation of esophagus and stomach.

## SECTION 12: Ecological information

### 12.1. Toxicity

3-Aminomethyl-3,5,5-trimethylcy clohexylamine	Daphnia EC50/48h: 23 mg/l	Algae IC50/72h: 50.0000 mg/l
	Fish LC50/96h: 110.0000 mg/l	
Benzyl alcohol	Daphnia EC50/48h: 400.0000 mg/l	Algae IC50/72h: 640.0000 mg/l
	Fish LC50/96h: 645.0000 mg/l	

# Centrecoat Epoxy Paste Adhesive - Curing Agent

Revision 0

Revision date 2019-10-02

## 12.2. Persistence and degradability

No data is available on this product.

## PBT

Not applicable.

## 12.3. Bioaccumulative potential

No data is available on this product.

## Partition coefficient

Centrecoat Epoxy Paste Adhesive - Curing Agent No data available

## 12.4. Mobility in soil

No data is available on this product.

## 12.5. Results of PBT and vPvB assessment

No data is available on this product.

## 12.6. Other adverse effects

No data is available on this product.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Dispose of in compliance with all local and national regulations.

## General information

08 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS.

08 02 wastes from MFSU of other coatings (including ceramic materials).

08 02 99 wastes not otherwise specified.

## Disposal methods

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. Waste packaging should be recycled if possible. Incineration should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned. Empty containers or liners may still contain residue. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## Disposal of packaging

Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. Do NOT reuse empty containers.

## SECTION 14: Transport information

### Hazard pictograms



# Centrecoat Epoxy Paste Adhesive - Curing Agent

Revision 0

Revision date 2019-10-02

<b>14.1. UN number</b>	
	UN2735
<b>14.2. UN proper shipping name</b>	
	AMINES, LIQUID, CORROSIVE N.O.S. (Isophoronediamine)
<b>14.3. Transport hazard class(es)</b>	
ADR/RID	8
Subsidiary risk	-
IMDG	8
Subsidiary risk	-
IATA	8
Subsidiary risk	-
<b>14.4. Packing group</b>	
Packing group	III
<b>14.5. Environmental hazards</b>	
Environmental hazards	No
Marine pollutant	No
<b>14.6. Special precautions for user</b>	
	Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of a spillage.
<b>14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b>	
	For transport approval see regulatory information.
<b>ADR/RID</b>	
Hazard ID	80
Tunnel Category	(E)
<b>IMDG</b>	
EmS Code	F-A S-B
<b>IATA</b>	
Packing Instruction (Cargo)	856
Maximum quantity	60 L
Packing Instruction (Passenger)	852
Maximum quantity	5 L
<b>SECTION 15: Regulatory information</b>	
<b>15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture</b>	
Regulations	<p>REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.</p> <p>COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.</p>

# Centrecoat Epoxy Paste Adhesive - Curing Agent

Revision 0

Revision date 2019-10-02

## 15.2. Chemical safety assessment

This product contains substances for which Chemical Safety Assessments are still required.

## SECTION 16: Other information

### Other information

#### Text of Hazard Statements in Section 3

Acute Tox. 4: H302 - Harmful if swallowed.  
 Acute Tox. 4: H332 - Harmful if inhaled.  
 Acute Tox. 4: H302+H332 - Harmful if swallowed or if inhaled  
 Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.  
 Skin Sens. 1: H317 - May cause an allergic skin reaction.  
 Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.  
 Acute Tox. 4: H312 - Harmful in contact with skin.  
 Eye Dam. 1: H318 - Causes serious eye damage.  
 Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

#### Maximum content of VOC

0 g/l.

### Further information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.