

**Classidur Universal Primer Xtrem Epoxy**



**SAFETY DATA SHEET**  
(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

**SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

**1.1. Product identifier**

Product name : Classidur Universal Primer Xtrem Epoxy

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Consumer and professional

Identified uses

Paint / see technical data sheet

**1.3. Details of the supplier of the safety data sheet**

Registered company name : VERNIS CLAESSENS SA.

Address : Avenue du Silo 6.CH-1020 .Renens.Suisse.

Telephone : +41 (0)21 637 17 17. Fax : +41 (0)21 637 17 29.

mail@claessens.com

www.claessens.com

REACH EU Only Representative : ICP Alltek , Lagnieu (France) reach@icp-alltek.com

**1.4. Emergency telephone number : 145.**

Association/Organisation : centre toxicologique Zurich.

**Other emergency numbers**

England : In an emergency Contact NHS 111 or a doctor / Belgium : +32 70 245 245

**>SECTION 2 : HAZARDS IDENTIFICATION**

**2.1. Classification of the substance or mixture**

**In compliance with EC regulation No. 1272/2008 and its amendments.**

May produce an allergic reaction (EUH208).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

**> 2.2. Label elements**

Contains biocidal products.

Preservatives for products during storage

**> In compliance with EC regulation No. 1272/2008 and its amendments.**

Additional labeling :

EUH208 Contains 1,2-BENZISOTHIAZOL-3(2H)-ONE. May produce an allergic reaction.

EUH208 Contains REACTION MASS OF 5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1). May produce an allergic reaction.

EUH208 Contains 2-METHYLISOTHIAZOL-3(2H)-ONE. May produce an allergic reaction.

Precautionary statements - General :

P102 Keep out of reach of children.

Precautionary statements - Prevention :

P271 Use only outdoors or in a well-ventilated area.

Precautionary statements - Disposal :

P501 Dispose of contents/container to hazardous or special waste collection point.

**2.3. Other hazards**

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC)  $\geq$  0.1% published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

**Classidur Universal Primer Xtrem Epoxy**

**>SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**

**3.2. Mixtures**

**> Composition :**

| Identification  | (EC) 1272/2008  | Note     | %               |
|---|---|----------|-----------------|
| CATIONIC EPOXY-AMINE POLYMER  | Aquatic Chronic 3, H412   |          | 2.5 <= x % < 10 |
| INDEX: 613-088-00-6<br>CAS: 2634-33-5<br>EC: 220-120-9<br><br>1,2-BENZISOTHIAZOL-3(2H)-ONE  | GHS05, GHS07, GHS09<br>Dgr<br>Acute Tox. 4, H302<br>Skin Irrit. 2, H315<br>Eye Dam. 1, H318<br>Skin Sens. 1, H317<br>Aquatic Acute 1, H400<br>M Acute = 1   | [1]      | 0 <= x % < 1    |
| INDEX: 613-167-00-5<br>CAS: 55965-84-9<br><br>REACTION MASS OF<br>5-CHLORO-2-METHYL-2H-ISOTHIAZOL-3-ONE AND<br>2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1) | GHS06, GHS05, GHS09<br>Dgr<br>Acute Tox. 3, H301<br>Acute Tox. 2, H310<br>Skin Corr. 1C, H314<br>Skin Sens. 1A, H317<br>Eye Dam. 1, H318<br>Acute Tox. 2, H330<br>Aquatic Acute 1, H400<br>M Acute = 100<br>Aquatic Chronic 1, H410<br>M Chronic = 100<br>EUH:071 | B<br>[1] | 0 <= x % < 1    |
| INDEX: 613-326-00-9<br>CAS: 2682-20-4<br>EC: 220-239-6<br><br>2-METHYLISOTHIAZOL-3(2H)-ONE  | GHS06, GHS05, GHS09<br>Dgr<br>Acute Tox. 3, H301<br>Acute Tox. 3, H311<br>Skin Corr. 1B, H314<br>Skin Sens. 1A, H317<br>Eye Dam. 1, H318<br>Acute Tox. 2, H330<br>Aquatic Acute 1, H400<br>M Acute = 10<br>Aquatic Chronic 1, H410<br>M Chronic = 1<br>EUH:071    | [1]      | 0 <= x % < 1    |

(Full text of H-phrases: see section 16)

**Information on ingredients :**

[1] Substance for which maximum workplace exposure limits are available.

**SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

**4.1. Description of first aid measures**

**In the event of exposure by inhalation :**

In the event of an allergic reaction, seek medical attention.

**In the event of splashes or contact with eyes :**

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

**In the event of splashes or contact with skin :**

In the event of an allergic reaction, seek medical attention.

**Classidur Universal Primer Xtrem Epoxy**

---

**In the event of swallowing :**

Seek medical attention, showing the label.

**4.2. Most important symptoms and effects, both acute and delayed**

No data available.

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available.

---

**SECTION 5 : FIREFIGHTING MEASURES**

Non-flammable.

**5.1. Extinguishing media**

**5.2. Special hazards arising from the substance or mixture**

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

**5.3. Advice for firefighters**

No data available.

---

**SECTION 6 : ACCIDENTAL RELEASE MEASURES**

**6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

**For first aid worker**

First aid workers will be equipped with suitable personal protective equipment (See section 8).

**6.2. Environmental precautions**

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

**6.3. Methods and material for containment and cleaning up**

Clean preferably with a detergent, do not use solvents.

**6.4. Reference to other sections**

No data available.

---

**SECTION 7 : HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

**7.1. Precautions for safe handling**

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

**Fire prevention :**

Prevent access by unauthorised personnel.

**Recommended equipment and procedures :**

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

**Prohibited equipment and procedures :**

No smoking, eating or drinking in areas where the mixture is used.

**7.2. Conditions for safe storage, including any incompatibilities**

No data available.

**Storage**

Keep out of reach of children.

**Classidur Universal Primer Xtrem Epoxy**

**Packaging**

Always keep in packaging made of an identical material to the original.

**7.3. Specific end use(s)**

No data available.

**>SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1. Control parameters**

**> Occupational exposure limits :**

- Netherlands / MAC-waarde (10 december 2014) :

| CAS        | TWA :                  | STEL : | Ceiling : | Definition : | Criteria : |
|------------|------------------------|--------|-----------|--------------|------------|
| 55965-84-9 | 0,05 mg/m <sup>3</sup> | -      | -         | -            | -          |

- Switzerland (SUVAPRO 2017) :

| CAS       | VME                     | VLE                     | Valeur plafond | Notations |
|-----------|-------------------------|-------------------------|----------------|-----------|
| 2682-20-4 | 0,2 i mg/m <sup>3</sup> | 0,4 i mg/m <sup>3</sup> |                | S SSC     |

**8.2. Exposure controls**

**Personal protection measures, such as personal protective equipment**

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

**- Eye / face protection**

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

**- Hand protection**

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Natural latex

Recommended properties :

- Impervious gloves in accordance with standard EN374

**- Body protection**

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

**>SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**

**9.1. Information on basic physical and chemical properties**

**General information :**

Physical state :

Viscous liquid.

**> Important health, safety and environmental information**

pH :

Not stated.

Neutral.

Boiling point/boiling range :

Not specified.

Flash point interval :

Not relevant.

Vapour pressure (50°C) :

Not relevant.

Density :

> 1

Water solubility :

Dilutable.

**Classidur Universal Primer Xtrem Epoxy**

---

Melting point/melting range : Not specified.  
Self-ignition temperature : Not specified.  
Decomposition point/decomposition range : Not specified.

**9.2. Other information**

No data available.

---

**SECTION 10 : STABILITY AND REACTIVITY**

**10.1. Reactivity**

No data available.

**10.2. Chemical stability**

This mixture is stable under the recommended handling and storage conditions in section 7.

**10.3. Possibility of hazardous reactions**

No data available.

**10.4. Conditions to avoid**

No data available.

**10.5. Incompatible materials**

No data available.

**10.6. Hazardous decomposition products**

The thermal decomposition may release/form :

- carbon monoxide (CO)
  - carbon dioxide (CO<sub>2</sub>)
- 

**SECTION 11 : TOXICOLOGICAL INFORMATION**

**11.1. Information on toxicological effects**

No data available.

**11.1.1. Substances**

No toxicological data available for the substances.

**11.1.2. Mixture**

**Respiratory or skin sensitisation :**

Contains at least one sensitising substance. May cause an allergic reaction.

**Monograph(s) from the IARC (International Agency for Research on Cancer) :**

CAS 13463-67-7 : IARC Group 2B : The agent is possibly carcinogenic to humans.

---

**>SECTION 12 : ECOLOGICAL INFORMATION**

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures.

**12.1. Toxicity**

**12.1.2. Mixtures**

No aquatic toxicity data available for the mixture.

**12.2. Persistence and degradability**

No data available.

**12.3. Bioaccumulative potential**

No data available.

**12.4. Mobility in soil**

No data available.

**12.5. Results of PBT and vPvB assessment**

No data available.

**Classidur Universal Primer Xtrem Epoxy**

---

**12.6. Other adverse effects**

No data available.

---

**SECTION 13 : DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

Conform to local regulations about water protection.

Waste and used packages must be eliminated following local regulations.

**13.1. Waste treatment methods**

Do not pour into drains or waterways.

**Waste :**

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

**Soiled packaging :**

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

**Codes of wastes (Decision 2014/955/EC, Directive 2008/98/EEC on hazardous waste) :**

15 01 02 plastic packaging

08 01 12 waste paint and varnish other than those mentioned in 08 01 11

---

**SECTION 14 : TRANSPORT INFORMATION**

Exempt from transport classification and labelling.

**14.1. UN number**

-

**14.2. UN proper shipping name**

-

**14.3. Transport hazard class(es)**

-

**14.4. Packing group**

-

**14.5. Environmental hazards**

-

**14.6. Special precautions for user**

-

---

**>SECTION 15 : REGULATORY INFORMATION**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Swiss Ordinance on Protection against Major Accidents no threshold quantity

Waters Protection Ordinance Category A

**> - Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2018/1480 (ATP 13)

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2019/521 (ATP 12)

**- Container information:**

No data available.

**- Labelling for VOCs present in varnishes, paints and in vehicle refinishing products (2004/42/EC) :**

The permitted European level of VOC in this ready-to-use product is limited to 30 g/l.

The permitted European levels of VOC in the ready-to-use product (category II Ag) are 50 g/l maximum in 2007 and 30 g/l maximum in 2010.

**Classidur Universal Primer Xtrem Epoxy**

---

**- Particular provisions :**

No data available.

**15.2. Chemical safety assessment**

No data available.

---

**>SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

**> Wording of the phrases mentioned in section 3 :**

|        |   |
|--------|---|
| H301   | Toxic if swallowed.                                   |
| H302   | Harmful if swallowed.                                 |
| H310   | Fatal in contact with skin.                           |
| H311   | Toxic in contact with skin.                           |
| H314   | Causes severe skin burns and eye damage.              |
| H315   | Causes skin irritation.                               |
| H317   | May cause an allergic skin reaction.                  |
| H318   | Causes serious eye damage.                            |
| H330   | Fatal if inhaled.                                     |
| H400   | Very toxic to aquatic life.                           |
| H410   | Very toxic to aquatic life with long lasting effects. |
| H412   | Harmful to aquatic life with long lasting effects.    |
| EUH071 | Corrosive to the respiratory tract.                   |

**Abbreviations :**

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.