



## Lacq Rapidoil 2C

Lacq Rapidoil 2C is a product consisting 2 components. The A component is based on a vegetable oil and completely free of solvents. Just one coat of the product gives colour and protection to the wooden surface. When the solvent free accelerator (B component) is added, the drying process of the oil is shortened considerably so the surface can be used in less time. The A component can be used as maintenance oil on surfaces that have been treated with Rapidoil before.

Colours and protects the wooden surface with just one coat

High penetration of the surface, nourishes the wood from within.

95% renewable product

8 premixed colours which can be used together to form new colours

Enriches the natural look of the wood

Completely solvent free

Durable protection with just one coat

Economical in use: ca. 30m<sup>2</sup>/L (depending on the surface)

Suited for all wooden surfaces

Flooring and furniture

Very Durable

Durable against heat

Rapid dryingtime: 80% in 2 days

Can be cleaned with water and soap after 5 days.

## **How to use**

1. Untreated wooden surface: Sand the surface according to the standards applied on the wood. Never sand above 120... Be aware that sanding marks and other inconsistencies will be extra visible after applying Rapidoil. After sanding make sure all dust and other remains are removed thoroughly.
2. Blend the A and B component together 3:1. Stir thoroughly for about 2 minutes.
3. Before applying Rapidoil, be sure the surface is completely dry. Use a small amount of Rapidoil and apply it on parts of the total surface of approx.. 5-10m<sup>2</sup>. Use a lint free cloth or as floorboy with beige pad.
4. Allow Rapidoil to work for a few minutes. Within 15 minutes, remove the ample oil . Use a lint free cloth or a floorboy with the white pad. The surface must be hand dry . Use this method for every zone.
5. In well ventilated rooms, the surface can be used again in just 24-36 hours. After five days the surface can be cleaned using water and the right soap.

Tools can be cleaned using white spirit.

## **Use:**

30-50 m<sup>2</sup>/L depending on the wood, sanding method, applying method and pre treatment. Lacq Rapidoil can be used 4-6 hours after putting both components together.

*The coverage of the product are indications. Results are strongly depending on the wood and the pre treatment. We recommend to always test the product first to measure the coverage and results.*

**Protects and colour the surface with just one coat**

**The product is ready to use, no dilution needed.**

**CAUTION!: Used cloths etc. Can selfcombust. Always overflow with water.**