

Declaration of performance: No. CPR-IT1/0084

1. Unique identification code of the product-type: **ELASTOCOLOR TONACHINO PLUS**
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

WATER BASED, ORGANIC RENDER/PLASTER

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

For external and internal use on walls, ceilings, columns and partitions

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5): **MAPEI S.p.A. – Via Cafiero, 22 – Milano (Italy) www.mapei.it**
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): **Not applicable**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 4
System 3 for reaction to fire
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

The notified testing laboratory SWISSI Process Safety GmbH, No. 2139, performed the determination of the class of reaction to fire on samples taken by the manufacturer, under system 3, and issued the report No. 909630-12-0078-13-Z.

8. In the case the declaration of performance concerning a construction product for which a European Technical assessment has been issued: **Not applicable**
9. Declared performance:


Essential characteristics	Performance	Harmonised technical specification
Water vapour permeability:	V2	EN 15824:2009
Water absorption:	W3	
Adhesion:	≥ 0,3 MPa	
Durability:	≥ 0,3 MPa	
Thermal conductivity:	0,93 W/mK	
Reaction to fire:	Class A2-s1,d0	
Dangerous substances:	see SDS	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.



This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by: **Paolo Murelli – Corporate Quality Management**
(name and function)

Milan, 01/07/2013
(place and date of issue)


.....
(signature)

CE MARKING according to CPR 305/2011 and EN 15824:2009

 2139	 Via Cafiero, 22 – 20158 Milano (Italy) www.mapei.it														
<p style="text-align: center;">13 CPR-IT1/0084 EN 15824:2009</p> <p style="text-align: center;">ELASTOCOLOR TONACHINO PLUS</p> <p style="text-align: center;"><i>Water based organic render/plaster for use on walls, ceilings, columns and partitions</i></p> <table><tr><td>Water vapour permeability:</td><td>V2</td></tr><tr><td>Water absorption:</td><td>W3</td></tr><tr><td>Adhesion:</td><td>≥ 0,3 MPa</td></tr><tr><td>Durability:</td><td>≥ 0,3 MPa</td></tr><tr><td>Thermal conductivity:</td><td>0,93 W/mK</td></tr><tr><td>Reaction to fire:</td><td>A2-s1,d0</td></tr><tr><td>Dangerous substances:</td><td>see SDS</td></tr></table>		Water vapour permeability:	V2	Water absorption:	W3	Adhesion:	≥ 0,3 MPa	Durability:	≥ 0,3 MPa	Thermal conductivity:	0,93 W/mK	Reaction to fire:	A2-s1,d0	Dangerous substances:	see SDS
Water vapour permeability:	V2														
Water absorption:	W3														
Adhesion:	≥ 0,3 MPa														
Durability:	≥ 0,3 MPa														
Thermal conductivity:	0,93 W/mK														
Reaction to fire:	A2-s1,d0														
Dangerous substances:	see SDS														