

Description

Centrecoat R10 Paint Stripper is an easy to use, water based paint stripper. Ideal for stripping paint, varnish, graffiti, powder coatings, Artex, stains, varnish and lacquers.

Centrecoat R10 Paint Stripper is ideal for use on wood, timber, brick, stone, fibreglass and many other substrates. The product does not include restricted chemicals such as N-Methylpyrrolidone (NMP) and Dichloro-methane (DCM).

Centrecoat R10 has a high level of penetration enabling it to go further into thick coatings & work from the substrate up.

Features

- ▶ Safe to use water-borne and non corrosive
- ▶ Does not contain any harmful or banned substances
- ▶ Fully conforms to current EEC Directives
- ▶ Low odour, biodegradable and non flammable
- ▶ Gel consistency suitable for floors, walls and ceilings
- ▶ Removes a wide range of coatings from different substrates
- ▶ Suitable for interior and exterior use
- ▶ Ideal for painters, decorators and contractors working with Class O upgrade schemes, flooring, decking and Artex

Application

Always test on a small trial area before use to test exposure time. Protect all surfaces that are not to be stripped including delicate areas. Confirm that the surface to be stripped is dry. Shake product well before use. Use direct from the container.

Layer the product onto the surface to be stripped using a brush, airless spray or roller. DO NOT DILUTE. Apply a generous even coat - do not brush out. Leave for the established exposure time as listed below. Multi layers will benefit from a second coat. If leaving overnight, the treated area can be covered with plastic sheeting to prevent the stripper from drying out. Softened coating is easy to remove with a scraper. Where coating is delaminating from the first treatment, remove residuals with a scraper and re-apply as necessary.

Clean off surface thoroughly using cold water and stainless steel scourer. Allow to dry. For a perfect finish, use a suitable Centrecoat cleaner to finish the substrate.

Working Times

Multi layers benefit from a second coat. If leaving overnight, the treated area can be covered with plastic sheeting, to help the stripping process.

The following exposure times are indicative only:

- ▶ Varnish: 5 to 30 minutes
 - ▶ Two Pack Varnish: 30 - 60 minutes
 - ▶ Heavy Multi Layered Paint: 90 minutes - 8 hours
 - ▶ Two Pack Lacquer: 30 minutes - 4 hours
 - ▶ Graffiti: 5 to 45 minutes
 - ▶ Powder Coating: 30 minutes to 1 hour
- ▶ Coverage is approximately 1- 4 m2 per litre, depending on the type and thickness of the coating to be removed and the base material.

Technical Data

- ▶ Colour: White
- ▶ Odour: Pleasant almond odour
- ▶ Density: 102 Kg / m³
- ▶ Consistency: Aqueous gel
- ▶ Combustibility: Non combustible
- ▶ Flash Point: >100°C
- ▶ Application Temperature: 5°C to 30°C
- ▶ Composition: Benzyl alcohol emulsion

Cleaner

Clean tools and equipment immediately after use with water.

Storage

Store away from frost and heat in a dry location. Store at temperatures between 5°C and 30°C.

Shelf Life

12 months if stored in original unopened container.

Packaging

Available in 1 and 5 Litres