

Description

Centrecoat R186 is a colour reviver and protector for faded black limestone surfaces. Centrecoat R186 Black Limestone Restorer forms a hard durable finish that chemically reacts with substrate. Incorporating different molecular weight polymers, this product will enable superior performance, with a water repellent surface. Silane / Siloxane resin.

Centrecoat R186 also allows the substrate to remain moisture vapour permeable, allowing stains to be easily cleaned.



Benefits

- ▶ Makes the substrate water repellent
- ▶ R186 is able to be reapplied with its self
- ▶ Allows stains to be easily cleaned
- ▶ Moisture vapour permeable
- ▶ Provides colour enhancement that embellishes and improves the overall appearance of the substrate
- ▶ Invisible when dry
- ▶ UV resistant
- ▶ Non hazardous
- ▶ Solvent free
- ▶ Life expectancy of between 5 to 10 years depending on foot traffic

Application

If the substrate is damp prior to application the final finish can appear patchy. The best way to rectify this is to wait until the surface has been subject to a prolonged period of warm/dry weather (7+ days), remove the finish using [Centrecoat R10 Paint Stripper](#) and re-apply Black Limestone Restorer. To ensure optimum results, grout should be untreated and cement based. Black Limestone Restorer is not recommended for epoxy, polyurethane or premixed majestic type grouts.

Do not apply Black Limestone Restorer if rain is expected within 4 hours. Water repellence is evident after initial curing but may take up to 7 days to reach 100% efficiency.

Always test first on a small hidden area of the substrate before use. This also needs to include any grout or jointing compound. Ensure the substrate is clean, free from dust, dirt oil, efflorescence and other contaminants. Ensure no organic growth and old coatings films are present.

Apply via short pile roller or paint pad. Subsequent applications should be applied within 20 minutes of the initial application. Single application provides a flat natural finish. Two applications allows for a sheen finish.

Maintenance

Surfaces should be maintained using non acid patio cleaner, and [Centrecoat R08 Render, Stone, Patio & Deck Cleaner](#) is ideal. On darker surfaces clay soiling should be removed immediately otherwise it may cure and become difficult to remove, especially on hot days.

Technical Data

- ▶ VOC: 0g/l
- ▶ Non combustible
- ▶ Low viscosity
- ▶ Odour: Low and pleasant
- ▶ Colour: Pale straw
- ▶ Composition: Silane/siloxane resin network

- ▶ Substrate Temperature: 10°C to 25°C
- ▶ Ambient Temperature: 10°C to 25°C
- ▶ Overcoatable: Within 20 minutes of the initial application
- ▶ Heavy Traffic Ready: 24 hours at 20°C

Coverage

Up to 30m² per litre. Coverage depends on porosity of the substrate.

Clean Up

Clean tools and equipment immediately after use with water.

Storage

Store away from frost and heat in a dry place. Store within 5°C to 30°C.

Shelf Life

24 months from the date of production when kept in the original unopened container.

Packaging

Available in 1 Litre.

Recommendations

- ▶ Wear protective gloves and glasses and appropriate clothing whilst using the product.
- ▶ Do not apply if rain is expected within 4 hours.
- ▶ Water repellence is evident after initial curing but may take up to 7 days to reach full efficiency.
- ▶ Not suitable for application on non porous substrates (eg polished natural stone, quarry tiles & engineering bricks)
- ▶ Keep pets away until surface is fully dry

