

Description

Centrecoat Water Based Driveway Paint is a water thinned coating designed to provide colour on asphalt and tarmac driveways. Ideal for domestic tarmac drives and paths.

Colours & Finish

Available in Red, Green and Black. Matt finish.

Preparation

All surfaces should be clean, dry, sound and free from contaminants. Existing painted surfaces should be cleaned, degreased and sanded to ensure an adequate "key" is produced. Remove all loose, flaking material and treat bare areas as new substrate then prepare accordingly.

Application

Mix well before use. Apply via brush or roller. Do not apply below 7°C. Thin up to 10% with clean water as necessary. In confined spaces, provide adequate ventilation during application and drying. Do not paint when temperature will be at or below 7 °C during the painting and drying process.

Apply a coat of Centrecoat Water Based Driveway Paint thinned 10% with clean water on porous surfaces otherwise apply direct.

Technical Data

- ▶ Specific Gravity: 1.25 - 1.31 at 20°C
- ▶ Volume Solids: 34 - 36%
- ▶ VOC: max 41 g/l
- ▶ Flash Point: Non flammable
- ▶ Wet Film Thickness: 100 to 110 microns
- ▶ Dry Film Thickness: 35 to 40 microns

- ▶ Touch Dry: 1 hour at 20°C
- ▶ Hard Dry: 4 hours at 20°C
- ▶ Overcoatable: 6 hours at 20°C
- ▶ Fully Cured: 5 to 7 days at 20°C

Coverage

Approx 5 to 9 m² per litre at 35 microns. The practical spreading rate may be lower as this depends on factors such as the porosity and roughness of the surface to be painted and material losses during application.

Clean Up

Clean up tools and equipment immediately after use with water.

Packaging

Available in 5 Litres