

Printing date 05.06.2014 Revision: 05.06.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking**I.1 Product identifier**

Trade name: Centrecoat Anti Slip Tape IPA Cleaner
CAS Number: 67-63-0
EC number: 200-661-7
Index number: 603-117-00-0
Registration number: 01-2119457558-25-XXXX

I.1 Relevant identified uses of the substance or mixture and uses advised against

Solvent for Industrial use
Laboratory
Cleaning Agent
Coatings
Adhesives
Blending and packing of mixtures
Process chemical
Distribution of substance
Manufacture of substance

Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
SU21 Consumer uses: Private households / general public / consumers
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
SU2b Offshore industries
SU5 Manufacture of textiles, leather, fur
SU6b Manufacture of pulp, paper and paper products
SU8 Manufacture of bulk, large scale chemicals (including petroleum products)
SU9 Manufacture of fine chemicals
SU10 Formulation [mixing] of preparations and/or re-packaging (excluding alloys)
SU11 Manufacture of rubber products
SU12 Manufacture of plastics products, including compounding and conversion
SU24 Scientific research and development
Application of the substance / the mixture Solvent

Trade name: Isopropanol

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flammable - Liq. 2 H225 Highly flammable liquid and vapour



GHS07

Eye Irritation - 2 H319 Causes serious eye irritation.

STOT SE 3 - H336 May cause drowsiness or dizziness.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xi; Irritant

R36: Irritating to eyes.



F+; Highly flammable

R11: Highly flammable.

R67: Vapours may cause drowsiness and dizziness.

Information concerning particular hazards for human and environment:

Vapours of the product are heavier than air and may accumulate on the ground, in the sump of pits, drains or cellars with higher concentrations. Ground level ventilation is recommended.

May have a narcotizing effect after prolonged exposure

2.2 Label elements

The substance is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02



GHS07

Signal word: Danger

Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

Results of PBT and vPvB assessment:

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.1 Chemical characterization: Substances

CAS No. Description: 67-63-0 propan-2-ol

Identification number(s):**EC number:** 200-661-7**Index number:** 603-117-00-0**SVHC** Not listed as a SVHC at the date of this document**SECTION 4: First aid measures****4.1 Description of first aid measures****· After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation, seek immediate medical advice.

After skin contact:

Repeated skin contact may result in irritation and dermatitis. Always wear protective gloves suitable for this product.

Immediately wash with water and soap and rinse thoroughly. Remove contaminated clothing.

After eye contact:

Rinse opened eye for at least 15 minutes under clean running water. Remove contact lenses if possible. Seek immediate medical advice.

Continue to irrigate the eye with clean water.

After swallowing:

Do NOT induce vomiting; rinse mouth with water, call for medical help immediately. Rinse out mouth and then drink plenty of water.

4.2 Most important symptoms and effects, both acute and delayed

Headache
Dizziness
Nausea

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Fire fighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with aqueous film forming foam (AFFF).
Cool containers with water spray. For safety reasons unsuitable extinguishing agents: Water
with full jet

5.2 Special hazards arising from the substance or mixture

Carbon monoxide (CO), if incomplete combustion

5.3 Advice for firefighters

Protective equipment:

Respiratory protective device

Additional information

Cool endangered receptacles with water spray.
Collect contaminated firefighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources.
Wear protective clothing.

6.2 Environmental precautions:

Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders,
sawdust).
Ensure adequate ventilation.
Send for recovery or disposal in suitable receptacles - may need to be UN approved.
Blanket spillage with AFFF Foam Spray to seal from sources of ignition as a precautionary
measure.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Store in cool, dry place in tightly closed receptacles.

Take note of emission threshold.

Use only in well ventilated areas.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Information about fire - and explosion protection:

Keep ignition sources away - no naked sparks/flames/fires. Ensure electrical equipment is protected to correct

Zone rating (DSEAR Assessed)

Protect against electrostatic charges. Where required - ensure bonding and earthing of containers and process equipment.

Static generation and accumulation may be increased when using fine filters, strainers, mixing with powders and immiscible liquids, high energy/speed mixers. Take extra precautions. Allow static relaxation time for charges to dissipate before next steps. Do not splash fill.

Do not spray onto a naked flame, hot surfaces, electrical switchgear, live/battery connected electrics, or near to any potential sources of ignition.

Flammable gas-air mixtures may form in empty receptacles.

Wear shoes with conductive soles.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Store in a cool location.

Provide solvent resistant, sealed floor.

Prevent any seepage into the ground.

Provide ventilation for receptacles.

Use only receptacles specifically permitted for this substance/product.

Unsuitable material for receptacle: aluminium.

Store in area marked with EX signs under Dangerous Substances and Explosive Atmosphere Regs.

Follow HSE guidance for storage of flammable substances.

Flameproof/explosion proof electrical equipment must be used (ATEX Regulations)

Only store in suitable bunded storage areas. Do not store plastic IBC's with metal drums of other flammable substances.

Information about storage in one common storage facility:

Do not store together with alkalis (caustic solutions).

Store away from oxidizing agents.

Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Store receptacle in a well ventilated area.

You are recommended to refer to HSE publications HSG51 - The Storage of Flammable Liquids in Containers; and HSG140 - The Safe Use and Handling of Flammable Liquids, for more detailed understanding of the practices to be adhered to.

Composite plastic IBC's risk sudden and total loss of product in event of fire, ensure bunded areas are adequate. Do not store composite plastic IBC's with other packaged flammable goods.

7.3 Specific end use(s) No further relevant information available.

Additional information about design of technical facilities:

No further data

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:	
67-63-0 propan-2-ol	
WEL	Short-term value: 1250 mg/m ³ , 500 ppm Long-term value: 999 mg/m ³ , 400 ppm

Additional information:

The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.
Avoid alcohol consumption while working with the product.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Filter AX

Protection of hands:



Protective gloves

Solvent resistant gloves. Use gloves approved to BS EN 374 : Protective Gloves against Chemicals.

Chemical Resistant Gloves, class 4 or higher for prolonged exposure.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles. EN166 Standard

Body protection:

Protective work clothing

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

General Information

Appearance:

Form: Liquid

Colour: Colourless (Aged product may darken depending upon storage conditions and time period)

Odour: Alcohol-like

pH-value (- g/l) : neutral

Change in condition:

Melting point/Melting range: -89.5 °C

Boiling point/Boiling range: 82 °C

Flash point: 13 °C

Ignition temperature: 425 °C

Danger of explosion:

Product is not explosive, however formation of explosive air/vapour mixtures are possible.

Explosion limits:

Lower: 2 Vol %

Upper: 12 Vol %

Vapour pressure at 20 °C: 43 hPa

Density at 20 °C: 0.785 g/cm³

Solubility in / Miscibility with water:
Fully miscible

Viscosity: Dynamic at 20 °C: 2.43 mPas

SECTION 10: Stability and reactivity

10.1 Reactivity

10.2 Chemical stability

Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications and industry good practice.

10.3 Possibility of hazardous reactions: No dangerous reactions known.

10.4 Conditions to avoid: No further relevant information available.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: Carbon monoxide if incomplete combustion.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity:

LD/LC50 values relevant for classification:		
Inhalative	LD50	30 mg/l (rat)
Dermal	LD50	mg/kg (rat)
Oral	LC50/4 h	mg/kg (rabbit)

Primary irritant effect:

On the skin: Prolonged contact may result in mild skin irritation.

On the eye: Irritating effect.

Sensitization: No sensitizing effects known.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability: No further relevant information available.

12.3 Bioaccumulative potential: No further relevant information available.

12.4 Mobility in soil: No further relevant information available.

Additional ecological information:
General notes:

Water hazard class I (German Regulation) (Assessment by list):

Slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects

No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household refuse, do not allow product to reach sewage system.

European waste catalogue:

Refer to our office for EWC codes for disposal of used solvent.

Uncleaned packaging:

Recommendation:

Waste Solvent Disposal must be made according to official regulations. Refer to Hazardous Waste Regulations

2005. Requires movement under Consignment note by licensed waste carrier. We can provide this service – please contact us for more details.


Empty contaminated packaging's thoroughly. They may be recycled after thorough and proper cleaning.

Containers to be scrapped as waste must be cleaned so that no hazardous substances remain, otherwise uncleaned containers containing residue will need to be consigned as hazardous waste as per WM2 version 3 2014.

Recommended cleansing agents:

Water, if necessary together with cleansing agents

SECTION 14: Transport information

14.1 UN-Number	
ADR, IMDG, IATA	1219
14.2 UN proper shipping name	
ADR	1219 ISOPROPANOL (ISOPROPYL ALCOHOL)
IMDG, IATA	ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
	
Class:	3 Flammable liquids.
Label:	3
14.4 Packing group:	
ADR, IMDG, IATA:	II
14.5 Environmental hazards: Not applicable.	
14.6 Special precautions for user Warning: Flammable liquids.	
Danger code (Kemler): 33	
EMS Number: F-E,S-D	
14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable.	
UN "Model Regulation": UN1219, ISOPROPANOL (ISOPROPYL ALCOHOL), 3, II	

SECTION 15: Regulatory information

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.