

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sikalastic Metal Primer Comp A



Revision Date 21.01.2015

Version 2.0

Print Date 21.01.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sikalastic Metal Primer Comp A

1.2 Relevant identified uses of the substance or mixture and uses advised against

At present there is no complete information available on identified uses. When the data becomes available, it will be integrated into the safety data sheet.

1.3 Details of the supplier of the safety data sheet

Company : Sika Limited
Watchmead
Welwyn Garden City
Hertfordshire AL7 1BQ
United Kingdom

Telephone : +44 (0)1707 394444

1.4 Emergency telephone number

Emergency telephone number : +44 (0)1707 363899 (available during office hours)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Type of product : Mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids , Category 3	H226: Flammable liquid and vapour.
Skin irritation , Category 2	H315: Causes skin irritation.
Eye irritation , Category 2	H319: Causes serious eye irritation.
Skin sensitisation , Category 1	H317: May cause an allergic skin reaction.
Chronic aquatic toxicity , Category 2	H411: Toxic to aquatic life with long lasting effects.

Classification (67/548/EEC, 1999/45/EC)

Flammable	R10: Flammable.
Sensitising	R43: May cause sensitisation by skin contact.
Irritant	R36/38: Irritating to eyes and skin.
Dangerous for the environment	R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sikalastic Metal Primer Comp A



Revision Date 21.01.2015

Version 2.0

Print Date 21.01.2015

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word :

Warning

Hazard statements :

H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements :

Prevention:
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P273 Avoid release to the environment.
Response:
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Hazardous components which must be listed on the label:

- 500-033-5 reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight \leq 700)

Additional Labelling:

Contains epoxy constituents. May produce an allergic reaction.

2.3 Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT).
This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical Name	Classification	Classification	Concentration
---------------	----------------	----------------	---------------

SAFETY DATA SHEET
 according to Regulation (EC) No. 1907/2006
Sikalastic Metal Primer Comp A



Revision Date 21.01.2015

Version 2.0

Print Date 21.01.2015

CAS-No. EC-No. Registration number	(67/548/EEC)	(REGULATION (EC) No 1272/2008)	[%]
reaction product: bisphenol-A- (epichlorhydrin) and epoxy resin (num- ber average molecular weight <= 700) 25068-38-6 500-033-5 01-2119456619-26-XXXX	Xi; R36/38 R43 N; R51/53	Eye Irrit.2; H319 Skin Irrit.2; H315 Skin Sens.1; H317 Aquatic Chronic2; H411	>= 50 - <= 100
xylene 1330-20-7 215-535-7 01-2119488216-32-XXXX	R10 Xn; R20/21 Xi; R38	Asp. Tox.1; H304 Flam. Liq.3; H226 Acute Tox.4; H332 Acute Tox.4; H312 Skin Irrit.2; H315	>= 2,5 - < 5
Hydrocarbons, C9, aromatics 64742-95-6 265-199-0 01-2119455851-35-XXXX	Xn; R65 R10 Xi; R37 R66 R67 N; R51/53	Flam. Liq.3; H226 STOT SE3; H335, H336 Asp. Tox.1; H304 Aquatic Chronic2; H411	>= 2,5 - < 5
1,2,4-trimethylbenzene 95-63-6 202-436-9	R10 Xn; R20 Xi; R36/37/38 N; R51/53	Flam. Liq.3; H226 Acute Tox.4; H332 Eye Irrit.2; H319 STOT SE3; H335 Skin Irrit.2; H315 Aquatic Chronic2; H411	>= 1 - < 2,5
1,3,5-trimethylbenzene 108-67-8 203-604-4	R10 Xi; R37 N; R51/53	Flam. Liq.3; H226 STOT SE3; H335 Aquatic Chronic2; H411	>= 0,25 - < 1
propylbenzene 103-65-1 203-132-9	R10 Xn; R65 Xi; R37 N; R51/53	Flam. Liq.3; H226 Asp. Tox.1; H304 STOT SE3; H335 Aquatic Chronic2; H411	< 0,25
cumene 98-82-8 202-704-5	R10 Xn; R65 Xi; R37 N; R51/53	Flam. Liq.3; H226 Asp. Tox.1; H304 STOT SE3; H335 Aquatic Chronic2; H411	< 0,25

Remarks : Substances with a workplace exposure limit

For the full text of the R-phrases mentioned in this Section, see Section 16.
 For the full text of the H-Statements mentioned in this Section, see Section 16.



SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Allergic reactions
Excessive lachrymation
Erythema
Dermatitis
See Section 11 for more detailed information on health effects and symptoms.
- Risks : irritant effects
sensitising effects

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam, Carbon dioxide (CO₂), Dry chemical
- Unsuitable extinguishing media : Water, High volume water jet

5.2 Special hazards arising from the substance or mixture

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sikalastic Metal Primer Comp A



Revision Date 21.01.2015

Version 2.0

Print Date 21.01.2015

Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire. Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Remove all sources of ignition.
Deny access to unprotected persons.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist. Avoid exceeding of the
Country GB 000000604209



given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharge. Open drum carefully as content may be under pressure. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Components with workplace control parameters

Components	CAS-No.	Value	Control parameters *	Basis *
xylene	1330-20-7	TWA	50 ppm 220 mg/m3	GB EH40
		STEL	100 ppm 441 mg/m3	GB EH40
		TWA	50 ppm 221 mg/m3	2000/39/EC
		STEL	100 ppm 442 mg/m3	2000/39/EC
1,2,4-trimethylbenzene	95-63-6	TWA	20 ppm	2000/39/EC

SAFETY DATA SHEET
 according to Regulation (EC) No. 1907/2006
Sikalastic Metal Primer Comp A



Revision Date 21.01.2015

Version 2.0

Print Date 21.01.2015

			100 mg/m3	
1,3,5-trimethylbenzene	108-67-8	TWA	20 ppm 100 mg/m3	2000/39/EC
cumene	98-82-8	TWA	20 ppm 100 mg/m3	2000/39/EC
		STEL	50 ppm 250 mg/m3	2000/39/EC
		TWA	25 ppm 125 mg/m3	GB EH40
		STEL	50 ppm 250 mg/m3	GB EH40

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
xylylene	1330-20-7	methyl hippuric acid: 650mmol/mol creatinine (Urine)	Post shift	GB EH40 BAT

8.2 Exposure controls

Personal protective equipment

- Eye protection : Safety glasses with side-shields
Eye wash bottle with pure water

- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.

Suitable for short time use or protection against splashes:
Butyl rubber/nitrile rubber gloves (0,4 mm),
Contaminated gloves should be removed.
Suitable for permanent exposure:
Viton gloves (0.4 mm),
breakthrough time >30 min.

- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.

- Respiratory protection : Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
organic vapor filter (Type A)
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sikalastic Metal Primer Comp A



Revision Date 21.01.2015

Version 2.0

Print Date 21.01.2015

Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

Environmental exposure controls

General advice : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: grey
Odour	: characteristic
Odour Threshold	: No data available
Flash point	: 43 °C
Ignition temperature	: 465 °C
Lower explosion limit (Vol%)	: No data available
Upper explosion limit (Vol%)	: No data available
Flammability (solid, gas)	: No data available
Oxidizing properties	: No data available
Auto-ignition temperature	: No data available
pH	: No data available
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: No data available
Vapour pressure	: No data available
Density	: ca.1,4 g/cm ³ at 20 °C

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sikalastic Metal Primer Comp A



Revision Date 21.01.2015

Version 2.0

Print Date 21.01.2015

Water solubility	:	Note: insoluble
Partition coefficient: n-octanol/water	:	No data available
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 7 mm ² /s at 40 °C
Relative vapour density	:	No data available
Evaporation rate	:	No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.
Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Components:

reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight <= 700) :

Acute oral toxicity : LD50 Oral rat: > 5.000 mg/kg

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sikalastic Metal Primer Comp A



Revision Date 21.01.2015

Version 2.0

Print Date 21.01.2015

Acute dermal toxicity : LD50 Dermal rabbit: > 20.000 mg/kg

xylene :

Acute dermal toxicity : Acute toxicity estimate : 1.100 mg/kg
Method: Converted acute toxicity point estimate

Hydrocarbons, C9, aromatics :

Acute oral toxicity : LD50 Oral rat: > 2.000 mg/kg

Acute dermal toxicity : LD50 Dermal rabbit: > 2.000 mg/kg

Skin corrosion/irritation

Product

Causes skin irritation.

Serious eye damage/eye irritation

Product

Causes serious eye irritation.

Respiratory or skin sensitisation

Product

May cause an allergic skin reaction.

Germ cell mutagenicity

Product

Mutagenicity : No data available

Carcinogenicity

Product

Carcinogenicity : No data available

Reproductive Toxicity/Fertility

Reproductive toxicity : No data available

No data available

Reproductive Toxicity/Development/Teratogenicity

Teratogenicity : No data available

No data available

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sikalastic Metal Primer Comp A



Revision Date 21.01.2015

Version 2.0

Print Date 21.01.2015

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

Hydrocarbons, C9, aromatics :

Toxicity to algae : 2,6 - 2,9 mg/l, 72 h, *Pseudokirchneriella subcapitata* (green algae)

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues.
This material and its container must be disposed of in a safe

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sikalastic Metal Primer Comp A



Revision Date 21.01.2015

Version 2.0

Print Date 21.01.2015

way.

Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

European Waste Catalogue : 08 01 11* waste paint and varnish containing organic solvents or other dangerous substances

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

ADR

14.1 UN number : 1263
14.2 Description of the goods : PAINT
14.3 Class : 3
14.4 Packing group : III
Classification Code : F1
Labels : 3
Tunnel restriction code : (D/E)
14.5 Environmentally hazardous : yes

ADR

Transport according to chapter 3.4 (LQ) possible

IATA

14.1 UN number : 1263
14.2 Description of the goods : Paint
14.3 Class : 3
14.4 Packing group : III
Labels : 3
14.5 Environmentally hazardous : yes

IMDG

14.1 UN number : 1263
14.2 Description of the goods : PAINT
(epoxy resin)
14.3 Class : 3
14.4 Packing group : III
Labels : 3
EmS Number 1 : F-E
EmS Number 2 : S-E
14.5 Marine pollutant : yes

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sikalastic Metal Primer Comp A



Revision Date 21.01.2015

Version 2.0

Print Date 21.01.2015

14.6 Special precautions for user

No data available

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Labelling according to EC Directives (1999/45/EC)

Hazard pictograms :



Irritant



Dangerous for the environment

R-phrases) : R10 Flammable.
R36/38 Irritating to eyes and skin.
R43 May cause sensitisation by skin contact.
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S-phrases) : S24 Avoid contact with skin.
S37 Wear suitable gloves.

Hazardous components which must be listed on the label:

- 500-033-5 reaction product: bisphenol-A-(epichlorhydrin) and epoxy resin (number average molecular weight <= 700)

Special labelling of certain mixtures : Contains epoxy constituents. See information supplied by the manufacturer.

Prohibition/Restriction

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed (=> 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : not applicable

REACH Information: All substances contained in our Products are

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sikalastic Metal Primer Comp A



Revision Date 21.01.2015

Version 2.0

Print Date 21.01.2015

- preregistered or registered by our upstream suppliers, and/or
- preregistered or registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

VOC-CH (VOCV) : 10,1 %

VOC-EU (solvent) : 10,1 %

If other regulatory information applies that is not already provided elsewhere in the Safety Data Sheet, then it is described in this subsection.

Health, safety and environmental regulation/legislation specific for the substance or mixture: : The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002
Control of Substances Hazardous to Health Regulations 2002
The Management of Health and Safety at Work Regulations 1999
Health and Safety at Work Act 1974
Environmental Protection Act 1990 & Subsidiary Regulations

15.2 Chemical Safety Assessment

This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Full text of R-Phrases

R10	Flammable.
R20	Harmful by inhalation.
R20/21	Harmful by inhalation and in contact with skin.
R36/37/38	Irritating to eyes, respiratory system and skin.
R36/38	Irritating to eyes and skin.
R37	Irritating to respiratory system.
R38	Irritating to skin.
R43	May cause sensitisation by skin contact.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

Full text of H-Statements

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.

SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Sikalastic Metal Primer Comp A



Revision Date 21.01.2015

Version 2.0

Print Date 21.01.2015

H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	Acute toxicity
Aquatic Chronic	Chronic aquatic toxicity
Asp. Tox.	Aspiration hazard
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquids
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitisation
STOT SE	Specific target organ toxicity - single exposure

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any any use and processing.



Changes as compared to previous version !