

### Description

Centrecoat HD Driveway & Floor Paint is a blend of high quality thermo-acrylic and polyurethane resins resulting in a heavy duty coating that offers excellent protection for high traffic areas. Elastomeric and therefore offers high levels of flexibility for a long lasting, durable finish.

Ideal for areas that are subjected to frequent heavy use such as driveways, car parks, stairs, walkways, high traffic public areas, and industrial work areas. Suitable for internal and external use.

### Colour and Finish

Available in Grey and Light Grey. Contains Dolomite stone to provide a very fine textured, almost smooth, anti-slip satin finish.

### Preparation

It is only necessary to seal a porous substrate such as new or bare concrete. A sealer coat is achieved by adding 10% Centrecoat HD Driveway & Floor Paint Thinner to the paint. Please note new concrete floors can only be painted after 6-8 weeks.

### Application

Suitable for application on to Concrete, Stone, Tarmac & Asphalt (if suitably aged), Ferrous Metals, Wood. The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil. Apply using a suitable brush or roller.

### Technical Data

- ▶ Volume Solids: 55%
- ▶ Flash Point: 42°C
- ▶ Specific Gravity: 1.22
  
- ▶ Touch Dry: 2 hours at 20°C
- ▶ Overcoatable: 24 hours at 20°C

### Coverage

- ▶ Approx 10 - 12m<sup>2</sup> per litre

### Clean Up

Clean tools immediately after use with [Centrecoat HD Driveway & Floor Paint Thinner](#).

### Packaging

Available in 5 Litres