



# SAFETY DATA SHEET

Paracem Universal

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : Paracem Universal  
**Product description** : Paint.  
**Product type** : Liquid.  
**UFI** : H6X0-7070-J00N-RC6S

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

| Identified uses                                       |        |
|---|--------|
| Industrial uses<br>Consumer uses<br>Professional uses |        |
| Uses advised against                                  | Reason |
| None identified.                                      | -      |

### 1.3 Details of the supplier of the safety data sheet

Rust-Oleum Europe - Martin Mathys NV, Kolenbergstraat 23, B-3545 Zelem, Belgium  
 Telephone no.: +32 (0) 13 460 200  
 Fax no.: +32 (0) 13 460 201

**e-mail address of person responsible for this SDS** : rpmeurohas@rustoleum.eu

### 1.4 Emergency telephone number

#### Supplier

**Telephone number** : +44 (0) 207 858 1228  
**Hours of operation** : 24 / 7

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

## SECTION 2: Hazards identification

**Hazard pictograms** :



**Signal word** : No signal word.

**Hazard statements** : Toxic to aquatic life with long lasting effects.

**Precautionary statements**

**General** : P103 - Read label before use.  
 P102 - Keep out of reach of children.  
 P101 - If medical advice is needed, have product container or label at hand.

**Prevention** : P273 - Avoid release to the environment.

**Response** : P391 - Collect spillage.

**Storage** : Not applicable.

**Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Hazardous ingredients** : Not applicable.

**Supplemental label elements** : Contains 1,2-benzisothiazol-3(2H)-one, 2-octyl-2H-isothiazol-3-one and Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.  
 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

**Special packaging requirements**

**Containers to be fitted with child-resistant fastenings** : Not applicable.

**Tactile warning of danger** : Not applicable.

### 2.3 Other hazards

**Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII** : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**Other hazards which do not result in classification** : None known.

## SECTION 3: Composition/information on ingredients

**3.2 Mixtures** : Mixture

| Product/ingredient name | Identifiers | % | Classification                      |      |
|-------------------------|-------------|---|-------------------------------------|------|
|                         |             |   | Regulation (EC) No. 1272/2008 [CLP] | Type |
|                         |             |   |                                     |      |

**SECTION 3: Composition/information on ingredients**

|                             |   |           |  |     |
|-----------------------------|---|-----------|--|-----|
| titanium dioxide            | REACH #:<br>01-2119489379-17<br>EC: 236-675-5<br>CAS: 13463-67-7                        | ≥10 - ≤25 | Carc. 2, H351  | [1] |
| propane-1,2-diol            | REACH #:<br>01-2119456809-23<br>EC: 200-338-0<br>CAS: 57-55-6                           | ≤3        | Not classified.  | [2] |
| terbutryn                   | EC: 212-950-5<br>CAS: 886-50-0  | ≤0,1      | Acute Tox. 4, H302<br>Skin Sens. 1B, H317<br>Aquatic Acute 1, H400 (M=100)<br>Aquatic Chronic 1, H410 (M=100)  | [1] |
| 2-octyl-2H-isothiazol-3-one | REACH #:<br>17-2119390467-28<br>EC: 247-761-7<br>CAS: 26530-20-1<br>Index: 613-112-00-5 | ≤0,1      | Acute Tox. 3, H301<br>Acute Tox. 3, H311<br>Acute Tox. 2, H330<br>Skin Corr. 1B, H314<br>Eye Dam. 1, H318<br>Skin Sens. 1A, H317<br>Aquatic Acute 1, H400 (M=10)<br>Aquatic Chronic 1, H410 (M=1)<br><b>See Section 16 for the full text of the H statements declared above.</b> | [1] |

**Notes**

**The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm.**

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard  
 [2] Substance with a workplace exposure limit  
 [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII  
 [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII  
 [5] Substance of equivalent concern  
 [6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

**SECTION 4: First aid measures****4.1 Description of first aid measures**

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

**4.2 Most important symptoms and effects, both acute and delayed**

## SECTION 4: First aid measures

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 1,2-benzisothiazol-3(2H)-one, 2-octyl-2H-isothiazol-3-one, Reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

### Over-exposure signs/symptoms

|                     |                     |
|---------------------|---------------------|
| <b>Eye contact</b>  | : No specific data. |
| <b>Inhalation</b>   | : No specific data. |
| <b>Skin contact</b> | : No specific data. |
| <b>Ingestion</b>    | : No specific data. |

### 4.3 Indication of any immediate medical attention and special treatment needed

|                            |   |
|----------------------------|---|
| <b>Notes to physician</b>  | : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. |
| <b>Specific treatments</b> | : No specific treatment.  |

See toxicological information (Section 11)

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

|                                       |  |
|---------------------------------------|--|
| <b>Suitable extinguishing media</b>   | : Recommended: alcohol-resistant foam, CO <sub>2</sub> , powders, water spray. |
| <b>Unsuitable extinguishing media</b> | : Do not use water jet.  |

### 5.2 Special hazards arising from the substance or mixture

|   |   |
|---|---|
| <b>Hazards from the substance or mixture</b>    | : In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. |
| <b>Hazardous thermal decomposition products</b> | : Decomposition products may include the following materials:<br>carbon dioxide<br>carbon monoxide<br>nitrogen oxides<br>metal oxide/oxides   |

### 5.3 Advice for firefighters

|   |   |
|---|---|
| <b>Special protective actions for fire-fighters</b>   | : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.   |
| <b>Special protective equipment for fire-fighters</b> | : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents. |
| <b>Additional information</b>                         | : No unusual hazard if involved in a fire.  |

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

### 6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

### 6.4 Reference to other sections

- : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

### 7.1 Precautions for safe handling

- : Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding.  
Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.  
Put on appropriate personal protective equipment (see Section 8).  
Never use pressure to empty. Container is not a pressure vessel.  
Always keep in containers made from the same material as the original one.  
Comply with the health and safety at work laws.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

#### Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

#### Additional information on storage conditions

Observe label precautions. Do not store below the following temperature: 0°C (32°F). Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

#### Danger criteria

**SECTION 7: Handling and storage**

| Category | Notification and MAPP threshold | Safety report threshold |
|----------|---------------------------------|-------------------------|
| E2       | 200 tonne                       | 500 tonne               |

**7.3 Specific end use(s)**

**Recommendations** : Not available.

**Industrial sector specific solutions** : Not available.

**SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

**8.1 Control parameters****Occupational exposure limits**

| Product/ingredient name | Exposure limit values   |
|-------------------------|---|
| propane-1,2-diol        | <b>EH40/2005 WELs (United Kingdom (UK), 12/2011).</b><br>TWA: 10 mg/m <sup>3</sup> 8 hours. Form: Particulate<br>TWA: 474 mg/m <sup>3</sup> 8 hours. Form: Sum of vapour and particulates<br>TWA: 150 ppm 8 hours. Form: Sum of vapour and particulates |

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

**DNELs/DMELs**

| Product/ingredient name | Type | Exposure             | Value                | Population                     | Effects  |
|-------------------------|------|----------------------|----------------------|--------------------------------|----------|
| titanium dioxide        | DNEL | Long term Inhalation | 10 mg/m <sup>3</sup> | Workers                        | Local    |
|                         | DNEL | Long term Oral       | 700 mg/kg bw/day     | General population [Consumers] | Systemic |

**PNECs**

| Product/ingredient name | Compartment Detail     | Value       | Method Detail |
|-------------------------|------------------------|-------------|---------------|
| titanium dioxide        | Fresh water            | 0,127 mg/l  | -             |
|                         | Marine                 | >1 mg/l     | -             |
|                         | Sewage Treatment Plant | >100 mg/l   | -             |
|                         | Fresh water sediment   | >1000 mg/kg | -             |
|                         | Marine water sediment  | >100 mg/kg  | -             |
|                         | Soil                   | 100 mg/kg   | -             |

**8.2 Exposure controls**



## SECTION 8: Exposure controls/personal protection

**Appropriate engineering controls** : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. Recommended: safety glasses with side-shields (EN 166)

### Skin protection

#### Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

**Gloves** : For prolonged or repeated handling, use the following type of gloves:

Recommended: > 8 hours (breakthrough time): nitrile rubber (0.5mm)

The recommendation for the type or types of glove to use when handling this product is based on information from the following source:

EN 374

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Wear overalls or long sleeved shirt. (EN 467)

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapour (Type A) and particulate filter (EN 141).

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties****Appearance**

|   |   |
|---|---|
| <b>Physical state</b>                               | : Liquid.   |
| <b>Colour</b>                                       | : Various   |
| <b>Odour</b>  | : Not available.  |
| <b>Odour threshold</b>                              | : Not available.  |
| <b>pH</b>   | : 7,5   |
| <b>Melting point/freezing point</b>                 | : 0°C   |
| <b>Initial boiling point and boiling range</b>      | : >100°C  |
| <b>Flash point</b>                                  | : [Product does not sustain combustion.]  |
| <b>Evaporation rate</b>                             | : <1 (butyl acetate = 1)  |
| <b>Flammability (solid, gas)</b>                    | : Non-flammable in the presence of the following materials or conditions: open flames, sparks and static discharge, heat and shocks and mechanical impacts. Non-flammable but will burn on prolonged exposure to flame or high temperature. |
| <b>Upper/lower flammability or explosive limits</b> | : Not applicable.   |
| <b>Vapour pressure</b>                              | : Not available.  |
| <b>Vapour density</b>                               | : >1 [Air = 1]  |
| <b>Relative density</b>                             | : 1,28  |
| <b>Solubility(ies)</b>                              | : Soluble in the following materials: cold water and hot water.<br>Very slightly soluble in the following materials: methanol and acetone.  |
| <b>Partition coefficient: n-octanol/ water</b>      | : Not available.  |
| <b>Auto-ignition temperature</b>                    | : Not available.  |
| <b>Decomposition temperature</b>                    | : Not available.  |
| <b>Viscosity</b>                                    | : Dynamic (room temperature): 1700 mPa·s  |
| <b>Explosive properties</b>                         | : Not applicable.   |
| <b>Oxidising properties</b>                         | : Not available.  |

**9.2 Other information**

No additional information.

**SECTION 10: Stability and reactivity**

|  |  |
|--|--|
| <b>10.1 Reactivity</b>                         | : No specific test data related to reactivity available for this product or its ingredients.                                     |
| <b>10.2 Chemical stability</b>                 | : Stable under recommended storage and handling conditions (see Section 7).  |
| <b>10.3 Possibility of hazardous reactions</b> | : Under normal conditions of storage and use, hazardous reactions will not occur.  |
| <b>10.4 Conditions to avoid</b>                | : When exposed to high temperatures may produce hazardous decomposition products.  |
| <b>10.5 Incompatible materials</b>             | : Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids. |



**SECTION 10: Stability and reactivity**

**10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced. If involved in a fire, toxic gases including CO, CO<sub>2</sub> and smoke can be generated.

**SECTION 11: Toxicological information****11.1 Information on toxicological effects****Acute toxicity**

| Product/ingredient name     | Result                          | Species            | Dose              | Exposure |
|-----------------------------|---------------------------------|--------------------|-------------------|----------|
| titanium dioxide            | LC50 Inhalation Dusts and mists | Rat - Male, Female | 3,43 to 5,09 mg/l | 4 hours  |
|                             | LD50 Dermal                     | Rabbit             | >10 g/kg          | -        |
|                             | LD50 Oral                       | Rat                | >24 g/kg          | -        |
| terbutryn                   | LC50 Inhalation Dusts and mists | Rat                | >2200 mg/l        | 4 hours  |
|                             | LD50 Dermal                     | Rabbit             | >10200 mg/kg      | -        |
|                             | LD50 Oral                       | Rat                | 2045 mg/kg        | -        |
| 2-octyl-2H-isothiazol-3-one | LC50 Inhalation Dusts and mists | Rat                | 0,27 mg/l         | 4 hours  |
|                             | LD50 Dermal                     | Rabbit             | 311 mg/kg         | -        |
|                             | LD50 Dermal                     | Rat                | >2000 mg/kg       | -        |
|                             | LD50 Oral                       | Rat                | 248 mg/kg         | -        |

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

**Acute toxicity estimates**

Not available.

**Irritation/Corrosion**

| Product/ingredient name     | Result                   | Species | Score | Exposure                             | Observation |
|-----------------------------|--------------------------|---------|-------|--------------------------------------|-------------|
| titanium dioxide            | Skin - Mild irritant     | Human   | -     | 72 hours 300 Micrograms Intermittent | -           |
| terbutryn                   | Eyes - Moderate irritant | Rabbit  | -     | 76 milligrams                        | -           |
|                             | Skin - Mild irritant     | Rabbit  | -     | 380 milligrams                       | -           |
| 2-octyl-2H-isothiazol-3-one | Eyes - Severe irritant   | Rabbit  | -     | -                                    | -           |

**Conclusion/Summary**

**Skin** : Based on available data, the classification criteria are not met.

**Eyes** : Based on available data, the classification criteria are not met.

**Respiratory** : Based on available data, the classification criteria are not met.

**Sensitisation**

| Product/ingredient name     | Route of exposure | Species    | Result          |
|-----------------------------|-------------------|------------|-----------------|
| titanium dioxide            | skin              | Guinea pig | Not sensitizing |
| 2-octyl-2H-isothiazol-3-one | skin              | Mouse      | Not sensitizing |
|                             | skin              | Rat        | Sensitising     |

**Conclusion/Summary**

**Skin** : Based on available data, the classification criteria are not met.

**Respiratory** : Based on available data, the classification criteria are not met.

**Mutagenicity**

**SECTION 11: Toxicological information**

| Product/ingredient name | Test     | Experiment  | Result   |
|-------------------------|----------|---|----------|
| titanium dioxide        | OECD 471 | Experiment: In vitro<br>Subject: Bacteria         | Negative |
|                         | OECD 476 | Experiment: In vitro<br>Subject: Mammalian-Animal | Negative |
|                         | OECD 474 | Experiment: In vivo<br>Subject: Mammalian-Animal  | Negative |
|                         | OECD 474 | Experiment: In vivo<br>Subject: Mammalian-Animal  | Negative |

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

**Carcinogenicity**

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

**Reproductive toxicity**

| Product/ingredient name | Maternal toxicity | Fertility | Developmental toxin | Species            | Dose                       | Exposure                 |
|-------------------------|-------------------|-----------|---------------------|--------------------|----------------------------|--------------------------|
| titanium dioxide        | Negative          | Negative  | Negative            | Rat - Male, Female | Oral: 100 to 3001000 mg/kg | 20 days; 7 days per week |

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

**Teratogenicity**

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

**Specific target organ toxicity (single exposure)**

Not available.

**Specific target organ toxicity (repeated exposure)**

Not available.

**Aspiration hazard**

Not available.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure****Short term exposure**

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

**Long term exposure**

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

**Potential chronic health effects**

| Product/ingredient name | Result  | Species    | Dose                               | Exposure      |
|-------------------------|---|------------|------------------------------------|---------------|
| titanium dioxide        | Chronic NOAEL Oral<br>Chronic NOAEL Inhalation<br>Dusts and mists | Rat<br>Rat | 3500 mg/kg<br>10 mg/m <sup>3</sup> | -<br>24 hours |

**Conclusion/Summary** : Not available.

**General** : No known significant effects or critical hazards.

**Carcinogenicity** : No known significant effects or critical hazards.

**Mutagenicity** : No known significant effects or critical hazards.

**Teratogenicity** : No known significant effects or critical hazards.

**Developmental effects** : No known significant effects or critical hazards.

**Fertility effects** : No known significant effects or critical hazards.

**SECTION 11: Toxicological information****Other information** : Not available.**SECTION 12: Ecological information****12.1 Toxicity**

There are no data available on the mixture itself.  
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

| Product/ingredient name     | Result                                      | Species  | Exposure |
|-----------------------------|---|--|----------|
| titanium dioxide            | Acute LC50 3 mg/l Fresh water               | Crustaceans - Ceriodaphnia dubia - Neonate   | 48 hours |
|                             | Acute LC50 6,5 mg/l Fresh water             | Daphnia spec. - Daphnia pulex - Neonate  | 48 hours |
| terbutryn                   | Acute LC50 >1000000 µg/l Marine water       | Fish - Fundulus heteroclitus   | 96 hours |
|                             | Acute EC50 0,1 µg/l Fresh water             | Algae - Fragilaria capucina ssp. rumpens   | 96 hours |
|                             | Acute EC50 2 µg/l Fresh water               | Algae - Pseudokirchneriella subcapitata  | 72 hours |
|                             | Acute EC50 2,66 ppm Fresh water             | Daphnia spec. - Daphnia magna  | 48 hours |
|                             | Acute IC50 0,0055 mg/l                      | Algae  | 72 hours |
|                             | Acute LC50 579,3 mg/l Fresh water           | Crustaceans - Pacifastacus leniusculus - Juvenile (Fledgling, Hatchling, Weanling) | 48 hours |
|                             | Acute LC50 1,8 to 1400 µg/l Fresh water     | Fish - Carassius carassius   | 96 hours |
|                             | Acute LC50 0,82 ppm Fresh water             | Fish - Oncorhynchus mykiss   | 96 hours |
| 2-octyl-2H-isothiazol-3-one | Chronic EC10 0,015 µg/l Fresh water         | Algae - Fragilaria capucina ssp. rumpens   | 96 hours |
|                             | Acute EC50 0,32 to 0,834 mg/l Fresh water   | Daphnia spec. - Daphnia magna  | 48 hours |
|                             | Acute IC50 0,084 mg/l                       | Algae  | 72 hours |
|                             | Acute LC50 0,14 to 0,202 mg/l Fresh water   | Fish - Pimephales promelas   | 96 hours |
|                             | Acute LC50 0,0655 to 0,104 mg/l Fresh water | Fish   | 96 hours |

**Conclusion/Summary** : Toxic to aquatic life with long lasting effects.**12.2 Persistence and degradability**

| Product/ingredient name     | Test      | Result                   | Dose             | Inoculum |
|-----------------------------|-----------|--------------------------|------------------|----------|
| 2-octyl-2H-isothiazol-3-one | OECD 309  | 90 % - Readily - 4 days  | 0,01 to 0,1 mg/l | -        |
|                             | OECD 303A | >80 % - Readily - 4 days | -                | -        |
|                             | OECD 309  | 50 % - Readily - 2 days  | 0,01 to 0,1 mg/l | -        |

**Conclusion/Summary** : This product has not been tested for biodegradation. Based on available data, the classification criteria are not met.

| Product/ingredient name     | Aquatic half-life        | Photolysis | Biodegradability |
|-----------------------------|--------------------------|------------|------------------|
| titanium dioxide            | -                        | -          | Not readily      |
| 2-octyl-2H-isothiazol-3-one | Fresh water 2 days, 20°C | -          | Readily          |

**12.3 Bioaccumulative potential**

| Product/ingredient name     | LogP <sub>ow</sub> | BCF | Potential |
|-----------------------------|--------------------|-----|-----------|
| terbutryn                   | 3,74               | -   | low       |
| 2-octyl-2H-isothiazol-3-one | 2,9                | -   | low       |

**SECTION 12: Ecological information****12.4 Mobility in soil**

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Nonvolatile liquid.

**12.5 Results of PBT and vPvB assessment**

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

**SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance.

**13.1 Waste treatment methods****Product**

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Yes.

**Disposal considerations** : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

**European waste catalogue (EWC)**

The European Waste Catalogue classification of this product, when disposed of as waste, is:

| Waste code | Waste designation   |
|------------|---|
| 08 01 15*  | aqueous sludges containing paint or varnish containing organic solvents or other hazardous substances |









**Packaging**

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Disposal considerations** : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spill material and runoff and contact with soil, waterways, drains and sewers.

**SECTION 14: Transport information**

|  | ADR/RID  | ADN  | IMDG  | IATA   |
|--|--|--|---|--|
| <b>14.1 UN number</b>                  | UN3082   | UN3082   | UN3082  | UN3082   |
| <b>14.2 UN proper shipping name</b>    | Environmentally hazardous substance, liquid, n.o.s. [terbutryn]  | Environmentally hazardous substance, liquid, n.o.s. [terbutryn]  | Environmentally hazardous substance, liquid, n.o.s. Marine pollutant [terbutryn]  | Environmentally hazardous substance, liquid, n.o.s. [terbutryn]  |
| <b>14.3 Transport hazard class(es)</b> | 9<br>  | 9<br>  | 9<br>  | 9<br>    |
| <b>14.4 Packing group</b>              | III  | III  | III   | III  |
| <b>14.5 Environmental hazards</b>      | Yes.   | Yes.   | Yes.  | Yes.   |
| <b>Additional information</b>          | <b>Remarks:</b><br>( $\leq$ 5L: ) Exempted<br><br>ADR Tunnel code: (E)   | -  | <b>Emergency schedules (EmS):</b><br>F-A + S-F<br><br><b>Marine pollutant (P)</b><br><br><b>Remarks:</b><br>( $\leq$ 5L: ) Exempted   | <b>Passenger and Cargo Aircraft</b><br>Quantity limitation:<br>450 L<br>Packaging instructions: 964<br><b>Cargo Aircraft Only</b><br>Quantity limitation:<br>450 L<br>Packaging instructions: 964<br><b>Limited Quantities - Passenger Aircraft</b><br>Quantity limitation: 30 Kg<br>Packaging instructions: Y 964 |

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****EU Regulation (EC) No. 1907/2006 (REACH)****Annex XIV - List of substances subject to authorisation****Annex XIV**

None of the components are listed.

**Substances of very high concern**

None of the components are listed.

## SECTION 15: Regulatory information

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

### Other EU regulations

**VOC** : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

**VOC for Ready-for-Use Mixture** : IIA/d. Interior/exterior trim and cladding paints for wood and metal. EU limit value for this product : 130g/l (2010.)  
This product contains a maximum of 35 g/l VOC.

**Europe inventory** : All components are listed or exempted.

| Product/ingredient name | Carcinogenic effects | Mutagenic effects | Developmental effects | Fertility effects |
|-------------------------|----------------------|-------------------|-----------------------|-------------------|
| titanium dioxide        | Not supported        | Not supported     | Not supported         | Not supported     |

### Ozone depleting substances (1005/2009/EU)

Not listed.

### Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

### Seveso Directive

This product is controlled under the Seveso Directive.

### Danger criteria

#### Category

E2

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

**References** : EH40/2005 Workplace exposure limits  
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2016/918

### International regulations

#### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

#### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

**CN code** : 3209 90 00

### International lists

#### National inventory

**Australia** : At least one component is not listed.

## SECTION 15: Regulatory information

|                          |  |
|--------------------------|--|
| <b>Canada</b>            | : Not determined.  |
| <b>China</b>             | : Not determined.  |
| <b>Japan</b>             | : <b>Japan inventory (ENCS)</b> : At least one component is not listed.<br><b>Japan inventory (ISHL)</b> : Not determined. |
| <b>Malaysia</b>          | : Not determined   |
| <b>New Zealand</b>       | : Not determined.  |
| <b>Philippines</b>       | : At least one component is not listed.  |
| <b>Republic of Korea</b> | : Not determined.  |
| <b>Taiwan</b>            | : At least one component is not listed.  |
| <b>Turkey</b>            | : Not determined.  |
| <b>United States</b>     | : At least one component is not listed.  |
| <b>Thailand</b>          | : Not determined.  |
| <b>Viet Nam</b>          | : Not determined.  |

**15.2 Chemical safety assessment** : No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** :

- ATE = Acute Toxicity Estimate
- CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
- DMEL = Derived Minimal Effect Level
- DNEL = Derived No Effect Level
- EUH statement = CLP-specific Hazard statement
- PBT = Persistent, Bioaccumulative and Toxic
- PNEC = Predicted No Effect Concentration
- RRN = REACH Registration Number
- vPvB = Very Persistent and Very Bioaccumulative

**Contains TiO2** : Yes

**Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**

| Classification          | Justification   |
|-------------------------|-----------------|
| Aquatic Chronic 2, H411 | Expert judgment |

**Full text of H-phrases referred to in sections 2 and 3**

|  |  |  |
|--|--|--|
| <b>Full text of abbreviated H statements</b> : | H301<br>H302<br>H311<br>H314<br>H317<br>H318<br>H330<br>H351<br>H400<br>H410<br>H411 | Toxic if swallowed.<br>Harmful if swallowed.<br>Toxic in contact with skin.<br>Causes severe skin burns and eye damage.<br>May cause an allergic skin reaction.<br>Causes serious eye damage.<br>Fatal if inhaled.<br>Suspected of causing cancer.<br>Very toxic to aquatic life.<br>Very toxic to aquatic life with long lasting effects.<br>Toxic to aquatic life with long lasting effects. |
|--|--|--|



**SECTION 16: Other information**

|   |   |  |
|---|---|--|
| <b>Full text of classifications [CLP/GHS]</b> | Acute Tox. 2<br>Acute Tox. 3<br>Acute Tox. 4<br>Aquatic Acute 1<br><br>Aquatic Chronic 1<br><br>Aquatic Chronic 2<br><br>Carc. 2<br>Eye Dam. 1<br>Skin Corr. 1B<br>Skin Sens. 1A<br>Skin Sens. 1B | ACUTE TOXICITY - Category 2<br>ACUTE TOXICITY - Category 3<br>ACUTE TOXICITY - Category 4<br>SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1<br><br>LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1<br><br>LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2<br><br>CARCINOGENICITY - Category 2<br>SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1<br>SKIN CORROSION/IRRITATION - Category 1B<br>SKIN SENSITISATION - Category 1A<br>SKIN SENSITISATION - Category 1B |
|---|---|--|

**Date of printing** : 18/05/2020

**Date of issue/ Date of revision** : 18/05/2020

**Date of previous issue** : 13/05/2019

**Version** : 3

**Notice to reader**

The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.