

Centrecoat Imprinted Driveway Sealer

Page 1/7

Revision 1

Revision date 2019-10-28

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Centrecoat Imprinted Driveway Sealer
--------------	--------------------------------------

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use	[SU3] Industrial uses: Uses of substances as such or in preparations at industrial sites; [PC9a] Coatings and paints, thinners, paint removers;
-------------	---

1.3. Details of the supplier of the safety data sheet

Company	Promain UK Limited
Address	Pierson Court Knowl Piece Hitchin, Hertfordshire SG4 0TY
Web	www.promain.co.uk
Telephone	01462 421333
Email	info@promain.co.uk

1.4. Emergency telephone number

Emergency telephone number	01462 421333 8.30am - 16.30pm Mon - Fri
----------------------------	--

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008	Flam. Liq. 3: H226; Skin Irrit. 2: H315;
--------------------------------------	--

2.2. Label elements

Hazard pictograms



Signal Word

Warning

Hazard Statement

Flam. Liq. 3: H226 - Flammable liquid and vapour.
Skin Irrit. 2: H315 - Causes skin irritation.

Precautionary Statement: Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/bond container and receiving equipment.

2.2. Label elements

Precautionary Statement: Response	P241 - Use explosion-proof electrical/ventilating/lighting// equipment. P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P264 - Wash thoroughly after handling. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
	P302+P352 - IF ON SKIN: Wash with plenty of water/ . P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P321 - Specific treatment (see on this label). P332+P313 - If skin irritation occurs: Get medical advice/attention. P370+P378 - In case of fire: Use to extinguish.
Precautionary Statement: Storage	P403+P235 - Store in a well-ventilated place. Keep cool.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to

SECTION 3: Composition/information on ingredients
3.2. Mixtures
EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Xylene (Xylene, o-,m-,p-or mixed isomers)	601-022-00-9	1330-20-7	215-535-7	01-2119488216-32		Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315;
Ethylbenzene	601-023-00-4	100-41-4	202-849-4			Flam. Liq. 2: H225; Acute Tox. 4: H332;

SECTION 4: First aid measures
4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing.
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing.
Ingestion	DO NOT INDUCE VOMITING. Transfer to hospital as soon as possible.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Inhalation may cause nausea and vomiting.
Eye contact	Irritating to eyes.
Skin contact	Irritating to skin.
Ingestion	Ingestion causes burns to the respiratory tract. Ingestion may cause nausea and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Inhalation	Seek medical attention.
Eye contact	Seek medical attention.
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	Transfer to hospital as soon as possible.

SECTION 5: Firefighting measures
5.1. Extinguishing media

	Use as appropriate: Carbon dioxide (CO2), Dry chemical, Foam. Do NOT use water jet.
--	---

5.2. Special hazards arising from the substance or mixture

5.2. Special hazards arising from the substance or mixture

. Burning produces irritating, toxic and obnoxious fumes. Vapour may travel considerable distance to source of ignition and flash back. Vapours are heavier than air.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Protective equipment. Self-contained breathing apparatus.

SECTION 6: Accidental release measures
6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation of the working area. Eliminate all sources of ignition. Wear suitable protective equipment. Avoid contact with skin and eyes. Do not breathe gas/fumes/vapour/spray.

6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

6.3. Methods and material for containment and cleaning up

Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal.

6.4. Reference to other sections

See section 8 for further information. See section 13 for further information.

SECTION 7: Handling and storage
7.1. Precautions for safe handling

Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking. Adopt best Manual Handling considerations when handling, carrying and dispensing.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers. Take precautionary measures against static discharges.

7.3. Specific end use(s)


See section 1.2 for further information.

SECTION 8: Exposure controls/personal protection
8.1. Control parameters
8.1.1. Exposure Limit Values

Ethylbenzene	WEL 8-hr limit ppm: 100	WEL 8-hr limit mg/m ³ : 441
	WEL 15 min limit ppm: 125	WEL 15 min limit mg/m ³ : 552
	WEL 8-hr limit mg/m ³ total - inhalable dust:	WEL 15 min limit mg/m ³ total - inhalable dust:
	WEL 8-hr limit mg/m ³ total - respirable dust:	WEL 15 min limit mg/m ³ total - respirable dust:
Xylene (Xylene, o-,m-,p-or mixed isomers)	WEL 8-hr limit ppm: 50	WEL 8-hr limit mg/m ³ : 220
	WEL 15 min limit ppm: 100	WEL 15 min limit mg/m ³ : 441
	WEL 8-hr limit mg/m ³ total - inhalable dust:	WEL 15 min limit mg/m ³ total - inhalable dust:
	WEL 8-hr limit mg/m ³ total - respirable dust:	WEL 15 min limit mg/m ³ total - respirable dust:

8.2. Exposure controls

8.2. Exposure controls

	
8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.
Skin protection - Handprotection	Chemical resistant gloves (PVC).
Respiratory protection	Wear protective clothing.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Cloudy
Odour	Strong/Characteristic
Odour threshold	No data available
pH	No data available
Melting point	No data available
Freezing Point	No data available
Initial boiling point	140 °C
Flash point	23 °C
Evaporation rate	15 g/min
Flammability (solid, gas)	No data available
Vapour pressure	< 950 Pa
Vapour density	3.7 g/cm ³
Relative density	No data available
Fat Solubility	No data available
Partition coefficient	No data available
Autoignition temperature	> 432 °C
Viscosity	0.6 mPas (Cone & Plate)
Explosive properties	No data available
Oxidising properties	No data available
Solubility	No data available

9.2. Other information

Conductivity	No data available
Surface tension	No data available
Gas group	No data available
Benzene Content	0 %
Lead content	0 %
VOC (Volatile organic compounds)	728 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

	Stable under normal conditions.
--	---------------------------------

10.2. Chemical stability

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Oxidising agents.

10.4. Conditions to avoid

Heat, sparks and open flames. Take precautionary measures against static discharges.
--

10.5. Incompatible materials

Acids. Strong oxidising agents.

10.6. Hazardous decomposition products

Will not decompose if stored and used as recommended.

SECTION 11: Toxicological information
11.1. Information on toxicological effects

Acute toxicity	Harmful by inhalation. Harmful if swallowed.
Skin corrosion/irritation	Irritating to skin.
Serious eye damage/irritation	Irritating to eyes.
Respiratory or skin sensitisation	No sensitization effects reported.
Germ cell mutagenicity	No mutagenic effects reported.
Carcinogenicity	No carcinogenic effects reported.
Reproductive toxicity	No teratogenic effects reported.

11.1.4. Toxicological Information

Xylene	Oral Rat LD50: 4300mg/kg Inhalation Rat LC50/4 h: 21.7mg/l	Dermal Rabbit LD50: 3200mg/kg
--------	---	-------------------------------

SECTION 12: Ecological information
12.1. Toxicity

Xylene	Fish LC50/96h: 26.7 mg/l
--------	--------------------------

12.2. Persistence and degradability

Evaporates readily. Insoluble in water. Readily biodegradable.
--

12.3. Bioaccumulative potential

BCF 25.9.

Partition coefficient

No data available

12.4. Mobility in soil

This product evaporates readily. Floats on water.

12.5. Results of PBT and vPvB assessment

No data is available on this product.

12.6. Other adverse effects

Avoid release to the environment.

SECTION 13: Disposal considerations
General information

General information

08 01 21* waste paint or varnish remover.
 08 01 wastes from MFSU and removal of paint and varnish.
 08 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS.

Disposal methods

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. Waste packaging should be recycled if possible. Incineration should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned. Empty containers or liners may still contain residue. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Disposal of packaging

Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

SECTION 14: Transport information
Hazard pictograms

14.1. UN number

UN1866

14.2. UN proper shipping name

RESIN SOLUTION (Contains Xylene)

14.3. Transport hazard class(es)

ADR/RID	3
Subsidiary risk	-
IMDG	3
Subsidiary risk	-
IATA	3
Subsidiary risk	-

14.4. Packing group

Packing group III

14.5. Environmental hazards

Environmental hazards	No
Marine pollutant	No

ADR/RID

Hazard ID	30
Tunnel Category	(D/E)

IMDG

IMDG

EmS Code	F-E S-E
----------	---------

IATA

Packing Instruction (Cargo)	366
Maximum quantity	220 L
Packing Instruction (Passenger)	355
Maximum quantity	60 L

SECTION 15: Regulatory information
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations	<p>COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.</p> <p>REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.</p>
-------------	--

15.2. Chemical safety assessment

	This product contains substances for which Chemical Safety Assessments are still required.
--	--

SECTION 16: Other information
Other information

Revision	This document differs from the previous version in the following areas: 4 - Eye contact.
Text of Hazard Statements in Section 3	Flam. Liq. 3: H226 - Flammable liquid and vapour. Acute Tox. 4: H312 - Harmful in contact with skin. Skin Irrit. 2: H315 - Causes skin irritation. Acute Tox. 4: H332 - Harmful if inhaled. Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
Maximum content of VOC	728 g/l.

Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
--	--