

Safety Data Sheet
MAPETHERM FLEX RP

Safety Data Sheet dated: 23/07/2021 - version 3



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: MAPETHERM FLEX RP

Trade code: 907MT9990

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Wall coating paste

Uses advised against: Data not available

1.3. Details of the supplier of the safety data sheet

Company: MAPEI U.K. Ltd - Mapei House Steel Park Road

Halesowen - West Midlands B62 8HD

phone: +44(0)121 508 6970 - fax: +44(0)121 5086 960 - www.mapei.co.uk (office hour 8:30-17:30)

Responsible: sicurezza@mapei.it

1.4. Emergency telephone number

call NHS 111 or a doctor/OHES Environmental Ltd +44(0)333 333 9962

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

Aquatic Chronic 3 Harmful to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard statements:

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P273 Avoid release to the environment.

P501 Dispose of contents/container to ...

Special Provisions:

EUH208 Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

EUH208 Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H - isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

EUH208 Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H - isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

No PBT/vPvB Ingredients are present

Other Hazards: No other hazards

This product contains crystalline silica (quartz sand). IARC has classified crystalline silica as a Group 1 carcinogen. Both IARC and NTP consider silica as a known human carcinogen. Evidence is based on the chronic and long-term exposure workers have had to respirable sized crystalline silica dust particles. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a silica dust hazard)

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: MAPETHERM FLEX RP

Hazardous components within the meaning of the CLP regulation and related classification:

Concentration	Name	Ident. Numb.	Classification	Registration Number
---------------	------	--------------	----------------	---------------------

(% w/w)

≥10 - <20 %	free crystalline silica (Ø >10 µ)	CAS:14808-60-7 EC:238-878-4	
≥0.1 - <0.25 %	polyethylene glycol monooleylether	CAS:9004-98-2	Skin Irrit. 2, H315; Aquatic Acute 1, H400
≥0.1 - <0.25 %	zinc pyrithione	CAS:13463-41-7 EC:236-671-3	Acute Tox. 3, H301; Acute Tox. 3, H331; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410, M-Chronic:10, M-Acute:100
≥0.025 - <0.05 %	free crystalline silica (Ø <10 µ)	CAS:14808-60-7 EC:238-878-4	STOT RE 1, H372
≥0.01 - <0.016 %	1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	CAS:2634-33-5 EC:220-120-9 Index:613-088-00-6	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 1, H400 Acute Tox. 4, H302 Skin Sens. 1, H317 Aquatic Chronic 2, H411 Specific Concentration Limits: C ≥ 0.05%: Skin Sens. 1 H317
≥0.0015 - <0.005 %	formaldehyde	CAS:50-00-0 EC:200-001-8 Index:605-001-00-5	Acute Tox. 3, H311 Acute Tox. 3, H331 Acute Tox. 3, H301 Skin Corr. 1B, H314 Skin Sens. 1, H317 Muta. 2, H341 Carc. 1B, H350 Specific Concentration Limits: 0.2% ≤ C < 100%: Skin Sens. 1 H317 5% ≤ C < 25%: Skin Irrit. 2 H315 5% ≤ C < 25%: Eye Irrit. 2 H319 5% ≤ C < 100%: STOT SE 3 H335 25% ≤ C < 100%: Skin Corr. 1B H314
<0.0015 %	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1)	CAS:55965-84-9 EC:611-341-5 Index:613-167-00-5	Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Acute Tox. 3, H301 Skin Corr. 1C, H314 Skin Sens. 1A, H317 Acute Tox. 2, H310 Acute Tox. 2, H330 Eye Dam. 1, H318, M-Chronic:100, M-Acute:100 Specific Concentration Limits: C ≥ 0.6%: Skin Corr. 1C H314 0.06% ≤ C < 0.6%: Skin Irrit. 2 H315 C ≥ 0.6%: Eye Dam. 1 H318 0.06% ≤ C < 0.6%: Eye Irrit. 2 H319 C ≥ 0.0015%: Skin Sens. 1A H317 C ≥ 0.6%: EUH071

SECTION 4: First aid measures**4.1. Description of first aid measures**

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

Wash immediately with water.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

N.A.

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: N.A.

(see paragraph 4.1)

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO₂).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

5.3. Advice for firefighters

Use suitable breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

List of components with OEL value

Component	OEL Type	Country	Ceiling	Long Term mg/m ³	Long Term ppm	Short Term mg/m ³	Short Term ppm	Behaviour	Note
free crystalline silica (Ø >10 µ)	NDS	POLAND		0.300					frakcja respirabilna
	National	DENMARK		0.3					DENMARK, inhalable aerosol
	National	DENMARK		0.100					DENMARK, respirable aerosol
	SUVA	GERMANY		0.150					50 µg/m ³ (Partikel Durchmesser < 12 µm) -

National SWEDEN		0.37	0.3		
National FRANCE			0.5		1
National SPAIN		0.37	0.3	0.74	0.6
National GREECE		2.5	2	2.5	2
National DENMARK	C			0.4	0.3
National FINLAND		0.37	0.3		
National FINLAND	C			1.2	1
National GERMANY		0.37	0.3		
National NORWAY		0.6	0.5		
National NORWAY	C			1.2	1
NDS POLAND		0.37			
NDSch POLAND				0.74	
CHE SWITZERLAND				0.74	0.6
NDS NETHERLANDS		0.15		0.5	
National CZECH REPUBLIC		0.5			
National HUNGARY		0.6		0.6	
Malaysi a OEL	MALAYSIA C			0.37	0.3
National PORTUGAL	C				0.3
National ESTONIA		0.6	0.5	1.2	1
National LATVIA		0.5			
National CZECH REPUBLIC	C			1	
National SLOVAKIA	C			0.74	
National SLOVAKIA		0.37	0.3		
National SLOVENIA		0.62	0.5	0.62	0.5
National UNITED KINGDOM		2.5	2	2.5	2
National BULGARIA		1.0		2.0	
National ROMANIA		1.2	1	3	2
National LITHUANIA		0.6	0.5		
National LITHUANIA	C			1.2	1
National CROATIA		2.5	2	2.5	2
EU		0.37	0.3		Binding

Predicted No Effect Concentration (PNEC) values

Component	CAS-No.	PNEC Limit	Exposure Route	Exposure Frequency	Remark
formaldehyde	50-00-0	0.47 mg/l	Fresh Water		
		0.47 mg/l	Marine water		
		4.7 mg/l	Intermittent release		
		0.19 mg/l	Microorganisms in sewage treatments		
		2.44 mg/kg	Freshwater sediments		
		2.44 mg/kg	Marine water sediments		
		0.21 mg/kg	Soil		

Derived No Effect Level. (DNEL)

Component	CAS-No.	Worker Industrial	Worker Professional	Consumer	Exposure Route	Exposure Frequency	Remark
-----------	---------	-------------------	---------------------	----------	----------------	--------------------	--------

formaldehyde	50-00-0	1		Human Inhalation	Short Term, local effects
		mg/m ³			
		240	102	Human Dermal	Long Term, systemic effects
		mg/kg	mg/kg		
		9	3.2	Human Inhalation	Long Term, systemic effects
mg/m ³	mg/m ³				
		0.037	0.012	Human Dermal	Long Term, local effects
		mg/cm ²	mg/cm ²		
		0.5	0.1	Human Inhalation	Long Term, local effects
		mg/m ³	mg/m ³		
			4.1	Human Oral	Long Term, systemic effects
			mg/kg		

8.2. Exposure controls

Eye protection:

Not needed for normal use. Anyway, operate according good working practices.

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

Suitable materials for safety gloves; EN ISO 374:

Polychloroprene - CR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Nitrile rubber - NBR: thickness $\geq 0,35\text{mm}$; breakthrough time $\geq 480\text{min}$.

Butyl rubber - IIR: thickness $\geq 0,5\text{mm}$; breakthrough time $\geq 480\text{min}$.

Fluorinated rubber - FKM: thickness $\geq 0,4\text{mm}$; breakthrough time $\geq 480\text{min}$.

Neoprene gloves are suggested (0,5 mm) not recommended gloves: not waterproof gloves

Respiratory protection:

Personal Protective Equipment should comply with relevant CE standards (as EN ISO 374 for gloves and EN ISO 166 for goggles), correctly maintained and stored. Consult the supplier to check the suitability of equipment against specific chemicals and for user information.

Hygienic and Technical measures

N.A.

Appropriate engineering controls:

N.A.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid

Appearance and colour: viscous liquid various

Odour: Characteristic

Odour threshold: N.A.

pH: N.A.

Melting point / freezing point: N.A.

Initial boiling point and boiling range: N.A.

Flash point: N.A.

Evaporation rate: N.A.

Upper/lower flammability or explosive limits: N.A.

Vapour density: N.A.

Vapour pressure: N.A.

Relative density: N.A.

Solubility in water: soluble

Solubility in oil: no data available

Partition coefficient (n-octanol/water): N.A.

Auto-ignition temperature: N.A.

Decomposition temperature: N.A.

Viscosity: 27,000.00 cPs

Explosive properties: N.A.

Oxidizing properties: N.A.

Solid/gas flammability: ==

9.2. Other information

No additional information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Stable under normal conditions.

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological information of the mixture:

a) acute toxicity	Not classified
	Based on available data, the classification criteria are not met
b) skin corrosion/irritation	Not classified
	Based on available data, the classification criteria are not met
c) serious eye damage/irritation	Not classified
	Based on available data, the classification criteria are not met
d) respiratory or skin sensitisation	Not classified
	Based on available data, the classification criteria are not met
e) germ cell mutagenicity	Not classified
	Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified
	Based on available data, the classification criteria are not met
g) reproductive toxicity	Not classified
	Based on available data, the classification criteria are not met
h) STOT-single exposure	Not classified
	Based on available data, the classification criteria are not met
i) STOT-repeated exposure	Not classified
	Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified
	Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

free crystalline silica (Ø >10 µ)	a) acute toxicity	LD50 Oral > 2000 mg/kg
		LD50 Skin > 2000 mg/kg
polyethylene glycol monooleylether	a) acute toxicity	LD50 Oral Rat 2700 mg/kg
		LD50 Oral Rat = 2700 mg/kg
zinc pyrithione	a) acute toxicity	LD50 Skin Rabbit = 100 mg/kg
		LD50 Oral Rat = 177 mg/kg
		LC50 Inhalation Rat 0.05 mg/l 4h
		LD50 Skin Rabbit = 100 mg/kg
free crystalline silica (Ø <10 µ)	a) acute toxicity	LD50 Oral Rat = 500 mg/kg
1,2-benzisothiazol-3(2H)-	a) acute toxicity	LD50 Oral Rat = 1020 mg/kg

one; 1,2-benzisothiazolin-3-one

formaldehyde	a) acute toxicity	LD50 Oral Rat = 700 mg/kg LC50 Inhalation Rat = 0.578 mg/l LD50 Skin Rabbit = 270 mg/kg LD50 Skin Rabbit = 270 mg/kg LC50 Inhalation Rat = 0.578 mg/l 4h LD50 Oral Rat = 100 mg/kg
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1)	a) acute toxicity	LC50 Inhalation Rat = 2.36000 mg/l 4h LD50 Skin Rabbit = 660.00000 mg/kg LD50 Oral Rat = 53.00000 mg/kg

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

List of Eco-Toxicological properties of the product

The product is classified: Aquatic Chronic 3(H412)

List of components with eco-toxicological properties

Component	Ident. Numb.	Ecotox Infos
zinc pyriithione	CAS: 13463-41-7 - EINECS: 236-671-3	G : LD50 Avian Colinus virginianus = 64 mg/kg NZ_CCID
1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one	CAS: 2634-33-5 - EINECS: 220-120-9 - INDEX: 613-088-00-6	a) Aquatic acute toxicity : LC50 Fish = 2.15000 mg/L b) Aquatic chronic toxicity : NOEC Algae = 0.04030 mg/L 72h b) Aquatic chronic toxicity : EC50 Algae = 0.11000 mg/L 72h b) Aquatic chronic toxicity : EC10 Algae = 0.04000 mg/L 72h b) Aquatic chronic toxicity : EC50 Daphnia = 3.27000 mg/L 48h NOEC Daphnia = 1.20000 mg/L 21d
formaldehyde	CAS: 50-00-0 - EINECS: 200-001-8 - INDEX: 605-001-00-5	a) Aquatic acute toxicity : LC50 Fish = 41 mg/L 96 a) Aquatic acute toxicity : EC50 Daphnia = 42 mg/L 24 a) Aquatic acute toxicity : LC50 Fish Pimephales promelas 22.6 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Lepomis macrochirus = 1510 µg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Brachydanio rerio = 41 mg/L 96h IUCLID a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss 0.032 mL/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss 100 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Fish Pimephales promelas 23.2 mg/L 96h EPA a) Aquatic acute toxicity : LC50 Daphnia Daphnia magna = 2 mg/L 48h IUCLID a) Aquatic acute toxicity : EC50 Daphnia Daphnia magna 11.3 mg/L 48h EPA

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) CAS: 55965-84-9 - EINECS: 611-341-5 - INDEX: 613-167-00-5 a) Aquatic acute toxicity : EC50 Daphnia = 0.12 mg/L 48

- a) Aquatic acute toxicity : LC50 Fish = 0.22 mg/L 96
- a) Aquatic acute toxicity : EC50 Algae = 0.048 mg/L 72
- b) Aquatic chronic toxicity : NOEC Algae = 0.0012 mg/L 72
- b) Aquatic chronic toxicity : NOEC Fish = 0.098 mg/L - 28 d
- b) Aquatic chronic toxicity : NOEC Daphnia = 0.004 mg/L - 21 d

12.2. Persistence and degradability

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT/vPvB Ingredients are present

12.6. Other adverse effects

N.A.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

A waste code (EWC) according to European List of Waste (LoW) cannot be specified, due to dependence on the usage. Contact and send to an authorized waste disposal service.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Hazardous waste: Yes

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

SECTION 14: Transport information

Not classified as dangerous in the meaning of transport regulations.

14.1. UN number

N.A.

14.2. UN proper shipping name

N.A.

14.3. Transport hazard class(es)

N.A.

14.4. Packing group

N.A.

14.5. Environmental hazards

N.A.

14.6. Special precautions for user

N.A.

Road and Rail (ADR-RID) :

N.A.

Air (IATA) :

N.A.

Sea (IMDG) :

N.A.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC (2004/42/EC) : N.A. g/l

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EU) 2015/830

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/669 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Provisions related to directive EU 2012/18 (Seveso III):

N.A.

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: 3, 40

Restrictions related to the substances contained: 28

SVHC Substances:

No data available

National regulations

Produktregisteret Norge: 608472

Produktregister Danmark: 4294131

MAL-kode: 1-3 (1993)

German Water Hazard Class (WGK)

N.A.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Code	Description
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.

H341	Suspected of causing genetic defects.
H350	May cause cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
3.1/3/Dermal	Acute Tox. 3	Acute toxicity (dermal), Category 3
3.1/3/Inhal	Acute Tox. 3	Acute toxicity (inhalation), Category 3
3.1/3/Oral	Acute Tox. 3	Acute toxicity (oral), Category 3
3.2/1B	Skin Corr. 1B	Skin corrosion, Category 1B
3.2/2	Skin Irrit. 2	Skin irritation, Category 2
3.3/1	Eye Dam. 1	Serious eye damage, Category 1
3.3/2	Eye Irrit. 2	Eye irritation, Category 2
3.4.2/1	Skin Sens. 1	Skin Sensitisation, Category 1
3.5/2	Muta. 2	Germ cell mutagenicity, Category 2
3.6/1B	Carc. 1B	Carcinogenicity, Category 1B
3.8/3	STOT SE 3	Specific target organ toxicity — single exposure, Category 3
3.9/1	STOT RE 1	Specific target organ toxicity — repeated exposure, Category 1
4.1/A1	Aquatic Acute 1	Acute aquatic hazard, category 1
4.1/C1	Aquatic Chronic 1	Chronic (long term) aquatic hazard, category 1
4.1/C3	Aquatic Chronic 3	Chronic (long term) aquatic hazard, category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008

4.1/C3 Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive

EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency
EINECS: European Inventory of Existing Commercial Chemical Substances.
ES: Exposure Scenario
GefStoffVO: Ordinance on Hazardous Substances, Germany.
GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
IARC: International Agency for Research on Cancer
IATA: International Air Transport Association.
IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
IC50: half maximal inhibitory concentration
ICAO: International Civil Aviation Organization.
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG: International Maritime Code for Dangerous Goods.
INCI: International Nomenclature of Cosmetic Ingredients.
IRCCS: Scientific Institute for Research, Hospitalization and Health Care
KSt: Explosion coefficient.
LC50: Lethal concentration, for 50 percent of test population.
LD50: Lethal dose, for 50 percent of test population.
LDLo: Leathal Dose Low
N.A.: Not Applicable
N/A: Not Applicable
N/D: Not defined/ Not available
NA: Not available
NIOSH: National Institute for Occupational Safety and Health
NOAEL: No Observed Adverse Effect Level
OSHA: Occupational Safety and Health Administration.
PBT: Persistent, Bioaccumulative and Toxic
PGK: Packaging Instruction
PNEC: Predicted No Effect Concentration.
PSG: Passengers
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
vPvB: Very Persistent, Very Bioaccumulative.
WGK: German Water Hazard Class.

Paragraphs modified from the previous revision:

- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 9. PHYSICAL AND CHEMICAL PROPERTIES
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 16. OTHER INFORMATION