

*

Reviewed on: 28/06/2021 Printing date: 02/07/2021

SECTION 01: Identification of the substance/mixture and of the company undertaking

- 1.1 Product identifier
- Trade name: HYDROPUR 7515-99 HARDENER
- Article number / Safety Data Sheet: H75150
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Application of the substance / the preparation Coating material
- 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Teknos AG Industriestrasse 7 LI-9487 Gamprin-Bendern T +423 375 94 00

- F +423 375 94 99
- Further information obtainable from:
- Product safety department. e-mail address: li-sdb@teknos.com 1.4 Emergency telephone number:
- Swiss Toxicological Information Centre, CH-8032 Zürich Emergency telephone: +41 (0)44 251 51 51 (International)

SECTION 02: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



Skin Sens. 1 - H317 May cause an allergic skin reaction. STOT SE 3 - H335 May cause respiratory irritation.

Aquatic Chronic 3 - H412 Harmful to aquatic life with long lasting effects.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
- Hazard pictograms



GHS07 Signal word

- Warning
- Hazard-determining components of labelling: Hydrophilic, aliphatic polyisocyanate based on HDI / Hexamethylene-1, 6-diisocyanate homopolymer / cyclohexyldimethylamine / hexamethylenedi-isocyanate
 Hazard statements H317 May cause an allergic skin reaction.
- H335 May cause respiratory irritation.
- H412 Harmful to aquatic life with long lasting effects. EUH204 Contains isocyanates. May produce an allergic reaction.
- Precautionary statements
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P302+P352 IF ON SKIN: Wash with plenty of water. P403+P233 Store in a well-ventilated place. Keep container tightly closed.

(continued on page 2)



Reviewed on: 28/06/2021 Printing date: 02/07/2021

PRODUCT : HYDROPUR 7515-99 HARDENER		
 2.3 Other haza 	of contents/container in accordance with local/regional/ national/inter Irds and vPvB assessment	<i>(continued of page 1)</i> national regulations.
SECTION 03:	Composition/information on ingredients	
 Description: 	characterization: Mixtures tances listed below with nonhazardous additions.	
• Dangerous con	nponents:	
CAS Number		%
822-06-0	hexamethylene-di-isocyanate EC number: 212-485-8 Record number 01-2119457571-37	0,0015- 0,50
98-94-2	cyclohexyldimethylamine EC number: 202-715-5 Record number 01-2119533030-60 ♦ Skin Corr. 1B - H314; ♦ Acute Tox. 3 - H311, Acute Tox. 2 - H330; ♦ Flam. Liq. 3 - H226; ♦ Acute Tox. 4 - H302	1,00- 5,00
666723-27-9	Hydrophilic, aliphatic polyisocyanate based on HDI Acute Tox. 4 - H332, Skin Sens. 1 - H317, STOT SE 3 - H335; Aquatic Chronic 3 -	40,00- 60,00
3779-63-3	H412 Hexamethylene-1,6-diisocyanate homopolymer Acute Tox. 4 - H332, Skin Sens. 1 -	10,00- 25,00
28182-81-2	H317, STOT SE 3 - H335 polyisocyanate aliphatic	10,00- 25,00

01-2119485796-17

Acute Tox. 4 - H332, Skin Sens. 1 -H317, STOT SE 3 - H335

Additional information:

For the wording of the listed risk phrases refer to section 16.

Record number

SECTION 04: First aid measures

• 4.1 Description of first aid measures

After inhalation: Supply fresh air and to be sure call for a doctor. In case of unconsciousness place patient stably in side position for transportation.
After skin contact:

Immediately wash with water and soap and rinse thoroughly.

(continued on page 3)



(continued of page 2)

2983315

Reviewed on: 28/06/2021 Printing date: 02/07/2021

PRODUCT : HYDROPUR 7515-99 HARDENER

Immediately rinse with water.

After eye contact:

- Rinse opened eye for several minutes under running water.
- After swallowing:
- Do not induce vomiting; call for medical help immediately.
- Information for doctor:
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 05: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- 5.2 Special hazards arising from the substance or mixture Formation of toxic gases is possible during heating or in case of fire.
- 5.3 Advice for firefighters
- Protective equipment:
- Mouth respiratory protective device.

Do not inhale explosion gases or combustion gases.

Additional information
 Cool endangered receptacles with water spray.
 Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 06: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation
 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. In case of seepage into the ground inform responsible authorities. In case of gas release or seepage into the ground inform responsible authorities. Do not allow to enter sewers/ surface or ground water.
 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 07: Handling and storage

• Handling:

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
 Take note of emission threshold.
- Information about fire and explosion protection: Prevent impact and friction.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- Information about storage in one common storage facility:



2983315

Reviewed on: 28/06/2021 Printing date: 02/07/2021

PRODUCT : H	YDROPUR 7515-99	HARDENER	
Not required.			(continued of page 3)
 Further informa Keep container Store in cool, d Protect from he 7.3 Specific er 	ry conditions in well se at and direct sunlight.	ealed receptacles.	
SECTION 08:	Exposure contr	ols/personal protection	<u>on</u>
 8.1 Control par Ingredients w 		equire monitoring at the work	place:
822-06-0	hexamethylene-		
WEL			
	term value	0.07	mg/m3
	erm value	0.02	mg/m3
•	s -NCO		
 Ingredients with 	n biological limit value	5:	
822-06-0	hexamethylene-	di-isocyanate	
BMGV			
1 µmo	l creatinine/mol		
Mediu	m: urine		
Sampl	ing time: At the end	of the period od exposure	
 Additional infor 	eter: isocyanate-deri mation: during the making were		
 General protect The usual protect Keep away from Immediately re Do not inhale g Do not inhale d Avoid contact w Do not eat or d Be sure to cleat Respiratory pro- or longer exposi- recommended. Protection of his preparation. Do preparation the 	ective equipment: tive and hygienic mea autionary measures a n foodstuffs, beverage move all soiled and cc ases / fumes / aeroso ust / smoke / mist. vith the eyes and skin. rink while working. n skin thoroughly after the the self-container ands: The glove mater is to missing tests no e chemical mixture. Set the degradation Prote	re to be adhered to when handlines and feed. ontaminated clothing ils. r work and before breaks. ef exposure or low pollution use d respiratory protective device. S rial has to be impermeable and r recommendation to the glove m	respiratory filter device. In case of intensive Suitable respiratory protective device resistant to the product/ the substance/ the paterial can be given for the product/ the consideration of the penetration times, rates
The selection of varies from ma the glove mate Penetration tim The exact brea observed. The determined	If the suitable gloves c nufacturer to manufac rial can not be calcula e of glove material k through time has to d penetration times ac	turer. As the product is a prepar ted in advance and has therefor be found out by the manufacture cording to EN 374 part III are no	terial, but also on further marks of quality and ration of several substances, the resistance of re to be checked prior to the application. er of the protective gloves and has to be ot performed under practical conditions.
 Eye protection. 			e penetration time, is recommended.



Reviewed on: 28/06/2021 Printing date: 02/07/2021

	(continued of page 4)
SECTION 09: Physical and che	mical properties
9.1 Information on basic physical and che	emical properties
Appearance	
Appearance:	
Form:	Liquid
Colour:	According to product specifica
Odour:	Characteristic Characteristic
Odour threshold:	Not determined.
pH-value:	at 20 °C 8,0
Change in condition	
Initial boiling point and boiling range:	153 °C
Flash point:	65 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	165 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Not determined.
Explosive properties:	Not determined.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure:	at 20 °C 0,7000 mbar
Density:	1,1100 g/cm3
Solubility in / Miscibility with	
water:	Not determined.
Viscosity:	
	Not determined.
	at 20 °C

SECTION 10: Stability and reactivity

- 10.1 Reactivity
- No further relevant information available.
- 10.2 Chemical stability Thermal decomposition / conditions to be avoided: .
- No decomposition if used according to specifications. 10.3 Possibility of hazardous reactions
- No dangerous reactions known. 10.4 Conditions to avoid
- No further relevant information available.
- 10.5 Incompatible materials:
- No further relevant information available. 10.6 Hazardous decomposition products:
- No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity .
- LD/LC50 values relevant for classification:

822-06-0 hexamethylene-di-isocyanate

Oral, LD50: 738 mg/kg (rat) Dermal, LD50: 593 mg/kg (rat) Oral, LD50: 348 mg/kg (rat) Inhalative, LC50/4h: 1,88 mg/l (rat)

(continued on page 6)



(continued of page 5)

2983315

Reviewed on: 28/06/2021 Printing date: 02/07/2021

PRODUCT : HYDROPUR 7515-99 HARDENER

98-94-2

cyclohexyldimethylamine

Primary irritant effect:

- Skin corrosion/irritation
- No irritant effect.
- Serious eye damage/irritation
- No irritating effect.
- Respiratory or skin sensitisation Sensitisation possible through skin contact.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

SECTION 12: Ecological information

• 12.1 Toxicity

- · Aquatic toxicity:
- No further relevant information available.
- 12.2 Persistence and degradability
- No further relevant information available.
- Behaviour in environmental systems:
- 12.3 Bioaccumulative potential
- No further relevant information available. • 12.4 Mobility in soil
- No further relevant information available.
- Ecotoxical effects:
- Remark:

Harmful to fish

Additional ecological information:

- General notes:
- Harmful to aquatic organisms

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

- Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- 12.5 Results of PBT and vPvB assessment
- *PBT*:

Not applicable.

• vPvB:

Not applicable.

12.6 Other adverse effects

No further relevant information available.

SECTION 13: Disposal considerations

```
• 13.1 Waste treatment methods
```

```
    European and swiss waste code

            B
            WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF
            COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS
            AND PRINTING INKS
            08 01
            wastes from MFSU and removal of paint and varnish
            08 01 11
            waste paint and varnish containing organic solvents or other hazardous
            substances
            Uncleaned packaging:
            Recommendation:
            Disposal must be made according to official regulations.
```

(continued on page 7)



Reviewed on: 28/06/2021 Printing date: 02/07/2021

		(continued of page 6)
SECTION 14: Tra	insport information	
• 14.1 UN-Number		
ADR	Void	
IMDG	Void	
ΙΑΤΑ	Void	
 14.2 UN proper sl 	nipping name	
ADR	Void	
IMDG	Void	
ΙΑΤΑ	Void	
 14.3 Transport ha ADR 	zard class(es)	
Class	Void	
IMDG		
Class	Void	
ΙΑΤΑ		
Class	Void	
 14.4 Packing group 	р	
ADR	Void	
IMDG	Void	
IATA	Void	
 14.5 Environment Not applicable. 14.7 Transport in Not applicable. 	tal hazards: bulk according to Annex II of MARPOL73/78 a	and the IBC Code

SECTION 15: Regulatory information

 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
 REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

National regulations:

· Information about limitation of use:

The above-mentioned manufacturer's information on the handling of isoc yanates is contained in the safety data sheet of the product. The Euro pean Committee of Paint, Printing Ink and Artists 'Colours Manufacture rs' Associations (CEPE) provides the following information on coatings isocyanates: Ready-to-use paints containing isocyanates may have an ir ritant effect on mucous membranes - especially on breathing organs - a nd cause hypersensitivity reactions. Inhalation of vapour or spray mist may cause sensitisation. When handling paints containing isocyanates , all precautions required for solvent-containing paints must be follo wed. Vapour and spray mist in particular should not be inhaled. Person s who are allergic, asthmatic, or prone to respiratory ailments should not work with isocyanate-containing paints.

- Technical instructions (air):
 Class Share in %
- Class Share in % I

1,32

• Waterhazard class:

Water hazard class 1 (Self-assessment): slightly hazardous for water.

- 15.2 Chemical safety assessment:
- A Chemical Safety Assessment has not been carried out.



2983315

Reviewed on: 28/06/2021 Printing date: 02/07/2021

	(continued of page 7
SECTION 1	6: Other information
This informat	tion is based on our present knowledge. However, this shall not constitute a guarantee for any specific
	ires and shall not establish a legally valid contractual relationship.
 Relevant p 	
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319 H330	Causes serious eye irritation. Fatal if inhaled.
H330 H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.
 Environme Abbreviation ADR: Acconcerning Rigilation IMDG: Integration IMDG: Integration IATA: I	nt issuing MSDS: Int protection department. Int protection department. Int protection department. International Carriage of Dangerous Goods by Road) International Carriage of Dangerous Goods by Road) International concernant le transport des marchandises dangereuses par chemin de fer Ins Concerning the International Transport of Dangerous Goods by Rail) International Maritime Code for Dangerous Goods International Air Transport Association International Civil Aviation Organisation International Civil Aviation Organisation International Civil Aviation Organisation International International Commercial Chemical Substances European Inventory of Existing Commercial Chemical Substances International Abstracts Service (division of the American Chemical Society) International Abstracts Service (division of the American Chemical Society) International Abstracts and Toxic
vPvB: very	Persistent and very Bioaccumulative
 * Data con 	npared to the previous version altered.