

according to 1907/2006/EC, Article 31

4075603

Reviewed on: 30/06/2021 Printing date: 30/06/2021

SECTION 01: Identification of the substance/mixture and of the company undertaking

- 1.1 Product identifier
- · Trade name:

PLATIN ANTIGLISS 4546

- · Article number / Safety Data Sheet:
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Application of the substance / the preparation

Coating material

- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Teknos AG

Industriestrasse 7

LI-9487 Gamprin-Bendern

T +423 375 94 00

F +423 375 94 99

- Further information obtainable from:
 - Product safety department. e-mail address: li-sdb@teknos.com
- 1.4 Emergency telephone number:

Swiss Toxicological Information Centre, CH-8032 Zürich Emergency telephone: +41 (0)44 251 51 51 (International)

SECTION 02: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008 Void
- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
- Hazard pictograms

Void

Signal word

Void

Hazard statements

EUH208 Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic

EUH210 Safety data sheet available on request.

- 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT:
- Not applicable.
- vPvB:

Not applicable.

SECTION 03: Composition/information on ingredients

- · 3.2 Chemical characterization: Mixtures
- Description:

Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS Number

108-01-0

2-dimethylaminoethanol

0,50- 1,00

EC number: 203-542-8

Record number 01-2119492298-24

Skin Corr. 1B - H314; 🏵 Flam. Liq.

Tox. 4 - H312, Acute Tox. 4 - H332

(continued on page 2)



according to 1907/2006/EC, Article 31

4075603

Reviewed on: 30/06/2021 Printing date: 30/06/2021

PRODUCT :	PLATIN ANTIGLISS 4546	
2634-33-5	1,2-benzisothiazol-3(2H)-one EC number: 220-120-9	(continued of page 1) 0,00- 0,50
	- H302, Skin Irrit. 2 - H315, Skin Sens. 1 - H317; 🔖 Aquatic Acute 1 - H400	
112-34-5	2-(2-butoxyethoxy)ethanol EC number: 203-961-6 Record number 01-2119475104-44 \$\frac{1}{2}\$ Eye Irrit. 2 - H319	1,00- 5,00
111-76-2	2-butoxyethanol EC number: 203-905-0 Record number 01-2119475108-36 1 Acute Tox. 4 - H302, Acute Tox. 4 -	1,00- 5,00
	H312, Acute Tox. 4 - H332, Skin Irrit. 2 - H315, Eye Irrit. 2 - H319	
57-55-6	Propylene glycol EC number: 200-338-0 Record number 01-2119456809-23 Acute Tox. 4 - H302	5,00- 10,00

SECTION 04: First aid measures

- 4.1 Description of first aid measures
- After inhalation:
- Supply fresh air; consult doctor in case of complaints.
- After skin contact:
- Immediately wash with water and soap and rinse thoroughly.
- After eye contact:

 Pince append eye f
- Rinse opened eye for several minutes under running water.
- · After swallowing:
- Do not induce vomiting; call for medical help immediately.
- Information for doctor:
- 4.2 Most important symptoms and effects, both acute and delayed
 - No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed
 - No further relevant information available.

SECTION 05: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:
- Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture
 - Formation of toxic gases is possible during heating or in case of fire.
- 5.3 Advice for firefighters
- Protective equipment:
- Mouth respiratory protective device.
- Do not inhale explosion gases or combustion gases.
- Additional information
- Cool endangered receptacles with water spray.
- Collect contaminated fire fighting water separately. It must not enter the sewage system.

GB



according to 1907/2006/EC, Article 31

4075603

Reviewed on: 30/06/2021 Printing date: 30/06/2021

> PRODUCT: **PLATIN ANTIGLISS 4546**

> > (continued of page 2)

SECTION 06: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 07: Handling and storage

- · Handling:
- 7.1 Precautions for safe handling
- Use only in well ventilated areas.
- Information about fire and explosion protection:

No special measures required.

- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

Information about storage in one common storage facility:

Not required.

Further information about storage conditions:

Protect from frost.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

7.3 Specific end use(s)

No further relevant information available.

SECTION 08: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

108-01-0 2-dimethylaminoethanol

WEL

Short-term value 22 mg/m3 6 ppm Long-term value 7.4 mg/m3 ppm

112-34-5 2-(2-butoxyethoxy)ethanol

WEL

Short-term value 101.2 mg/m3 15 ppm Long-term value 67.5 mg/m3 10 ppm

111-76-2 2-butoxyethanol

WEL

Short-term value 246 ma/m3

(continued on page 4)



according to 1907/2006/EC, Article 31

4075603

Reviewed on: 30/06/2021 Printing date: 30/06/2021

> PRODUCT: **PLATIN ANTIGLISS 4546**

> > Long-term value

(continued of page 3)

ppm

50 123 mg/m3

ppm

Sk. BMGV

57-55-6 Propylene glycol

WEL

Long-term value 474* 10** mg/m3 150* ppm

25

*total vapour and particulates **particulates

· Ingredients with biological limit values: 111-76-2 2-butoxyethanol

BMGV

240 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: butoxyacetic acid

Additional information:

The lists valid during the making were used as basis.

- 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Do not eat or drink while working.

Be sure to clean skin thoroughly after work and before breaks.

- Respiratory protection: Suitable respiratory protective device recommended. Use suitable respiratory protective device in case of insufficient ventilation.
- Protection of hands: The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Impervious gloves
- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

- Eye protection: Safety glasses
- Body protection: Protective work clothing

SECTION 09: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance Appearance:

Form: Liquid

Colour: According to product specifica Characteristic Characteristic Odour:

Odour threshold: Not determined.

Change in condition

0°C Melting point/freezing point:

Initial boiling point and boiling range: Undetermined. Flash point: 100 °C

(continued on page 5)



according to 1907/2006/EC, Article 31

4075603

Reviewed on: 30/06/2021 Printing date: 30/06/2021

PRODUCT ·	DI ATINI	ANITICI	ISS 4546
PRUDULL			155 4540

		(continued of page 4)
Flammability (solid, gas):	Not applicable.	
Ignition temperature:	Undetermined.	
Decomposition temperature:	Not determined.	
Auto-ignition temperature:	Not determined.	
Explosive properties:	Not determined.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapour pressure:	at 20 °C 23,0000 mbar	
Density:	1,0600 g/cm3	
Solubility in / Miscibility with		
water:	Not determined.	
Viscosity:		
	Not determined.	
	at 20 °C 18 - 21 s DIN 4 mm	
9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- 10.1 Reactivity
 - No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions
- No dangerous reactions known. 10.4 Conditions to avoid
- No further relevant information available.
- 10.5 Incompatible materials:
- No further relevant information available.
- 10.6 Hazardous decomposition products:
 No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity
- LD/LC50 values relevant for classification:

7631-86-9 silicon dioxide, chemically prepared

Oral, LD50: 10000 mg/kg (rat) Oral, LD50: 2000 mg/kg (rat) Dermal, LD50: 1370 mg/kg (Rabbit) Inhalative, LC50 4h: 3,25 mg/l (mouse) Oral, LD50: 5660 mg/kg (rat) Dermal, LD50: 4000 mg/kg (Rabbit) Oral, LD50: 1746 mg/kg (rat) Oral, LD50: 1414 mg/kg (guinea Pig) Dermal, LD50: 2000 mg/kg (rat) Dermal, LD50: 1000 mg/kg (Rabbit) Dermal, LD50: 2000 mg/kg (rat) Dermal, LD50: 20800 mg/kg (Rabbit) Oral, LD50: 5135 mg/kg (rat) Dermal, LD50: >19000 mg/kg (Rabbit)

108-01-0 2-dimethylaminoethanol 112-34-5 2-(2-butoxyethoxy)ethanol

111-76-2 2-butoxyethanol 57-55-6 Propylene glycol

34590-94-8 Dipropylene glycol monomethyl ether

- Primary irritant effect:
- Skin corrosion/irritation
- No irritant effect.
- Serious eye damage/irritation
 - No irritating effect.
- Respiratory or skin sensitisation No sensitising effects known.

(continued on page 6)



according to 1907/2006/EC, Article 31

4075603

Reviewed on: 30/06/2021 Printing date: 30/06/2021

> PRODUCT: **PLATIN ANTIGLISS 4546**

> > (continued of page 5)

Additional toxicological information:

The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version.

SECTION 12: Ecological information

- 12.1 Toxicity
- Aquatic toxicity:

No further relevant information available.

12.2 Persistence and degradability

No further relevant information available.

- · Behaviour in environmental systems:
- 12.3 Bioaccumulative potential
- No further relevant information available.

12.4 Mobility in soil No further relevant information available.

- Additional ecological information:
- General notes.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- PBT:
- Not applicable.
- vPvB:
- Not applicable.
- 12.6 Other adverse effects

No further relevant information available.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- European and swiss waste code

0.8

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

wastes from MFSU and removal of paint and varnish

aqueous suspensions containing paint or varnish containing organic solvents or other hazardous substances

- Uncleaned packaging:
- Recommendation:
- Disposal must be made according to official regulations.
- Recommended cleansing agents:

Water, if necessary together with cleansing agents.

SECTION 14: Transport information

• 14.1 UN-Number

Void **ADR IMDG** Void IATA Void · 14.2 UN proper shipping name Void **ADR IMDG** Void Void 14.3 Transport hazard class(es)

(continued on page 7)

ADR



according to 1907/2006/EC, Article 31

4075603

Reviewed on: 30/06/2021 Printing date: 30/06/2021

> PRODUCT: **PLATIN ANTIGLISS 4546**

> > (continued of page 6)

Class

Void

IMDG Class

Void

IATA

Void

Class

· 14.4 Packing group **ADR** Void **IMDG** Void IATA Void

• 14.5 Environmental hazards:

Not applicable.

- 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.
- Transport/Additional information:

Not applicable.

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 55
- · National regulations:
- · Classification according to VbF:

Technical instructions (air):

Class Share in %

Ι

3,08 III 5,45

Waterhazard class:

Water hazard class 1 (Self-assessment): slightly hazardous for water.

15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour. H302 Harmful if swallowed H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage. Causes serious eye irritation. H319 Harmful if inhaled. H332 H400 Very toxic to aquatic life.

· Department issuing MSDS:

Environment protection department.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

(continued on page 8)

Page: 8 / 8

MATERIAL SAFETY DATA SHEET



according to 1907/2006/EC, Article 31

4075603

Reviewed on: 30/06/2021 Printing date: 30/06/2021

PRODUCT: **PLATIN ANTIGLISS 4546**

(continued of page 7)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer

(Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VbF: Verordnung über brennbare Flüssigkeiten, Österreich (Ordinance on the storage of combustible liquids,

Austria)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative • * Data compared to the previous version altered.