

Reviewed on: 28/06/2021 Printing date: 30/06/2021

## SECTION 01: Identification of the substance/mixture and of the company undertaking • 1.1 Product identifier Trade name: ALPOCRYL KLARLACK 1495 · Article number / Safety Data Sheet: 149500 1.2 Relevant identified uses of the substance or mixture and uses advised against Application of the substance / the preparation Coating material 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: \* Teknos AG \* Industriestrasse 7 LI-9487 Gamprin-Bendern T +423 375 94 00 F +423 375 94 99 Further information obtainable from: Product safety department. e-mail address: li-sdb@teknos.com 1.4 Emergency telephone number: Swiss Toxicological Information Centre, CH-8032 Zürich Emergency telephone: +41 (0)44 251 51 51 (International) SECTION 02: Hazards identification 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 GHS02 Flam. Liq. 3 - H226 Flammable liquid and vapour. GHS07 Skin Sens. 1 - H317 May cause an allergic skin reaction. STOT SE 3 - H336 May cause drowsiness or dizziness. Aquatic Chronic 3 - H412 Harmful to aquatic life with long lasting effects. 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 Hazard pictograms GHS02 GHS07 Signal word Warning Hazard-determining components of labelling: n-butyl acetate / Solvent naphtha (petroleum), light arom. / BENZOTRIAZOL DERIVATIVES Index no. 607-176-00-3 / Bis(1,2,2,6,6pentamethyl-4-piperidyl)sebacate Hazard statements H226 Flammable liquid and vapour. H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects. Precautionary statements (continued on page 2)



	(continued of page 1)
	p away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Kee	p container tightly closed.
P240 Gro	und and bond container and receiving equipment.
P302+P35	2 IF ON SKIN: Wash with plenty of water.
	33 Store in a well-ventilated place. Keep container tightly closed.
	ose of contents/container in accordance with local/regional/ national/international regulations.
• 2.3 Other	
	PBT and vPvB assessment
• PBT:	
Not applic	able.
<ul> <li>vPvB:</li> </ul>	
Not applic	able.

<ul> <li>Description:</li> </ul>	characterization: Mixtures stances listed below with nonhazardous additions.	
Dangerous col	mponents:	
CAS Number		%
123-86-4	n-butyl acetate EC number: 204-658-1 Record number 01-2119485493-29 ♦ Flam. Liq. 3 - H226; ♦ STOT SE 3 -	25,00- 40,00
64742-95-6	H336 <b>Solvent naphtha (petroleum), light arom.</b> EC number: 265-199-0 Record number 01-2119455851-35 <b>Solvent Solution</b> Asp. Tox. 1 - H304; <b>Solution</b> Flam. Liq. 3 - H226; <b>Acute Tox. 4 - H332, STOT SE 3</b>	5,00- 10,00
	- H335; 🚸 Aquatic Chronic 2 - H411	
1330-20-7	xylene EC number: 215-535-7 Record number 01-2119488216-32 ♦ Flam. Liq. 3 - H226; ♦ Acute Tox. 4 - H312, Acute Tox. 4 - H332, Skin Irrit. 2 - H315	5,00- 10,00
100-41-4	ethylbenzene EC number: 202-849-4 Record number 01-2119489370-35 ♦ Flam. Liq. 2 - H225; ♦ STOT RE 2 - H373, Asp. Tox. 1 - H304; ♦ Acute Tox. 4 - H332 BENZOTRIAZOL DERIVATIVES Index no. 607-176-	1,00- 5,00 1,00- 5,00
	00-3 EC number: 400-830-7 Record number 01-0000015075-76 ♦ Skin Sens. 1 - H317; ♦ Aquatic Chronic 2 - H411	
41556-26-7	Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	0,50- 1,00



Reviewed on: 28/06/2021 Printing date: 30/06/2021

PRODUCT :	ALPOCRYL KLARLACK 1495	
	🚸 Skin Sens. 1 - H317; 🚸 Aquatic	(continued of page 2)
	Acute 1 - H400, Aquatic Chronic 1 - H410	
82919-37-7	Methyl1,2,2,6,6-pentamethyl-4-piperidyl EC number: 280-060-4 Record number 01-2119976378-19	0,00- 0,50
108-88-3	Acute 1 - H400, Aquatic Chronic 1 - H410 toluene	0,50- 1,00
	EC number: 203-625-9 Record number 01-2119471310-51 Ilam. Liq. 2 - H225; 😵 Repr. 2 -	
	H361d, STOT RE 2 - H373, Asp. Tox. 1 - H304; Skin Irrit. 2 - H315, STOT SE 3 - H336	

### SECTION 04: First aid measures

- 4.1 Description of first aid measures
  After inhalation: Supply fresh air and to be sure call for a doctor. In case of unconsciousness place patient stably in side position for transportation.
  After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:
   Pince operad eve for soveral minutes upder running water
- Rinse opened eye for several minutes under running water. • After swallowing:
- Do not induce vomiting; call for medical help immediately.
- Information for doctor:
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

### SECTION 05: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents:
- Water with full jet
- 5.2 Special hazards arising from the substance or mixture
- Formation of toxic gases is possible during heating or in case of fire.
- 5.3 Advice for firefighters
  Protective equipment:
- Mouth respiratory protective device.
- Do not inhale explosion gases or combustion gases.
- Additional information
   Cool endangered receptacles with water spray.
   Collect contaminated fire fighting water separately. It must not enter the sewage system.

# SECTION 06: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation
   6.2 Environmental precautions:
- Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system.

(continued on page 4)



(continued of page 3)

#### 1684329

Reviewed on: 28/06/2021 Printing date: 30/06/2021

### PRODUCT : ALPOCRYL KLARLACK 1495

Do not allow to enter sewers/ surface or ground water.

- · 6.3 Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
- 6.4 Reference to other sections
   See Section 7 for information on safe handling.
   See Section 8 for information on personal protection equipment.
   See Section 13 for disposal information.

### SECTION 07: Handling and storage

#### • Handling:

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols. Take note of emission threshold. Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
  Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed. Store in cool, dry conditions in well sealed receptacles. Protect from heat and direct sunlight.
   7.3 Specific end use(s)
- No further relevant information available.

### SECTION 08: Exposure controls/personal protection

- 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:
- 123-86-4 n-butyl acetate

WEL			
	Short-term value	966	mg/m3
		200	ppm
	Long-term value	724	mg/m3
		150	ppm
1330-20-7 WEL	7 xylene		
	Short-term value	441	mg/m3
		100	ppm
	Long-term value	220	mg/m3
	-	50	ppm
	Sk; BMGV		
100-41-4 WEL	ethylbenzene		
	Short-term value	552	mg/m3
		125	ppm
	Long-term value	441	<b>mg/m3</b> (continued on page 5)



(continued on page 6)

#### 1684329

Reviewed on: 28/06/2021 Printing date: 30/06/2021

			(continued of page 4)
		100	(continuou of page ) ppm
	Sk		
108-88-3 WEL	toluene		
VV CL	Short-term value	384	mg/m3
		100	ppm
	Long-term value	191	mg/m3
	term tallet	50	ppm
	Sk		FF.
<ul> <li>Ingredie</li> </ul>	ents with biological limit val	ues:	
1330-20-	7 xylene		
BMGV			
	650 mmol/mol creatinine	9	
	Medium: urine	_	
	Sampling time: post shit		
• Additio	Parameter: methyl hippu nal information:	Iric acid	
	s valid during the making w	vere used as basis.	
	oosure controls		
Do not Avoid c Do not Be sure • Respira or long recomm • Protect prepara of diffus • Materia	atory protection: In case of l er exposure use self-contai nended. ion of hands: The glove ma ation. Due to missing tests i ation/ the chemical mixture. sion and the degradation Pi l of gloves ection of the suitable glove	sols. kin. fter work and before breaks. brief exposure or low pollution use respi and respiratory protective device. Suitab aterial has to be impermeable and resista no recommendation to the glove material Selection of the glove material on consi rotective gloves Impervious gloves s does not only depend on the material,	ble respiratory protective device ant to the product/ the substance/ the al can be given for the product/ the ideration of the penetration times, rates
varies f the glov Penetra The exa observe The det Therefo • Eye pro	ve material can not be calcu ation time of glove material act break through time has ed. termined penetration times	ulated in advance and has therefore to b to be found out by the manufacturer of t according to EN 374 part III are not perf e, which corresponds to 50% of the pen uhtly sealed goggles	be checked prior to the application. The protective gloves and has to be formed under practical conditions.
varies f the glov Penetra The exa observe The del Therefo <i>Eye pro</i> <i>Body p</i>	ve material can not be calcu ation time of glove material act break through time has ed. termined penetration times ore a maximum wearing tim otection: Safety glasses Tig rotection: Protective work c	ulated in advance and has therefore to b to be found out by the manufacturer of t according to EN 374 part III are not perf e, which corresponds to 50% of the pen thtly sealed goggles elothing	be checked prior to the application. The protective gloves and has to be formed under practical conditions.
varies f the glov • Penetra The exa observe The det Therefo • Eye pro • Body p	ve material can not be calcu- ation time of glove material act break through time has ed. termined penetration times ore a maximum wearing tim <i>otection: Safety glasses Tig</i> <i>rotection: Protective work c</i>	ulated in advance and has therefore to b to be found out by the manufacturer of t according to EN 374 part III are not perf e, which corresponds to 50% of the pen htty sealed goggles clothing	be checked prior to the application. The protective gloves and has to be formed under practical conditions.
varies f the glov • Penetra The exa observe The del Therefo • Eye pro • Body pa	ve material can not be calcu ation time of glove material act break through time has ed. termined penetration times ore a maximum wearing tim otection: Safety glasses Tig rotection: Protective work of 09: Physical and tion on basic physical an	ulated in advance and has therefore to b to be found out by the manufacturer of t according to EN 374 part III are not perf e, which corresponds to 50% of the pen htty sealed goggles clothing	be checked prior to the application. The protective gloves and has to be formed under practical conditions.
varies f the glov • Penetra The exa observe The del Therefo • <i>Eye</i> pro • <i>Body</i> pro <b>SECTION</b> 9.1 Informa	ve material can not be calcu- ation time of glove material act break through time has ed. termined penetration times bre a maximum wearing tim batection: Safety glasses Tig rotection: Protective work of 09: Physical and tion on basic physical an	ulated in advance and has therefore to b to be found out by the manufacturer of t according to EN 374 part III are not perf e, which corresponds to 50% of the pen htty sealed goggles clothing	he protective gloves and has to be formed under practical conditions.
varies f the glov • Penetra The exa observe The det Therefo • Eye pro • Body po SECTION 9.1 Informa Appearance	ve material can not be calcu- ation time of glove material act break through time has ed. termined penetration times bre a maximum wearing tim batection: Safety glasses Tig rotection: Protective work of 09: Physical and tion on basic physical an	ulated in advance and has therefore to b to be found out by the manufacturer of t according to EN 374 part III are not perf e, which corresponds to 50% of the pen thtly sealed goggles elothing chemical properties d chemical properties	be checked prior to the application. The protective gloves and has to be formed under practical conditions.
varies f the glov • Penetra The exa observe The del Therefo • <i>Eye pro</i> • <i>Body p</i> <b>SECTION</b> 9.1 Informa Appearance Form:	ve material can not be calcu- ation time of glove material act break through time has ed. termined penetration times bre a maximum wearing tim batection: Safety glasses Tig rotection: Protective work of 09: Physical and tion on basic physical an	ulated in advance and has therefore to b to be found out by the manufacturer of t according to EN 374 part III are not perf e, which corresponds to 50% of the pen thtly sealed goggles elothing chemical properties d chemical properties	be checked prior to the application. The protective gloves and has to be formed under practical conditions.
varies f the glov • Penetra The exa observe The det Therefo • Eye pro • Body po SECTION 9.1 Informa Appearance	ve material can not be calcu- ation time of glove material act break through time has ed. termined penetration times bre a maximum wearing tim batection: Safety glasses Tig rotection: Protective work of 09: Physical and tion on basic physical an	ulated in advance and has therefore to b to be found out by the manufacturer of t according to EN 374 part III are not perf e, which corresponds to 50% of the pen thtly sealed goggles elothing chemical properties d chemical properties	be checked prior to the application. The protective gloves and has to be formed under practical conditions.

Change in condition



Beviewed on: 28/06/2021 Printing date: 30/06/2021

#### **PRODUCT: ALPOCRYL KLARLACK 1495** (continued of page 5) Initial boiling point and boiling range: 124 °C 27 °C Flash point: Flammability (solid, gas): Not applicable. 425 °C Ignition temperature: Not determined. Decomposition temperature: Auto-ignition temperature: Not determined. Not determined. **Explosive properties: Explosion limits:** Lower: 1 Vol % Upper: 7 Vol % Vol % 10,7000 mbar at 20 °C 50 °C 55,0000 Vapour pressure: at mbar Density: 0,9900 g/cm3 Solubility in / Miscibility with water: Not determined. Viscosity: Not determined. 60 s DIN 4 mm 20 °C 40 at 9.2 Other information No further relevant information available.

### SECTION 10: Stability and reactivity

- 10.1 Reactivity
- No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid
- No further relevant information available.
- 10.5 Incompatible materials:
- No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity
- LD/LC50 values relevant for classification:
- 123-86-4

n-butyl acetate Oral, LD50: 13100 mg/kg (rat) Dermal, LD50: >5000 mg/kg (Rabbit) Inhalative, LC50/4h: >21 mg/l (rat) Oral, LD50: >6800 mg/kg (rat) Dermal, LD50: >3400 mg/kg (Rabbit) Inhalative, LC50/4h: >10,2 mg/l (rat) Oral, LD50: 4300 mg kg (rat) Dermal, LD50: 2000 mg/kg (Rabbit) Oral, LD50: 3500 mg/kg (rat) Dermal, LD50: 17800 mg/kg (Rabbit) Oral, LD50: 5000 mg/kg (rat) Inhalative, LC50/4h: 24 mg/l (rat) Oral, LD50: 5000 mg/kg (rat) Dermal, LD50: 12124 mg/kg (Rabbit) Inhalative, LC50/4h: 5320 mg/l (mouse)

#### 64742-95-6 Solvent naphtha (petroleum), light arom.

04142 00 0	oonvent napin
1330-20-7	xylene
100-41-4	ethylbenzene
100-42-5	styrene
108-88-3	toluene
<ul> <li>Primary irritant offer</li> </ul>	ect.

- rimary irritant effect.
- Skin corrosion/irritation No irritant effect.


(continued on page 7)



### 1684329

	(continued of page 6
<ul> <li>Serious eye</li> </ul>	e damage/irritation
No irritating	
	or skin sensitisation
Sensitisatio	n possible through skin contact.
	toxicological information:
	t shows the following dangers according to the calculation method of the General EU Classification for Preparations as issued in the latest version:
Irritant	
SECTION 12	Ecological information
• 12.1 Toxici	
<ul> <li>Aquatic tox</li> </ul>	
	elevant information available.
	stence and degradability elevant information available.
	in environmental systems:
	cumulative potential
	elevant information available.
<ul> <li>12.4 Mobilit</li> </ul>	y in soil
	elevant information available.
Ecotoxical	effects:
Remark:	iinh .
Harmful to	ecological information:
<ul> <li>General no</li> </ul>	
	aquatic organisms
	rd class 2 (German Regulation) (Self-assessment): hazardous for water
	v product to reach ground water, water course or sewage system.
	Irinking water if even small quantities leak into the ground.
<ul> <li>12.5 Result</li> <li>PBT:</li> </ul>	ts of PBT and vPvB assessment
Not applica	hle
<ul> <li>vPvB;</li> </ul>	50.
Not applica	ble.
	adverse effects
No further r	elevant information available.
SECTION 13	: Disposal considerations
• 13.1 Waste	treatment methods
<ul> <li>European a</li> </ul>	and swiss waste code
08	
	FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF
	G (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS
	NTING INKS
08 01	from MECH and removal of point and remain
	from MFSU and removal of paint and varnish
08 01 11	
waste pa substand	aint and varnish containing organic solvents or other hazardous
Indoara	neekoging
<ul> <li>Uncleaned</li> <li>Recomment</li> </ul>	
	ust be made according to official regulations.
DISDOSALITI	







Reviewed on: 28/06/2021 Printing date: 30/06/2021

		(continued of page 8
Limited quantities (LQ)	5L	(continued of page of
Excepted quantities (EQ)	E1	
	E1	
<ul> <li>UN "Model Regulation": UN 1263 PAINT, 3, III</li> </ul>		
614 1266 1 All 1, 6, III		
SECTION 15: Regulato	<u>pry information</u>	
• 15 1 Safety health and e	nvironmental regulations/legislation spec	ific for the substance or mixture
	nvironmental regulations/legislation spec	ific for the substance or mixture
<ul> <li>REGULATION (EC) No 19</li> </ul>	07/2006 ANNEX XVII	ific for the substance or mixture
	07/2006 ANNEX XVII	ific for the substance or mixture
<ul> <li>REGULATION (EC) No 19</li> </ul>	07/2006 ANNEX XVII	ific for the substance or mixture
<ul> <li>REGULATION (EC) No 19 Conditions of rest</li> <li>National regulations:</li> </ul>	07/2006 ANNEX XVII ariction: 3, 48	ific for the substance or mixture
• REGULATION (EC) No 19 Conditions of rest	07/2006 ANNEX XVII ariction: 3, 48	ific for the substance or mixture
<ul> <li>REGULATION (EC) No 19 Conditions of rest</li> <li>National regulations:</li> </ul>	07/2006 ANNEX XVII ariction: 3, 48	ific for the substance or mixture
<ul> <li>REGULATION (EC) No 19 Conditions of rest</li> <li>National regulations:</li> <li>Classification according to -</li> </ul>	07/2006 ANNEX XVII rriction: 3, 48 VbF:	ific for the substance or mixture
<ul> <li>REGULATION (EC) No 19 Conditions of rest</li> <li>National regulations:</li> <li>Classification according to         <ul> <li>Technical instructions (air)</li> </ul> </li> </ul>	07/2006 ANNEX XVII rriction: 3, 48 VbF:	ific for the substance or mixture
<ul> <li>REGULATION (EC) No 19 Conditions of rest</li> <li>National regulations:</li> <li>Classification according to -</li> </ul>	07/2006 ANNEX XVII rriction: 3, 48 VbF:	ific for the substance or mixture

• Waterhazard class:

Water hazard class 2 (Self-assessment): hazardous for water.

 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.Relevant phrases

	ricievani pinas		
	H225	Highly flammable liquid and vapour.	
	H226	Flammable liquid and vapour.	
	H304	May be fatal if swallowed and enters airways.	
	H312	Harmful in contact with skin.	
	H315	Causes skin irritation.	
	H317	May cause an allergic skin reaction.	
	H332	Harmful if inhaled.	
	H335	May cause respiratory irritation.	
	H336	May cause drowsiness or dizziness.	
	H361d	Suspected of damaging the unborn child.	
	H373	May cause damage to organs through prolonged or repeated exposure.	
	H400	Very toxic to aquatic life.	
	H410	Very toxic to aquatic life with long lasting effects.	
	H411	Toxic to aquatic life with long lasting effects.	
•	Department is	ssuing MSDS:	
	Environment pr	rotection department.	
•	Abbreviations a	and acronyms:	
	ADR: Accord e	européen sur le transport des marchandises dangereuses par Route (Europea	an Agreement
	concerning the	International Carriage of Dangerous Goods by Road)	
		nt international concernant le transport des marchandises dangereuses par c	nemin de fer
	(Regulations C	concerning the International Transport of Dangerous Goods by Rail)	
	IMDG: Internat	tional Maritime Code for Dangerous Goods	
	IATA: Internation	onal Air Transport Association	
		ional Civil Aviation Organisation	
		Harmonised System of Classification and Labelling of Chemicals	
		pean Inventory of Existing Commercial Chemical Substances	
		pean List of Notified Chemical Substances	
	CAS: Chemica	I Abstracts Service (division of the American Chemical Society)	
			continued on page 10)

## Page : 10 / 10 MATERIAL SAFETY DATA SHEET according to 1907/2006/EC, Article 31



1684329

PRODUCT : ALPOCRYL KLARLACK 1495
(continued of page 9) VbF: Verordnung über brennbare Flüssigkeiten, Österreich (Ordinance on the storage of combustible liquids, Austria) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative • * Data compared to the previous version altered.