

according to 1907/2006/EC, Article 31

2922717

Reviewed on: 28/06/2021 Printing date: 02/07/2021

SECTION 01: Identification of the substance/mixture and of the company undertaking

- 1.1 Product identifier
- Trade name:

UNIPUR 279 / 1910-99 HARDENER

- Article number / Safety Data Sheet: H90100
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Application of the substance / the preparation Coating material
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
- Teknos AG
- * Industriestrasse 7

LI-9487 Gamprin-Bendern

T +423 375 94 00

F +423 375 94 99

- Further information obtainable from:
 - Product safety department. e-mail address: li-sdb@teknos.com
- 1.4 Emergency telephone number:
- * Swiss Toxicological Information Centre, CH-8032 Zürich Emergency telephone: +41 (0)44 251 51 51 (International)

SECTION 02: Hazards identification

- 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02

Flam. Liq. 3 - H226 Flammable liquid and vapour.



GHS07

Acute Tox. 4 - H332 Harmful if inhaled.

Skin Sens. 1 - H317 May cause an allergic skin reaction.

STOT SE 3 - H335-H336 May cause respiratory irritation. May cause

drowsiness or dizziness.

- 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008
- Hazard pictograms





GHS02 GHS07
Signal word
Warning

- · Hazard-determining components of labelling:
- polyisocyanate aliphatic / hexamethylene-di-isocyanate
- Hazard statements

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H317 May cause an allergic skin reaction.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH204 Contains isocyanates. May produce an allergic reaction.

Precautionary statements

(continued on page 2)



according to 1907/2006/EC, Article 31

2922717

Reviewed on: 28/06/2021 Printing date: 02/07/2021

PRODUCT: UNIPUR 279 / 1910-99 HARDENER

(continued of page 1)

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P302+P352 IF ON SKIN: Wash with plenty of water.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/ national/international regulations.

- · 2.3 Other hazards
- Results of PBT and vPvB assessment
- · PBT:

Not applicable.

vPvB:

Not applicable.

SECTION 03: Composition/information on ingredients

- · 3.2 Chemical characterization: Mixtures
- Description:

Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

 CAS Number
 %

 123-86-4
 n-butyl acetate
 40,00- 60,00

EC number: 204-658-1

🚸 Flam. Liq. 3 - H226; 🔱 STOT SE 3 -

H336

822-06-0 hexamethylene-di-isocyanate 0,00- 0,50

EC number: 212-485-8

Acute Tox. 1 - H330; Resp. Sens. 1 - H334; Acute Tox. 4 - H302, Skin Irrit. 2 - H315, Eye Irrit. 2 - H319, Skin

Sens. 1 - H317, STOT SE 3 - H335

28182-81-2 polyisocyanate aliphatic

EC number: 500-060-2

Acute Tox. 4 - H332, Skin Sens. 1 -

H317, STOT SE 3 - H335

SECTION 04: First aid measures

- 4.1 Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water.

After swallowing:

Do not induce vomiting; call for medical help immediately.

- Information for doctor:
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

GB

40,00-60,00



according to 1907/2006/EC, Article 31

2922717

Reviewed on: 28/06/2021 Printing date: 02/07/2021

PRODUCT: UNIPUR 279 / 1910-99 HARDENER

(continued of page 2)

SECTION 05: Firefighting measures

• 5.1 Extinguishing media

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents:

Water with full jet

5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

· Protective equipment:

Mouth respiratory protective device.

Do not inhale explosion gases or combustion gases.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 06: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 07: Handling and storage

- · Handling:
- 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Take note of emission threshold.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

• 7.3 Specific end use(s)

No further relevant information available.



according to 1907/2006/EC, Article 31

2922717

Reviewed on: 28/06/2021 Printing date: 02/07/2021

> PRODUCT: **UNIPUR 279 / 1910-99 HARDENER**

> > (continued of page 3)

SECTION 08: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-butyl acetate

WFI

Short-term value 966 mg/m3 200 maa 724 Long-term value mg/m3 150 ppm

822-06-0 hexamethylene-di-isocyanate

WEL

Short-term value 0.07 mg/m3 0.02 Long-term value mg/m3

Sen; as -NCO

Additional information:

The lists valid during the making were used as basis.

- 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Do not eat or drink while working.

Be sure to clean skin thoroughly after work and before breaks.

- Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Suitable respiratory protective device recommended.
- Protection of hands: The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Protective gloves Impervious gloves
- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

- Eye protection: Safety glasses Tightly sealed goggles
- Body protection: Protective work clothing

SECTION 09: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance Appearance:

Form: Liauid

Colour: Colourless, Yellowish Characteristic Characteristic Odour:

Not determined. Odour threshold:

Change in condition

130 °C Boiling point/Boiling range:

(continued on page 5)



according to 1907/2006/EC, Article 31

2922717

Reviewed on: 28/06/2021 Printing date: 02/07/2021

PRODUCT:	UNIPUR 279 /	1910-99 HARDENER
----------	---------------------	-------------------------

			(continu	ed of page 4)
Flash point:	27 °C c.c.			
Flammability (solid, gaseous):	Not applicable.			
Ignition temperature:	415 °C			
Decomposition temperature:	Not determined.			
Self-igniting:	Not determined.			
Danger of explosion:	Not determined.			
Explosion limits:				
Lower:	Not determined.			
Upper:	Not determined.			
Vapour pressure:	at 20 °C mbar	10,7000 mbar at	50 °C	55,0000
Density:	0,9900 g/cm3			
Solubility in / Miscibility with				
water:	Not determined.			
Viscosity:				
	at 23 °C	7 mPa.s		
	at 20 °C			
9.2 Other information	No further relevar	t information available.		

SECTION 10: Stability and reactivity

- 10.1 Reactivity
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions
- No dangerous reactions known.
- 10.4 Conditions to avoid
- No further relevant information available.
- 10.5 Incompatible materials:
 - No further relevant information available.
- 10.6 Hazardous decomposition products:
 - No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity:
- LD/LC50 values relevant for classification:

123-86-4 n-butyl acetate

Oral, LD50: 13100 mg/kg (rat) Dermal, LD50: >5000 mg/kg (Rabbit) Inhalative, LC50/4h: >21,0 mg/l (rat) Oral, LD50: 738 mg/kg (rat) Dermal, LD50: 593 mg/kg (rat)

822-06-0 hexamethylene-di-isocyanate

- Primary irritant effect:
- on the skin:
 - No irritant effect.
- on the eye:
 - No irritating effect.
- Sensitization:
- Sensitisation possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful Irritant

Irrita

₹ TEKNOS

according to 1907/2006/EC, Article 31

2922717

Reviewed on: 28/06/2021 Printing date: 02/07/2021

PRODUCT: UNIPUR 279 / 1910-99 HARDENER

(continued of page 5)

SECTION 12: Ecological information

- 12.1 Toxicity
- · Aquatic toxicity:

No further relevant information available.

12.2 Persistence and degradability

No further relevant information available.

- · Behaviour in environmental systems:
- · 12.3 Bioaccumulative potential
- No further relevant information available.
- 12.4 Mobility in soil

No further relevant information available.

- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

- · 12.5 Results of PBT and vPvB assessment
- DDT.

Not applicable.

- vPvB:
 - Not applicable.
- · 12.6 Other adverse effects

No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- European and swiss waste code

08

WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS

08 01

wastes from MFSU and removal of paint and varnish

08 01 11

waste paint and varnish containing organic solvents or other hazardous substances $% \left(1\right) =\left(1\right) +\left(1\right) +$

- · Uncleaned packaging:
- Recommendation:

Disposal must be made according to official regulations.

SECTION 14: Transport information

• 14.1 UN-Number

 ADR
 UN1263

 IMDG
 UN1263

 IATA
 UN1263

• 14.2 UN proper shipping name

ADR 1263 PAINT RELATED MATERIAL IMDG PAINT RELATED MATERIAL PAINT RELATED MATERIAL

· 14.3 Transport hazard class(es)

ADR

Class 3 Flammable liquids.

(continued on page 7)

GB



according to 1907/2006/EC, Article 31

2922717

Reviewed on: 28/06/2021 Printing date: 02/07/2021

> PRODUCT: **UNIPUR 279 / 1910-99 HARDENER**

> > (continued of page 6)

Label



IMDG

Class

3 Flammable liquids.

Label



IATA

Class

3 Flammable liquids.

Label



• 14.4 Packing group

ADR Ш **IMDG** Ш Ш IATA

• 14.5 Environmental hazards:

Not applicable.

· 14.6 Special precautions for user Warning: Flammable liquids. Danger code (Kemler):

EMS Number:

F-E,S-E

- 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.
- · Transport/Additional information:

Not applicable.

Excepted quantities (EQ): E1 Limited quantities (LQ) 5L Transport category 3 D/E **Tunnel restriction code**

IMDG

Limited quantities (LQ) 5L **Excepted quantities (EQ)** E1

• UN "Model Regulation":

UN 1263 PAINT RELATED MATERIAL, 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· National regulations:

(continued on page 8)



according to 1907/2006/EC, Article 31

2922717

Reviewed on: 28/06/2021 Printing date: 02/07/2021

PRODUCT: UNIPUR 279 / 1910-99 HARDENER

(continued of page 7)

· Classification according to VbF:

AII

• Technical instructions (air):

Class Share in %

III 55,00 I 0,20

· Waterhazard class:

Water hazard class 1 (Self-assessment): slightly hazardous for water.

· 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour. H302 Harmful if swallowed. H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H330 Fatal if inhaled.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

Department issuing MSDS:

Environment protection department.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VbF: Verordnung über brennbare Flüssigkeiten, Österreich (Ordinance on the storage of combustible liquids, Austria)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

* Data compared to the previous version altered.