

## SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830 - United Kingdom (UK)

# Centrecoat MMA FG Deck Coat Base

**Page** 1/8

Revision 1

Revision date 2019-10-29

1.1. Product identifier	
	0.44
Product name	Centrecoat MMA FG Deck Coat - Base
1.2. Relevant identified uses of t	the substance or mixture and uses advised against
Product Use	[SU3] Industrial uses: Uses of substances as such or in preparations at industrial sites; [PC9a] Coatings and paints, thinners, paint removers; [PROC10] Roller application or brushing;
	[SU22] Professional uses: Public domain (administration, education, entertainment, services, craftsmen);
1.3. Details of the supplier of the	safety data sheet
Company	Promain UK Limited
Address	C1 Pierson Court
	Knowl Piece, Hitchin
	Hertfordshire
	SG4 0TY
Web	www.promain.co.uk
Telephone	01462 421333
Fax	-
Email	info@promain.co.uk
Email address of the competent person	
1.4. Emergency telephone numb	per
Emergency telephone number	01462 421333
	8.30am - 5.30pm Mon - Thurs. 8.30am - 4.30pm Fri
SECTION 2: Hazards identifi	cation
2.1. Classification of the substan	nce or mixture

2.1.2. Classification - EC
1272/2008

Flam. Liq. 2: H225; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT SE 3: H335;

## 2.2. Label elements

#### Hazard pictograms





## Signal Word

**Hazard Statement** 

Danger

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

Revision 1
Revision date 2019-10-29

#### 2.2. Label elements

# Precautionary Statement: Prevention

STOT SE 3: H335 - May cause respiratory irritation.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground/bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting// equipment.

P242 - Use only non-sparking tools.

P243 - Take precautionary measures against static discharge.

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 - Wash thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

# Precautionary Statement: Response

P302+P352 - IF ON SKIN: Wash with plenty of water/.

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Kill Willi Walei/Silowei.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 - Call a POISON CENTER/doctor/ /if you feel unwell.

P321 - Specific treatment (see on this label).

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P370+P378 - In case of fire: Use to extinguish.

# Precautionary Statement: Storage

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

Precautionary Statement: Disposal

P501 - Dispose of contents/container to

#### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

#### EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification
Methyl methacrylate	607-035-00-6	80-62-6	201-297-1	01-2119452498-28		Flam. Liq. 2: H225; STOT SE
						3: H335; Skin Irrit. 2: H315;
						Skin Sens. 1: H317;
2-Ethylhexyl acrylate	607-107-00-7	103-11-7	203-080-7	01-2119453158-37		STOT SE 3: H335; Skin Irrit.
						2: H315; Skin Sens. 1: H317;
N,N-Dimethyl-p-toluidine	612-056-00-9	99-97-8	202-805-4			Acute Tox. 3: H331; Acute
						Tox. 3: H311; Acute Tox. 3:
						H301; STOT RE 2: H373;
						Aquatic Chronic 3: H412;
N,N-bis-(2-hydroxypropyl)		38668-48-3	254-075-1	01-2119980937-17		Acute Tox. 2: H300; Eye Irrit.
-p-toluidine						2: H319; Aquatic Chronic 3:
						H412;

## **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Remove contact
	lenses, if present and easy to do. Continue rinsing.
Skin contact	Wash off immediately with plenty of soap and water. Remove contaminated clothing.
Ingestion	DO NOT INDUCE VOMITING. Drink 1 to 2 glasses of water.

#### 4.2. Most important symptoms and effects, both acute and delayed

**Inhalation** Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system.

Revision 1
Revision date 2019-10-29

40 Martine at at a second	Revision date 2019-10-29
4.2. Most important symptoms	and effects, both acute and delayed
Eye contact	Irritating to eyes.
Skin contact	Irritating to skin.
Ingestion	Ingestion may cause nausea and vomiting.
4.3. Indication of any immediat	te medical attention and special treatment needed
Inhalation	Seek medical attention.
Eye contact	Seek medical attention if irritation or symptoms persist.
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	Seek medical attention.
SECTION 5: Firefighting m	easures
5.1. Extinguishing media	
	Carbon oxides. Dry chemical. Foam. Do NOT use water jet.
5.2. Special hazards arising fro	om the substance or mixture
<u> </u>	Highly flammable. Burning produces irritating, toxic and obnoxious fumes. Vapour may travel
	considerable distance to source of ignition and flash back.
5.3. Advice for firefighters	
	Self-contained breathing apparatus. Wear protective clothing.
SECTION 6: Accidental rele	ease measures
6.1. Personal precautions, pro-	tective equipment and emergency procedures
	Ensure adequate ventilation of the working area. Wear suitable protective equipment. Eliminate all sources of ignition. Evacuate personnel to a safe area. Wear suitable respiratory equipment when necessary.
6.2. Environmental precautions	\$
	Do not allow product to enter drains. Prevent further spillage if safe.
6.3. Methods and material for o	containment and cleaning up
	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water. Use explosion proof equipment.
6.4. Reference to other section	is .
	See section 8 for further information.
	See section 13 for further information.
SECTION 7: Handling and	storage
7.1. Precautions for safe hand	ling
	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking. Vapours are heavier than air.
7.2. Conditions for safe storage	e, including any incompatibilities
	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled
	containers. Store in original container.
7.3. Specific end use(s)	
	See section 1.2 for further information.
SECTION 8: Exposure con	trols/personal protection
8.1. Control parameters	
<u> </u>	
8.1.1. Exposure Limit Values	

Revision Revision date 2019-10-29

8.1.1. Exposure Limit Values

Methyl methacrylate WEL 8-hr limit ppm: 50 WEL 8-hr limit mg/m3: 208 WEL 15 min limit ppm: 100 WEL 15 min limit mg/m3: 416 WEL 8-hr limit mg/m3 total WEL 15 min limit mg/m3 total inhalable dust: inhalable dust: WEL 8-hr limit mg/m3 total WEL 15 min limit mg/m3 total respirable dust: respirable dust:

#### 8.2. Exposure controls



8.2.1. Appropriate engineering

controls

8.2.2. Individual protection measures

Eye / face protection

Skin protection -Handprotection

Skin protection - Other

Respiratory protection

Ensure adequate ventilation of the working area.

Wear chemical protective clothing.

Approved safety goggles.

Chemical resistant gloves (PVC). Butyl rubber gloves.

Wear suitable protective clothing

Wear suitable respiratory equipment when necessary.

## SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Colour

Appearance | Liquid

Various Odour Strong/Characteristic

Freezing Point -48 °C

Initial boiling point 100 °C Flash point 10 °C

Upper Explosive Limit | 12.5 % Lower Explosive Limit 2.1 %

Autoignition temperature 430 °C

> Viscosity 750 mPas (Cone & Plate)

Vapour pressure No data available Evaporation rate No data available

Flammability (solid, gas) No data available

Odour threshold No data available

> No data available pН Melting point No data available

Relative density No data available **Fat Solubility** No data available Partition coefficient No data available Oxidising properties No data available

Vapour density > 1 g/cm<sup>3</sup> **Explosive properties** Not applicable.

> Solubility Slightly soluble in water

### 9.2. Other information

Revision Revision date 2019-10-29

9.2. Other information

Benzene Content 0 % Lead content

VOC (Volatile organic

compounds) Conductivity

No data available Surface tension No data available No data available Gas group

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

See section 10.2 for further information.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Oxidising agents.

#### 10.4. Conditions to avoid

Heat, sparks and open flames.

#### 10.5. Incompatible materials

Alkalis. Oxidising agents. Peroxides. Reducing agents. Sulphur oxides.

#### 10.6. Hazardous decomposition products

Will not decompose if stored and used as recommended.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity	Oral Rat LD50 = >5,000mg/kg (Methyl Methacrylate).
Skin corrosion/irritation	Irritating to skin.
Serious eye damage/irritation	May cause irritation to eyes.
Respiratory or skin sensitisation	May cause sensitisation by skin contact.
Germ cell mutagenicity	No mutagenic effects reported.

Carcinogenicity

No carcinogenic effects reported.

Reproductive toxicity Aspiration hazard

No observed effect level. No teratogenic effects reported.

No Significant Hazard.

#### 11.1.4. Toxicological Information

2-Ethylhexyl acrylate	Oral Rat LD50: 4,435mg/kg	Dermal Rabbit LD50: >5,000mg/kg
Methyl methacrylate	Dermal Rat LD50: >5,000mg/kg	Oral Rat LD50: >2,000mg/kg
	Dermal Rabbit LD50: >5,000mg/kg	Inhalation Rat LC50/4 h: 29.8mg/kg
N,N-bis-(2-hydroxypropyl)	Oral Rat LD50: 172mg/kg	
-p-toluidine		

#### **SECTION 12: Ecological information**

#### 12.1. Toxicity

Methyl methacrylate Daphnia EC50/48h: 69.0000 mg/l Fish LC50/96h: 79.0000 mg/l

#### 12.2. Persistence and degradability

Readily biodegradable. OECD 301C, 14D.

Revision 1
Revision date 2019-10-29

	170 1011 date 2010 10 20
12.3. Bioaccumulative potential	
	No observed effect level.
Partition coefficient	
	Centrecoat MMA FG Deck Coat - Base No data available
12.4. Mobility in soil	
	Slightly soluble in water.
12.5. Results of PBT and vPvB	assessment
	PBT no. vPvB no.
12.6. Other adverse effects	
	No data is available on this product.
SECTION 13: Disposal cons	iderations
General information	
	08 01 11* waste paint and varnish containing organic solvents or other dangerous substances.
Dianagal mathada	1 00 0 1 11 waste paint and varnish containing organic solvents of other dangerous substances.
Disposal methods	
	The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable
	effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste
	disposal contractor. Disposal of this product, solutions and any by products should at all times
	comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. Waste packaging should be recycled if possible. Incineration should
	only be considered when recycling is not feasible. This material and its container must be disposed
	of in a safe way. Care should be taken when handling emptied containers that have not been
	cleaned. Empty containers or liners may still contain residue. Avoid dispersal of spilt material and runoff and contact sith soil, waterways, drains and sewers.
Disposal of packaging	Turion and contact sith son, waterways, drains and sewers.
Disposal of packaging	Residues and empty containers should be taken care of as hazardous waste according to local
	and national provisions.
SECTION 14: Transport info	rmation
Hazard pictograms	
	<b>A</b>
	3
14.1. UN number	<u> </u>
- Triti Ort Hambol	UN1866
14.2. UN proper shipping name	0111000
14.2. Old proper shipping hame	RESIN SOLUTION (contains Methyl Methacrylate)
14.3. Transport hazard class(es	
ADR/RID	
Subsidiary risk	] 3 ] _
IMDG	3
Subsidiary risk	1 -
IATA	3

Revision 1
Revision date 2019-10-29

14.3. Transport hazard class(es			
Subsidiary risk	-		
14.4. Packing group			
Packing group	П		
14.5. Environmental hazards			
Environmental hazards	No		
Marine pollutant	No		
14.6. Special precautions for us	14.6. Special precautions for user		
	Not applicable.		
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code			
	Not applicable.		
ADR/RID			
Hazard ID	33		
Tunnel Category	(D/E)		
IMDG			
EmS Code	F-E S-E		
IATA			
Packing Instruction (Cargo)	364		
Maximum quantity	60 L		
Packing Instruction (Passenger)	353		
Maximum quantity	5 L		
Further information			
	The product is not classified as dangerous for carriage.		

#### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

#### 15.2. Chemical safety assessment

This product contains substances for which Chemical Safety Assessments are still required.

#### SECTION 16: Other information

#### Other information

**Revision** This document differs from the previous version in the following areas:.

4 - Eye contact.

Revision 1
Revision date 2019-10-29

Other information Text of Hazard Statements in Flam. Lig. 2: H225 - Highly flammable liquid and vapour. Section 3 Skin Irrit. 2: H315 - Causes skin irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. STOT SE 3: H335 - May cause respiratory irritation. Acute Tox. 3: H301 - Toxic if swallowed. Acute Tox. 3: H311 - Toxic in contact with skin. Acute Tox. 3: H331 - Toxic if inhaled. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure. Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects. Acute Tox. 2: H300 - Fatal if swallowed. Eye Irrit. 2: H319 - Causes serious eye irritation. Maximum content of VOC 0 g/l. **Further information** The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.