

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830 - United Kingdom (UK)

Page: 1 Compilation date: 15/01/2015 Revision date: 12/03/2015 Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: Centrecoat Block Paving Sealer

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC9a: Coatings and paints, thinners, paint removers.

1.3. Details of the supplier of the safety data sheet

Company name: Promain UK Limited

Unit C1 Pierson Court, Knowl Piece, Hitchin,

Hertfordshire, SG4 0TY United Kingdom T 01462 421333

sales@promain.co.uk - www.promain.co.uk

Tel: 01462 421333

Email: info@promain.co.uk

1.4. Emergency telephone number

Emergency tel: 01462 421333

(08.30 to 16.30 Mon to Fri)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: Xi: R37; N: R51/53; -: R66; -: R67

Classification under CLP: STOT SE 3: H336; Aquatic Chronic 2: H411; STOT SE 3: H335

Most important adverse effects: Irritating to respiratory system. Toxic to aquatic organisms, may cause long-term

adverse effects in the aquatic environment. Repeated exposure may cause skin dryness

or cracking. Vapours may cause drowsiness and dizziness.

2.2. Label elements

Label elements under CLP:

Hazard statements: H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

Signal words: Warning



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830 - United Kingdom (UK)

Page: 2

Hazard pictograms: GHS07: Exclamation mark

GHS09: Environmental





Precautionary statements: P261: Avoid breathing vapours.

P271: Use only outdoors or in a well-ventilated area.

P273: Avoid release to the environment.

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P312: Call a POISON CENTRE or doctor if you feel unwell.

P391: Collect spillage.

Label elements under CHIP:

Hazard symbols: Irritant.

Dangerous for the environment.





Risk phrases: R37: Irritating to respiratory system.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Safety phrases: S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

HYDROCARBONS, C9, AROMATICS

EINECS	CAS	CHIP Classification	CLP Classification	Percent
-	918-688-5 Xi: R37; N: R51/53; Xn: R65; -: F		Flam. Liq. 3: H226; Aquatic Chronic 2:	70-90%
		R66; -: R67; -: R10	H411; Asp. Tox. 1: H304; STOT SE 3:	
			H336; STOT SE 3: H335	



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830 - United Kingdom (UK)

Page: 3

MESITYLENE

203-604-4	108-67-8	-: R10; Xi: R37; N: R51/53	Flam. Liq. 3: H226; STOT SE 3: H335; Aquatic Chronic 2: H411	10-30%
CUMENE				
202-704-5	98-82-8	-: R10; Xi: R37; N: R51/53; Xn: R65	Flam. Liq. 3: H226; Asp. Tox. 1: H304; STOT SE 3: H335; Aquatic Chronic 2: H411	<1%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove contaminated clothing and seek medical attention if irritation or symptoms

persist. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Seek medical attention if irritation or symptoms persist.

Inhalation: Inhalation may cause coughing, tightness of the chest and irritation of the respiratory

system. Move the exposed person to fresh air. Seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Irritating to eyes.

Eye contact: There may be irritation and redness.

Ingestion: No data available.
Inhalation: No data available.
Delayed / immediate effects: No data available.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Show this safety data sheet to the doctor in attendance.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Harmful.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear protective clothing to prevent contact with skin and eyes. Wear self-contained

breathing apparatus.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Wear suitable Personal Protective Equipment. Ensure adequate ventilation of working

area. Eliminate all sources of ignition. Evacuate personnel to a safe area.



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830 - United Kingdom (UK)

Page: 4

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a suitable container. Wash the ground with an appropriate self-emulsifying

solvent.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Keep away from sources of ignition - No Smoking.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Store in correctly labelled containers.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): PC9a: Coatings and paints, thinners, paint removers.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

MESITYLENE

Workplace exposure limits:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	25 ppm	-		-

Respirable dust

CUMENE

				1
UK	405/0	250/2		
ı un ı	125 mg/m3	250 mg/m3	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection not required.

Hand protection: Nitrile gloves. Protective gloves.Eye protection: Safety glasses. Safety goggles.

Skin protection: Protective clothing.

Environmental: An environmental assessment must be made to ensure compliance with local

environmental legislation.



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830 - United Kingdom (UK)

Page: 5

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Yellow-orange

Odour: Characteristic odour

Viscosity: Non-viscous

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: No data available.

10.6. Hazardous decomposition products

Haz. decomp. products: No data available.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

HYDROCARBONS, C9, AROMATICS

DERMAL	-	LD50	>3160	mg/kg
ORAL	RAT	LD50	3492	mg/kg

MESITYLENE

IPR	GPG	LDLO	1303	ma/ka



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830 - United Kingdom (UK)

Page: 6

CUMENE

ORL	MUS	LD50	12750	mg/kg
ORL	RAT	LD50	1400	mg/kg

Relevant effects for mixture:

Effect	Route	Basis
Irritation	INH	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Irritating to eyes.

Eye contact: There may be irritation and redness.

Ingestion: No data available.
Inhalation: No data available.
Delayed / immediate effects: No data available.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

Other information: Not applicable.

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: No data available.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Dispose of in compliance with all local and national regulations.

Recovery operations: Solvent reclamation/regeneration.

Disposal of packaging: Dispose of in compliance with all local and national regulations.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830 - United Kingdom (UK)

Page: 7

Section 14: Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

Shipping name: PAINT

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: Yes

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E
Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: The Chemicals (Hazard Information and Packaging) Regulations applied in the UK.

The COSHH Regulations applied in the UK.

The Health and Safety at Work Act applied in the UK

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830 - United Kingdom (UK)

Page: 8

R10: Flammable.

R37: Irritating to respiratory system.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Legend to abbreviations: PNEC = predicted no effect concentration

DNEL = derived no effect level

LD50 = median lethal dose

LC50 = median lethal concentration

EC50 = median effective concentration

IC50 = median inhibitory concentration

dw = dry weight

bw = body weight

cc = closed cup

oc = open cup

MUS = mouse

GPG = guinea pig

RBT = rabbit

HAM = hamster

HMN = human

MAM = mammal

PGN = pigeon

IVN = intravenous

SCU = subcutaneous

SKN = skin

DRM = dermal

OCC = ocular/corneal

OPT = optical

INH = inhalation

PCP = phycico-chemical properties

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.