



## SAFETY DATA SHEET

### ViterShield SPF

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

**Product name** ViterShield SPF

**Product number** 3403/-

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Paint.

##### 1.3. Details of the supplier of the safety data sheet

**Supplier** Axalta Coating Systems Huthwaite UK Ltd.  
Blackwell Road,  
Huthwaite,  
Notts. NG17 2RG  
UK  
+44 (0)1623 510585  
info-huthwaite@axalta.com

##### 1.4. Emergency telephone number

**Emergency telephone** +44 (0)1623 510585 (not 24 Hours)

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification (EC 1272/2008)

**Physical hazards** Flam. Liq. 3 - H226

**Health hazards** Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Muta. 2 - H341 STOT RE 2 - H373  
Asp. Tox. 1 - H304

**Environmental hazards** Aquatic Chronic 2 - H411

##### 2.2. Label elements

###### Hazard pictograms



###### Signal word

Danger

###### Hazard statements

H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H317 May cause an allergic skin reaction.  
H341 Suspected of causing genetic defects.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H304 May be fatal if swallowed and enters airways.  
H411 Toxic to aquatic life with long lasting effects.

## ViterShield SPF

### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P243 Take action to prevent static discharges.

P261 Avoid breathing vapour/ spray.

P264 Wash contaminated skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321 Specific treatment (see medical advice on this label).

P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337+P313 If eye irritation persists: Get medical advice/ attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.

P391 Collect spillage.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/ container in accordance with national regulations.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

### Contains

Phenol, 4,4'-(1-methylethylidene)bis-,polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane], xylene

### 2.3. Other hazards

#### SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

Phenol, 4,4'-(1-methylethylidene)bis-,polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane] CAS number: 25036-25-3	10-30%
<b>Classification</b> Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317	

## ViterShield SPF

xylene			10-30%
CAS number: 1330-20-7	EC number: 215-535-7	REACH registration number: 01-2119488216-32-XXXX	
<b>Classification</b> Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335 STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic Chronic 3 - H412			
1-methoxy-2-propanol			5-10%
CAS number: 107-98-2	EC number: 203-539-1	REACH registration number: 01-2119457435-35-XXXX	
<b>Classification</b> Flam. Liq. 3 - H226 STOT SE 3 - H336			
trizinc bis(orthophosphate)			5-10%
CAS number: 7779-90-0	EC number: 231-944-3	REACH registration number: 01-2119485044-40-XXXX	
M factor (Acute) = 1	M factor (Chronic) = 1		
<b>Classification</b> Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410			
butan-1-ol			1-5%
CAS number: 71-36-3	EC number: 200-751-6	REACH registration number: 01-2119484630-38-XXXX	
<b>Classification</b> Flam. Liq. 3 - H226 Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT SE 3 - H335, H336			
Urea P/W formaldehyde, isobutylated			1-5%
CAS number: 68002-18-6			
<b>Classification</b> Aquatic Chronic 4 - H413			

## ViterShield SPF

<b>zinc oxide</b> <span style="float: right;"><b>&lt;1%</b></span>		
CAS number: 1314-13-2	EC number: 215-222-5	REACH registration number: 01-2119463881-32-XXXX
M factor (Acute) = 1	M factor (Chronic) = 1	
<b>Classification</b> Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410		

  

<b>formaldehyde</b> <span style="float: right;"><b>&lt;1%</b></span>		
CAS number: 50-00-0	EC number: 200-001-8	REACH registration number: 01-2119488953-20-XXXX
<b>Classification</b> Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 2 - H330 Skin Corr. 1B - H314 Skin Sens. 1A - H317 Muta. 2 - H341 Carc. 1B - H350 STOT SE 3 - H335		

  

<b>ethylbenzene</b> <span style="float: right;"><b>&lt;1%</b></span>		
CAS number: 100-41-4	EC number: 202-849-4	REACH registration number: 01-2119489370-35-XXXX
<b>Classification</b> Flam. Liq. 2 - H225 Acute Tox. 4 - H332 Eye Irrit. 2 - H319 STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic Chronic 3 - H412		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>General information</b>	If in doubt, get medical attention promptly. Never give anything by mouth to an unconscious person. Place unconscious person on their side in the recovery position and ensure breathing can take place.
<b>Inhalation</b>	Move affected person to fresh air at once. Keep affected person warm and at rest. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. If breathing stops, provide artificial respiration.
<b>Ingestion</b>	Get medical attention immediately. Keep affected person warm and at rest. Do not induce vomiting.
<b>Skin contact</b>	Remove contaminated clothing immediately and wash skin with soap and water. Do not use organic solvents.

## ViterShield SPF

<b>Eye contact</b>	Remove any contact lenses and open eyelids wide apart. Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes and get medical attention.
<b>Protection of first aiders</b>	No action shall be taken without appropriate training or involving any personal risk. First aid personnel should wear appropriate protective equipment during any rescue. It may be dangerous for first aid personnel to carry out mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it from the affected person, or wear gloves.

### 4.2. Most important symptoms and effects, both acute and delayed

<b>Inhalation</b>	Gas or vapour may irritate the respiratory system. Prolonged or repeated exposure may cause the following adverse effects: Coughing. May cause nausea, headache, dizziness and intoxication.
<b>Ingestion</b>	May cause chemical burns in mouth, oesophagus and stomach. May cause stomach pain or vomiting.
<b>Skin contact</b>	Causes skin irritation.
<b>Eye contact</b>	Causes serious eye damage. Prolonged or repeated exposure may cause the following adverse effects: Pain or irritation. Profuse watering of the eyes. Redness.

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	Development of symptoms may be delayed for 24 to 48 hours.
<b>Specific treatments</b>	No specific chemical antidote is known to be required after exposure to this product.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

<b>Suitable extinguishing media</b>	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2. Special hazards arising from the substance or mixture

<b>Specific hazards</b>	Flammable liquid and vapour. Containers can burst violently or explode when heated, due to excessive pressure build-up. Fire-water run-off in sewers may create fire or explosion hazard.
<b>Hazardous combustion products</b>	Thermal decomposition or combustion products may include the following substances: Carbon dioxide (CO <sub>2</sub> ). Carbon monoxide (CO). Acrid smoke or fumes. Oxides of nitrogen. Oxides of phosphorus. Halogenated hydrocarbons.

### 5.3. Advice for firefighters

<b>Protective actions during firefighting</b>	In case of fire: Evacuate area. No action shall be taken without appropriate training or involving any personal risk. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.
<b>Special protective equipment for firefighters</b>	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

## ViterShield SPF

**For non-emergency personnel** No action shall be taken without appropriate training or involving any personal risk. Evacuate area. Keep unnecessary and unprotected personnel away from the spillage. Do not touch or walk into spilled material. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Do not breathe gas, fume, vapours or spray. Provide adequate ventilation. If ventilation is inadequate, suitable respiratory protection must be worn. Use protective equipment appropriate for surrounding materials.

**For emergency responders** Wear protective clothing as described in Section 8 of this safety data sheet.

### 6.2. Environmental precautions

**Environmental precautions** Avoid the spillage or runoff entering drains, sewers or watercourses. Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air). Contain spillage with sand, earth or other suitable non-combustible material.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Small Spillages: Stop leak if safe to do so. Move containers from spillage area. Absorb spillage with non-combustible, absorbent material. Place waste in labelled, sealed containers. Large Spillages: Stop leak if safe to do so. Move containers from spillage area. Approach the spillage from upwind. No smoking, sparks, flames or other sources of ignition near spillage. Avoid the spillage or runoff entering drains, sewers or watercourses. Dispose of waste via a licensed waste disposal contractor. The contaminated absorbent may pose the same hazard as the spilled material.

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. For waste disposal, see Section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Note:** The information in this section contains generic advice and guidance.

**Usage precautions** For professional users only. Eliminate all sources of ignition. Use only in well-ventilated areas. Wear protective clothing as described in Section 8 of this safety data sheet. Earth container and transfer equipment to eliminate sparks from static electricity. For the greatest protection, clothing should include anti-static overalls, boots and gloves. Use only non-sparking tools. Keep away from heat, sparks and open flame. Avoid inhalation of vapours/spray and contact with skin and eyes. Inhalation of dust during cutting, grinding or sanding operations involving this product may cause irritation of the respiratory tract.

**Advice on general occupational hygiene** In confined or poorly-ventilated spaces, a supplied-air respirator must be worn. Do not eat, drink or smoke when using this product. Good personal hygiene procedures should be implemented. Wash hands thoroughly after handling. Take off contaminated clothing and wash it before reuse. Remove contaminated clothing and protective equipment before entering eating areas. Change work clothing daily before leaving workplace.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Store in accordance with local regulations. Store at temperatures between 5°C and 25°C. Store in tightly-closed, original container. Avoid contact with oxidising agents. Avoid contact with acids and alkalis. Read label before use. Avoid exposure to high temperatures or direct sunlight. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly sealed when not in use.

**Storage class** Flammable liquid storage.

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## ViterShield SPF

### SECTION 8: Exposure controls/Personal protection

#### 8.1. Control parameters

##### Occupational exposure limits

##### **xylene**

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m<sup>3</sup>

Sk

##### **1-methoxy-2-propanol**

Long-term exposure limit (8-hour TWA): WEL 100 ppm 375 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 150 ppm 560 mg/m<sup>3</sup>

Sk

##### **butan-1-ol**

Short-term exposure limit (15-minute): WEL 50 ppm 154 mg/m<sup>3</sup>

Sk

##### **formaldehyde**

Long-term exposure limit (8-hour TWA): WEL 2 ppm 2.5 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 2 ppm 2.5 mg/m<sup>3</sup>

##### **ethylbenzene**

Long-term exposure limit (8-hour TWA): WEL 100 ppm 441 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 125 ppm 552 mg/m<sup>3</sup>

Sk

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through the skin.

#### **xylene (CAS: 1330-20-7)**

##### **DNEL**

Workers - Inhalation; Long term systemic effects: 77 mg/m<sup>3</sup>

Workers - Inhalation; Short term systemic effects: 289 mg/m<sup>3</sup>

Workers - Inhalation; Short term local effects: 289 mg/m<sup>3</sup>

##### **PNEC**

- Fresh water; 0.327 mg/l

- marine water; 0.327 mg/l

- Intermittent release; 0.327 mg/l

- STP; 6.58 mg/l

- Sediment (Freshwater); 12.46 mg/kg

- Sediment (Marinewater); 12.46 mg/kg

- Soil; 2.31 mg/kg

#### **1-methoxy-2-propanol (CAS: 107-98-2)**

##### **DNEL**

Industry - Inhalation; : 553.5 mg/m<sup>3</sup>

Industry - Inhalation; Long term : 369 mg/m<sup>3</sup>

Industry - Dermal; Long term : 50.6 mg/kg/day

##### **PNEC**

- Fresh water; 10 mg/l

- marine water; 1 mg/l

- STP; 100 mg/l

- Sediment (Freshwater); 41.6 mg/kg

- Sediment (Marinewater); 4.17 mg/kg

- Soil; 2.47 mg/kg

#### **trizinc bis(orthophosphate) (CAS: 7779-90-0)**

## ViterShield SPF

**DNEL** Workers - Inhalation; Long term systemic effects: 5 mg/m<sup>3</sup>  
Workers - Dermal; Long term systemic effects: 83 mg/kg/day

**PNEC**

- Fresh water; 20.6 µg/l
- marine water; 6.1 µg/l
- STP; 52 µg/l
- Sediment (Freshwater); 117.8 mg/kg dwt
- Sediment (Marinewater); 56.5 mg/kg dwt
- Soil; 35.6 mg/kg dwt

### butan-1-ol (CAS: 71-36-3)

**DNEL** Industry - Inhalation; : 310 mg/m<sup>3</sup>  
Industry - Inhalation; : 100 ppm

**PNEC**

- Fresh water; 0.082 mg/l
- marine water; 0.0082 mg/l
- Sediment (Freshwater); 0.178 mg/kg
- Sediment (Marinewater); .0178 mg/kg
- Soil; 0.015 mg/kg

### zinc oxide (CAS: 1314-13-2)

**DNEL** Workers - Inhalation; Long term systemic effects: 5 mg/m<sup>3</sup>  
Workers - Dermal; Long term systemic effects: 87 mg/kg/day

**PNEC**

- Fresh water; 20.6 µg/l
- marine water; 6.1 µg/l
- Sediment (Freshwater); 117 mg/kg dwt
- Sediment (Marinewater); 56.5 mg/kg dwt
- STP; 52 µg/l
- Soil; 35.6 mg/kg dwt

### formaldehyde (CAS: 50-00-0)

**DNEL** Workers - Inhalation; Short term local effects: 0.8 mg/kg  
Workers - Dermal; Long term systemic effects: 240 mg/kg/day  
Workers - Inhalation; Long term systemic effects: 9 mg/m<sup>3</sup>  
Workers - Dermal; Long term local effects: 0.037 mg/cm<sup>2</sup>  
Workers - Inhalation; Long term local effects: 0.4 mg/kg

**PNEC**

- Fresh water; 0.47 mg/l
- marine water; 0.47 mg/l
- Sediment (Freshwater); 2.44 mg/kg
- Sediment (Marinewater); 2.44 mg/kg
- Soil; 0.21 mg/kg
- STP; 0.19 mg/l
- Intermittent release; 4.7 mg/l

### ethylbenzene (CAS: 100-41-4)

**DNEL** Workers - Inhalation; Long term systemic effects: 77 mg/m<sup>3</sup>  
Workers - Inhalation; Short term local effects: 293 mg/m<sup>3</sup>  
Workers - Dermal; Long term systemic effects: 180 mg/kg/day

## 8.2. Exposure controls



## ViterShield SPF

### Protective equipment



### Appropriate engineering controls

As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapour or mist. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilating equipment.

### Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Chemical splash goggles or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

### Hand protection

To protect hands from chemicals, gloves should comply with European Standard EN374. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. The selected gloves should have a breakthrough time of at least 4-8 hours.

### Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Wear suitable protective equipment for prolonged exposure and/or high concentrations of vapours, spray or mist. For the greatest protection, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for information on material and design requirements and test methods.

### Hygiene measures

Good personal hygiene procedures should be implemented. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Care should be taken to avoid contact with contaminants when removing contaminated clothing. Remove contaminated clothing and protective equipment before entering eating areas. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke. Eye wash facilities and emergency shower must be available when handling this product.

### Respiratory protection

Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator. When spraying, wear a respirator fitted with the following cartridge: Combination filter, type A2/P2. In confined or poorly-ventilated spaces, a supplied-air respirator must be worn.

### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. Keep container tightly sealed when not in use. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Various colours.
Odour	Characteristic.

## ViterShield SPF

Flash point	21-32°C
Vapour density	Heavier than air.
Relative density	1.70-1.75
Solubility(ies)	Immiscible with water.

### 9.2. Other information

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reactivity	No test data specifically related to reactivity available for this product or its ingredients.
------------	--

### 10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
-----------	---

### 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Under normal conditions of storage and use, no hazardous reactions will occur.
------------------------------------	--

### 10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition. Do not pressurise, cut, weld, drill, grind or otherwise expose containers to heat or sources of ignition. Avoid the accumulation of vapours in low or confined areas.
---------------------	---

### 10.5. Incompatible materials

Materials to avoid	Avoid contact with the following materials: Oxidising agents.
--------------------	---

### 10.6. Hazardous decomposition products

Hazardous decomposition products	Does not decompose when used and stored as recommended.
----------------------------------	---

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity - oral

ATE oral (mg/kg)	96,270.02
------------------	-----------

#### Acute toxicity - dermal

ATE dermal (mg/kg)	7,990.27
--------------------	----------

#### Acute toxicity - inhalation

ATE inhalation (vapours mg/l)	79.9
-------------------------------	------

## SECTION 12: Ecological information

### 12.1. Toxicity

### 12.2. Persistence and degradability

### 12.3. Bioaccumulative potential

### 12.4. Mobility in soil

### 12.5. Results of PBT and vPvB assessment

### 12.6. Other adverse effects

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

## ViterShield SPF

<b>General information</b>	Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements.
<b>Disposal methods</b>	Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. Do not empty into drains.
<b>Waste class</b>	08 01 11 Waste paint and varnish containing organic solvents or other dangerous substances If this product is mixed with other wastes, this code may no longer apply. If mixed with other wastes, the appropriate code should be assigned. For further information, contact your local waste authority.

### SECTION 14: Transport information

#### 14.1. UN number

UN No. (ADR/RID)	1263
UN No. (IMDG)	1263
UN No. (ICAO)	1263
UN No. (ADN)	1263

#### 14.2. UN proper shipping name

Proper shipping name (ADR/RID)	PAINT
Proper shipping name (IMDG)	PAINT
Proper shipping name (ICAO)	PAINT
Proper shipping name (ADN)	PAINT

#### 14.3. Transport hazard class(es)

ADR/RID class	3
ADR/RID classification code	F1
ADR/RID label	3
IMDG class	3
ICAO class/division	3
ADN class	3

#### Transport labels



#### 14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ICAO packing group	III
ADN packing group	III

#### 14.5. Environmental hazards

## ViterShield SPF

Environmentally hazardous substance/marine pollutant



### 14.6. Special precautions for user

EmS	F-E, S-E
ADR transport category	3
Emergency Action Code	•3YE
Hazard Identification Number (ADR/RID)	33
Tunnel restriction code	(D/E)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

#### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Health and environmental listings	None of the ingredients are listed.
Authorisations (Annex XIV Regulation 1907/2006)	No specific authorisations are known for this product.
Restrictions (Annex XVII Regulation 1907/2006)	No specific restrictions on use are known for this product.

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

#### SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet	ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement PNEC = Predicted No Effect Concentration RRN = REACH Registration Number
Revision date	10/08/2022
Revision	8
Supersedes date	17/10/2019
SDS number	5104

## ViterShield SPF

<b>Hazard statements in full</b>	<p>H225 Highly flammable liquid and vapour.</p> <p>H226 Flammable liquid and vapour.</p> <p>H301 Toxic if swallowed.</p> <p>H302 Harmful if swallowed.</p> <p>H304 May be fatal if swallowed and enters airways.</p> <p>H311 Toxic in contact with skin.</p> <p>H312 Harmful in contact with skin.</p> <p>H314 Causes severe skin burns and eye damage.</p> <p>H315 Causes skin irritation.</p> <p>H317 May cause an allergic skin reaction.</p> <p>H318 Causes serious eye damage.</p> <p>H319 Causes serious eye irritation.</p> <p>H330 Fatal if inhaled.</p> <p>H332 Harmful if inhaled.</p> <p>H335 May cause respiratory irritation.</p> <p>H336 May cause drowsiness or dizziness.</p> <p>H341 Suspected of causing genetic defects.</p> <p>H350 May cause cancer.</p> <p>H373 May cause damage to organs through prolonged or repeated exposure.</p> <p>H373 May cause damage to organs (Hearing organs) through prolonged or repeated exposure.</p> <p>H400 Very toxic to aquatic life.</p> <p>H410 Very toxic to aquatic life with long lasting effects.</p> <p>H411 Toxic to aquatic life with long lasting effects.</p> <p>H412 Harmful to aquatic life with long lasting effects.</p> <p>H413 May cause long lasting harmful effects to aquatic life.</p>
<b>Description</b>	Two Pack Epoxy Zinc Phosphate Primer-Finish
<b>Component</b>	Base
<b>Mix Ratio</b>	Mix 3:1 by volume with Activator
<b>Shelf life</b>	2 year
<b>EU Dir 1</b>	2004/42/11A(j)(500g/l2010)384g/l
<b>EU Dir 2</b>	

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.