SAFETY DATA SHEET



Murfill Waterproofing Coating

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name : Murfill Waterproofing Co	ating
Product description : Paint	
Product type : Liquid.	
UFI : PUE1-A0U8-900Q-4G8I	1

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
Consumer use Industrial use Professional use	
Uses advised against	Reason
None identified.	-

1.3 Details of the supplier of the safety data sheet

RUST-OLEUM EUROPE Martin Mathys NV, Kolenbergstraat 23, B-3545 Zelem, Belgium Telephone no.: +32 (0) 13 460 200 Fax no.: +32 (0) 13 460 201

Tor Coatings Limited Unit 21, White Rose Way, Follingsby Park, Gateshead, Tyne & Wear, NE10 8YX United Kingdom Telephone no.: +44 (0) 191 4106611 Fax no.: +44 (0) 191 4920125 enquiries@tor-coatings.com

e-mail address of person : rpmeurohas@rustoleum.eu responsible for this SDS

1.4 Emergency telephone number

National advisory body/Poison CentreSupplierTelephone number: +44 870 8200418 / +44 2038073798Hours of operation: 24 / 7

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Sens. 1, H317 Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

Date of issue/Date of revision : 30/11/2021 Date of previous issue : 30/11/2021

SECTION 2: Hazards identification

2.2 Label elements		
Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	1	May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.
Precautionary statements		
General	-	P103 - Read carefully and follow all instructions. P102 - Keep out of reach of children. P101 - If medical advice is needed, have product container or label at hand.
Prevention	1	P280 - Wear protective gloves.
Response	1	Not applicable.
Storage	1	Not applicable.
Disposal	1	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazardous ingredients	:	Poly[oxy(methyl-1,2-ethanediyl)],α-(methylphenyl)-ω-hydroxy- Octene, hydroformylation products, high-boiling 1,2-benzisothiazol-3(2H)-one 2-octyl-2H-isothiazol-3-one reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)
Supplemental label elements	1	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Supplemental label elements : Detergents - Regulation (EC) No 907/2006	:	Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Special packaging requirem	en	<u>ts</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do : None known. not result in classification

Murfill Waterproofing Coating

SECTION 3: Composition/information on ingredients

3.2 Mixtures

: Mixture

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Туре
barium diboron tetraoxide	REACH #: 01-2119983530-36 EC: 237-222-4	≤3	Acute Tox. 4, H302 Repr. 1B, H360F	[1] [2]
Poly[oxy(methyl-1,2-ethanediyl)],α-(methylphenyl)-ω-hydroxy-	CAS: 13701-59-2 REACH #: 02-2119549982-25 EC: 618-605-9 CAS: 9064-13-5	≤1	Skin Sens. 1B, H317	[1]
Octene, hydroformylation products, high-boiling	REACH #: 01-2119486463-31 EC: 271-237-7 CAS: 68526-89-6	≤0,3	Skin Sens. 1B, H317	[1]
2-octyl-2H-isothiazol-3-one	EC: 247-761-7 CAS: 26530-20-1 Index: 613-112-00-5	≤0,3	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330	[1]
1,2-benzisothiazol-3(2H)-one	REACH #: 01-2120761540-60 EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	≤0,1	Acute Tox. 2, H330 Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411	[1]
2-octyl-2H-isothiazol-3-one	REACH #: 17-2119390467-28 EC: 247-761-7 CAS: 26530-20-1 Index: 613-112-00-5	≤0,1	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 2, H330 Skin Corr. 1, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1,	[1]
pyrithione zinc	REACH #: 01-2119511196-46 EC: 236-671-3 CAS: 13463-41-7	≤0,1	H410 (M=100) Acute Tox. 3, H301 Acute Tox. 2, H330 Eye Dam. 1, H318 Repr. 1B, H360D STOT RE 1, H372 Aquatic Acute 1, H400 (M=1000) Aquatic Chronic 1, H410 (M=10)	[1]
terbutryn	EC: 212-950-5 CAS: 886-50-0	≤0,1	Acute Tox. 4, H302 Skin Sens. 1B, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100)	[1]
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H- isothiazol-3-one [EC no. 220-239-6] (3:1)	REACH #: 01-2120764691-48 EC: 611-341-5 CAS: 55965-84-9 Index: 613-167-00-5	≤0,1	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317	[1]

Murfill Waterproofing Coating

SECTION 3: Composition/information on ingredients	
	Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100)
	See Section 16 for the full text of the H statements declared above.

<u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

[6] Additional disclosure due to company policy

This mixture contains \geq 1% of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

SCL (Specific Concentration Limits)	
1,2-benzisothiazol-3(2H)-one	H317 = 0.05 %
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	H317 = 0.0015 %
2-octyl-2H-isothiazol-3-one	H317 = 0.0015 %
ATE (acute toxicity estimates)	
2-octyl-2H-isothiazol-3-one	H330: ATE= 0,27 mg/L (dusts/mists) H311: ATE= 311 mg/kg H301: ATE= 125 mg/kg
Nanoform	

Particle characteristics	Particle Size	
This product does not contains nanomaterials.	Not applicable.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact
- : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

Murfill Waterproofing Coating

SECTION 4: First aid measures

Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No specific data.
4.3 Indication of any imm	ediate medical attention and special treatment needed
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large

	quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.

5.2 Special hazards arising from the substance or mixture

Hazards from the : substance or mixture	In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated
	with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

SECTION 5: Firefighting measures

Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide sulfur oxides metal oxide/oxides
5.3 Advice for firefighters	
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.
Additional information	: No unusual hazard if involved in a fire.

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	tec	tive equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store between the following temperatures: 4 to 26°C (39,2 to 78,8°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s) Recommendations

: Not available.

Industrial sector specific : No solutions

: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

United Kingdom: Great Britain

Product/ingredier	nt name	Exposure limit values
barium diboron tetraoxide		EH40/2005 WELs (United Kingdom (UK), 12/2011). Notes: as Ba TWA: 0,5 mg/m ³ , (as Ba) 8 hours.
Recommended monitoring procedures	atmosphere or h of the ventilation protective equip the following: E the assessment limit values and atmospheres - (exposure to che (Workplace atm for the measure	ontains ingredients with exposure limits, personal, workplace biological monitoring may be required to determine the effectiveness of or other control measures and/or the necessity to use respiratory ment. Reference should be made to monitoring standards, such as uropean Standard EN 689 (Workplace atmospheres - Guidance for of exposure by inhalation to chemical agents for comparison with measurement strategy) European Standard EN 14042 (Workplace Guide for the application and use of procedures for the assessment of mical and biological agents) European Standard EN 482 hospheres - General requirements for the performance of procedures ment of chemical agents) Reference to national guidance methods for the determination of hazardous substances will also be
DNELs/DMELs		

Murfill Waterproofing Coating

SECTION 8: Exposure controls/personal protection

Product/ingredient name	Туре	Exposure	Value	Population	Effects
Octene, hydroformylation products, high-boiling	DNEL	Long term Oral	25 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	50 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	87 mg/m³	General population	Systemic
	DNEL	Long term Dermal	116,7 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	411,4 mg/ m ³	Workers	Systemic

PNECs

No PNECs available

8.2 Exposure controls

Appropriate engineering controls	:	Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
Individual protection measure	<u>es</u>	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	-	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. Use eye protection according to EN 166. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): nitrile rubber (0.5mm).

The recommendation for the type or types of glove to use when handling this product is based on information from the following source: EN374. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

SECTION 8: Exposure controls/personal protection

Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Wear overalls or long sleeved shirt. (EN 467)
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: In case of insufficient ventilation, wear suitable respiratory equipment. organic vapour filter (Type A) (EN 140)
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Physical state	iquid. [Viscous liquid.]	
Colour	eige. Black. Blue. Brown. Grey. Green. Orange. Pink Purple. Red. White ellow. [Light]	Э.
Odour	aint odour.	
Odour threshold	ot available.	
Melting point/freezing point	°C [Literature]	
Initial boiling point and boiling range	100°C (>212°F) [Literature]	
Flammability (solid, gas)	on-flammable in the presence of the following materials or conditions: c ames, sparks and static discharge, heat and shocks and mechanical im onflammable, but will burn on prolonged exposure to flame or high tem	pacts.
Upper/lower flammability or explosive limits	ot available.	
Flash point	losed cup: >100°C (>212°F) [Literature] [Product does not sustain comb	oustion.]
Auto-ignition temperature	ot relevant due to nature of the product.	
Decomposition temperature	ot available.	
рН	to 9 [OECD 122]	
pH : Justification	ot available.	
Viscosity	ynamic: 18000 to 26000 mPa·s [ISO EN BS DIN 3219]	
Solubility(ies)	oluble in the following materials: cold water and hot water. ery slightly soluble in the following materials: methanol and acetone.	
Solubility in water	lot available.	
Partition coefficient: n-octanol/ water	ot applicable.	
Vapour pressure	,3 kPa (17,25 mm Hg) [Literature]	
Evaporation rate	1 (butyl acetate = 1)	
Relative density	,32 to 1,37 [DIN 53217]	
Density	,32 to 1,37 g/cm³ [20°C (68°F)] [DIN 53217]	
Vapour density	1 [Air = 1]	

Murfill Waterproofing Coating

SECTION 9: Physical and chemical properties

Explosive properties	:	Non-explosive in the presence of the following materials or conditions: open
		flames, sparks and static discharge and heat. No unusual hazard if involved in a fire.
Oxidising properties	4	Not available.
Particle characteristics		
Median particle size	1	Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.	
10.2 Chemical stability	: The product is stable.	
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.	
10.4 Conditions to avoid	: No specific data.	
10.5 Incompatible materials	: No specific data.	
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.	

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
barium diboron tetraoxide	LC50 Inhalation Dusts and mists	Rat	3,54 mg/l	4 hours
	LD50 Oral	Rat - Female	530 mg/kg	-
	LD50 Oral	Rat - Male	850 mg/kg	-
Poly[oxy(methyl-1,2-ethanediyl)],α-(methylphenyl)-ω-hydroxy-	LD50 Oral	Rat	6000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
2-octyl-2H-isothiazol-3-one	LC50 Inhalation Dusts and mists	Rat	0,27 mg/l	4 hours
	LD50 Dermal	Rabbit	311 mg/kg	-
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	248 mg/kg	-
1,2-benzisothiazol-3(2H)- one	LC50 Inhalation Dusts and mists	Rat	0,11 mg/l	4 hours
	LC50 Inhalation Dusts and mists	Rat - Male, Female	0,5 mg/l	4 hours
	LD50 Oral	Rat - Male	490 mg/kg	-
2-octyl-2H-isothiazol-3-one	LC50 Inhalation Dusts and mists	Rat	0,27 mg/l	4 hours
5	LD50 Oral	Rat	248 mg/kg	-
pyrithione zinc	LC50 Inhalation Dusts and mists	Rat	140 mg/m ³	4 hours
	LD50 Dermal	Rabbit	100 mg/kg	-
	LD50 Oral	Rat	177 mg/kg	-
terbutryn	LC50 Inhalation Dusts and mists	Rat	>2200 mg/l	4 hours
	LD50 Dermal	Rabbit	>10200 mg/kg	-
	LD50 Oral	Rat	2045 mg/kg	-
reaction mass of: 5-chloro-	LC50 Inhalation Dusts and mists	Rat - Male,	0,171 mg/l	4 hours
2-methyl-4-isothiazolin-		Female	_	
3-one [EC no. 247-500-7]				
and 2-methyl-2H-isothiazol-				
3-one [EC no. 220-239-6] (3:				

Murfill Waterproofing Coating

SECTION 11: Toxicological information							
1)	LD50 Dermal LD50 Oral	Rabbit Rat	92,4 mg/kg 64 mg/kg	-			

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
barium diboron tetraoxide	530	N/A	N/A	N/A	N/A
$Poly[oxy(methyl-1,2-ethanediyl)], \alpha-(methylphenyl)-\omega-hydroxy-$	6000	N/A	N/A	N/A	N/A
2-octyl-2H-isothiazol-3-one	125	311	N/A	N/A	0,27
1,2-benzisothiazol-3(2H)-one	490	N/A	N/A	0,5	N/A
2-octyl-2H-isothiazol-3-one	125	311	N/A	N/A	0,27
pyrithione zinc	221	N/A	N/A	N/A	0,14
terbutryn	500	N/A	N/A	N/A	N/A
reaction mass of: 5-chloro-2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H- isothiazol-3-one [EC no. 220-239-6] (3:1)	64	92,4	N/A	N/A	0,171

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-octyl-2H-isothiazol-3-one	Eyes - Severe irritant	Rabbit	-	-	-
terbutryn	Eyes - Moderate irritant	Rabbit	-	76 milligrams	-
	Skin - Mild irritant	Rabbit	-	380 milligrams	-
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	Skin - Severe irritant	Human	-	0.01 Percent	-
,	Skin - Severe irritant	Rabbit	-	-	1 to 4 hours
	Eyes - Severe irritant	Rabbit	-	-	-

Conclusion/Summary

Skin Eyes : Based on available data, the classification criteria are not met.

: Based on available data, the classification criteria are not met.

Respiratory

: Based on available data, the classification criteria are not met.

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
Poly[oxy(methyl-1,2-ethanediyl)],α-(methylphenyl)-ω-hydroxy-	skin	Mouse	Sensitising
1,2-benzisothiazol-3(2H)-one 2-octyl-2H-isothiazol-3-one reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	skin skin skin	Guinea pig Rat Guinea pig	Sensitising Sensitising Sensitising
Conclusion/Summary Skin		allergic skin reaction.	

Respiratory

- : Based on available data, the classification criteria are not met.

Date of issue/Date of revision

: 30/11/2021

Murfill Waterproofing Coating

SECTION 11: Toxicological information

Mutagenicity

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Carcinogenicity

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.

Conclusion/Summary	:	Based on available data, the classification criteria are not met.
Reproductive toxicity		
Conclusion/Summary	:	Based on available data, the classification criteria are not met.
Teratogenicity		
Conclusion/Summary	÷	Based on available data, the classification criteria are not met.
• • • • • • • • • • • • • • • • • • •		· · · · · · · · · · · · · · · · · · ·

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
pyrithione zinc	Category 1	-	-

Aspiration hazard

Not available.

Information on likely routes of exposure	:	Routes of entry anticipated: Routes of entry not anticipate					
Potential acute health effects							
Eye contact	:	No known significant effects	or critical hazards.				
Inhalation	:	: No known significant effects or critical hazards.					
Skin contact	:	: May cause an allergic skin reaction.					
Ingestion	:	: No known significant effects or critical hazards.					
Symptoms related to the physical	sic	cal, chemical and toxicologic	cal characteristics				
Eye contact	:	No specific data.					
Inhalation	:	No specific data.					
Skin contact	:	Adverse symptoms may incl irritation redness	ude the following:				
Ingestion	:	No specific data.					
Delayed and immediate effec	<u>ts</u>	as well as chronic effects fr	om short and long	<u>g-term exposure</u>			
Short term exposure							
Potential immediate effects	:	Not available.					
Potential delayed effects	:	Not available.					
Long term exposure							
Potential immediate effects	:	Not available.					
Potential delayed effects	:	Not available.					
Potential chronic health effe	ect	<u>s</u>					
Product/ingredient name	F	Result	Species	Dose	E		
barium diboron tetraoxide	6		Pat Male	70 ma/ka	0		

 Product/ingredient name
 Result
 Species
 Dose
 Exposure

 barium diboron tetraoxide
 Sub-chronic NOAEL Oral
 Rat - Male
 70 mg/kg
 91 days; 7 days per week

 Date of issue/Date of revision
 : 30/11/2021
 Date of previous issue
 : 30/11/2021
 Version
 : 9
 12/19

SECTION 11: Toxicological information

Conclusion/Summary	: Based on available data, the classification criteria are not met.
General	: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.
Endocrine disrupting properties	: Not available.
Other information	: Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
barium diboron tetraoxide	Acute EC50 20,3 to 22,4 ppm Fresh	Daphnia spec Daphnia	48 hours
	water	magna - Larvae	
	Acute LC50 151 to 299 ppm Fresh water	Fish - Lepomis macrochirus	96 hours
	Acute LC50 145 µg/l Fresh water	Fish - Rasbora heteromorpha	96 hours
	Acute LC50 62 to 84,5 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
1,2-benzisothiazol-3(2H)-one	Acute EC50 0,067 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 0,11 mg/l	Algae	72 hours
	Acute EC50 0,9893 mg/l Marine water	Crustaceans - Opossum Shrimp	96 hours
	Acute EC50 2,94 mg/l Fresh water	Daphnia spec.	48 hours
	Acute LC50 8 to 13 mg/l	Fish - Alburnus alburnus	96 hours
	Acute LC50 2,18 mg/l Fresh water	Fish	96 hours
	Acute LC50 1,6 to 2,8 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Chronic NOEC 90 mg/l	Aquatic plants - Phaseolus vulgaris	20 days
	Chronic NOEC 1,2 mg/l	Daphnia spec.	21 days
	Chronic NOEC 0,21 mg/l	Fish	28 days
	Chronic NOEL 0,0403 mg/l	Algae	72 hours
2-octyl-2H-isothiazol-3-one	Acute EC50 0,32 to 0,834 mg/l Fresh water	Daphnia spec Daphnia magna	48 hours
	Acute IC50 0,084 mg/l	Algae	72 hours
	Acute LC50 0,14 to 0,202 mg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute LC50 0,0655 to 0,104 mg/l Fresh water	Fish	96 hours
pyrithione zinc	Acute EC50 0,51 µg/l Marine water	Algae - Thalassiosira pseudonana	96 hours
	Acute EC50 38 µg/l Fresh water	Crustaceans - Ilyocypris dentifera	48 hours
	Acute EC50 80 µg/l Fresh water	Crustaceans - Chydorus sphaericus	48 hours
	Acute EC50 8,25 ppb Fresh water	Daphnia spec Daphnia magna	48 hours
	Acute EC50 61 µg/l Fresh water	Daphnia spec Daphnia magna - Nauplii	48 hours
	Acute LC50 2,68 ppb Fresh water	Fish - Pimephales promelas	96 hours
	Chronic EC10 0,36 µg/l Marine water	Algae - Thalassiosira pseudonana	96 hours
	Chronic NOEC 2,7 ppb Marine water	Daphnia spec Daphnia magna	21 days
terbutryn	Acute EC50 0,1 µg/l Fresh water	Algae - Fragilaria capucina ssp. rumpens	96 hours
	Acute EC50 2 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
ate of issue/Date of revision	: 30/11/2021 Date of previous issue	: 30/11/2021 Version	:9 13/1

Murfill Waterproofing Coating

SECTION 12: Ecological information

	Acute EC50 2,66 ppm Fresh water	Daphnia spec Daphnia magna	48 hours
	Acute IC50 0,0055 mg/l	Algae	72 hours
	Acute LC50 579,3 mg/l Fresh water	Crustaceans - Pacifastacus	48 hours
		leniusculus - Juvenile (Fledgling,	
		Hatchling, Weanling)	
	Acute LC50 1,8 to 1400 µg/l Fresh water	Fish - Carassius carassius	96 hours
	Acute LC50 0,82 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Chronic EC10 0,015 µg/l Fresh water	Algae - Fragilaria capucina ssp.	96 hours
		rumpens	
reaction mass of: 5-chloro-	Acute EC50 0,037 mg/l Fresh water	Algae	48 hours
2-methyl-4-isothiazolin-		-	
3-one [EC no. 247-500-7]			
and 2-methyl-2H-isothiazol-			
3-one [EC no. 220-239-6] (3:			
1)			
	Acute EC50 0,16 mg/l Fresh water	Daphnia spec.	48 hours
	Acute LC50 0,19 mg/l Fresh water	Fish	96 hours
	Acute NOEC 0,004 mg/l Marine water	Algae	48 hours
	Chronic NOEC 0,18 mg/l	Daphnia spec.	21 days
	Chronic NOEC 0,02 mg/l Fresh water	Fish	38 days
Conclusion/Summary	: Harmful to aquatic life with long lasting	g effects.	

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
$Poly[oxy(methyl-1,2\text{-}ethanediyl)], \alpha\text{-}(methylphenyl)\text{-}\omega\text{-}hydroxy\text{-}$	OECD 301F	80 to 90 % - Readily - 28 days	-	Activated sludge
1,2-benzisothiazol-3(2H)-one 2-octyl-2H-isothiazol-3-one	OECD 303A OECD 309 OECD 303A OECD 309	>80 % - Readily - 4 days	- 0,01 to 0,1 mg/l - 0,01 to 0,1 mg/l	- - -
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	OECD 301D	>60 % - Readily - 28 days	-	-
• /	-	<50 % - 10 days	-	-

: This product has not been tested for biodegradation. **Conclusion/Summary**

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
$Poly[oxy(methyl-1,2\text{-}ethanediyl)], \alpha\text{-}(methylphenyl)\text{-}\omega\text{-}hydroxy\text{-}$	-	-	Readily
2-octyl-2H-isothiazol-3-one 1,2-benzisothiazol-3(2H)-one 2-octyl-2H-isothiazol-3-one reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	- - Fresh water 2 days, 20°C -	- - -	Readily Readily Readily Readily

12.3 Bioaccumulative potential

Murfill Waterproofing Coating

SECTION 12: Ecological information

Product/ingredient name	LogPow	BCF	Potential
${\sf Poly}[oxy(methyl-1,2\text{-}ethanediyl)], \alpha\text{-}(methylphenyl)\text{-}\omega\text{-}hydroxy\text{-}$	2,78	-	low
Octene, hydroformylation products, high-boiling	>3.8	-	high
2-octyl-2H-isothiazol-3-one	2,9	-	low
1,2-benzisothiazol-3(2H)-one	0,64	-	low
2-octyl-2H-isothiazol-3-one	2,9	-	low
pyrithione zinc	0,9	11	low
terbutryn	3,74	-	low
reaction mass of: 5-chloro-	-0.83 to 0.75	-	low
2-methyl-4-isothiazolin-			
3-one [EC no. 247-500-7]			
and 2-methyl-2H-isothiazol-			
3-one [EC no. 220-239-6] (3:			
1)			

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Nonvolatile liquid.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting	: No known significant effects or critical hazards.
properties	
12.7 Other adverse effects	: No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance.

13.1 Waste treatment methods

Product	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: Yes.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 15*	aqueous sludges containing paint or varnish containing organic solvents or other hazardous substances
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

ADR/RID	ADN	IMDG	IATA
Not regulated.	Not regulated.	Not regulated.	Not regulated.
-	-	-	-
-	-	-	-
-	-	-	-
No.	No.	No.	No.
	Not regulated	Not regulated. Not regulated. - - - - - - - - - - - - - - - - - -	Not regulated.Not regulated

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk	: Not available.
according to IMO	
instruments	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH) Annex XIV - List of substances subject to authorisation **Annex XIV** None of the components are listed. Substances of very high concern None of the components are listed. **Annex XVII - Restrictions** : Not applicable. on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles **Other EU regulations** VOC 2 VOC for Ready-for-Use : IIA/i. One-pack performance coatings. EU limit value for this product : 140g/I (2010.) Mixture This product contains a maximum of 25 g/l VOC. : Not listed Industrial emissions (integrated pollution prevention and control) -Air Industrial emissions : Not listed (integrated pollution prevention and control) -Water

Ozone depleting substances (1005/2009/EC)

SECTION 15: Regulatory information

Not listed.

Prior Informed Consent (PIC) (649/2012/EC)

Not listed.

Persistent Organic Pollutants (850/2004/EC)

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

United Kingdom: Great Britain

References	 EH40/2005 Workplace exposure limits Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2020/878 REGULATION (EU) 2016/425 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 9 March 2016 on personal protective equipment and repealing Council Directive 89/686/EEC
------------	--

International regulations

Stockholm Convention on Persistent Organic Pollutants

List name	Ingredient name	Status
Not listed.		

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

List name	Ingredient name	Status
Not listed.		

CN code	1	3209	10	00	00
CN code	н,	3209	10	00	0

Inventory list	
Australia	: At least one component is not listed.
Canada	: At least one component is not listed.
China	: At least one component is not listed.
Europe	: All components are listed or exempted.
Japan	: Japan inventory (CSCL): At least one component is not listed. Japan inventory (ISHL): At least one component is not listed.
New Zealand	: At least one component is not listed.
Philippines	: At least one component is not listed.
Republic of Korea	: At least one component is not listed.
Taiwan	: At least one component is not listed.
Thailand	: Not determined.
Turkey	: Not determined.
United States	: At least one component is not listed.
Viet Nam	: Not determined.
15.2 Chemical safety assessment	: This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

	Indicates information	that has changed from	previously issued version.
--	-----------------------	-----------------------	----------------------------

Abbreviations and acronyms	: ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	EUH statement = CLP-specific Hazard statement
	N/A = Not available
	PBT = Persistent, Bioaccumulative and Toxic
	PNEC = Predicted No Effect Concentration
	RRN = REACH Registration Number
	SGG = Segregation Group
	vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Sens. 1, H317	Calculation method
Aquatic Chronic 3, H412	Calculation method

Full text of abbreviated H statements

United Kingdom: Great Britain					
Full text of abbreviated H :	H301 To	xic if swallowed.			
statements		rmful if swallowed.			
		tal in contact with skin.			
		xic in contact with skin.			
		uses severe skin burns and eye damage.			
		uses skin irritation.			
	H317 Ma	y cause an allergic skin reaction.			
		uses serious eye damage.			
	H330 Fa	tal if inhaled.			
	H360D Ma	y damage the unborn child.			
	H360F Ma	y damage fertility.			
		uses damage to organs through prolonged or repeated exposure.			
		ry toxic to aquatic life.			
		ry toxic to aquatic life with long lasting effects.			
		xic to aquatic life with long lasting effects.			
	H412 Ha	rmful to aquatic life with long lasting effects.			
Full text of classifications :	Acute Tox. 2	ACUTE TOXICITY - Category 2			
[CLP/GHS]	Acute Tox. 3	ACUTE TOXICITY - Category 3			
	Acute Tox. 4	ACUTE TOXICITY - Category 4			
	Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1			
	Aquatic	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1			
	Chronic 1				
	Aquatic	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2			
	Chronic 2				
	Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3			
	Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1			
	Repr. 1B	REPRODUCTIVE TOXICITY - Category 1B			
	Skin Corr. 1	SKIN CORROSION/IRRITATION - Category 1			
	Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1			
	Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2			
	Skin Sens. 1	SKIN SENSITISATION - Category 1			
	Skin Sens. 1A	SKIN SENSITISATION - Category 1A			
	Skin Sens. 1B	SKIN SENSITISATION - Category 1B			
	STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED			
		EXPOSURE - Category 1			
Date of printing :	30/11/2021				

SECTION 16: Other information

Date of issue/ Date of revision	: 30/11/2021
Date of previous issue	: 30/11/2021
Version	: 9

Notice to reader

IMPORTANT NOTE: The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates. Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.