

RUST-OLEUM®
— INDUSTRIAL —



ASPHALT REPAIR



Immediately pot-hole repair

- Simple to use - no mixing required
- Repairs can be driven over immediately after application
- Ideal for repairs 10 mm – 70 mm
- Coverage approx. 0.5 m² per 25 kg at 24 mm thick
- Withstands heavy traffic

KNOW-HOW TO PROTECT™

WWW.RUST-OLEUM.EU

ASPHALT REPAIR

DESCRIPTION

A durable bitumen-based patch repair for use on exterior pot-holed asphalt and concrete based on polished aggregate together with liquid binder based on bitumen plus resins and adhesives. Ideal for potholes in roads, car parks, paths and other bituminous and concrete surfaces.

RECOMMENDED USE

Ideal for pot-holes in roadways, vehicle parks, loading docks, paths, airfields etc, on bituminous and concrete surfaces.

RECOMMENDED DRY FILM THICKNESS

between 25 and 100 mm

THEORETICAL CONSUMPTION

At a film thickness of 24 mm 25 kg will cover approximately 0.5m². The product can be applied up to 100mm film thickness.

PRACTICAL CONSUMPTION

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

SURFACE PREPARATION

Remove all loose material and surface water, oil etc. Apply the primer with a brush on the prepared surface.

APPLICATION CONDITIONS

Temperature of air, substrate and coating material between 5 and 25°C. At lower temperatures the product will be tougher and is therefore more difficult to apply.

APPLICATION & THINNING: RAKE/TROWEL

Do not dilute the product.

SHELF LIFE

Minimum of 2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 25°C.

Date issued: 24/06/2022

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu