

SAFETY DATA SHEET

9202 Rust-O-Thane® Activator

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : 9202 Rust-O-Thane® Activator

Product description : Hardener.

Product type : Liquid.

UFI : 9080-60QX-W00E-C18U

1.2 Relevant identified uses of the substance or mixture and uses advised against

	Identified uses
Industrial use Professional use	

Uses advised against	Reason
Consumer use	Product is not intended for consumer use.

1.3 Details of the supplier of the safety data sheet

RUST-OLEUM EUROPE

Martin Mathys NV, Kolenbergstraat 23, B-3545 Zelem, Belgium

Telephone no.: +32 (0) 13 460 200

Fax no.: +32 (0) 13 460 201

Tor Coatings Limited

Unit 21, White Rose Way, Follingsby Park, Gateshead, Tyne & Wear, NE10 8YX United Kingdom

Telephone no.: +44 (0) 191 4106611

Fax no.: +44 (0) 191 4920125 enquiries@tor-coatings.com

e-mail address of person : rpmeurohas@rustoleum.eu

responsible for this SDS

1.4 Emergency telephone number

National advisory body/Poison Centre

Supplier

Telephone number : +44 870 8200418 / +44 2038073798

Hours of operation : 24 / 7

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Acute Tox. 4, H332 Skin Sens. 1B, H317 STOT SE 3, H335 Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

Date of issue/Date of revision : 7/09/2021 Date of previous issue : 7/09/2021 Version : 6 1/16

SECTION 2: Hazards identification

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms

(!)

Signal word : Warning

Hazard statements : May cause an allergic skin reaction.

Harmful if inhaled.

May cause respiratory irritation.

Harmful to aquatic life with long lasting effects.

Precautionary statements

General : Not applicable.

Prevention: P280 - Wear protective gloves.

P284 - In case of inadequate ventilation wear respiratory protection.

P271 - Use only outdoors or in a well-ventilated area.

Response : P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

Storage : Not applicable.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Hazardous ingredients : Hexane, 1,6-diisocyanato-, homopolymer, polyethylene glycol mono-Me ether-

blocked

hexamethylene-di-isocyanate

Supplemental label

elements

: Contains isocyanates. May produce an allergic reaction.

Supplemental label elements : Detergents - Regulation (EC) No

907/2006

: Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and

articles

: Not applicable.

Special packaging requirements

Containers to be fitted with child-resistant

fastenings

: Not applicable.

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification

: None known.

Date of issue/Date of revision : 7/09/2021 Date of previous issue : 7/09/2021 Version : 6 2/16

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

United Kingdom: Great Britain

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Туре
Hexane, 1,6-diisocyanato-, homopolymer, polyethylene glycol mono-Me ether-blocked	CAS: 160994-68-3	≥90	Acute Tox. 4, H332 Skin Sens. 1B, H317 STOT SE 3, H335 Aquatic Chronic 3, H412	[1] [2]
hexamethylene-di-isocyanate	REACH #: 01-2119457571-37 EC: 212-485-8 CAS: 822-06-0 Index: 615-011-00-1	≤0,1	Acute Tox. 4, H302 Acute Tox. 1, H330 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 STOT SE 3, H335	[1] [2]
			See Section 16 for the full text of the H statements declared above.	

<u>Type</u>

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

SCL (Specific Concentration Limits) hexamethylene-di-isocyanate	H334 = 0.5 % H317 = 0.5 %
ATE (acute toxicity estimates) Not applicable.	Not applicable.
Nanoform Particle characteristics This product does not contains nanomaterials.	Particle Size Not applicable.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Date of issue/Date of revision : 7/09/2021 Date of previous issue : 7/09/2021 Version : 6 3/16

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

Date of issue/Date of revision : 7/09/2021 Date of previous issue : 7/09/2021 Version : 6 4/16

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

: None known.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products

: No specific data.

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Additional information

: No unusual hazard if involved in a fire.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadeguate. Put on appropriate personal protective equipment.

For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

Date of issue/Date of revision : 7/09/2021 Date of previous issue : 7/09/2021 Version : 6 5/16

9202 Rust-O-Thane® Activator

SECTION 6: Accidental release measures

6.4 Reference to other sections

: See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations : Not available.
Industrial sector specific : Not available.
solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

United Kingdom: Great Britain

Product/ingredient name	Exposure limit values
Hexane, 1,6-diisocyanato-, homopolymer, polyethylene glycol mono-Me ether-blocked	EH40/2005 WELs (United Kingdom (UK), 8/2018). Inhalation sensitiser. STEL: 0,07 mg/m³, (as NCO) 15 minutes. TWA: 0,02 mg/m³, (as NCO) 8 hours.
hexamethylene-di-isocyanate	EH40/2005 WELs (United Kingdom (UK), 12/2011). Inhalation sensitiser. STEL: 0,07 mg/m³, (as NCO) 15 minutes. TWA: 0,02 mg/m³, (as NCO) 8 hours.

Date of issue/Date of revision : 7/09/2021 Date of previous issue : 7/09/2021 Version : 6 6/16

SECTION 8: Exposure controls/personal protection

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
hexamethylene-di-isocyanate	DNEL	Short term Inhalation	1 mg/m³	Workers	Local
	DNEL	Long term Inhalation	0,5 mg/m³	Workers	Local

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
hexamethylene-di-isocyanate	Fresh water	0,127 mg/l	-
	Marine	0,0127 mg/l	-
	Sediment	266700 mg/kg dwt	-
	Soil	53182 mg/kg dwt	-
	Sewage Treatment	38,28 mg/l	-
	Plant		

8.2 Exposure controls

Appropriate engineering controls

: No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. Use eye protection according to EN 166. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. Recommended: safety glasses with side-shields (EN 166).

Skin protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Date of issue/Date of revision : 7/09/2021 Date of previous issue : 7/09/2021 Version : 6 7/16

SECTION 8: Exposure controls/personal protection

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Recommended: For prolonged or repeated handling, use the following type of gloves: butyl rubber (0.6 mm) or fluor rubber (EN 374-1) (breakthrough time) >8 hours.

The recommendation for the type or types of glove to use when handling this product is based on information from the following source: EN374. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included

in the user's risk assessment.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Wear overalls or long sleeved shirt.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: During fumigation/spraying wear suitable respiratory equipment. supplied-air respirator By other operations than spraying, in well ventilated areas, air-fed respirators could be replaced by a combination charcoal filter and particulate filter mask. Filter type: (A2-P2)(EN 140).

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Physical state : Liquid. Colour : Yellow. **Odour** : Odourless. : Not available. **Odour threshold**

Melting point/freezing point

: Not available.

Initial boiling point and boiling

range

: Not relevant due to nature of the product.

Flammability (solid, gas)

: Slightly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge.

Emits highly toxic fumes when heated to decomposition.

Upper/lower flammability or explosive limits

: Not available.

Flash point

: Closed cup: >250°C (>482°F) [DIN 53213]

Auto-ignition temperature

: 465°C (869°F) [DIN 51794]

Decomposition temperature

: >200°C : Not applicable.

: Product is non-soluble (in water).

pH: Justification **Viscosity**

: Dynamic: 2800 mPa·s [DIN EN ISO 3219]

Solubility(ies)

: Insoluble in the following materials: cold water and hot water.

Date of issue/Date of revision : 7/09/2021 Date of previous issue : 7/09/2021 Version : 6 8/16

9202 Rust-O-Thane® Activator

SECTION 9: Physical and chemical properties

Solubility in water : Not available.

Partition coefficient: n-octanol/ : Not applicable.

water

Vapour pressure : Not relevant due to nature of the product.

Evaporation rate : Not available. **Relative density** : 1,16 [DIN 53217]

Density : 1,16 g/cm³ [20°C (68°F)] [DIN 53217]

Vapour density : Not available.

Explosive properties : No unusual hazard if involved in a fire.

Oxidising properties : Not available.

Particle characteristics

Median particle size : Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product may not be stable under certain conditions of storage or use. See

"Possibility of Hazardous Reactions" for further information.

hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products

Acute toxicity estimates

10.3 Possibility of

: Under normal conditions of storage and use, hazardous decomposition products should not be produced. If involved in a fire, toxic gases including CO, CO2 and

smoke can be generated.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 <u>Acute toxicity</u>

Product/ingredient name	Result	Species	Dose	Exposure
Hexane, 1,6-diisocyanato-, homopolymer, polyethylene glycol mono-Me ether- blocked	LC50 Inhalation Dusts and mists	Rat - Female	0,39 mg/l	4 hours
	LD50 Oral	Rat	>2000 mg/kg	-
hexamethylene-di- isocyanate	LC50 Inhalation Dusts and mists	Rat	0,124 mg/m ³	4 hours
	LCLo Inhalation Dusts and mists LD50 Dermal	Rat Rabbit	60 mg/m³ >7000 mg/kg	4 hours

Conclusion/Summary : Harmful if inhaled.

Date of issue/Date of revision : 7/09/2021 Date of previous issue : 7/09/2021 Version : 6 9/16

9202 Rust-O-Thane® Activator

SECTION 11: Toxicological information

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Hexane, 1,6-diisocyanato-, homopolymer, polyethylene glycol mono-Me ether-blocked	N/A	N/A	N/A	N/A	1,5
hexamethylene-di-isocyanate	500	N/A	N/A	0,05	N/A

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Hexane, 1,6-diisocyanato-, homopolymer, polyethylene glycol mono-Me ether- blocked	Skin - Primary dermal irritation index (PDII)	Rabbit	1	-	-
hexamethylene-di-isocyanate	Skin - Erythema/Eschar Eyes - Redness of the conjunctivae	Rabbit Rabbit	3	-	-

Conclusion/Summary

Skin : Based on available data, the classification criteria are not met.

Eyes : Based on available data, the classification criteria are not met.

Respiratory: May cause respiratory irritation.

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
Hexane, 1,6-diisocyanato-, homopolymer, polyethylene glycol mono-Me ether- blocked	skin	Guinea pig	Sensitising
hexamethylene-di-isocyanate	Respiratory skin Respiratory	Guinea pig Guinea pig Guinea pig	Not sensitizing Sensitising Sensitising

Conclusion/Summary

Skin: May cause an allergic skin reaction.

Respiratory: Based on available data, the classification criteria are not met.

Mutagenicity

Product/ingredient name	Test	Experiment	Result
Hexane, 1,6-diisocyanato-, homopolymer, polyethylene glycol mono-Me ether- blocked	OECD 471	Experiment: In vitro Subject: Bacteria	Negative
hexamethylene-di-isocyanate	OECD 471	Experiment: In vitro Subject: Bacteria	Negative
	OECD 476	Experiment: In vitro Subject: Mammalian-Animal	Negative
	OECD 474	Experiment: In vivo Subject: Mammalian-Animal	Negative

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Carcinogenicity

Conclusion/Summary: Based on available data, the classification criteria are not met.

Reproductive toxicity

Conclusion/Summary: Based on available data, the classification criteria are not met.

Teratogenicity

Conclusion/Summary: Based on available data, the classification criteria are not met.

Date of issue/Date of revision : 7/09/2021 Date of previous issue : 7/09/2021 Version : 6 10/16

9202 Rust-O-Thane® Activator

SECTION 11: Toxicological information

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Hexane, 1,6-diisocyanato-, homopolymer, polyethylene glycol mono-Me ether-blocked	Category 3	Not applicable.	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes

of exposure

: Routes of entry anticipated: Dermal, Inhalation.

Potential acute health effects

Eye contactInhalation: No known significant effects or critical hazards.: Harmful if inhaled. May cause respiratory irritation.

Skin contact: May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion: No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Product/ingredient name	Result	Species	Dose	Exposure
hexamethylene-di-isocyanate	Chronic LCLo Inhalation Vapour	Rat	0,025 p.p.m.	30 days; 6 hours per day Intermittent

Conclusion/Summary: Based on available data, the classification criteria are not met.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

Date of issue/Date of revision : 7/09/2021 Date of previous issue : 7/09/2021 Version : 6 11/16

9202 Rust-O-Thane® Activator

SECTION 11: Toxicological information

Endocrine disrupting

properties

: Not available.

Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
Hexane, 1,6-diisocyanato-, homopolymer, polyethylene glycol mono-Me ether- blocked	Acute EC50 >100 mg/l	Algae - Scenedesmus subspicatus	72 hours
	Acute EC50 >100 mg/l	Daphnia spec.	48 hours
	Acute LC50 28,3 mg/l	Fish	96 hours
hexamethylene-di-isocyanate	Acute EC50 >77,4 mg/l Acute EC50 842 mg/l	Algae Bacteria	72 hours 3 hours

Conclusion/Summary: Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
Hexane, 1,6-diisocyanato-, homopolymer, polyethylene glycol mono-Me ether- blocked	OECD 301F	2 % - Not readily - 28 days	-	-
hexamethylene-di-isocyanate	OECD 301F EU 301F Ready Biodegradability - Manometric Respirometry Test	42 % - 10 days 42 % - 28 days	-	-

Conclusion/Summary : This product has not been tested for biodegradation.

Based on available data, the classification criteria are not met.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Hexane, 1,6-diisocyanato-, homopolymer, polyethylene glycol mono-Me ether- blocked	-	-	Not readily
hexamethylene-di-isocyanate	-	-	Not readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
hexamethylene-di-isocyanate	0,02	57,63	low

12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Mobility : Nonvolatile liquid.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Date of issue/Date of revision : 7/09/2021 Date of previous issue : 7/09/2021 Version : 6 12/16

9202 Rust-O-Thane® Activator

SECTION 12: Ecological information

12.6 Endocrine disrupting

: No known significant effects or critical hazards.

properties

12.7 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance.

13.1 Waste treatment methods

Product

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes. European waste catalogue (EWC)

Waste code	Waste designation
08 01 15*	aqueous sludges containing paint or varnish containing organic solvents or other hazardous substances

Special precautions

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

14.6 Special precautions for user

: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments

: Not available.

Date of issue/Date of revision : 7/09/2021 Date of previous issue : 7/09/2021 Version : 6 13/16

9202 Rust-O-Thane® Activator

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions

: Not applicable.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and

articles

Other EU regulations

VOC

VOC for Ready-for-Use : 2004/42/EC - IIA/j: 140g/l (2010). <= 35g/l VOC.

Mixture

Industrial emissions : Not listed

(integrated pollution prevention and control) -

Air

Industrial emissions : Not listed

(integrated pollution prevention and control) -

Water

Ozone depleting substances (1005/2009/EC)

Not listed.

Prior Informed Consent (PIC) (649/2012/EC)

Not listed.

Persistent Organic Pollutants (850/2004/EC)

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

United Kingdom: Great Britain

References : EH40/2005 Workplace exposure limits

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by

Regulation (EU) No. 2020/878

REGULATION (EU) 2016/425 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 9 March 2016 on personal protective equipment and repealing Council

Directive 89/686/EEC

International regulations

Stockholm Convention on Persistent Organic Pollutants

List name	Ingredient name	Status
Not listed.		

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Date of issue/Date of revision : 7/09/2021 Date of previous issue : 7/09/2021 Version : 6 14/16

9202 Rust-O-Thane® Activator

SECTION 15: Regulatory information

List name	Ingredient name	Status
Not listed.		

CN code : 3909 50 90 90

Inventory list

Australia : Not determined.

Canada : At least one component is not listed in DSL but all such components are listed in

NDSL.

China : Not determined.

Europe : All components are listed or exempted.
 Japan inventory (CSCL): Not determined.
 Japan inventory (ISHL): Not determined.

New Zealand : All components are listed or exempted.

Philippines : Not determined.

Republic of Korea : All components are listed or exempted.

Taiwan : All components are listed or exempted.

Thailand : Not determined.

Turkey : Not determined.

United States : Not determined.

Viet Nam : Not determined.

15.2 Chemical safety

assessment

: This product contains substances for which Chemical Safety Assessments are still

required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Acute Tox. 4, H332	On basis of test data
Skin Sens. 1B, H317	Expert judgment
STOT SE 3, H335	Expert judgment
Aquatic Chronic 3, H412	Expert judgment

Full text of abbreviated H statements

United Kingdom: Great Britain

Date of issue/Date of revision : 7/09/2021 Date of previous issue : 7/09/2021 Version : 6 15/16

9202 Rust-O-Thane® Activator

SECTION 16: Other information

Full text of abbreviated	Н
statements	

H302 Harmful if swallowed. H315 Causes skin irritation. May cause an allergic skin reaction. H317 Causes serious eve irritation. H319 Fatal if inhaled. H330 H332 Harmful if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation. H412 Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

Acute Tox. 1 ACUTE TOXICITY - Category 1 Acute Tox. 4 **ACUTE TOXICITY - Category 4** Aquatic LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3 Chronic 3 Eye Irrit. 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2 Resp. Sens. 1 **RESPIRATORY SENSITISATION - Category 1** Skin Irrit. 2 SKIN CORROSION/IRRITATION - Category 2 Skin Sens. 1 SKIN SENSITISATION - Category 1 SKIN SENSITISATION - Category 1B Skin Sens. 1B SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE -STOT SE 3 Category 3

Date of printing : 25/10/2021

Date of issue/ Date of : 7/09/2021

revision

Date of previous issue : 7/09/2021

Version : 6

Notice to reader

IMPORTANT NOTE: The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates. Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.