

## COO-VAR ANTI-GRAFFITI LACQUER CLEAR GLAZE

DESCRIPTION COO-VAR ANTI-GRAFFITI LACQUER CLEAR GLAZE is a surface sealer for application to masonry surfaces to reduce surface absorbency and ensure ease of cleaning to remove unwanted Graffiti.

### Composition

Two Pack Water Based polyurethane resin system

### Appearance

Gloss clear finish.

### Durability

Impact and abrasive resistant clear surface sealer.

### Typical Installations

COO-VAR ANTI-GRAFFITI LACQUER CLEAR GLAZE, can be used where high levels of graffiti occur.

### Substrates

COO-VAR ANTI -GRAFFITI LACQUER CLEAR GLAZE, adheres well to concrete and brickwork. It can also be applied to sound existing paintwork.

### Surface Preparation

It is essential that all surfaces are laitence free, clean, dry and free from any contaminants such as loose particles, dust, grease, oils, fats and water. "Green" concrete and render must be left for one to two months to dry. If in doubt contact Technical Services on 01482 – 328053.

### Application

COO-VAR ANTI -GRAFFITI LACQUER CLEAR GLAZE, when mixed is an off white emulsion which can be applied using a brush or roller to achieve an even applied coverage.

### Application Conditions

Air temperature 5-30°C, Humidity 85% RH maximum, non condensing.

### Mixing

The entire contents of the hardener tin must be added to the resin base and mixed thoroughly, using the mixing tool provided for two minutes ensuring the mixing action takes in full depth and perimeter of the container.

### Coverage

COO-VAR ANTI- GRAFFITI LACQUER CLEAR GLAZE covers 14-18 square metres per kit.

COO-VAR ANTI -GRAFFITI LACQUER CLEAR GLAZE is supplied in 2.5 kilo kits.

### Curing Schedule

COO-VAR ANTI- GRAFFITI LACQUER CLEAR GLAZE will dry clear in one or two hours and generally will be tack free overnight. Full cure is achieved in three to seven days under ambient conditions

### Handling precautions

Coo-Var resins and hardeners are generally harmless in use provided that certain precautions normally taken when handling chemicals are observed. The uncured material must not be allowed to come into contact with foodstuffs or food utensils, and measures should also be taken to prevent skin contact, since people with sensitive skin may be affected. The use of protective clothing, barrier creams, gloves and goggles is recommended. The skin should be thoroughly washed at the end of each working period, using either soap and water or resin removing creams. Do not wash the skin with cleaning solvents. Adequate ventilation in the working area is recommended. In case of accidental mouth or eye contact - wash thoroughly with clean water if in any doubt - consult a doctor immediately.

Read hazard warning labels on product containers. Ask for product safety sheet.

For further information please contact our technical department.

April 2004

COO-VAR ANTI -GRAFFITI LACQUER CLEAR GLAZE