

**RUST-OLEUM®**  
— INDUSTRIAL —



## GROUND MARKER FLUORESCENT



**For marking & locating in  
construction & civil  
engineering**

- Optimised for ground marking
- Spray through cap for ease of use
- Easier writing
- Quick drying (5 - 10 minutes)

KNOW-HOW TO PROTECT™

[WWW.RUST-OLEUM.EU](http://WWW.RUST-OLEUM.EU)



# GROUND MARKER FLUORESCENT

## DESCRIPTION

For quick and easy marking of construction and excavation sites, underground utilities and for traffic safety. Optimised for ground marking. By means of the 360° valve the aerosol is sprayable in all directions. RUST-OLEUM® Spot Marking Aerosol 2800 is based on a fast drying acrylic resin. All products in this range are aromatic free and based on lead- and chromate free pigments.

## RECOMMENDED USE

RUST-OLEUM® Spot Marking Aerosol 2800 can be used on metal, concrete, asphalt, gravel, soil and grass, etc. RUST-OLEUM® Spot Marking Aerosol 2800 is not water-soluble and should be used in light industrial exposures, normal humidity and interior applications. RUST-OLEUM® Spot Marking Aerosol 2800 is designed for quick and easy marking of construction and excavation sites, underground utilities and for traffic safety

## TECHNICAL DATA

Gloss Level: Matt  
Heat Resistance: 100°C (dry heat)

## DRY TIMES BY 20° C/RV 50%

Touch dry: 5 minutes  
Dry to handle: 30 minutes

## THEORETICAL CONSUMPTION

500 ml: 1,5 m² per spray can at 25 µm dry

## PRACTICAL CONSUMPTION

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

## SURFACE PREPARATION

Remove dirt, grease, oil and all other surface contaminants by appropriate means. The surface must be clean and dry during application.

## APPLICATION CONDITIONS

For good results the relative humidity shall be below 85% and the temperature of the can and substrate above 0°C.

## APPLICATION & THINNING: AEROSOL

Shake vigorously for at least one minute after the rattle of mixing ball is heard. Shake frequently during use. It is not possible to clean the spray button in the usual way. Due to the use of the 360° valve this is not necessary.

## SHELF LIFE

Minimum of 3 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Date issued: 24/06/2022

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)