



## Betolux Akva Primer

|                  |                                                                                                                                                                                                                                                                           |
|------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Description      | Water-borne non-yellowing acrylate primer.                                                                                                                                                                                                                                |
| Product features | Suitable for priming new and previously painted concrete floors prior to finishing with Betolux Akva floor paint. Betolux Akva Primer is absorbed into the concrete reducing absorbency and improving topcoat adhesion. Betolux Akva Primer can be used as a dust binder. |
| Recommended uses | Concrete floors and stairs, in dry residential, commercial and storage premises. Suitable for dry floors exposed to light mechanical and chemical stress.                                                                                                                 |



### TECHNICAL DATA

|                                                   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|---------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                   |       |
| Coverage                                          | 5-10 m <sup>2</sup> /l.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Can sizes                                         | 5 l.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Thinner                                           | Water                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Application method                                | Brush or roller.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Drying time at 23°C and 50% relative air humidity | Dust-dry after approx. 1 h. Over-coatable after approx. 2 hours.                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Solids volume                                     | n. 9 %                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Density                                           | n. 1 kg/l, ISO 2811                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Storage                                           | Protect from frost.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Product code                                      | 270_6001/3                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |

### APPLICATION DETAILS

|                        |                                                                                                                                                                                                                                                                                                                                                                      |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Application conditions | The surface of the concrete must be dry and at least 4 weeks old. Relative humidity of the concrete must be below 97%. During painting work and drying the temperature of the air, surface and paint must be at least 10 °C, and the relative humidity of the air below 80 %.                                                                                        |
| Preparation            | Do not apply on wet or non-absorbing substrate.<br>Remove laitance with a sanding machine.<br>Remove sanding dust.                                                                                                                                                                                                                                                   |
| Priming                | Stir Betolux Akva Primer well before use.<br>Spread non-diluted Primer on the floor with a roller or brush. The amount of the Primer is adequate when it is absorbed into concrete pores and does not leave a varnish-like film on the surface.<br>The primed surface can be painted with Betolux Akva Floor Paint after approx. 2 hours under normal circumstances. |
| Cleaning of tools      | Clean tools with water or Tikkurila Pensselipesu (Tool Cleaner).                                                                                                                                                                                                                                                                                                     |

### HEALTH AND SAFETY LABELLING

according to Regulation (EC) No. 1272/2008

The product is not classified as dangerous. A Safety Data Sheet is available on request.

 [Safety data sheet](#)



## Betolux Akva Primer

ENVIRONMENTAL and WASTE  
DISPOSAL  
TRANSPORT

Empty cans should be recycled or disposed of in accordance with local regulations. Liquid waste should be destroyed according to the local regulations.  
VAK/ADR: not classified

ser050916 / sa250208 / akk030308 / lko250208 / 0066300-

---